

COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.484	12.29	S-3182	12.0	304.8	.422	10.7	.10	.02	8.1	206	.82	3.6	3.91	99.2	0.031	0.8	125.0	SST	C	N
0.485	12.32	12693	1.00	25.4	.277	7.0	441	77	.15	3.7	65	288	.83	21.1	0.104	2.6	8.00	SST	CG	N
0.492	12.50	12715	.97	24.6	.402	10.2	13	2.3	.65	17	8.6	38	.32	8.0	0.045	1.1	7.00	MW	CG	Z
0.500	12.70	B8-11	.25	6.4	.402	10.2	90	16	.10	2.5	9.1	40	.15	3.7	0.049	1.2	3.00	SPR	CG	GI
0.500	12.70	G-100	.38	9.5	.464	11.8	.45	.08	.27	6.8	.12	.53	.11	2.7	0.018	0.5	5.00	MW	C	N
0.500	12.70	G-19	.38	9.5	.450	11.4	5.2	.92	.28	7.0	1.4	6.4	.10	2.5	0.025	0.6	3.00	MW	C	Z
0.500	12.70	S-1097	.38	9.5	.448	11.4	1.8	.31	.22	5.6	.39	1.7	.16	4.0	0.026	0.7	5.00	SST	C	N
0.500	12.70	L-4	.38	9.5	.402	10.2	90	16	.10	2.5	9.1	40	.20	5.0	0.049	1.2	3.00	SPR	C	Z
0.500	12.70	LL-83	.38	9.5	.356	9.0	493	86	.05	1.3	25	110	.29	7.3	0.072	1.8	3.00	SPR	C	Z
0.500	12.70	BB-92	.41	10.3	.432	11.0	8.3	1.4	.27	6.9	2.2	9.9	.14	3.5	0.034	0.9	4.00	SST	CG	N
0.500	12.70	10884	.44	11.1	.468	11.9	.17	.03	.31	7.9	.05	.23	.13	3.3	0.016	0.4	7.00	MW	C	Z
0.500	12.70	H-54	.44	11.1	.448	11.4	6.2	1.1	.33	8.3	2.0	9.0	.08	2.0	0.026	0.7	3.00	MW	CG	Z
0.500	12.70	S-351	.44	11.1	.422	10.7	7.5	1.3	.20	5.2	1.5	6.8	.23	5.9	0.039	1.0	6.00	SST	CG	N
0.500	12.70	3751	.44	11.1	.386	9.8	87	15	.15	3.8	13	59	.23	5.8	0.057	1.4	4.00	SPR	CG	Z
0.500	12.70	4179	.50	12.7	.462	11.7	.56	.10	.39	9.8	.22	.96	.11	2.9	0.019	0.5	5.00	MW	C	BO
0.500	12.70	S-108	.50	12.7	.460	11.7	.60	.11	.38	9.7	.23	1.0	.12	3.0	0.020	0.5	5.00	SST	C	N
0.500	12.70	2931	.50	12.7	.456	11.6	1.0	.18	.37	9.3	.38	1.7	.13	3.4	0.022	0.6	5.00	MW	C	Z
0.500	12.70	S-905	.50	12.7	.444	11.3	3.4	.60	.36	9.1	1.2	5.5	.14	3.6	0.028	0.7	4.00	SST	C	N
0.500	12.70	4118	.50	12.7	.432	11.0	19	3.3	.17	4.3	3.2	14	.14	3.5	0.034	0.9	3.00	SPR	C	Z
0.500	12.70	Y-41	.50	12.7	.430	10.9	11	1.9	.31	7.9	3.3	15	.14	3.6	0.035	0.9	4.00	SPR	CG	Z
0.500	12.70	S-118	.50	12.7	.406	10.3	33	5.7	.23	5.8	7.5	33	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.500	12.70	NN-4	.50	12.7	.400	10.2	39	6.9	.23	5.8	9.0	40	.23	5.7	0.050	1.3	4.50	SPR	CG	N
0.500	12.70	B1-33	.50	12.7	.388	9.9	72	13	.16	4.2	12	52	.22	5.7	0.056	1.4	4.00	SST	CG	N
0.500	12.70	3215	.53	13.5	.460	11.7	.69	.12	.43	11	.30	1.3	.10	2.5	0.020	0.5	5.00	MW	CG	Z
0.500	12.70	G-11	.53	13.5	.398	10.1	36	6.3	.23	5.7	8.1	36	.31	7.8	0.051	1.3	5.00	SPR	C	N
0.500	12.70	O-52	.53	13.5	.310	7.9	766	134	.06	1.6	49	218	.38	9.7	0.095	2.4	4.00	SST	CG	N
0.500	12.70	L-52	.55	13.9	.300	7.6	1123	197	.05	1.4	61	271	.40	10.2	0.100	2.5	4.00	SPR	CG	Z
0.500	12.70	F-78	.56	14.3	.456	11.6	1.0	.18	.43	11	.44	2.0	.13	3.4	0.022	0.6	5.00	MW	C	Z
0.500	12.70	EE-22	.56	14.3	.420	10.7	8.2	1.4	.32	8.2	2.6	12	.24	6.1	0.040	1.0	6.00	SST	CG	N
0.500	12.70	LL-26	.56	14.3	.420	10.7	17	2.9	.30	7.5	5.0	22	.17	4.3	0.040	1.0	4.25	SPR	CG	GI
0.500	12.70	VV-37	.56	14.3	.416	10.6	23	4.1	.25	6.3	5.7	26	.21	5.3	0.042	1.1	4.00	SPR	C	GI
0.500	12.70	S-1304	.56	14.3	.392	10.0	48	8.4	.22	5.6	11	47	.24	6.2	0.054	1.4	4.50	SST	CG	N
0.500	12.70	JJ-37	.56	14.3	.380	9.7	55	9.6	.20	5.1	11	49	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.500	12.70	XX-62	.56	14.3	.316	8.0	607	106	.08	2.0	48	214	.41	10.5	0.092	2.3	4.50	SPR	CG	Z
0.500	12.70	S-1398	.56	14.3	.310	7.9	681	119	.07	1.8	49	218	.40	10.3	0.095	2.4	4.25	SST	CG	N
0.500	12.70	3611	.59	15.1	.430	10.9	11	1.9	.42	11	4.5	20	.18	4.4	0.035	0.9	4.00	MW	C	Z
0.500	12.70	12673	.59	15.1	.426	10.8	14	2.4	.40	10	5.5	24	.19	4.7	0.037	0.9	4.00	MW	C	Z
0.500	12.70	O-79	.59	15.1	.412	10.5	19	3.3	.35	8.8	6.6	29	.22	5.6	0.044	1.1	5.00	SPR	CG	Z
0.500	12.70	A14-55	.61	15.5	.420	10.7	19	3.3	.26	6.7	5.0	22	.16	4.1	0.040	1.0	4.00	SPR	CG	GI
0.500	12.70	Q-12	.63	15.9	.436	11.1	4.3	.75	.43	11	1.8	8.2	.19	4.9	0.032	0.8	5.00	SST	C	N
0.500	12.70	A14-46	.63	15.9	.424	10.8	13	2.4	.30	7.5	4.0	18	.15	3.9	0.038	1.0	4.00	SST	CG	N
0.500	12.70	PP-94	.63	15.9	.424	10.8	12	2.1	.35	8.9	4.3	19	.17	4.3	0.038	1.0	4.50	SPR	CG	GI
0.500	12.70	A11-35	.63	15.9	.422	10.7	15	2.6	.29	7.3	4.3	19	.16	4.0	0.039	1.0	4.00	SST	CG	N
0.500	12.70	AA-74	.63	15.9	.420	10.7	13	2.2	.39	9.8	4.9	22	.24	6.1	0.040	1.0	5.00	SPR	C	N
0.500	12.70	OO-8	.63	15.9	.420	10.7	15	2.6	.33	8.4	5.0	22	.18	4.6	0.040	1.0	4.50	SPR	CG	N
0.500	12.70	3831	.63	15.9	.416	10.6	16	2.7	.37	9.4	5.7	26	.25	6.4	0.042	1.1	5.00	SPR	C	Z
0.500	12.70	S-1302	.63	15.9	.412	10.5	20	3.5	.31	7.9	6.2	27	.20	5.0	0.044	1.1	4.50	SST	CG	N
0.500	12.70	3905	.63	15.9	.410	10.4	31	5.5	.23	5.7	7.0	31	.18	4.6	0.045	1.1	4.00	SPR	CG	Z
0.500	12.70	A15-4	.63	15.9	.404	10.3	20	3.4	.35	8.9	6.8	30	.28	7.0	0.048	1.2	5.75	SST	CG	N
0.500	12.70	B14-37	.63	15.9	.394	10.0	45	7.9	.22	5.7	10	45	.24	6.1	0.053	1.3	4.50	SST	CG	N
0.500	12.70	10976	.63	15.9	.392	10.0	55	9.7	.20	5.2	11	50	.30	7.5	0.054	1.4	4.50	HD	C	Z
0.500	12.70	10102	.63	15.9	.376	9.6	126	22	.13	3.4	17	75	.25	6.3	0.062	1.6	4.00	HD	CG	Z
0.500	12.70	2606	.63	15.9	.370	9.4	125	22	.16	3.9	19	86	.29	7.4	0.065	1.7	4.50	SPR	CG	Z
0.500	12.70	CC-8	.63	15.9	.356	9.0	143	25	.16	4.1	23	103	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.500	12.70	B-22	.66	16.7	.394	10.0	56	9.9	.19	4.8	11	47	.28	7.1	0.053	1.3	4.25	HD	C	N
0.500	12.70	S-99	.69	17.4	.410	10.4	14	2.4	.42	11	5.8	26	.27	6.9	0.045	1.1	6.00	SST	CG	N
0.500	12.70	11444	.69	17.4	.410	10.4	12	2.2	.39	10	4.9	22	.29	7.4	0.045	1.1	6.50	SST	CG	N
0.500	12.70	S-1457	.69	17.4	.408	10.4	24	4.2	.29	7.5	7.0	31	.21	5.3	0.046	1.2	4.50	SST	CG	N
0.500	12.70	3825	.69	17.4	.372	9.4	129	23	.14	3.6	19	82	.27	6.9	0.064	1.6	4.25	SPR	CG	N
0.500	12.70	LL-4	.69	17.4	.320	8.1	342	60	.13	3.4	45	201	.54	13.7	0.090	2.3	6.00	SPR	CG	GI
0.500	12.70	B5-9	.72	18.2	.424	10.8	12	2.1	.35	8.9	4.3	19	.17	4.3	0.038	1.0	4.50	SPR	CG	N
0.500	12.70	EE-78	.72	18.2	.416	10.6	21	3.6	.28	7.1	5.7	26	.18	4.5	0.042	1.1	4.25	SPR	CG	N
0.500	12.70	1881	.72	18.2	.376	9.6	101	18	.23	5.9	23	104	.28	7.1	0.062	1.6	4.50	MW	CG	Z
0.500	12.70	1932	.72	18.2	.376	9.6	84	15	.20	5.1	17	75	.37	9.4	0.062	1.6	5.00	SPR	C	Z
0.500	12.70	G-85	.72	18.2	.296	7.5	897	157	.07	1.8	64	287	.48	12.3	0.102	2.6	4.75	SPR	CG	N
0.500	12.70	B14-6	.72	18.2	.278	7.1	1236	216	.06	1.6	79	351	.56	14.1	0.111	2.8	5.00	SPR	CG	N
0.500	12.70	3967	.75	19.1	.438	11.1	4.0	.69	.56	14	2.2	9.8	.19	4.9	0.031	0.8	5.25	MW	C	Z
0.500	12.70	PP-89	.75	19.1	.432	11.0	6.0	1.1	.50	13	3.0	13	.20	5.0	0.034	0.9	4.75	SST	C	N
0.500	12.70	B3-68	.75	19.1	.426	10.8	9.0	1.6	.53	13	4.8	21	.22	5.6	0.037	0.9	5.00	MW	C	T
0.500	12.70	S-754	.75	19.1	.416	10.6	15	2.6	.37	9.3	5.4	24	.24	6.1	0.042	1.1	4.75	SST	C	N
0.500	12.70	3545	.75	19.1	.410	10.4	31	5.5	.31	7.9	9.8	43	.18	4.6	0.045	1.1	4.00	MW	CG	Z
0.500	12.70	GG-27	.75	19.1	.410	10.4	23	4.0	.31	7.9	7.0	31	.21	5.4	0.045	1.1	4.75	SPR	CG	N
0.500	12.70	S-1211	.75	19.1	.410	10.4	18	3.2	.36	9.2	6.6	29	.27	6.9	0.045	1.1	5.00	SST	C	N
0.500	12.70	10133	.75	19.1	.406	10.3	25	4.4	.32	8.1	8.0	36	.24	6.0	0.047	1.2	5.00	SPR	CG	Z
0.500	12.70	3572	.75	19.1	.398	10.1	23	4.0	.41	10	9.2	41	.34	8.7	0.051	1.3	6.75	HD	CG	Z
0.500	12.70	10141	.75	19.1	.392	10.0	46	8.0	.25	6.2	11	50	.27	6.9	0.054	1.4	5.00	SPR	CG	Z
0.500	12.70	10283	.75	19.1	.392	10.0	34	6.0	.33	8.3	11	50	.38	9.6	0.054	1.4	6.00	SPR	C	Z
0.500	12.70	B1-34	.75	19.1	.392	10.0	35	6.1	.30	7.7	11	47	.30	7.5	0.054	1.4	5.50	SST	CG	N
0.500	12.70	B18-161	.75	19.1	.388	9.9	54	9.4	.23	5.9	13	56	.28	7.1	0.056	1.4	5.00	SPR	CG	GI
0.500	12.70	B10-40	.75	19.1	.370	9.4	83	15	.23	5.9	19	86	.37	9.5	0.065	1.7	5.75	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.500	12.70	B14-41	.75	19.1	.344	8.7	140	24	.21	5.3	29	130	.51	12.9	0.078	2.0	6.50	SST	CG	N
0.500	12.70	12583	.75	19.1	.340	8.6	199	35	.17	4.3	34	149	.48	12.2	0.080	2.0	6.00	SPR	CG	N
0.500	12.70	K-62	.75	19.1	.316	8.0	433	76	.11	2.8	48	214	.51	12.9	0.092	2.3	5.50	SPR	CG	Z
0.500	12.70	S-341	.78	19.8	.448	11.4	1.5	.26	.63	16	.92	4.1	.15	3.8	0.026	0.7	5.75	SST	CG	N
0.500	12.70	10466	.78	19.8	.418	10.6	14	2.5	.38	9.7	5.4	24	.21	5.2	0.041	1.0	5.00	SPR	CG	GI
0.500	12.70	3599	.78	19.8	.352	8.9	139	24	.27	6.8	37	167	.44	11.3	0.074	1.9	6.00	MW	CG	GI
0.500	12.70	12728	.81	20.6	.444	11.3	1.9	.33	.60	15	1.1	5.0	.21	5.3	0.028	0.7	6.50	MW	C	Z
0.500	12.70	S-167	.81	20.6	.442	11.2	2.0	.35	.60	15	1.2	5.3	.21	5.3	0.029	0.7	6.25	SST	C	N
0.500	12.70	H-51	.81	20.6	.432	11.0	5.5	.96	.54	14	3.0	13	.20	5.2	0.034	0.9	5.00	SST	C	N
0.500	12.70	A11-33	.81	20.6	.424	10.8	9.0	1.6	.45	11	4.0	18	.19	4.8	0.038	1.0	5.00	SST	CG	N
0.500	12.70	YY-34	.81	20.6	.412	10.5	16	2.9	.37	9.5	6.2	27	.26	6.7	0.044	1.1	5.00	SST	C	N
0.500	12.70	S-1572	.81	20.6	.412	10.5	17	2.9	.37	9.3	6.2	27	.22	5.6	0.044	1.1	5.00	SST	CG	N
0.500	12.70	JJ-88	.81	20.6	.408	10.4	8.9	1.6	.41	10	3.6	16	.40	10.2	0.046	1.2	8.75	SST	CG	N
0.500	12.70	B14-29	.81	20.6	.394	10.0	42	7.4	.25	6.4	11	47	.27	6.7	0.053	1.3	5.00	SPR	CG	Z
0.500	12.70	12325	.81	20.6	.392	10.0	34	6.0	.33	8.3	11	50	.32	8.2	0.054	1.4	6.00	SPR	CG	Z
0.500	12.70	K-47	.81	20.6	.340	8.6	138	24	.23	5.8	31	140	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.500	12.70	10323	.81	20.6	.316	8.0	337	59	.14	3.6	48	214	.60	15.2	0.092	2.3	6.50	SPR	CG	Z
0.500	12.70	A15-40	.84	21.4	.432	11.0	3.7	.66	.62	16	2.3	10	.22	5.6	0.034	0.9	6.50	SST	CG	N
0.500	12.70	J-62	.84	21.4	.372	9.4	86	15	.21	5.5	19	82	.41	10.4	0.064	1.6	5.25	SPR	C	Z
0.500	12.70	10836	.88	22.2	.464	11.8	.16	.03	.69	17	.11	.49	.19	4.8	0.018	0.5	9.50	SST	C	N
0.500	12.70	B14-52	.88	22.2	.414	10.5	13	2.3	.44	11	5.8	26	.28	7.1	0.043	1.1	5.50	SST	C	N
0.500	12.70	S-1411	.88	22.2	.410	10.4	9.1	1.6	.47	12	4.3	19	.41	10.3	0.045	1.1	8.00	SST	C	N
0.500	12.70	N-135	.88	22.2	.400	10.2	25	4.3	.36	9.2	9.0	40	.30	7.6	0.050	1.3	6.00	SPR	CG	Z
0.500	12.70	S-757	.88	22.2	.390	9.9	32	5.7	.34	8.7	11	50	.39	9.8	0.055	1.4	6.00	SST	C	N
0.500	12.70	A11-40	.88	22.2	.386	9.8	44	7.6	.30	7.7	13	59	.34	8.7	0.057	1.4	6.00	SPR	CG	GI
0.500	12.70	3810	.88	22.2	.380	9.7	44	7.7	.35	8.9	15	68	.42	10.7	0.060	1.5	7.00	SPR	CG	GI
0.500	12.70	S-761	.88	22.2	.374	9.5	56	9.7	.30	7.6	17	74	.46	11.6	0.063	1.6	6.25	SST	C	N
0.500	12.70	MM-40	.88	22.2	.372	9.4	73	13	.25	6.5	19	82	.38	9.8	0.064	1.6	6.00	SPR	CG	N
0.500	12.70	L-48	.88	22.2	.340	8.6	159	28	.21	5.4	34	149	.64	16.3	0.080	2.0	7.00	SPR	CG	Z
0.500	12.70	Z-63	.88	22.2	.300	7.6	488	86	.12	2.9	57	252	.60	15.2	0.100	2.5	6.00	SST	CG	N
0.500	12.70	GG-39	.88	22.2	.280	7.1	887	155	.09	2.2	77	343	.66	16.8	0.110	2.8	6.00	SPR	CG	Z
0.500	12.70	2819	.88	22.2	.230	5.8	2455	430	.05	1.3	130	579	.81	20.6	0.135	3.4	6.00	SPR	CG	Z
0.500	12.70	A10-49	.89	22.6	.372	9.4	36	6.4	.25	6.4	9.1	40	.64	16.3	0.064	1.6	10.0	SPR	CG	Z
0.500	12.70	A9-31	.91	23.0	.460	11.7	.26	.05	.71	18	.19	.83	.20	5.1	0.020	0.5	9.00	SST	C	N
0.500	12.70	S-390	.91	23.0	.428	10.9	5.4	.94	.64	16	3.4	15	.22	5.5	0.036	0.9	6.00	SST	CG	N
0.500	12.70	S-1482	.91	23.0	.398	10.1	19	3.3	.48	12	9.0	40	.36	9.1	0.051	1.3	7.00	SST	CG	N
0.500	12.70	A15-30	.92	23.4	.420	10.7	10	1.8	.45	11	4.7	21	.21	5.3	0.040	1.0	5.25	SST	CG	N
0.500	12.70	A14-40	.94	23.8	.416	10.6	12	2.1	.46	12	5.4	24	.23	5.9	0.042	1.1	5.50	SST	CG	N
0.500	12.70	A14-61	.94	23.8	.406	10.3	21	3.6	.39	9.9	8.0	36	.27	6.8	0.047	1.2	5.75	SPR	CG	Z
0.500	12.70	S-1510	.94	23.8	.392	10.0	20	3.5	.45	11	9.0	40	.49	12.3	0.054	1.4	8.00	SST	C	N
0.500	12.70	10669	.94	23.8	.318	8.1	360	63	.13	3.3	47	208	.64	16.2	0.091	2.3	6.00	SPR	C	Z
0.500	12.70	L-31	.94	23.8	.300	7.6	372	65	.15	3.9	57	252	.73	18.4	0.100	2.5	7.25	SST	CG	N
0.500	12.70	A14-37	.97	24.6	.412	10.5	15	2.7	.44	11	6.6	29	.25	6.4	0.044	1.1	5.75	SPR	CG	N
0.500	12.70	O-38	.97	24.6	.380	9.7	24	4.2	.37	9.3	8.7	39	.60	15.2	0.060	1.5	10.0	SST	CG	N
0.500	12.70	NN-83	.97	24.6	.340	8.6	144	25	.23	5.9	34	149	.60	15.2	0.080	2.0	7.50	SPR	CG	Z
0.500	12.70	3953	1.00	25.4	.444	11.3	1.4	.25	.78	20	1.1	4.8	.22	5.7	0.028	0.7	8.00	MW	CG	Z
0.500	12.70	GG-95	1.00	25.4	.432	11.0	4.7	.83	.63	16	3.0	13	.22	5.6	0.034	0.9	5.50	SST	C	N
0.500	12.70	YY-35	1.00	25.4	.426	10.8	6.7	1.2	.55	14	3.7	16	.20	5.2	0.037	0.9	5.50	SST	CG	N
0.500	12.70	MM-89	1.00	25.4	.424	10.8	8.7	1.5	.68	17	5.9	26	.25	6.3	0.038	1.0	5.50	MW	C	N
0.500	12.70	WW-35	1.00	25.4	.424	10.8	7.6	1.3	.56	14	4.3	19	.27	6.8	0.038	1.0	6.00	SPR	C	Z
0.500	12.70	10056	1.00	25.4	.422	10.7	9.7	1.7	.48	12	4.6	21	.25	6.5	0.039	1.0	5.50	SPR	CG	GI
0.500	12.70	10326	1.00	25.4	.422	10.7	9.7	1.7	.66	17	6.4	28	.25	6.5	0.039	1.0	5.50	MW	C	GI
0.500	12.70	Z-45	1.00	25.4	.418	10.6	6.5	1.1	.61	16	3.9	18	.39	9.9	0.041	1.0	8.50	SPR	C	Z
0.500	12.70	S-755	1.00	25.4	.416	10.6	10	1.8	.53	14	5.4	24	.29	7.5	0.042	1.1	6.00	SST	C	N
0.500	12.70	A11-44	1.00	25.4	.416	10.6	13	2.3	.43	11	5.7	26	.23	5.9	0.042	1.1	5.50	SPR	CG	GI
0.500	12.70	10020	1.00	25.4	.414	10.5	15	2.6	.42	11	6.2	27	.24	6.0	0.043	1.1	5.50	SPR	CG	Z
0.500	12.70	A13-7	1.00	25.4	.408	10.4	17	3.0	.44	11	7.5	33	.28	7.0	0.046	1.2	6.00	SPR	CG	N
0.500	12.70	3635	1.00	25.4	.406	10.3	13	2.2	.62	16	7.8	35	.38	9.6	0.047	1.2	8.00	HD	CG	Z
0.500	12.70	S-1479	1.00	25.4	.406	10.3	15	2.6	.51	13	7.5	33	.35	9.0	0.047	1.2	6.50	SST	C	N
0.500	12.70	10069	1.00	25.4	.404	10.3	18	3.2	.46	12	8.5	38	.36	9.1	0.048	1.2	6.50	SPR	C	Z
0.500	12.70	Q-10	1.00	25.4	.400	10.2	22	3.8	.41	10	9.0	40	.38	9.5	0.050	1.3	6.50	SPR	C	Z
0.500	12.70	10041	1.00	25.4	.398	10.1	13	2.4	.44	11	5.9	26	.56	14.2	0.051	1.3	10.0	SPR	C	Z
0.500	12.70	2976	1.00	25.4	.392	10.0	23	4.0	.49	12	11	50	.43	11.0	0.054	1.4	8.00	SPR	CG	Z
0.500	12.70	10146	1.00	25.4	.390	9.9	31	5.5	.38	9.6	12	53	.37	9.4	0.055	1.4	6.75	SPR	CG	Z
0.500	12.70	S-758	1.00	25.4	.390	9.9	27	4.8	.41	10	11	50	.43	10.8	0.055	1.4	6.75	SST	C	N
0.500	12.70	510	1.00	25.4	.376	9.6	45	7.8	.38	9.6	17	75	.54	13.6	0.062	1.6	7.75	HD	C	Z
0.500	12.70	S-762	1.00	25.4	.374	9.5	47	8.3	.35	9.0	17	74	.50	12.8	0.063	1.6	7.00	SST	C	N
0.500	12.70	3821	1.00	25.4	.366	9.3	55	9.6	.39	9.8	21	94	.57	14.5	0.067	1.7	8.50	SPR	CG	Z
0.500	12.70	3897	1.00	25.4	.356	9.0	82	14	.30	7.7	25	110	.58	14.6	0.072	1.8	8.00	HD	CG	Z
0.500	12.70	2994	1.00	25.4	.350	8.9	118	21	.24	6.0	28	124	.53	13.3	0.075	1.9	7.00	SPR	CG	Z
0.500	12.70	3834	1.00	25.4	.336	8.5	148	26	.24	6.2	36	160	.66	16.7	0.082	2.1	8.00	SPR	CG	GI
0.500	12.70	S-498	1.03	26.2	.420	10.7	8.2	1.4	.57	14	4.7	21	.28	7.1	0.040	1.0	6.00	SST	C	N
0.500	12.70	10093	1.03	26.2	.250	6.4	1331	233	.08	2.1	109	486	.88	22.2	0.125	3.2	7.00	SPR	CG	Z
0.500	12.70	12170	1.06	27.0	.436	11.1	2.9	.52	.84	21	2.5	11	.22	5.7	0.032	0.8	7.00	SPR	CG	N
0.500	12.70	1725	1.06	27.0	.398	10.1	13	2.4	.55	14	7.4	33	.51	13.0	0.051	1.3	10.0	SPR	CG	Z
0.500	12.70	3809	1.06	27.0	.380	9.7	27	4.8	.46	12	13	56	.60	15.2	0.060	1.5	10.0	SPR	CG	Z
0.500	12.70	NN-97	1.09	27.8	.422	10.7	8.5	1.5	.54	14	4.6	21	.23	5.9	0.039	1.0	6.00	SPR	CG	Z
0.500	12.70	M-101	1.09	27.8	.410	10.4	4.9	.87	.51	13	2.5	11	.59	14.9	0.045	1.1	13.0	SST	CG	N
0.500	12.70	A14-8	1.09	27.8	.408	10.4	14	2.4	.52	13	7.0	31	.30	7.6	0.046	1.2	6.50	SST	CG	N
0.500	12.70	2961	1.13	28.6	.440	11.2	.94	.17	.68	17	.64	2.9	.45	11.3	0.030	0.8	14.0	MW	C	Z

CENTURY SPRINGS PTY. LTD.

213·749·1466 800·237·5225 FAX 213·749·3802

MATERIAL: MW - Music Wire; SPR - Spring Steel; **HD** - Hard Drawn; **OT** - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.500	12.70	S-1392	1.13	28.6	.422	10.7	6.9	1.2	.62	16	4.3	19	.24	6.2	0.039	1.0	6.25	SST	CG	N
0.500	12.70	S-3154	1.13	28.6	.412	10.5	16	2.9	.37	9.5	6.2	27	.26	6.7	0.044	1.1	5.00	SST	C	N
0.500	12.70	S-90	1.13	28.6	.410	10.4	19	3.2	.36	9.1	6.6	29	.27	6.9	0.045	1.1	5.00	SST	C	N
0.500	12.70	12472	1.13	28.6	.400	10.2	16	2.9	.55	14	9.0	40	.45	11.4	0.050	1.3	8.00	SPR	C	Z
0.500	12.70	S-803	1.13	28.6	.378	9.6	30	5.3	.50	13	15	67	.53	13.6	0.061	1.5	8.75	SST	CG	N
0.500	12.70	11395	1.13	28.6	.376	9.6	33	5.7	.52	13	17	75	.60	15.4	0.062	1.6	9.75	HD	CG	Z
0.500	12.70	B7-66	1.13	28.6	.340	8.6	159	28	.21	5.4	34	149	.64	16.3	0.080	2.0	7.00	SPR	C	N
0.500	12.70	3748	1.13	28.6	.290	7.4	420	74	.17	4.2	70	311	.92	23.3	0.105	2.7	8.75	SPR	CG	Z
0.500	12.70	S-112	1.13	28.6	.230	5.8	1708	299	.07	1.7	117	521	.95	24.0	0.135	3.4	7.00	SST	CG	N
0.500	12.70	12650	1.14	29.0	.410	10.4	10	1.8	.68	17	7.0	31	.36	9.1	0.045	1.1	8.00	SPR	CG	N
0.500	12.70	S-328	1.16	29.4	.438	11.1	1.6	.28	.84	21	1.3	5.9	.32	8.1	0.031	0.8	9.25	SST	C	N
0.500	12.70	S-499	1.16	29.4	.422	10.7	7.4	1.3	.59	15	4.3	19	.23	5.9	0.039	1.0	6.00	SST	CG	N
0.500	12.70	12632	1.17	29.7	.406	10.3	13	2.2	.79	20	10	44	.38	9.6	0.047	1.2	8.00	MW	CG	N
0.500	12.70	3491	1.19	30.2	.446	11.3	1.4	.25	.97	25	1.4	6.2	.22	5.5	0.027	0.7	7.00	MW	C	Z
0.500	12.70	W-100	1.19	30.2	.430	10.9	4.1	.73	.76	19	3.1	14	.26	6.7	0.035	0.9	6.50	SST	C	N
0.500	12.70	10774	1.19	30.2	.412	10.5	11	2.0	.58	15	6.6	29	.31	7.8	0.044	1.1	7.00	SPR	CG	Z
0.500	12.70	S-1	1.19	30.2	.406	10.3	9.6	1.7	.77	19	7.3	33	.42	10.7	0.047	1.2	9.00	SST	CG	N
0.500	12.70	S-922	1.19	30.2	.374	9.5	30	5.3	.50	13	15	66	.69	17.6	0.063	1.6	10.0	SST	C	N
0.500	12.70	FF-97	1.19	30.2	.260	6.6	836	146	.12	3.0	98	435	1.02	25.9	0.120	3.0	8.50	SPR	CG	Z
0.500	12.70	II-91	1.22	31.0	.440	11.2	1.4	.25	.92	23	1.3	5.7	.30	7.6	0.030	0.8	10.0	MW	CG	N
0.500	12.70	LL-28	1.22	31.0	.360	9.1	47	8.2	.46	12	21	95	.72	18.2	0.070	1.8	10.3	SST	CG	N
0.500	12.70	A14-59	1.23	31.3	.420	10.7	8.7	1.5	.57	14	5.0	22	.25	6.4	0.040	1.0	6.25	SPR	CG	Z
0.500	12.70	3619	1.25	31.8	.442	11.2	.97	.17	.87	22	.85	3.8	.38	9.6	0.029	0.7	12.0	MW	C	Z
0.500	12.70	3755	1.25	31.8	.440	11.2	3.2	.56	.96	24	3.1	14	.20	5.0	0.030	0.8	5.50	MW	C	Z
0.500	12.70	S-756	1.25	31.8	.416	10.6	8.1	1.4	.66	17	5.4	24	.34	8.5	0.042	1.1	7.00	SST	C	N
0.500	12.70	3787	1.25	31.8	.410	10.4	13	2.2	.56	14	7.0	31	.36	9.1	0.045	1.1	7.00	SPR	C	Z
0.500	12.70	RR-70	1.25	31.8	.402	10.2	9.8	1.7	.76	19	7.5	33	.49	12.4	0.049	1.2	10.0	SST	CG	N
0.500	12.70	S-759	1.25	31.8	.390	9.9	21	3.6	.54	14	11	50	.51	12.9	0.055	1.4	8.25	SST	C	N
0.500	12.70	3512	1.25	31.8	.374	9.5	39	6.8	.62	16	24	107	.63	16.0	0.063	1.6	9.00	MW	C	Z
0.500	12.70	S-763	1.25	31.8	.374	9.5	35	6.1	.48	12	17	74	.61	15.6	0.063	1.6	8.75	SST	C	N
0.500	12.70	12197	1.25	31.8	.352	8.9	93	16	.29	7.3	27	119	.67	16.9	0.074	1.9	8.00	SPR	C	Z
0.500	12.70	EE-79	1.25	31.8	.340	8.6	93	16	.36	9.1	34	149	.84	21.3	0.080	2.0	10.5	SPR	CG	Z
0.500	12.70	Y-36	1.31	33.3	.440	11.2	1.4	.25	1.0	26	1.4	6.3	.30	7.6	0.030	0.8	10.0	MW	CG	Z
0.500	12.70	3863	1.31	33.3	.422	10.7	5.7	.99	.82	21	4.6	21	.35	8.9	0.039	1.0	8.00	SPR	C	Z
0.500	12.70	FF-82	1.31	33.3	.400	10.2	9.9	1.7	.66	17	6.5	29	.65	16.5	0.050	1.3	12.0	SPR	C	Z
0.500	12.70	L-62	1.31	33.3	.372	9.4	29	5.1	.54	14	16	70	.77	19.5	0.064	1.6	12.0	SPR	CG	Z
0.500	12.70	H-87	1.31	33.3	.340	8.6	77	13	.41	10	31	140	.88	22.4	0.080	2.0	11.0	SST	CG	N
0.500	12.70	1605	1.38	34.9	.454	11.5	.44	.08	1.1	28	.48	2.2	.27	6.7	0.023	0.6	10.5	MW	C	Z
0.500	12.70	10181	1.38	34.9	.446	11.3	.90	.16	1.1	27	.97	4.3	.30	7.5	0.027	0.7	10.0	MW	C	N
0.500	12.70	11347	1.38	34.9	.444	11.3	1.2	.22	1.1	29	1.4	6.2	.25	6.4	0.028	0.7	8.00	SST	C	N
0.500	12.70	I-34	1.38	34.9	.436	11.1	.95	.17	.85	22	.80	3.6	.53	13.4	0.032	0.8	15.5	SST	C	N
0.500	12.70	S-1399	1.38	34.9	.426	10.8	4.7	.83	.78	20	3.7	16	.26	6.6	0.037	0.9	7.00	SST	C	N
0.500	12.70	A15-32	1.38	34.9	.416	10.6	7.5	1.3	.72	18	5.4	24	.36	9.1	0.042	1.1	7.50	SST	C	N
0.500	12.70	YY-29	1.38	34.9	.402	10.2	9.0	1.6	.74	19	6.7	30	.64	16.2	0.049	1.2	12.0	SPR	C	Z
0.500	12.70	XX-70	1.38	34.9	.400	10.2	12	2.2	.73	18	9.0	40	.50	12.7	0.050	1.3	10.0	SPR	CG	Z
0.500	12.70	4161	1.38	34.9	.398	10.1	13	2.4	.71	18	9.5	42	.51	13.0	0.051	1.3	10.0	SPR	CG	Z
0.500	12.70	3242	1.38	34.9	.396	10.1	12	2.0	.75	19	8.8	39	.62	15.8	0.052	1.3	12.0	SPR	CG	Z
0.500	12.70	503	1.38	34.9	.356	9.0	58	10	.43	11	25	110	.83	21.0	0.072	1.8	10.5	HD	C	Z
0.500	12.70	A15-50	1.41	35.7	.406	10.3	14	2.4	.58	15	8.0	36	.35	9.0	0.047	1.2	7.50	SPR	CG	GI
0.500	12.70	K-49	1.44	36.5	.450	11.4	.87	.15	1.2	31	1.1	4.7	.23	5.7	0.025	0.6	8.00	MW	C	N
0.500	12.70	S-1292	1.44	36.5	.406	10.3	12	2.1	.63	16	7.5	33	.40	10.1	0.047	1.2	7.50	SST	C	N
0.500	12.70	10135	1.50	38.1	.424	10.8	5.5	.97	.77	20	4.3	19	.32	8.2	0.038	1.0	7.50	SPR	C	Z
0.500	12.70	S-1293	1.50	38.1	.424	10.8	5.0	.88	.79	20	4.0	18	.28	7.0	0.038	1.0	7.25	SST	CG	N
0.500	12.70	11745	1.50	38.1	.424	10.8	6.1	1.1	.70	18	4.3	19	.27	6.8	0.038	1.0	7.00	SPR	CG	Z
0.500	12.70	3878	1.50	38.1	.420	10.7	7.6	1.3	.66	17	5.0	22	.32	8.1	0.040	1.0	7.00	SPR	C	Z
0.500	12.70	521	1.50	38.1	.418	10.6	5.3	.92	1.0	26	5.4	24	.45	11.5	0.041	1.0	10.0	HD	C	Z
0.500	12.70	B6-1	1.50	38.1	.418	10.6	6.8	1.2	.74	19	5.0	22	.35	8.9	0.041	1.0	7.50	SST	C	N
0.500	12.70	S-1290	1.50	38.1	.418	10.6	6.4	1.1	.79	20	5.0	22	.32	8.1	0.041	1.0	7.75	SST	CG	N
0.500	12.70	S-1296	1.50	38.1	.418	10.6	4.1	.71	1.0	27	4.3	19	.45	11.5	0.041	1.0	11.0	SST	CG	N
0.500	12.70	S-806	1.50	38.1	.418	10.6	4.1	.72	1.0	27	4.3	19	.45	11.5	0.041	1.0	11.0	SST	CG	N
0.500	12.70	10081	1.50	38.1	.418	10.6	7.3	1.3	.73	19	5.4	24	.32	8.1	0.041	1.0	7.75	SPR	CG	GI
0.500	12.70	S-122	1.50	38.1	.406	10.3	8.2	1.4	.91	23	7.5	33	.47	11.9	0.047	1.2	10.0	SST	CG	N
0.500	12.70	S-247	1.50	38.1	.396	10.1	14	2.4	.70	18	9.5	42	.49	12.5	0.052	1.3	9.50	SST	CG	N
0.500	12.70	11421	1.50	38.1	.396	10.1	11	1.9	.85	22	9.5	42	.65	16.5	0.052	1.3	12.5	HD	CG	Z
0.500	12.70	S-243	1.50	38.1	.392	10.0	17	3.0	.62	16	11	47	.49	12.3	0.054	1.4	9.00	SST	CG	N
0.500	12.70	10059	1.50	38.1	.390	9.9	20	3.5	.60	15	12	53	.52	13.3	0.055	1.4	9.50	SPR	CG	GI
0.500	12.70	S-760	1.50	38.1	.390	9.9	17	2.9	.67	17	11	50	.59	15.0	0.055	1.4	9.75	SST	C	N
0.500	12.70	2536	1.50	38.1	.374	9.5	34	5.9	.52	13	18	79	.63	16.0	0.063	1.6	10.0	SPR	CG	Z
0.500	12.70	3944	1.50	38.1	.374	9.5	29	5.1	.60	15	18	79	.71	18.0	0.063	1.6	11.3	SPR	CG	Z
0.500	12.70	S-764	1.50	38.1	.374	9.5	29	5.0	.58	15	17	74	.71	18.0	0.063	1.6	10.3	SST	C	N
0.500	12.70	K-56	1.50	38.1	.356	9.0	55	9.6	.45	11	25	110	.79	20.1	0.072	1.8	11.0	SPR	CG	Z
0.500	12.70	3080	1.50	38.1	.332	8.4	114	20	.34	8.6	39	172	.90	22.9	0.084	2.1	10.8	SPR	CG	Z
0.500	12.70	J-30	1.50	38.1	.332	8.4	153	27	.25	6.4	39	172	.71	18.1	0.084	2.1	8.50	SPR	CG	Z
0.500	12.70	4229	1.50	38.1	.212	5.4	1957	343	.08	2.0	154	683	1.30	32.9	0.144	3.7	9.00	SPR	CG	N
0.500	12.70	S-384	1.56	39.7	.452	11.5	.39	.07	1.3	32	.49	2.2	.31	7.8	0.024	0.6	12.0	SST	C	N
0.500	12.70	12252	1.56	39.7	.390	9.9	19	3.3	.64	16	12	53	.55	14.0	0.055	1.4	10.0	SPR	CG	Z
0.500	12.70	3040	1.56	39.7	.380	9.7	25	4.3	.62	16	15	68	.65	16.6	0.060	1.5	11.0	SPR	CG	Z
0.500	12.70	4201	1.56	39.7	.318	8.1	175	31	.27	6.8	47	208	.93	23.7	0.091	2.3	10.3	SPR	CG	BO
0.500	12.70	S-193	1.59	40.5	.434	11.0	3.0	.52	.92	23	2.7	12	.26	6.7	0.033	0.8	7.00	SST	C	N
0.500	12.70	BB-58	1.63	41.3	.440	11.2	1.9	.33	1.4	35	2.6	12	.24	6.1	0.030	0.8	8.00	MW	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.500	12.70	S-3100	1.63	41.3	.436	11.1	2.3	.41	1.1	27	2.5	11	.27	6.9	0.032	0.8	7.50	SST	C	N
0.500	12.70	F-53	1.63	41.3	.426	10.8	1.8	.32	1.0	25	1.8	8.0	.63	16.0	0.037	0.9	17.0	SPR	CG	Z
0.500	12.70	HH-56	1.63	41.3	.416	10.6	6.2	1.1	.93	24	5.7	26	.44	11.2	0.042	1.1	9.50	SPR	C	Z
0.500	12.70	4124	1.63	41.3	.392	10.0	20	3.4	.57	15	11	50	.54	13.7	0.054	1.4	9.00	SPR	C	Z
0.500	12.70	12189	1.63	41.3	.386	9.8	17	3.0	.78	20	13	59	.70	17.9	0.057	1.4	12.3	SPR	CG	Z
0.500	12.70	S-1365	1.63	41.3	.384	9.8	13	2.2	.70	18	8.8	39	.93	23.6	0.058	1.5	15.0	SST	C	N
0.500	12.70	3364	1.63	41.3	.366	9.3	40	6.9	.53	14	21	94	.80	20.4	0.067	1.7	11.0	SPR	C	Z
0.500	12.70	11159	1.66	42.1	.330	8.4	100	18	.40	10	40	178	1.06	27.0	0.085	2.2	12.5	SPR	CG	Z
0.500	12.70	B14-55	1.69	42.8	.410	10.4	6.3	1.1	1.1	29	7.0	31	.54	13.7	0.045	1.1	12.0	SPR	CG	N
0.500	12.70	A10-58	1.72	43.6	.394	10.0	13	2.2	.84	21	11	47	.64	16.2	0.053	1.3	12.0	SPR	CG	N
0.500	12.70	QQ-58	1.75	44.5	.420	10.7	3.4	.60	1.2	30	4.1	18	.56	14.2	0.040	1.0	13.0	MW	C	Z
0.500	12.70	511	1.75	44.5	.376	9.6	24	4.1	.72	18	17	75	.85	21.7	0.062	1.6	12.8	HD	C	Z
0.500	12.70	JJ-89	1.75	44.5	.368	9.3	34	6.0	.59	15	20	90	.84	21.4	0.066	1.7	11.8	SPR	C	N
0.500	12.70	359	1.75	44.5	.356	9.0	43	7.6	.57	14	25	110	1.03	26.2	0.072	1.8	13.3	HD	C	Z
0.500	12.70	11582	1.75	44.5	.354	9.0	48	8.3	.54	14	26	115	1.02	26.0	0.073	1.9	13.0	SPR	CG	N
0.500	12.70	10311	1.81	46.0	.384	9.8	13	2.2	.84	21	11	48	.97	24.7	0.058	1.5	16.8	SPR	CG	Z
0.500	12.70	K-99	1.81	46.0	.356	9.0	35	6.2	.66	17	23	103	1.15	29.3	0.072	1.8	16.0	SPR	CG	GI
0.500	12.70	B14-69	1.84	46.8	.322	8.2	144	25	.32	8.0	46	203	.98	24.9	0.089	2.3	11.0	SPR	CG	Z
0.500	12.70	QQ-53	1.88	47.6	.406	10.3	6.3	1.1	1.2	30	7.4	33	.71	17.9	0.047	1.2	14.0	HD	C	Z
0.500	12.70	3580	1.88	47.6	.396	10.1	8.9	1.6	1.1	28	9.7	43	.79	20.0	0.052	1.3	15.0	HD	CG	Z
0.500	12.70	A12-40	1.88	47.6	.394	10.0	11	1.8	.95	24	10	45	.66	16.8	0.053	1.3	12.5	SST	CG	N
0.500	12.70	3608	1.88	47.6	.392	10.0	9.2	1.6	.90	23	8.3	37	.97	24.7	0.054	1.4	17.0	SPR	C	Z
0.500	12.70	10384	1.88	47.6	.380	9.7	15	2.6	.80	20	12	52	1.08	27.4	0.060	1.5	17.0	SPR	C	Z
0.500	12.70	11772	1.91	48.4	.440	11.2	1.4	.25	1.6	41	2.3	10	.30	7.6	0.030	0.8	10.0	MW	CG	GI
0.500	12.70	10603	1.91	48.4	.392	10.0	14	2.4	.82	21	11	50	.65	16.5	0.054	1.4	12.0	SPR	CG	Z
0.500	12.70	12317	1.91	48.4	.374	9.5	32	5.6	.55	14	18	79	.72	18.4	0.063	1.6	10.5	SPR	C	Z
0.500	12.70	12724	1.92	48.8	.438	11.1	1.6	.28	1.6	41	2.6	12	.31	7.9	0.031	0.8	10.0	MW	CG	GI
0.500	12.70	4232	1.94	49.2	.356	9.0	55	9.6	.45	11	25	110	.86	21.9	0.072	1.8	11.0	SPR	C	Z
0.500	12.70	K-53	1.97	50.0	.406	10.3	5.6	.98	1.2	31	6.9	31	.73	18.5	0.047	1.2	15.5	SPR	CG	Z
0.500	12.70	FF-55	2.00	50.8	.424	10.8	2.6	.46	1.5	38	4.0	18	.49	12.5	0.038	1.0	12.0	SST	C	N
0.500	12.70	B10-63	2.00	50.8	.420	10.7	4.7	.83	1.1	27	5.0	22	.44	11.2	0.040	1.0	10.0	SPR	C	Z
0.500	12.70	3994	2.00	50.8	.418	10.6	3.0	.53	1.3	33	3.9	17	.70	17.7	0.041	1.0	16.0	SPR	C	Z
0.500	12.70	O-95	2.00	50.8	.408	10.4	5.1	.89	1.3	33	6.6	29	.71	18.1	0.046	1.2	15.5	SPR	CG	Z
0.500	12.70	15	2.00	50.8	.406	10.3	7.2	1.3	1.1	28	8.0	36	.64	16.1	0.047	1.2	12.5	HD	C	Z
0.500	12.70	2721	2.00	50.8	.406	10.3	5.8	1.0	1.2	32	7.2	32	.75	19.1	0.047	1.2	15.0	HD	C	Z
0.500	12.70	AA-87	2.00	50.8	.400	10.2	5.9	1.0	1.2	30	6.9	31	.83	21.0	0.050	1.3	16.5	SST	CG	N
0.500	12.70	12233	2.00	50.8	.388	9.9	13	2.3	.97	25	13	56	.81	20.6	0.056	1.4	14.5	SPR	CG	GI
0.500	12.70	3004	2.00	50.8	.376	9.6	24	4.2	.70	18	17	75	.78	19.7	0.062	1.6	12.5	SPR	CG	Z
0.500	12.70	S-765	2.00	50.8	.374	9.5	21	3.6	.81	21	17	74	.91	23.2	0.063	1.6	13.5	SST	C	N
0.500	12.70	4215	2.00	50.8	.372	9.4	34	6.0	.54	14	19	82	.74	18.7	0.064	1.6	10.5	SPR	C	Z
0.500	12.70	504	2.00	50.8	.356	9.0	38	6.6	.65	17	25	110	1.15	29.3	0.072	1.8	15.0	HD	C	Z
0.500	12.70	2652	2.03	51.6	.462	11.7	.14	.02	1.7	44	.24	1.1	.29	7.4	0.019	0.5	14.3	MW	C	T
0.500	12.70	3160	2.03	51.6	.362	9.2	28	4.9	.82	21	23	103	1.14	28.9	0.069	1.8	16.5	SPR	CG	Z
0.500	12.70	12684	2.06	52.4	.330	8.4	91	16	.61	16	56	249	1.15	29.2	0.085	2.2	13.5	MW	CG	Z
0.500	12.70	S-39	2.13	54.0	.406	10.3	3.1	.53	1.0	26	3.1	14	1.10	28.1	0.047	1.2	23.5	SST	CG	N
0.500	12.70	3558	2.13	54.0	.402	10.2	11	2.0	1.1	28	13	56	.49	12.4	0.049	1.2	10.0	MW	CG	Z
0.500	12.70	Q-61-A	2.13	54.0	.388	9.9	10	1.8	1.1	29	12	52	.87	22.0	0.056	1.4	15.5	SST	CG	N
0.500	12.70	10033	2.19	55.6	.312	7.9	124	22	.41	10	51	228	1.46	37.0	0.094	2.4	15.5	SPR	CG	Z
0.500	12.70	YY-62	2.25	57.2	.460	11.7	.23	.04	2.0	52	.46	2.0	.22	5.6	0.020	0.5	10.0	SST	C	N
0.500	12.70	4322	2.25	57.2	.340	8.6	69	12	.49	12	34	149	1.08	27.4	0.080	2.0	13.5	SPR	CG	Z
0.500	12.70	12020	2.31	58.7	.398	10.1	13	2.4	.71	18	9.5	42	.51	13.0	0.051	1.3	10.0	SPR	CG	Z
0.500	12.70	3776	2.31	58.7	.356	9.0	32	5.6	.78	20	25	110	1.26	32.0	0.072	1.8	17.5	HD	CG	GI
0.500	12.70	J-34	2.31	58.7	.356	9.0	58	10	.43	11	25	110	.76	19.2	0.072	1.8	10.5	HD	CG	Z
0.500	12.70	3159	2.38	60.3	.372	9.4	20	3.6	.91	23	19	82	1.04	26.4	0.064	1.6	16.3	SPR	CG	Z
0.500	12.70	10042	2.38	60.3	.366	9.3	34	6.0	.62	16	21	94	.90	23.0	0.067	1.7	12.5	SPR	C	Z
0.500	12.70	4266	2.44	61.9	.376	9.6	17	3.0	.98	25	17	75	1.04	26.4	0.062	1.6	16.8	SPR	CG	Z
0.500	12.70	12599	2.50	63.5	.424	10.8	3.0	.53	1.9	49	5.9	26	.49	12.5	0.038	1.0	12.0	MW	C	T
0.500	12.70	EE-59	2.50	63.5	.400	10.2	13	2.3	.68	17	9.0	40	.48	12.1	0.050	1.3	9.50	SPR	CG	N
0.500	12.70	24	2.50	63.5	.376	9.6	16	2.8	1.1	27	17	75	1.18	29.9	0.062	1.6	18.0	HD	C	Z
0.500	12.70	3035	2.50	63.5	.376	9.6	21	3.7	.80	20	17	75	.87	22.0	0.062	1.6	14.0	SPR	CG	Z
0.500	12.70	S-1133	2.50	63.5	.376	9.6	13	2.3	1.2	31	16	71	1.24	31.5	0.062	1.6	19.0	SST	C	N
0.500	12.70	11928	2.50	63.5	.356	9.0	38	6.6	.65	17	25	110	1.08	27.4	0.072	1.8	15.0	SPR	CG	Z
0.500	12.70	12287	2.53	64.3	.376	9.6	17	3.0	1.0	25	17	75	1.12	28.3	0.062	1.6	17.0	SPR	C	Z
0.500	12.70	12302	2.59	65.9	.424	10.8	2.1	.37	2.0	50	4.1	18	.63	15.9	0.038	1.0	16.5	SPR	CG	Z
0.500	12.70	11843	2.63	66.7	.426	10.8	1.5	.26	2.0	50	2.9	13	.67	16.9	0.037	0.9	18.0	SST	CG	N
0.500	12.70	2601	2.63	66.7	.416	10.6	3.6	.63	2.0	51	7.1	32	.63	16.0	0.042	1.1	15.0	MW	CG	Z
0.500	12.70	1645	2.63	66.7	.406	10.3	4.9	.85	1.6	42	8.0	36	.82	20.9	0.047	1.2	17.5	SPR	CG	Z
0.500	12.70	3256	2.63	66.7	.376	9.6	14	2.5	1.2	31	17	75	1.30	33.1	0.062	1.6	20.0	HD	C	Z
0.500	12.70	3741	2.63	66.7	.376	9.6	14	2.4	1.2	31	17	75	1.32	33.5	0.062	1.6	20.3	HD	C	GI
0.500	12.70	1793	2.75	69.9	.376	9.6	19	3.3	.90	23	17	75	.96	24.4	0.062	1.6	15.5	HD	CG	Z
0.500	12.70	11	2.75	69.9	.356	9.0	28	4.9	.88	22	25	110	1.48	37.5	0.072	1.8	19.5	HD	C	Z
0.500	12.70	M-77	2.81	71.4	.300	7.6	102	18	.41	10	42	187	2.40	61.0	0.100	2.5	24.0	SPR	CG	Z
0.500	12.70	4110	2.88	73.0	.374	9.5	15	2.6	1.2	30	18	79	1.32	33.6	0.063	1.6	20.0	SPR	C	Z
0.500	12.70	11033	2.88	73.0	.340	8.6	50	8.8	.67	17	34	149	1.50	38.1	0.080	2.0	17.8	HD	CG	Z
0.500	12.70	2918	2.97	75.4	.372	9.4	20	3.6	.91	23	19	82	1.11	28.2	0.064	1.6	16.3	SPR	C	Z
0.500	12.70	11876	3.00	76.2	.410	10.4	3.1	.55	2.0	51	6.3	28	.99	25.1	0.045	1.1	22.0	SPR	CG	N
0.500	12.70	10	3.00	76.2	.406	10.3	4.6	.80	1.7	43	7.8	35	.90	22.9	0.047	1.2	18.3	HD	C	Z
0.500	12.70	2751	3.00	76.2	.404	10.3	6.4	1.1	1.3	34	8.5	38	.77	19.5	0.048	1.2	15.0	HD	C	Z
0.500	12.70	3231	3.00	76.2	.404	10.3	3.8	.67	1.8	46	7.0	31	1.18	29.9	0.048	1.2	23.5	SPR	C	Z
0.500	12.70	3819	3.00	76.2	.366	9.3	21	3.7	1.0	26	21	94	1.27	32.3	0.067	1.7	19.0	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; **HD** - Hard Drawn; **OT** - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.500	12.70	HH-82	3.25	82.6	.400	10.2	5.5	.96	1.6	42	9.0	40	1.00	25.4	0.050	1.3	20.0	SPR	CG	GI
0.500	12.70	12123	3.28	83.3	.372	9.4	15	2.5	1.3	32	19	82	1.41	35.8	0.064	1.6	22.0	SPR	CG	GI
0.500	12.70	S-1238	3.69	93.6	.372	9.4	10	1.8	1.7	43	17	77	1.70	43.1	0.064	1.6	26.5	SST	CG	N
0.500	12.70	11766	3.81	96.8	.354	9.0	24	4.2	1.1	27	26	115	1.75	44.5	0.073	1.9	24.0	SPR	CG	Z
0.500	12.70	WW-60	3.88	98.4	.420	10.7	2.0	.35	2.3	59	4.7	21	.78	19.8	0.040	1.0	18.5	SST	C	N
0.500	12.70	10693	4.00	101.6	.398	10.1	4.7	.83	2.3	58	11	48	1.26	32.1	0.051	1.3	24.8	BC	CG	N
0.500	12.70	10290	4.13	104.8	.356	9.0	26	4.5	.97	25	25	110	1.53	38.9	0.072	1.8	21.3	SPR	CG	GI
0.500	12.70	12139	4.19	106.4	.424	10.8	1.4	.25	3.0	75	4.3	19	.87	22.2	0.038	1.0	23.0	SPR	CG	Z
0.500	12.70	3476	4.50	114.3	.356	9.0	29	5.1	.85	22	25	110	1.44	36.6	0.072	1.8	19.0	HD	C	Z
0.500	12.70	11651	4.75	120.7	.408	10.4	1.8	.32	2.9	74	5.3	23	1.84	46.7	0.046	1.2	40.0	SPR	CG	Z
0.500	12.70	K-37	4.75	120.7	.318	8.1	40	7.0	1.2	30	47	208	3.46	87.8	0.091	2.3	38.0	SPR	CG	GI
0.500	12.70	12690	5.50	139.7	.406	10.3	2.4	.43	3.3	84	8.0	36	1.60	40.6	0.047	1.2	33.0	HD	C	BO
0.500	12.70	B15-55	5.50	139.7	.406	10.3	2.6	.46	3.1	78	8.0	36	1.46	37.0	0.047	1.2	31.0	SPR	CG	Z
0.500	12.70	3251	5.50	139.7	.364	9.2	8.9	1.6	2.4	62	22	96	3.06	77.7	0.068	1.7	45.0	SPR	CG	Z
0.500	12.70	12218	5.94	150.8	.336	8.5	42	7.4	.85	22	36	160	1.89	47.9	0.082	2.1	23.0	SPR	CG	Z
0.500	12.70	S-1277	6.50	165.1	.392	10.0	3.2	.55	3.4	85	11	47	2.16	54.9	0.054	1.4	40.0	SST	CG	N
0.500	12.70	12688	9.00	228.6	.376	9.6	4.2	.74	4.0	102	17	75	3.91	99.2	0.062	1.6	62.0	SPR	C	Z
0.500	12.70	3998	10.5	266.7	.356	9.0	7.4	1.3	3.3	85	25	110	4.93	125.3	0.072	1.8	68.5	SPR	CG	Z
0.500	12.70	880	12.0	304.8	.376	9.6	3.1	.54	5.4	138	17	75	5.24	133.1	0.062	1.6	83.5	HD	C	Z
0.500	12.70	886	12.0	304.8	.340	8.6	9.0	1.6	3.8	95	34	149	7.34	186.4	0.080	2.0	90.8	HD	C	Z
0.500	12.70	3155	14.0	355.6	.392	10.0	1.9	.34	5.9	149	11	50	4.03	102.4	0.054	1.4	74.0	SPR	C	Z
0.500	12.70	514	16.0	406.4	.392	10.0	1.4	.24	8.2	209	11	50	5.59	142.0	0.054	1.4	102.0	HD	C	Z
0.515	13.08	V-21	.50	12.7	.371	9.4	296	52	.08	2.1	24	107	.25	6.4	0.072	1.8	3.50	SPR	CG	GI
0.515	13.08	O-115	.56	14.3	.437	11.1	8.9	1.6	.33	8.3	2.9	13	.23	5.9	0.039	1.0	5.00	SST	C	N
0.515	13.08	A14-4	.56	14.3	.401	10.2	74	13	.17	4.4	13	57	.24	6.0	0.057	1.4	4.13	SPR	CG	GI
0.515	13.08	B15-16	.56	14.3	.355	9.0	318	56	.10	2.6	33	146	.34	8.6	0.080	2.0	4.25	SPR	CG	N
0.515	13.08	B15-65	.63	15.9	.481	12.2	.78	.14	.55	14	.43	1.9	.07	1.8	0.017	0.4	3.25	MW	C	Z
0.515	13.08	B2-41	.63	15.9	.443	11.3	2.4	.42	.27	6.7	.63	2.8	.36	9.1	0.036	0.9	10.0	SST	CG	N
0.515	13.08	3258	.63	15.9	.345	8.8	629	110	.06	1.6	39	173	.38	9.7	0.085	2.2	3.50	SPR	C	Z
0.515	13.08	2657	.69	17.4	.345	8.8	290	51	.13	3.4	39	173	.45	11.3	0.085	2.2	5.25	SPR	CG	Z
0.515	13.08	3136	.75	19.1	.407	10.3	36	6.2	.31	7.8	11	49	.30	7.5	0.054	1.4	5.50	SPR	CG	Z
0.515	13.08	W-37	.75	19.1	.407	10.3	25	4.4	.37	9.4	9.3	41	.38	9.6	0.054	1.4	7.00	SPR	CG	Z
0.515	13.08	2640	.78	19.8	.391	9.9	87	15	.26	6.7	23	101	.29	7.3	0.062	1.6	4.75	MW	CG	Z
0.515	13.08	A15-70	.81	20.6	.411	10.4	19	3.3	.45	11	8.4	37	.36	9.2	0.052	1.3	7.00	SST	CG	N
0.515	13.08	3389	.81	20.6	.391	9.9	57	10	.29	7.3	16	73	.37	9.4	0.062	1.6	6.00	SPR	CG	Z
0.515	13.08	DD-96	.81	20.6	.355	9.0	131	23	.23	5.9	31	136	.54	13.7	0.080	2.0	6.75	SST	CG	N
0.515	13.08	FF-20	.88	22.2	.455	11.6	3.1	.55	.69	17	2.2	9.6	.19	4.8	0.030	0.8	5.25	MW	C	Z
0.515	13.08	Y-23	.88	22.2	.415	10.5	22	3.9	.39	9.9	8.7	39	.30	7.6	0.050	1.3	6.00	SPR	CG	N
0.515	13.08	S-1060	.88	22.2	.405	10.3	20	3.4	.44	11	8.5	38	.44	11.2	0.055	1.4	8.00	SST	CG	N
0.515	13.08	3841	.94	23.8	.331	8.4	272	48	.17	4.4	47	209	.64	16.4	0.092	2.3	7.00	HD	CG	GI
0.515	13.08	OO-79	.97	24.6	.435	11.0	4.6	.80	.63	16	2.9	13	.34	8.6	0.040	1.0	8.50	SST	CG	N
0.515	13.08	KK-48	1.00	25.4	.455	11.6	3.4	.60	.85	22	2.9	13	.15	3.8	0.030	0.8	5.00	MW	CG	N
0.515	13.08	B3-36	1.00	25.4	.443	11.3	6.8	1.2	.72	18	4.9	22	.23	5.7	0.036	0.9	5.25	MW	C	N
0.515	13.08	K-29	1.00	25.4	.419	10.6	10	1.8	.60	15	6.3	28	.40	10.1	0.048	1.2	8.25	SST	CG	N
0.515	13.08	WW-43	1.00	25.4	.379	9.6	63	11	.34	8.7	22	96	.58	14.7	0.068	1.7	7.50	SPR	C	Z
0.515	13.08	S-1171	1.00	25.4	.355	9.0	124	22	.25	6.3	31	136	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.515	13.08	Y-30	1.06	27.0	.453	11.5	2.0	.34	.81	21	1.6	7.1	.25	6.3	0.031	0.8	8.00	MW	CG	Z
0.515	13.08	10838	1.06	27.0	.447	11.4	2.4	.42	.75	19	1.8	7.9	.32	8.0	0.034	0.9	9.25	SPR	CG	Z
0.515	13.08	12481	1.06	27.0	.425	10.8	7.6	1.3	.59	15	4.5	20	.47	12.0	0.045	1.1	9.50	MW	C	N
0.515	13.08	11107	1.13	28.6	.457	11.6	1.5	.26	.86	22	1.3	5.7	.26	6.6	0.029	0.7	8.00	MW	C	Z
0.515	13.08	S-235	1.13	28.6	.453	11.5	1.4	.25	.81	21	1.1	5.0	.32	8.1	0.031	0.8	9.25	SST	C	N
0.515	13.08	2715	1.13	28.6	.387	9.8	48	8.4	.52	13	25	111	.48	12.2	0.064	1.6	7.50	MW	CG	Z
0.515	13.08	S-1051	1.13	28.6	.305	7.7	367	64	.17	4.4	63	282	.84	21.3	0.105	2.7	8.00	SST	CG	N
0.515	13.08	B10-64	1.16	29.4	.379	9.6	53	9.3	.41	10	22	96	.58	14.7	0.068	1.7	8.50	SPR	CG	Z
0.515	13.08	S-1613	1.19	30.2	.407	10.3	14	2.4	.65	16	9.0	40	.54	13.7	0.054	1.4	10.0	SST	CG	N
0.515	13.08	11338	1.19	30.2	.341	8.7	175	31	.24	6.0	42	185	.78	19.9	0.087	2.2	8.00	SPR	C	Z
0.515	13.08	S-1032	1.25	31.8	.459	11.7	.42	.07	.75	19	.31	1.4	.50	12.8	0.028	0.7	18.0	SST	CG	N
0.515	13.08	3972	1.25	31.8	.391	9.9	48	8.4	.34	8.7	16	73	.42	10.6	0.062	1.6	6.75	SPR	CG	Z
0.515	13.08	10460	1.30	32.9	.397	10.1	27	4.8	.49	12	13	59	.47	12.0	0.059	1.5	8.00	SST	CG	N
0.515	13.08	2526	1.38	34.9	.427	10.8	9.4	1.6	.68	17	6.4	29	.37	9.5	0.044	1.1	7.50	SPR	C	Z
0.515	13.08	3535	1.41	35.7	.421	10.7	12	2.2	.87	22	11	48	.35	9.0	0.047	1.2	7.50	MW	CG	Z
0.515	13.08	10809	1.50	38.1	.485	12.3	.08	.01	1.4	34	.11	.50	.15	3.8	0.015	0.4	9.00	MW	C	N
0.515	13.08	2560	1.50	38.1	.451	11.5	1.7	.29	1.2	30	2.0	8.8	.32	8.1	0.032	0.8	10.0	HD	CG	Z
0.515	13.08	Z-24	1.50	38.1	.451	11.5	2.7	.47	.98	25	2.6	12	.26	6.5	0.032	0.8	7.00	SPR	C	Z
0.515	13.08	10718	1.50	38.1	.433	11.0	5.7	.99	.92	23	5.2	23	.40	10.2	0.041	1.0	8.75	SPR	C	Z
0.515	13.08	S-1139	1.50	38.1	.411	10.4	9.2	1.6	.82	21	7.6	34	.68	17.2	0.052	1.3	12.0	SST	C	N
0.515	13.08	2709	1.53	38.9	.361	9.2	69	12	.43	11	29	130	.83	21.0	0.077	2.0	10.8	SPR	CG	Z
0.515	13.08	10178	1.56	39.7	.433	11.0	3.2	.56	.99	25	3.1	14	.57	14.6	0.041	1.0	14.0	SPR	CG	Z
0.515	13.08	S-407	1.56	39.7	.433	11.0	4.2	.74	1.1	28	4.7	21	.45	11.5	0.041	1.0	10.0	SST	C	N
0.515	13.08	2513	1.56	39.7	.395	10.0	22	3.8	.90	23	20	88	.66	16.8	0.060	1.5	11.0	MW	CG	Z
0.515	13.08	O-69	1.56	39.7	.395	10.0	19	3.4	.72	18	14	62	.66	16.8	0.060	1.5	11.0	SST	CG	N
0.515	13.08	3046	1.56	39.7	.355	9.0	79	14	.41	10	33	146	.88	22.4	0.080	2.0	11.0	SPR	CG	Z
0.515	13.08	S-1162	1.63	41.3	.439	11.2	2.5	.44	1.2	29	2.9	13	.48	12.1	0.038	1.0	11.5	SST	C	N
0.515	13.08	3924	1.63	41.3	.391	9.9	25	4.4	.65	16	16	73	.74	18.9	0.062	1.6	11.0	HD	C	Z
0.515	13.08	2696	1.63	41.3	.381	9.7	36	6.3	.80	20	29	127	.74	18.7	0.067	1.7	11.0	MW	CG	Z
0.515	13.08	12292	1.66	42.1	.399	10.1	17	3.0	.79	20	14	60	.70	17.7	0.058	1.5	12.0	SPR	CG	N
0.515	13.08	3681	1.69	42.8	.389	9.9	43	7.5	.40	10	17	77	.49	12.4	0.063	1.6	7.75	SPR	CG	Z
0.515	13.08	S-1501	1.81	46.0	.459	11.7	1.1	.19	1.5	37	1.6	7.3	.22	5.7	0.028	0.7	8.00	SST	CG	N
0.515	13.08	11621	1.88	47.6	.411	10.4	7.6	1.3	1.0	26	7.9	35	.83	21.1	0.052	1.3	16.0	SPR	CG	Z
0.515	13.08	11753	1.97	50.0	.433	11.0	6.4	1.1	.82	21	5.2	23	.37	9.4	0.041	1.0	8.00	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.515	13.08	4357	2.00	50.8	.453	11.5	1.5	.26	1.7	43	2.5	11	.31	7.9	0.031	0.8	10.0	MW	CG	Z
0.515	13.08	12748	2.00	50.8	.421	10.7	6.8	1.2	1.1	29	7.8	35	.61	15.5	0.047	1.2	12.0	SPR	C	N
0.515	13.08	10926	2.00	50.8	.399	10.1	16	2.8	.83	21	14	60	.78	19.9	0.058	1.5	12.5	SPR	C	Z
0.515	13.08	K-35	2.13	54.0	.409	10.4	9.1	1.6	1.1	27	9.7	43	.69	17.5	0.053	1.3	13.0	SST	CG	N
0.515	13.08	S-397	2.16	54.8	.329	8.4	101	18	.45	11	45	200	1.33	33.9	0.093	2.4	14.3	SST	CG	N
0.515	13.08	3689	2.22	56.4	.439	11.2	1.8	.32	1.5	39	2.8	13	.68	17.4	0.038	1.0	17.0	SPR	C	Z
0.515	13.08	3475	2.25	57.2	.355	9.0	64	11	.51	13	33	146	1.06	26.9	0.080	2.0	13.3	SPR	CG	Z
0.515	13.08	12603	2.33	59.1	.379	9.6	30	5.2	1.0	25	30	133	.99	25.0	0.068	1.7	13.5	MW	C	T
0.515	13.08	S-278	2.50	63.5	.411	10.4	6.1	1.1	1.5	38	9.2	41	.94	23.8	0.052	1.3	17.0	SST	C	N
0.515	13.08	3429	2.63	66.7	.265	6.7	438	77	.24	6.2	107	476	1.94	49.2	0.125	3.2	15.5	SPR	CG	Z
0.515	13.08	A13-37	2.66	67.5	.369	9.4	25	4.3	.95	24	24	105	1.46	37.1	0.073	1.9	19.0	SST	C	N
0.515	13.08	11635	2.69	68.2	.415	10.5	5.6	.98	1.6	40	8.7	39	.90	22.9	0.050	1.3	18.0	SPR	CG	Z
0.515	13.08	3838	2.69	68.2	.387	9.8	11	2.0	1.1	28	12	55	1.60	40.6	0.064	1.6	25.0	SPR	CG	Z
0.515	13.08	2558	2.69	68.2	.265	6.7	382	67	.39	9.9	150	665	2.19	55.6	0.125	3.2	17.5	MW	CG	Z
0.515	13.08	3140	2.75	69.9	.437	11.1	4.2	.74	1.1	27	4.5	20	.40	10.2	0.039	1.0	9.25	SPR	C	Z
0.515	13.08	12300	3.00	76.2	.395	10.0	11	1.9	1.4	34	15	66	1.20	30.5	0.060	1.5	20.0	SPR	CG	Z
0.515	13.08	2510	3.25	82.6	.399	10.1	12	2.1	1.6	41	19	83	.96	24.3	0.058	1.5	16.5	MW	CG	Z
0.515	13.08	B-26	3.28	83.3	.433	11.0	3.8	.67	1.4	35	5.2	23	.53	13.5	0.041	1.0	12.0	HD	C	N
0.515	13.08	11557	3.59	91.3	.387	9.8	12	2.1	1.5	38	18	80	1.60	40.6	0.064	1.6	24.0	SPR	CG	N
0.515	13.08	10928	4.00	101.6	.347	8.8	40	7.0	.95	24	38	168	2.14	54.4	0.084	2.1	24.5	SPR	C	Z
0.515	13.08	10705	5.31	134.9	.315	8.0	54	9.5	1.1	28	60	265	3.90	99.1	0.100	2.5	39.0	SPR	CG	Z
0.515	13.08	11517	5.50	139.7	.421	10.7	2.4	.41	3.3	84	7.8	35	1.50	38.2	0.047	1.2	31.0	SPR	CG	Z
0.515	13.08	12298	6.00	152.4	.421	10.7	3.6	.63	2.2	55	7.8	35	.99	25.1	0.047	1.2	21.0	SPR	CG	Z
0.515	13.08	11431	7.63	193.7	.411	10.4	1.8	.31	4.3	110	7.6	34	3.30	83.9	0.052	1.3	62.5	HD	C	Z
0.515	13.08	1609	8.50	215.9	.391	9.9	5.3	.93	3.1	78	16	73	2.79	70.9	0.062	1.6	45.0	SPR	CG	Z
0.515	13.08	S-188	8.75	222.3	.391	9.9	4.6	.81	3.3	85	15	69	2.79	70.9	0.062	1.6	45.0	SST	CG	N
0.515	13.08	1809	12.0	304.8	.391	9.9	2.9	.51	7.0	177	20	91	5.02	127.6	0.062	1.6	80.0	MW	C	Z
0.531	13.49	N-81	.28	7.1	.437	11.1	62	11	.12	3.1	7.6	34	.14	3.6	0.047	1.2	3.00	SPR	CG	N
0.531	13.49	3050	.31	7.9	.467	11.9	12	2.1	.21	5.3	2.5	11	.10	2.4	0.032	0.8	3.00	SPR	CG	Z
0.531	13.49	2851	.44	11.1	.485	12.3	1.5	.27	.32	8.2	.50	2.2	.12	2.9	0.023	0.6	4.00	MW	C	Z
0.531	13.49	B10-36	.44	11.1	.441	11.2	19	3.3	.22	5.7	4.2	19	.21	5.4	0.045	1.1	4.75	SPR	CG	Z
0.531	13.49	I-14	.50	12.7	.441	11.2	30	5.2	.21	5.3	6.2	28	.16	4.0	0.045	1.1	3.50	SST	CG	N
0.531	13.49	S-17	.50	12.7	.437	11.1	27	4.7	.26	6.7	7.1	32	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.531	13.49	PP-32	.56	14.3	.387	9.8	107	19	.15	3.8	16	70	.41	10.5	0.072	1.8	5.75	SPR	CG	Z
0.531	13.49	G-57	.56	14.3	.371	9.4	186	33	.16	4.1	30	133	.40	10.2	0.080	2.0	5.00	SST	CG	N
0.531	13.49	S-823	.63	15.9	.481	12.2	.75	.13	.43	11	.32	1.4	.20	5.1	0.025	0.6	7.00	SST	C	N
0.531	13.49	2670	.63	15.9	.465	11.8	6.9	1.2	.40	10	2.8	12	.17	4.2	0.033	0.8	4.00	SPR	C	Z
0.531	13.49	M-131	.63	15.9	.459	11.7	5.9	1.0	.45	11	2.6	12	.18	4.6	0.036	0.9	5.00	SST	CG	N
0.531	13.49	L-35	.63	15.9	.407	10.3	73	13	.21	5.2	15	67	.28	7.1	0.062	1.6	4.50	SST	CG	N
0.531	13.49	F-54	.66	16.7	.405	10.3	88	15	.19	4.8	17	74	.28	7.2	0.063	1.6	4.50	HD	CG	Z
0.531	13.49	YY-58	.69	17.4	.463	11.8	7.8	1.4	.39	9.9	3.0	13	.17	4.3	0.034	0.9	4.00	SPR	C	GI
0.531	13.49	N-132	.69	17.4	.407	10.3	69	12	.23	5.9	16	71	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.531	13.49	3906	.72	18.2	.451	11.5	7.8	1.4	.44	11	3.4	15	.28	7.1	0.040	1.0	6.00	SPR	C	Z
0.531	13.49	CC-53	.75	19.1	.467	11.9	4.0	.71	.56	14	2.3	10	.19	4.9	0.032	0.8	5.00	MW	C	Z
0.531	13.49	2586	.75	19.1	.449	11.4	14	2.4	.51	13	7.0	31	.18	4.7	0.041	1.0	4.50	MW	CG	Z
0.531	13.49	4269	.75	19.1	.437	11.1	15	2.7	.42	11	6.5	29	.33	8.4	0.047	1.2	6.00	SPR	C	Z
0.531	13.49	B11-51	.75	19.1	.403	10.2	53	9.2	.31	8.0	16	73	.38	9.8	0.064	1.6	6.00	SST	CG	N
0.531	13.49	10260	.75	19.1	.349	8.9	386	68	.11	2.9	44	197	.46	11.6	0.091	2.3	5.00	SPR	CG	Z
0.531	13.49	1953	.78	19.8	.487	12.4	.68	.12	.63	16	.43	1.9	.15	3.8	0.022	0.6	5.75	MW	C	Z
0.531	13.49	S-919	.78	19.8	.387	9.8	99	17	.22	5.6	22	98	.40	10.1	0.072	1.8	5.50	SST	CG	N
0.531	13.49	2592	.78	19.8	.321	8.2	646	113	.10	2.6	67	296	.58	14.7	0.105	2.7	5.50	SPR	CG	Z
0.531	13.49	B11-37	.81	20.6	.467	11.9	4.0	.71	.63	16	2.5	11	.16	4.1	0.032	0.8	5.00	SPR	CG	N
0.531	13.49	S-446	.81	20.6	.407	10.3	72	13	.21	5.3	15	67	.28	7.1	0.062	1.6	4.50	SST	CG	N
0.531	13.49	2787	.81	20.6	.345	8.8	320	56	.15	3.7	47	210	.56	14.2	0.093	2.4	6.00	SPR	CG	Z
0.531	13.49	2559	.84	21.4	.423	10.7	23	3.9	.47	12	10	47	.38	9.6	0.054	1.4	7.00	HD	CG	Z
0.531	13.49	V-29	.84	21.4	.407	10.3	45	7.8	.34	8.5	15	67	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.531	13.49	S-895	.88	22.2	.467	11.9	3.5	.62	.67	17	2.4	10	.16	4.1	0.032	0.8	5.00	SST	CG	N
0.531	13.49	10734	.88	22.2	.449	11.4	8.6	1.5	.59	15	5.1	22	.25	6.2	0.041	1.0	6.00	SPR	CG	Z
0.531	13.49	3836	.88	22.2	.427	10.8	32	5.6	.30	7.6	9.5	42	.31	7.9	0.052	1.3	5.00	SPR	C	Z
0.531	13.49	2636	.91	23.0	.417	10.6	28	5.0	.44	11	12	55	.40	10.1	0.057	1.4	7.00	HD	CG	Z
0.531	13.49	JJ-17	.94	23.8	.471	12.0	1.9	.32	.70	18	1.3	5.7	.24	6.1	0.030	0.8	7.00	MW	C	Z
0.531	13.49	S-1412	.94	23.8	.449	11.4	8.6	1.5	.55	14	4.7	21	.23	5.7	0.041	1.0	5.50	SST	CG	N
0.531	13.49	2896	.94	23.8	.429	10.9	22	3.8	.41	10	9.0	40	.36	9.1	0.051	1.3	6.00	SPR	C	Z
0.531	13.49	I-47	.94	23.8	.407	10.3	21	3.6	.19	4.9	4.0	18	.74	18.9	0.062	1.6	12.0	HD	CG	N
0.531	13.49	A12-12	1.00	25.4	.471	12.0	1.6	.28	.74	19	1.2	5.3	.26	6.7	0.030	0.8	7.75	MW	C	N
0.531	13.49	A12-30	1.00	25.4	.471	12.0	1.5	.27	.73	19	1.1	5.0	.27	6.9	0.030	0.8	8.00	MW	C	Z
0.531	13.49	11204	1.00	25.4	.467	11.9	1.7	.30	.70	18	1.2	5.4	.30	7.5	0.032	0.8	8.25	SST	C	N
0.531	13.49	S-81	1.00	25.4	.443	11.3	10	1.8	.57	15	5.8	26	.31	7.8	0.044	1.1	6.00	SST	C	N
0.531	13.49	11208	1.00	25.4	.407	10.3	33	5.8	.45	11	15	67	.47	11.8	0.062	1.6	7.50	SST	CG	N
0.531	13.49	S-916	1.00	25.4	.405	10.3	64	11	.25	6.2	16	70	.32	8.0	0.063	1.6	5.00	SST	CG	N
0.531	13.49	10034	1.00	25.4	.381	9.7	120	21	.22	5.6	26	117	.45	11.4	0.075	1.9	6.00	SPR	CG	Z
0.531	13.49	11200	1.03	26.2	.469	11.9	1.6	.27	.75	19	1.2	5.3	.28	7.1	0.031	0.8	8.00	SST	C	N
0.531	13.49	B10-39	1.03	26.2	.441	11.2	8.9	1.6	.68	17	6.1	27	.35	8.9	0.045	1.1	7.75	SPR	CG	N
0.531	13.49	12401	1.03	26.2	.321	8.2	432	76	.15	3.9	67	296	.73	18.5	0.105	2.7	7.00	SPR	CG	N
0.531	13.49	12497	1.06	27.0	.473	12.0	1.4	.24	.81	21	1.1	5.0	.25	6.5	0.029	0.7	7.75	MW	C	N
0.531	13.49	10691	1.06	27.0	.463	11.8	2.0	.34	.72	18	1.4	6.3	.34	8.6	0.034	0.9	10.0	SPR	CG	Z
0.531	13.49	12313	1.06	27.0	.435	11.0	11	1.9	.62	16	6.7	30	.44	11.3	0.048	1.2	8.25	HD	C	Z
0.531	13.49	B7-10	1.08	27.4	.469	11.9	2.7	.47	.80	20	2.1	9.5	.20	5.1	0.031	0.8	5.50	SST	C	N
0.531	13.49	10585	1.13	28.6	.407	10.3	51	9.0	.31	7.9	16	71	.43	11.0	0.062	1.6	6.00	SPR	C	Z
0.531	13.49	B12-47	1.13	28.6	.405	10.3	47	8.1	.36	9.1	17	74	.43	10.8	0.063	1.6	6.75	SPR	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.531	13.49	1751	1.13	28.6	.281	7.1	1234	216	.08	2.2	105	466	.78	19.8	0.125	3.2	6.25	SPR	CG	Z
0.531	13.49	S-57	1.19	30.2	.437	11.1	7.8	1.4	.72	18	5.6	25	.47	11.9	0.047	1.2	9.00	SST	C	N
0.531	13.49	2616	1.19	30.2	.385	9.8	61	11	.40	10	24	109	.66	16.7	0.073	1.9	9.00	HD	CG	Z
0.531	13.49	S-1449	1.22	31.0	.423	10.7	14	2.4	.72	18	9.7	43	.50	12.7	0.054	1.4	9.25	SST	CG	N
0.531	13.49	2689	1.22	31.0	.407	10.3	26	4.5	.60	15	15	69	.62	15.7	0.062	1.6	10.0	HD	CG	Z
0.531	13.49	S-1348	1.22	31.0	.321	8.2	314	55	.20	5.0	62	275	.87	22.0	0.105	2.7	8.25	SST	CG	N
0.531	13.49	S-136	1.25	31.8	.461	11.7	4.4	.77	.67	17	3.0	13	.23	5.8	0.035	0.9	5.50	SST	C	N
0.531	13.49	S-18	1.25	31.8	.387	9.8	45	7.8	.49	12	22	98	.70	17.8	0.072	1.8	9.75	SST	CG	N
0.531	13.49	S-847	1.28	32.5	.467	11.9	.69	.12	.72	18	.49	2.2	.57	14.4	0.032	0.8	17.8	SST	CG	N
0.531	13.49	S-990	1.28	32.5	.441	11.2	12	2.1	.52	13	6.2	28	.26	6.6	0.045	1.1	5.75	SST	CG	N
0.531	13.49	A13-63	1.31	33.3	.453	11.5	7.0	1.2	.62	16	4.4	19	.23	5.9	0.039	1.0	6.00	SPR	CG	N
0.531	13.49	B1-68	1.31	33.3	.415	10.5	26	4.5	.51	13	13	58	.46	11.8	0.058	1.5	8.00	SPR	CG	Z
0.531	13.49	OO-20	1.31	33.3	.311	7.9	353	62	.21	5.3	73	327	1.10	27.9	0.110	2.8	10.0	SPR	CG	GI
0.531	13.49	Z-26	1.34	34.1	.471	12.0	1.6	.29	1.1	28	1.8	8.1	.24	6.1	0.030	0.8	7.00	SST	C	N
0.531	13.49	S-1493	1.38	34.9	.473	12.0	1.4	.24	1.2	30	1.6	7.3	.20	5.2	0.029	0.7	7.00	SST	CG	N
0.531	13.49	3191	1.38	34.9	.403	10.2	30	5.2	.59	15	18	78	.64	16.3	0.064	1.6	10.0	SPR	CG	GI
0.531	13.49	3685	1.41	35.7	.387	9.8	57	10	.41	10	23	104	.65	16.5	0.072	1.8	9.00	SPR	CG	Z
0.531	13.49	B18-192	1.41	35.7	.321	8.2	301	53	.22	5.6	67	296	1.00	25.3	0.105	2.7	9.50	SPR	CG	Z
0.531	13.49	2572	1.44	36.5	.435	11.0	12	2.2	.90	23	11	50	.36	9.1	0.048	1.2	7.50	MW	CG	Z
0.531	13.49	10700	1.44	36.5	.423	10.7	10	1.8	.74	19	7.5	34	.70	17.8	0.054	1.4	13.0	SPR	CG	GI
0.531	13.49	B12-56	1.44	36.5	.385	9.8	71	12	.34	8.8	24	109	.58	14.8	0.073	1.9	8.00	SPR	CG	Z
0.531	13.49	3956	1.44	36.5	.321	8.2	301	53	.22	5.6	67	296	1.00	25.3	0.105	2.7	9.50	SPR	CG	Z
0.531	13.49	S-1487	1.50	38.1	.477	12.1	1.2	.20	1.2	31	1.4	6.3	.20	5.1	0.027	0.7	6.50	SST	C	N
0.531	13.49	10137	1.50	38.1	.461	11.7	3.5	.62	.89	23	3.2	14	.28	7.1	0.035	0.9	7.00	SPR	C	Z
0.531	13.49	S-1509	1.50	38.1	.461	11.7	1.7	.30	1.1	27	1.8	8.2	.42	10.7	0.035	0.9	11.0	SST	C	N
0.531	13.49	B5-46	1.50	38.1	.443	11.3	8.9	1.6	.70	18	6.2	28	.32	8.1	0.044	1.1	7.25	SPR	CG	N
0.531	13.49	3477	1.50	38.1	.421	10.7	14	2.4	.83	21	11	50	.61	15.4	0.055	1.4	11.0	SPR	CG	Z
0.531	13.49	4390	1.50	38.1	.327	8.3	282	49	.22	5.5	61	273	.92	23.3	0.102	2.6	9.00	SPR	CG	Z
0.531	13.49	10803	1.53	38.9	.453	11.5	3.5	.62	1.2	29	4.1	18	.35	8.9	0.039	1.0	9.00	SST	CG	N
0.531	13.49	2904	1.56	39.7	.361	9.2	107	19	.35	9.0	38	169	.84	21.3	0.085	2.2	10.0	SPR	CG	Z
0.531	13.49	QQ-30	1.63	41.3	.483	12.3	.49	.09	1.4	35	.68	3.0	.23	5.8	0.024	0.6	8.50	SST	C	N
0.531	13.49	3415	1.63	41.3	.467	11.9	2.0	.35	1.3	32	2.5	11	.29	7.3	0.032	0.8	8.00	HD	C	T
0.531	13.49	3478	1.63	41.3	.445	11.3	3.5	.62	1.0	26	3.6	16	.60	15.3	0.043	1.1	14.0	SPR	CG	Z
0.531	13.49	I-58	1.63	41.3	.411	10.4	19	3.4	.70	18	14	61	.60	15.2	0.060	1.5	10.0	SST	CG	N
0.531	13.49	11390	1.63	41.3	.401	10.2	28	4.9	.65	17	18	82	.72	18.2	0.065	1.7	11.0	SPR	CG	Z
0.531	13.49	10303	1.63	41.3	.371	9.4	61	11	.52	13	32	142	1.00	25.4	0.080	2.0	12.5	SPR	CG	Z
0.531	13.49	11246	1.66	42.1	.407	10.3	21	3.6	.77	20	16	71	.74	18.9	0.062	1.6	12.0	SPR	CG	Z
0.531	13.49	11134	1.69	42.8	.431	10.9	8.1	1.4	1.0	27	8.5	38	.60	15.2	0.050	1.3	12.0	SPR	CG	GI
0.531	13.49	FF-32	1.75	44.5	.471	12.0	1.3	.23	1.5	37	1.9	8.5	.30	7.6	0.030	0.8	9.00	MW	C	N
0.531	13.49	10629	1.78	45.2	.403	10.2	22	3.8	.81	21	18	78	.83	21.1	0.064	1.6	13.0	SPR	CG	Z
0.531	13.49	12519	1.88	47.6	.467	11.9	2.1	.37	1.6	41	3.4	15	.28	7.1	0.032	0.8	7.75	MW	C	GI
0.531	13.49	2901	1.88	47.6	.391	9.9	31	5.4	.71	18	22	96	.95	24.0	0.070	1.8	13.5	SPR	CG	Z
0.531	13.49	3974	1.88	47.6	.347	8.8	119	21	.39	9.8	46	203	1.22	31.0	0.092	2.3	12.3	SPR	C	Z
0.531	13.49	U-46	2.00	50.8	.449	11.4	2.5	.44	1.4	36	3.6	16	.57	14.6	0.041	1.0	14.0	SST	CG	N
0.531	13.49	3671	2.03	51.6	.385	9.8	42	7.4	.57	15	24	109	.95	24.1	0.073	1.9	12.0	SPR	C	Z
0.531	13.49	11938	2.09	53.2	.367	9.3	53	9.3	.64	16	34	152	1.27	32.3	0.082	2.1	15.5	SPR	CG	Z
0.531	13.49	S-3129	2.13	54.0	.466	11.8	1.1	.18	1.7	44	1.8	8.0	.40	10.2	0.033	0.8	12.0	SST	C	N
0.531	13.49	11761	2.19	55.6	.413	10.5	14	2.5	.96	24	14	61	.80	20.2	0.059	1.5	13.5	SPR	CG	Z
0.531	13.49	10532	2.22	56.4	.383	9.7	30	5.2	.86	22	25	113	1.28	32.4	0.074	1.9	17.3	SPR	CG	Z
0.531	13.49	S-968	2.25	57.2	.405	10.3	9.6	1.7	.80	20	7.7	34	1.45	36.8	0.063	1.6	22.0	SST	C	N
0.531	13.49	4364	2.38	60.3	.407	10.3	15	2.7	1.0	27	16	71	.96	24.4	0.062	1.6	15.5	SPR	CG	Z
0.531	13.49	S-1367	2.44	61.9	.407	10.3	16	2.7	.96	24	15	67	.84	21.3	0.062	1.6	13.5	SST	CG	N
0.531	13.49	10743	2.50	63.5	.469	11.9	1.9	.34	1.7	42	3.2	14	.26	6.7	0.031	0.8	7.50	MW	C	GI
0.531	13.49	2967	2.50	63.5	.449	11.4	4.1	.71	1.2	32	5.1	22	.47	12.0	0.041	1.0	10.5	SPR	C	Z
0.531	13.49	11818	2.50	63.5	.407	10.3	16	2.8	1.0	26	16	71	.93	23.6	0.062	1.6	15.0	SPR	CG	Z
0.531	13.49	11560	2.78	70.6	.403	10.2	12	2.1	1.3	34	16	72	1.44	36.6	0.064	1.6	21.5	SPR	CG	Z
0.531	13.49	11547	2.81	71.4	.401	10.2	13	2.3	1.4	35	18	82	1.38	35.1	0.065	1.7	21.3	SPR	CG	Z
0.531	13.49	S-3089	2.88	73.0	.407	10.3	6.8	1.2	1.1	27	7.2	32	1.81	46.1	0.062	1.6	28.3	SST	C	N
0.531	13.49	12067	3.38	85.7	.359	9.1	64	11	.62	16	39	175	1.38	35.0	0.086	2.2	16.0	SPR	CG	Z
0.531	13.49	3676	3.44	87.3	.395	10.0	14	2.5	1.5	38	21	93	1.63	41.5	0.068	1.7	24.0	SPR	CG	Z
0.531	13.49	3699	4.06	103.2	.405	10.3	9.5	1.7	1.8	45	17	74	1.59	40.4	0.063	1.6	25.3	SPR	CG	GI
0.531	13.49	11234	4.13	104.8	.437	11.1	3.3	.59	2.3	57	7.6	34	.96	24.5	0.047	1.2	20.5	SPR	CG	Z
0.531	13.49	11243	4.19	106.4	.407	10.3	14	2.4	1.2	30	16	71	1.05	26.8	0.062	1.6	17.0	HD	CG	Z
0.531	13.49	S-1566	4.81	122.2	.333	8.5	74	13	.71	18	52	233	2.23	56.6	0.099	2.5	22.5	SST	CG	N
0.531	13.49	2770	5.75	146.1	.337	8.6	43	7.5	1.2	32	53	237	3.72	94.4	0.097	2.5	38.0	SPR	CG	Z
0.531	13.49	10824	6.25	158.8	.403	10.2	5.8	1.0	3.0	76	18	78	2.72	69.1	0.064	1.6	42.5	SPR	CG	Z
0.531	13.49	12273	6.50	165.1	.437	11.1	3.3	.57	2.3	59	7.6	34	.99	25.1	0.047	1.2	21.0	SPR	CG	Z
0.540	13.72	71633	.50	12.7	.458	11.6	21	3.7	.33	8.3	6.9	31	.14	3.6	0.041	1.0	3.50	MW	CG	N
0.540	13.72	71633S	.50	12.7	.458	11.6	18	3.1	.26	6.6	4.7	21	.14	3.6	0.041	1.0	3.50	SST	CG	N
0.540	13.72	71646	.50	12.7	.448	11.4	31	5.4	.31	7.9	9.7	43	.17	4.4	0.046	1.2	3.75	MW	CG	N
0.540	13.72	71646S	.50	12.7	.448	11.4	26	4.6	.25	6.3	6.5	29	.17	4.4	0.046	1.2	3.75	SST	CG	N
0.540	13.72	71659	.50	12.7	.432	11.0	57	10	.25	6.4	15	65	.21	5.3	0.054	1.4	3.88	MW	CG	N
0.540	13.72	71659S	.50	12.7	.432	11.0	49	8.5	.20	5.1	9.8	44	.21	5.3	0.054	1.4	3.88	SST	CG	N
0.540	13.72	71672	.50	12.7	.424	10.8	76	13	.24	6.0	18	80	.22	5.7	0.058	1.5	3.88	MW	CG	N
0.540	13.72	71672S	.50	12.7	.424	10.8	64	11	.19	4.8	12	54	.22	5.7	0.058	1.5	3.88	SST	CG	N
0.540	13.72	71685	.50	12.7	.414	10.5	105	18	.22	5.5	23	102	.25	6.4	0.063	1.6	4.00	MW	CG	N
0.540	13.72	71685S	.50	12.7	.414	10.5	90	16	.17	4.4	15	69	.25	6.4	0.063	1.6	4.00	SST	CG	N
0.540	13.72	71698	.50	12.7	.406	10.3	137	24	.20	5.1	27	122	.27	6.8	0.067	1.7	4.00	MW	CG	N
0.540	13.72	71698S	.50	12.7	.406	10.3	116	20	.16	4.0	19	83	.27	6.8	0.067	1.7	4.00	SST	CG	N
0.540	13.72	71634	.63	16.0	.458	11.6	16	2.9	.42	11	6.9	31	.16	4.2	0.041	1.0	4.00	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.540	13.72	71634S	.63	16.0	.458	11.6	14	2.4	.34	8.5	4.7	21	.16	4.2	0.041	1.0	4.00	SST	CG	N
0.540	13.72	71647	.63	16.0	.448	11.4	24	4.2	.40	10	9.7	43	.20	5.0	0.046	1.2	4.25	MW	CG	N
0.540	13.72	71647S	.63	16.0	.448	11.4	20	3.6	.32	8.1	6.5	29	.20	5.0	0.046	1.2	4.25	SST	CG	N
0.540	13.72	71660	.63	16.0	.432	11.0	43	7.6	.33	8.5	15	65	.24	6.2	0.054	1.4	4.50	MW	CG	N
0.540	13.72	71660S	.63	16.0	.432	11.0	37	6.5	.27	6.8	9.8	44	.24	6.2	0.054	1.4	4.50	SST	CG	N
0.540	13.72	71673	.63	16.0	.424	10.8	57	10	.31	8.0	18	80	.26	6.6	0.058	1.5	4.50	MW	CG	N
0.540	13.72	71673S	.63	16.0	.424	10.8	49	8.5	.25	6.3	12	54	.26	6.6	0.058	1.5	4.50	SST	CG	N
0.540	13.72	71686	.63	16.0	.414	10.5	79	14	.29	7.4	23	102	.29	7.4	0.063	1.6	4.63	MW	CG	N
0.540	13.72	71686S	.63	16.0	.414	10.5	67	12	.23	5.9	15	69	.29	7.4	0.063	1.6	4.63	SST	CG	N
0.540	13.72	71699	.63	16.0	.406	10.3	102	18	.27	6.8	27	122	.31	7.9	0.067	1.7	4.63	MW	CG	N
0.540	13.72	71699S	.63	16.0	.406	10.3	87	15	.21	5.4	19	83	.31	7.9	0.067	1.7	4.63	SST	CG	N
0.540	13.72	71635	.75	19.1	.458	11.6	13	2.3	.52	13	6.9	31	.18	4.7	0.041	1.0	4.50	MW	CG	N
0.540	13.72	71635S	.75	19.1	.458	11.6	11	2.0	.41	10	4.7	21	.18	4.7	0.041	1.0	4.50	SST	CG	N
0.540	13.72	71648	.75	19.1	.448	11.4	20	3.4	.50	13	9.7	43	.22	5.5	0.046	1.2	4.75	MW	CG	N
0.540	13.72	71648S	.75	19.1	.448	11.4	17	2.9	.39	10	6.5	29	.22	5.5	0.046	1.2	4.75	SST	CG	N
0.540	13.72	71661	.75	19.1	.432	11.0	35	6.1	.42	11	15	65	.27	6.9	0.054	1.4	5.00	MW	CG	N
0.540	13.72	71661S	.75	19.1	.432	11.0	30	5.2	.33	8.4	9.8	44	.27	6.9	0.054	1.4	5.00	SST	CG	N
0.540	13.72	71674	.75	19.1	.424	10.8	46	8.0	.39	9.9	18	80	.30	7.6	0.058	1.5	5.13	MW	CG	N
0.540	13.72	71674S	.75	19.1	.424	10.8	39	6.8	.31	7.9	12	54	.30	7.6	0.058	1.5	5.13	SST	CG	N
0.540	13.72	71687	.75	19.1	.414	10.5	63	11	.36	9.2	23	102	.33	8.4	0.063	1.6	5.25	MW	CG	N
0.540	13.72	71687S	.75	19.1	.414	10.5	54	9.4	.29	7.3	15	69	.33	8.4	0.063	1.6	5.25	SST	CG	N
0.540	13.72	71700	.75	19.1	.406	10.3	81	14	.34	8.6	27	122	.36	9.1	0.067	1.7	5.38	MW	CG	N
0.540	13.72	71700S	.75	19.1	.406	10.3	69	12	.27	6.8	19	83	.36	9.1	0.067	1.7	5.38	SST	CG	N
0.540	13.72	71636	.88	22.4	.458	11.6	11	2.0	.61	16	6.9	31	.20	5.1	0.041	1.0	4.88	MW	CG	N
0.540	13.72	71636S	.88	22.4	.458	11.6	9.5	1.7	.49	12	4.7	21	.20	5.1	0.041	1.0	4.88	SST	CG	N
0.540	13.72	71649	.88	22.4	.448	11.4	16	2.9	.59	15	9.7	43	.24	6.1	0.046	1.2	5.25	MW	CG	N
0.540	13.72	71649S	.88	22.4	.448	11.4	14	2.4	.47	12	6.5	29	.24	6.1	0.046	1.2	5.25	SST	CG	N
0.540	13.72	71662	.88	22.4	.432	11.0	29	5.1	.50	13	15	65	.30	7.7	0.054	1.4	5.63	MW	CG	N
0.540	13.72	71662S	.88	22.4	.432	11.0	25	4.4	.40	10	9.8	44	.30	7.7	0.054	1.4	5.63	SST	CG	N
0.540	13.72	71675	.88	22.4	.424	10.8	38	6.7	.47	12	18	80	.33	8.5	0.058	1.5	5.75	MW	CG	N
0.540	13.72	71675S	.88	22.4	.424	10.8	33	5.7	.37	9.5	12	54	.33	8.5	0.058	1.5	5.75	SST	CG	N
0.540	13.72	71688	.88	22.4	.414	10.5	53	9.2	.43	11	23	102	.38	9.6	0.063	1.6	6.00	MW	CG	N
0.540	13.72	71688S	.88	22.4	.414	10.5	45	7.8	.35	8.8	15	69	.38	9.6	0.063	1.6	6.00	SST	CG	N
0.540	13.72	71701	.88	22.4	.406	10.3	68	12	.41	10	27	122	.40	10.2	0.067	1.7	6.00	MW	CG	N
0.540	13.72	71701S	.88	22.4	.406	10.3	57	10	.32	8.2	19	83	.40	10.2	0.067	1.7	6.00	SST	CG	N
0.540	13.72	71637	1.00	25.4	.458	11.6	9.7	1.7	.71	18	6.9	31	.22	5.6	0.041	1.0	5.38	MW	CG	N
0.540	13.72	71637S	1.00	25.4	.458	11.6	8.2	1.4	.57	14	4.7	21	.22	5.6	0.041	1.0	5.38	SST	CG	N
0.540	13.72	71650	1.00	25.4	.448	11.4	14	2.5	.69	17	9.7	43	.26	6.7	0.046	1.2	5.75	MW	CG	N
0.540	13.72	71650S	1.00	25.4	.448	11.4	12	2.1	.55	14	6.5	29	.26	6.7	0.046	1.2	5.75	SST	CG	N
0.540	13.72	71663	1.00	25.4	.432	11.0	25	4.4	.58	15	15	65	.34	8.6	0.054	1.4	6.25	MW	CG	N
0.540	13.72	71663S	1.00	25.4	.432	11.0	21	3.8	.46	12	9.8	44	.34	8.6	0.054	1.4	6.25	SST	CG	N
0.540	13.72	71676	1.00	25.4	.424	10.8	33	5.8	.54	14	18	80	.37	9.4	0.058	1.5	6.38	MW	CG	N
0.540	13.72	71676S	1.00	25.4	.424	10.8	28	4.9	.43	11	12	54	.37	9.4	0.058	1.5	6.38	SST	CG	N
0.540	13.72	71689	1.00	25.4	.414	10.5	45	7.9	.51	13	23	102	.42	10.6	0.063	1.6	6.63	MW	CG	N
0.540	13.72	71689S	1.00	25.4	.414	10.5	38	6.7	.40	10	15	69	.42	10.6	0.063	1.6	6.63	SST	CG	N
0.540	13.72	71702	1.00	25.4	.406	10.3	58	10	.47	12	27	122	.45	11.5	0.067	1.7	6.75	MW	CG	N
0.540	13.72	71702S	1.00	25.4	.406	10.3	49	8.6	.38	9.6	19	83	.45	11.5	0.067	1.7	6.75	SST	CG	N
0.540	13.72	71638	1.25	31.8	.458	11.6	7.6	1.3	.91	23	6.9	31	.26	6.5	0.041	1.0	6.25	MW	CG	N
0.540	13.72	71638S	1.25	31.8	.458	11.6	6.5	1.1	.72	18	4.7	21	.26	6.5	0.041	1.0	6.25	SST	CG	N
0.540	13.72	71652	1.25	31.8	.448	11.4	11	1.9	.87	22	9.7	43	.32	8.0	0.046	1.2	6.88	MW	CG	N
0.540	13.72	71652S	1.25	31.8	.448	11.4	9.4	1.6	.70	18	6.5	29	.32	8.0	0.046	1.2	6.88	SST	CG	N
0.540	13.72	71664	1.25	31.8	.432	11.0	20	3.4	.74	19	15	65	.40	10.1	0.054	1.4	7.38	MW	CG	N
0.540	13.72	71664S	1.25	31.8	.432	11.0	17	2.9	.59	15	9.8	44	.40	10.1	0.054	1.4	7.38	SST	CG	N
0.540	13.72	71677	1.25	31.8	.424	10.8	26	4.5	.70	18	18	80	.44	11.2	0.058	1.5	7.63	MW	CG	N
0.540	13.72	71677S	1.25	31.8	.424	10.8	22	3.8	.56	14	12	54	.44	11.2	0.058	1.5	7.63	SST	CG	N
0.540	13.72	71690	1.25	31.8	.414	10.5	35	6.1	.65	17	23	102	.50	12.8	0.063	1.6	8.00	MW	CG	N
0.540	13.72	71690S	1.25	31.8	.414	10.5	30	5.2	.52	13	15	69	.50	12.8	0.063	1.6	8.00	SST	CG	N
0.540	13.72	71703	1.25	31.8	.406	10.3	45	7.8	.61	16	27	122	.54	13.8	0.067	1.7	8.13	MW	CG	N
0.540	13.72	71703S	1.25	31.8	.406	10.3	38	6.7	.49	12	19	83	.54	13.8	0.067	1.7	8.13	SST	CG	N
0.540	13.72	71639	1.50	38.1	.458	11.6	6.3	1.1	1.1	28	6.9	31	.30	7.6	0.041	1.0	7.25	MW	CG	N
0.540	13.72	71639S	1.50	38.1	.458	11.6	5.3	.93	.88	22	4.7	21	.30	7.6	0.041	1.0	7.25	SST	CG	N
0.540	13.72	71651	1.50	38.1	.448	11.4	9.1	1.6	1.1	27	9.7	43	.36	9.2	0.046	1.2	7.88	MW	CG	N
0.540	13.72	71651S	1.50	38.1	.448	11.4	7.7	1.4	.85	21	6.5	29	.36	9.2	0.046	1.2	7.88	SST	CG	N
0.540	13.72	71665	1.50	38.1	.432	11.0	16	2.8	.90	23	15	65	.47	11.8	0.054	1.4	8.63	MW	CG	N
0.540	13.72	71665S	1.50	38.1	.432	11.0	14	2.4	.72	18	9.8	44	.47	11.8	0.054	1.4	8.63	SST	CG	N
0.540	13.72	71678	1.50	38.1	.424	10.8	21	3.7	.85	22	18	80	.51	13.1	0.058	1.5	8.88	MW	CG	N
0.540	13.72	71678S	1.50	38.1	.424	10.8	18	3.1	.68	17	12	54	.51	13.1	0.058	1.5	8.88	SST	CG	N
0.540	13.72	71691	1.50	38.1	.414	10.5	29	5.0	.80	20	23	102	.58	14.8	0.063	1.6	9.25	MW	CG	N
0.540	13.72	71691S	1.50	38.1	.414	10.5	24	4.3	.63	16	15	69	.58	14.8	0.063	1.6	9.25	SST	CG	N
0.540	13.72	71704	1.50	38.1	.406	10.3	37	6.4	.75	19	27	122	.64	16.2	0.067	1.7	9.50	MW	CG	N
0.540	13.72	71704S	1.50	38.1	.406	10.3	31	5.4	.60	15	19	83	.64	16.2	0.067	1.7	9.50	SST	CG	N
0.540	13.72	71640	1.75	44.5	.458	11.6	5.3	.93	1.3	33	6.9	31	.33	8.5	0.041	1.0	8.13	MW	CG	N
0.540	13.72	71640S	1.75	44.5	.458	11.6	4.5	.79	1.0	26	4.7	21	.33	8.5	0.041	1.0	8.13	SST	CG	N
0.540	13.72	71653	1.75	44.5	.448	11.4	7.7	1.4	1.3	32	9.7	43	.41	10.4	0.046	1.2	8.88	MW	CG	N
0.540	13.72	71653S	1.75	44.5	.448	11.4	6.6	1.2	1.0	25	6.5	29	.41	10.4	0.046	1.2	8.88	SST	CG	N
0.540	13.72	71666	1.75	44.5	.432	11.0	14	2.4	1.1	27	15	65	.53	13.4	0.054	1.4	9.75	MW	CG	N
0.540	13.72	71666S	1.75	44.5	.432	11.0	12	2.0	.85	21	9.8	44	.53	13.4	0.054	1.4	9.75	SST	CG	N
0.540	13.72	71679	1.75	44.5	.424	10.8	18	3.1	1.0	26	18	80	.59	14.9	0.058	1.5	10.1	MW	CG	N
0.540	13.72	71679S	1.75	44.5	.424	10.8	15	2.6	.80	20	12	54	.59	14.9	0.058	1.5	10.1	SST	CG	N
0.540	13.72	71692	1.75	44.5	.414	10.5	24	4.3	.94	24	23	102	.67	17.0	0.063	1.6	10.6	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.540	13.72	71692S	1.75	44.5	.414	10.5	21	3.6	.75	19	15	69	.67	17.0	0.063	1.6	10.6	SST	CG	N
0.540	13.72	71705	1.75	44.5	.406	10.3	31	5.4	.88	22	27	122	.73	18.5	0.067	1.7	10.9	MW	CG	N
0.540	13.72	71705S	1.75	44.5	.406	10.3	26	4.6	.70	18	19	83	.73	18.5	0.067	1.7	10.9	SST	CG	N
0.540	13.72	71641	2.00	50.8	.458	11.6	4.6	.81	1.5	38	6.9	31	.37	9.5	0.041	1.0	9.13	MW	CG	N
0.540	13.72	71641S	2.00	50.8	.458	11.6	3.9	.69	1.2	30	4.7	21	.37	9.5	0.041	1.0	9.13	SST	CG	N
0.540	13.72	71654	2.00	50.8	.448	11.4	6.7	1.2	1.4	37	9.7	43	.46	11.7	0.046	1.2	10.0	MW	CG	N
0.540	13.72	71654S	2.00	50.8	.448	11.4	5.7	1.0	1.1	29	6.5	29	.46	11.7	0.046	1.2	10.0	SST	CG	N
0.540	13.72	71667	2.00	50.8	.432	11.0	12	2.1	1.2	31	15	65	.59	15.1	0.054	1.4	11.0	MW	CG	N
0.540	13.72	71667S	2.00	50.8	.432	11.0	10	1.8	.97	25	9.8	44	.59	15.1	0.054	1.4	11.0	SST	CG	N
0.540	13.72	71680	2.00	50.8	.424	10.8	16	2.7	1.2	29	18	80	.66	16.8	0.058	1.5	11.4	MW	CG	N
0.540	13.72	71680S	2.00	50.8	.424	10.8	13	2.3	.92	23	12	54	.66	16.8	0.058	1.5	11.4	SST	CG	N
0.540	13.72	71693	2.00	50.8	.414	10.5	21	3.7	1.1	28	23	102	.75	19.0	0.063	1.6	11.9	MW	CG	N
0.540	13.72	71693S	2.00	50.8	.414	10.5	18	3.1	.87	22	15	69	.75	19.0	0.063	1.6	11.9	SST	CG	N
0.540	13.72	71706	2.00	50.8	.406	10.3	27	4.7	1.0	26	27	122	.82	20.8	0.067	1.7	12.3	MW	CG	N
0.540	13.72	71706S	2.00	50.8	.406	10.3	23	4.0	.81	21	19	83	.82	20.8	0.067	1.7	12.3	SST	CG	N
0.540	13.72	71642	2.25	57.2	.458	11.6	4.1	.72	1.7	43	6.9	31	.41	10.4	0.041	1.0	10.0	MW	CG	N
0.540	13.72	71642S	2.25	57.2	.458	11.6	3.5	.61	1.3	34	4.7	21	.41	10.4	0.041	1.0	10.0	SST	CG	N
0.540	13.72	71655	2.25	57.2	.448	11.4	5.9	1.0	1.6	41	9.7	43	.51	12.9	0.046	1.2	11.0	MW	CG	N
0.540	13.72	71655S	2.25	57.2	.448	11.4	5.0	.88	1.3	33	6.5	29	.51	12.9	0.046	1.2	11.0	SST	CG	N
0.540	13.72	71668	2.25	57.2	.432	11.0	11	1.8	1.4	35	15	65	.65	16.6	0.054	1.4	12.1	MW	CG	N
0.540	13.72	71668S	2.25	57.2	.432	11.0	8.9	1.6	1.1	28	9.8	44	.65	16.6	0.054	1.4	12.1	SST	CG	N
0.540	13.72	71681	2.25	57.2	.424	10.8	14	2.4	1.3	33	18	80	.73	18.6	0.058	1.5	12.6	MW	CG	N
0.540	13.72	71681S	2.25	57.2	.424	10.8	12	2.0	1.0	27	12	54	.73	18.6	0.058	1.5	12.6	SST	CG	N
0.540	13.72	71694	2.25	57.2	.414	10.5	19	3.3	1.2	31	23	102	.83	21.2	0.063	1.6	13.3	MW	CG	N
0.540	13.72	71694S	2.25	57.2	.414	10.5	16	2.8	.98	25	15	69	.83	21.2	0.063	1.6	13.3	SST	CG	N
0.540	13.72	71707	2.25	57.2	.406	10.3	24	4.1	1.2	29	27	122	.91	23.2	0.067	1.7	13.6	MW	CG	N
0.540	13.72	71707S	2.25	57.2	.406	10.3	20	3.5	.92	23	19	83	.91	23.2	0.067	1.7	13.6	SST	CG	N
0.540	13.72	71643	2.50	63.5	.458	11.6	3.7	.64	1.9	48	6.9	31	.45	11.3	0.041	1.0	10.9	MW	CG	N
0.540	13.72	71643S	2.50	63.5	.458	11.6	3.1	.55	1.5	38	4.7	21	.45	11.3	0.041	1.0	10.9	SST	CG	N
0.540	13.72	71656	2.50	63.5	.448	11.4	5.3	.93	1.8	46	9.7	43	.55	14.0	0.046	1.2	12.0	MW	CG	N
0.540	13.72	71656S	2.50	63.5	.448	11.4	4.5	.79	1.4	37	6.5	29	.55	14.0	0.046	1.2	12.0	SST	CG	N
0.540	13.72	71669	2.50	63.5	.432	11.0	9.4	1.6	1.5	39	15	65	.72	18.3	0.054	1.4	13.4	MW	CG	N
0.540	13.72	71669S	2.50	63.5	.432	11.0	8.0	1.4	1.2	31	9.8	44	.72	18.3	0.054	1.4	13.4	SST	CG	N
0.540	13.72	71682	2.50	63.5	.424	10.8	12	2.1	1.5	37	18	80	.80	20.4	0.058	1.5	13.9	MW	CG	N
0.540	13.72	71682S	2.50	63.5	.424	10.8	10	1.8	1.2	30	12	54	.80	20.4	0.058	1.5	13.9	SST	CG	N
0.540	13.72	71695	2.50	63.5	.414	10.5	17	2.9	1.4	35	23	102	.92	23.4	0.063	1.6	14.6	MW	CG	N
0.540	13.72	71695S	2.50	63.5	.414	10.5	14	2.5	1.1	28	15	69	.92	23.4	0.063	1.6	14.6	SST	CG	N
0.540	13.72	71708	2.50	63.5	.406	10.3	21	3.7	1.3	33	27	122	1.01	25.5	0.067	1.7	15.0	MW	CG	N
0.540	13.72	71708S	2.50	63.5	.406	10.3	18	3.1	1.0	26	19	83	1.01	25.5	0.067	1.7	15.0	SST	CG	N
0.540	13.72	71644	2.75	69.9	.458	11.6	3.3	.58	2.1	53	6.9	31	.49	12.4	0.041	1.0	11.9	MW	CG	N
0.540	13.72	71644S	2.75	69.9	.458	11.6	2.8	.49	1.6	42	4.7	21	.49	12.4	0.041	1.0	11.9	SST	CG	N
0.540	13.72	71657	2.75	69.9	.448	11.4	4.8	.84	2.0	51	9.7	43	.60	15.3	0.046	1.2	13.1	MW	CG	N
0.540	13.72	71657S	2.75	69.9	.448	11.4	4.1	.72	1.6	41	6.5	29	.60	15.3	0.046	1.2	13.1	SST	CG	N
0.540	13.72	71670	2.75	69.9	.432	11.0	8.5	1.5	1.7	43	15	65	.78	19.9	0.054	1.4	14.5	MW	CG	N
0.540	13.72	71670S	2.75	69.9	.432	11.0	7.2	1.3	1.4	35	9.8	44	.78	19.9	0.054	1.4	14.5	SST	CG	N
0.540	13.72	71683	2.75	69.9	.424	10.8	11	1.9	1.6	41	18	80	.88	22.5	0.058	1.5	15.3	MW	CG	N
0.540	13.72	71683S	2.75	69.9	.424	10.8	9.4	1.6	1.3	33	12	54	.88	22.5	0.058	1.5	15.3	SST	CG	N
0.540	13.72	71696	2.75	69.9	.414	10.5	15	2.6	1.5	39	23	102	1.00	25.4	0.063	1.6	15.9	MW	CG	N
0.540	13.72	71696S	2.75	69.9	.414	10.5	13	2.2	1.2	31	15	69	1.00	25.4	0.063	1.6	15.9	SST	CG	N
0.540	13.72	71709	2.75	69.9	.406	10.3	19	3.3	1.4	36	27	122	1.10	27.9	0.067	1.7	16.4	MW	CG	N
0.540	13.72	71709S	2.75	69.9	.406	10.3	16	2.8	1.1	29	19	83	1.10	27.9	0.067	1.7	16.4	SST	CG	N
0.540	13.72	71645	3.00	76.2	.458	11.6	3.0	.53	2.3	57	6.9	31	.52	13.3	0.041	1.0	12.8	MW	CG	N
0.540	13.72	71645S	3.00	76.2	.458	11.6	2.6	.45	1.8	46	4.7	21	.52	13.3	0.041	1.0	12.8	SST	CG	N
0.540	13.72	71658	3.00	76.2	.448	11.4	4.4	.77	2.2	56	9.7	43	.65	16.5	0.046	1.2	14.1	MW	CG	N
0.540	13.72	71658S	3.00	76.2	.448	11.4	3.7	.66	1.7	44	6.5	29	.65	16.5	0.046	1.2	14.1	SST	CG	N
0.540	13.72	71671	3.00	76.2	.432	11.0	7.8	1.4	1.9	48	15	65	.85	21.6	0.054	1.4	15.8	MW	CG	N
0.540	13.72	71671S	3.00	76.2	.432	11.0	6.6	1.2	1.5	38	9.8	44	.85	21.6	0.054	1.4	15.8	SST	CG	N
0.540	13.72	71684	3.00	76.2	.424	10.8	10	1.8	1.8	45	18	80	.95	24.1	0.058	1.5	16.4	MW	CG	N
0.540	13.72	71684S	3.00	76.2	.424	10.8	8.6	1.5	1.4	36	12	54	.95	24.1	0.058	1.5	16.4	SST	CG	N
0.540	13.72	71697	3.00	76.2	.414	10.5	14	2.4	1.7	42	23	102	1.09	27.6	0.063	1.6	17.3	MW	CG	N
0.540	13.72	71697S	3.00	76.2	.414	10.5	12	2.0	1.3	34	15	69	1.09	27.6	0.063	1.6	17.3	SST	CG	N
0.540	13.72	71710	3.00	76.2	.406	10.3	18	3.1	1.6	40	27	122	1.18	30.0	0.067	1.7	17.6	MW	CG	N
0.540	13.72	71710S	3.00	76.2	.406	10.3	15	2.6	1.2	32	19	83	1.18	30.0	0.067	1.7	17.6	SST	CG	N
0.546	13.87	S-56	.28	7.1	.484	12.3	4.3	.75	.13	3.2	.54	2.4	.16	3.9	0.031	0.8	4.00	SST	C	N
0.546	13.87	A9-48	.31	7.9	.454	11.5	23	4.0	.13	3.3	2.9	13	.18	4.7	0.046	1.2	4.00	SST	CG	N
0.546	13.87	YY-68	.31	7.9	.422	10.7	187	33	.08	2.1	16	69	.19	4.7	0.062	1.6	3.00	SPR	CG	Z
0.546	13.87	S-830	.34	8.7	.436	11.1	49	8.6	.12	3.1	6.1	27	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.546	13.87	K-27	.38	9.5	.452	11.5	49	8.6	.14	3.6	6.9	31	.14	3.6	0.047	1.2	3.00	SST	CG	N
0.546	13.87	MM-60	.41	10.3	.446	11.3	44	7.6	.18	4.5	7.8	35	.18	4.4	0.050	1.3	3.50	SST	CG	N
0.546	13.87	G-91	.41	10.3	.414	10.5	123	21	.14	3.6	18	78	.25	6.3	0.066	1.7	3.75	SST	CG	N
0.546	13.87	12194	.41	10.3	.346	8.8	1080	189	.05	1.3	57	252	.35	8.9	0.100	2.5	3.50	SPR	CG	Z
0.546	13.87	B6-8	.44	11.1	.500	12.7	1.1	.20	.33	8.5	.38	1.7	.10	2.6	0.023	0.6	4.50	MW	CG	N
0.546	13.87	B1-21	.44	11.1	.450	11.4	55	9.6	.13	3.4	7.3	33	.19	4.9	0.048	1.2	3.00	SST	C	N
0.546	13.87	S-1114	.44	11.1	.446	11.3	64	11	.12	3.1	7.8	35	.15	3.8	0.050	1.3	3.00	SST	CG	N
0.546	13.87	B7-8	.47	11.9	.456	11.6	24	4.2	.26	6.5	6.1	27	.17	4.3	0.045	1.1	3.75	SST	CG	N
0.546	13.87	S-1579	.50	12.7	.452	11.5	33	5.8	.21	5.2	6.9	31	.16	4.2	0.047	1.2	3.50	SST	CG	N
0.546	13.87	A14-34	.53	13.5	.436	11.1	49	8.6	.21	5.3	10	46	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.546	13.87	O-98	.53	13.5	.418	10.6	72	13	.21	5.4	15	67	.32	8.1	0.064	1.6	5.00	SPR	CG	Z
0.546	13.87	A11-8	.53	13.5	.376	9.6	383	67	.10	2.5	37	165	.43	10.8	0.085	2.2	4.00	SPR	C	N
0.546	13.87	GG-80	.53	13.5	.346	8.8	1080	189	.05	1.3	57	252	.35	8.9	0.100	2.5	3.50	SPR	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.546	13.87	S-1370	.56	14.3	.506	12.9	.34	.06	.42	11	.14	.64	.14	3.6	0.020	0.5	6.00	SST	C	N
0.546	13.87	O-151	.56	14.3	.478	12.1	8.3	1.5	.33	8.4	2.7	12	.15	3.9	0.034	0.9	3.50	SST	C	N
0.546	13.87	3178	.56	14.3	.462	11.7	14	2.4	.37	9.5	5.2	23	.19	4.8	0.042	1.1	4.50	SPR	CG	Z
0.546	13.87	10051	.56	14.3	.422	10.7	83	15	.19	4.7	16	69	.26	6.7	0.062	1.6	4.25	SPR	CG	Z
0.546	13.87	U-29	.59	15.1	.460	11.7	19	3.4	.29	7.4	5.7	25	.17	4.4	0.043	1.1	4.00	SPR	CG	N
0.546	13.87	A11-26	.59	15.1	.446	11.3	22	3.8	.29	7.4	6.4	28	.30	7.6	0.050	1.3	5.00	SST	C	N
0.546	13.87	B11-3	.63	15.9	.438	11.1	40	7.1	.24	6.1	9.7	43	.23	5.8	0.054	1.4	4.25	SST	CG	N
0.546	13.87	M-109	.66	16.7	.480	12.2	2.8	.49	.44	11	1.2	5.5	.21	5.4	0.033	0.8	6.50	SPR	CG	N
0.546	13.87	2953	.69	17.4	.498	12.6	.79	.14	.54	14	.42	1.9	.15	3.8	0.024	0.6	6.25	MW	CG	Z
0.546	13.87	BB-69	.69	17.4	.486	12.3	1.9	.33	.49	12	.93	4.1	.20	5.0	0.030	0.8	6.50	MW	CG	BO
0.546	13.87	G-92	.69	17.4	.470	11.9	7.2	1.3	.51	13	3.7	16	.18	4.6	0.038	1.0	4.75	SST	CG	N
0.546	13.87	A9-68	.69	17.4	.452	11.5	14	2.5	.41	10	5.7	25	.28	7.2	0.047	1.2	6.00	SPR	CG	N
0.546	13.87	A13-24	.69	17.4	.434	11.0	39	6.8	.28	7.1	11	48	.27	6.8	0.056	1.4	4.75	SST	CG	N
0.546	13.87	B6-68	.72	18.2	.476	12.1	8.1	1.4	.38	9.7	3.1	14	.14	3.6	0.035	0.9	4.00	SPR	CG	N
0.546	13.87	A13-48	.72	18.2	.468	11.9	11	2.0	.35	8.9	4.0	18	.16	4.0	0.039	1.0	4.00	SST	CG	N
0.546	13.87	JJ-93	.75	19.1	.466	11.8	14	2.5	.32	8.2	4.6	20	.20	5.1	0.040	1.0	4.00	SPR	C	N
0.546	13.87	10054	.75	19.1	.456	11.6	19	3.3	.35	8.8	6.5	29	.20	5.1	0.045	1.1	4.50	SPR	CG	GI
0.546	13.87	B14-34	.75	19.1	.454	11.5	6.4	1.1	.24	6.2	1.6	7.0	.51	12.9	0.046	1.2	10.0	SPR	C	Z
0.546	13.87	S-1408	.75	19.1	.434	11.0	42	7.3	.26	6.6	11	48	.31	7.8	0.056	1.4	4.50	SST	C	N
0.546	13.87	K-61	.75	19.1	.422	10.7	36	6.3	.35	8.8	13	56	.40	10.2	0.062	1.6	6.50	SST	CG	N
0.546	13.87	3597	.75	19.1	.420	10.7	67	12	.34	8.6	23	101	.32	8.0	0.063	1.6	5.00	MW	CG	Z
0.546	13.87	WW-64	.75	19.1	.402	10.2	121	21	.19	4.8	23	102	.36	9.1	0.072	1.8	5.00	HD	CG	Z
0.546	13.87	A14-57	.78	19.8	.434	11.0	36	6.2	.31	7.8	11	48	.28	7.1	0.056	1.4	5.00	SST	CG	N
0.546	13.87	10662	.81	20.6	.504	12.8	.55	.10	.68	17	.37	1.7	.14	3.5	0.021	0.5	5.50	MW	C	Z
0.546	13.87	A11-59	.81	20.6	.464	11.8	7.9	1.4	.57	14	4.5	20	.25	6.2	0.041	1.0	6.00	SPR	CG	Z
0.546	13.87	A15-57	.81	20.6	.456	11.6	14	2.4	.44	11	6.1	27	.23	5.7	0.045	1.1	5.00	SST	CG	N
0.546	13.87	S-1194	.81	20.6	.422	10.7	65	11	.22	5.7	15	65	.28	7.1	0.062	1.6	4.50	SST	CG	N
0.546	13.87	B1-30	.81	20.6	.418	10.6	55	9.6	.29	7.5	16	71	.35	8.9	0.064	1.6	5.50	SST	CG	N
0.546	13.87	A-60	.81	20.6	.356	9.0	319	56	.15	3.9	49	218	.57	14.5	0.095	2.4	6.00	SPR	CG	Z
0.546	13.87	G-81	.84	21.4	.482	12.2	1.9	.34	.60	15	1.1	5.1	.25	6.3	0.032	0.8	7.75	HD	CG	N
0.546	13.87	S-1633	.84	21.4	.464	11.8	10	1.8	.45	11	4.6	20	.19	4.9	0.041	1.0	4.75	SST	CG	N
0.546	13.87	S-1049	.88	22.2	.422	10.7	47	8.2	.31	8.0	15	65	.34	8.7	0.062	1.6	5.50	SST	CG	N
0.546	13.87	G-50	.88	22.2	.402	10.2	90	16	.24	6.0	21	95	.40	10.1	0.072	1.8	5.50	SST	CG	N
0.546	13.87	L-26	.88	22.2	.402	10.2	84	15	.25	6.5	21	95	.41	10.5	0.072	1.8	5.75	SST	CG	N
0.546	13.87	A13-61	.91	23.0	.416	10.6	61	11	.29	7.4	18	79	.37	9.5	0.065	1.7	5.75	SPR	CG	GI
0.546	13.87	S-869	.94	23.8	.484	12.3	2.1	.37	.75	19	1.6	7.1	.19	4.7	0.031	0.8	6.00	SST	CG	N
0.546	13.87	10176	.94	23.8	.452	11.5	7.5	1.3	.44	11	3.3	15	.49	12.5	0.047	1.2	9.50	SPR	C	Z
0.546	13.87	S-1061	1.00	25.4	.472	12.0	5.9	1.0	.57	15	3.4	15	.22	5.6	0.037	0.9	5.00	SST	C	N
0.546	13.87	A15-27	1.00	25.4	.456	11.6	12	2.1	.51	13	6.1	27	.25	6.3	0.045	1.1	5.50	SST	CG	N
0.546	13.87	S-271	1.00	25.4	.438	11.1	18	3.1	.55	14	9.7	43	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.546	13.87	B1-55	1.00	25.4	.434	11.0	29	5.1	.40	10	12	51	.34	8.7	0.056	1.4	6.00	SPR	CG	GI
0.546	13.87	YY-70	1.00	25.4	.412	10.5	59	10	.33	8.5	20	87	.44	11.1	0.067	1.7	6.50	SPR	CG	Z
0.546	13.87	12327	1.09	27.8	.426	10.8	32	5.7	.44	11	14	63	.42	10.7	0.060	1.5	7.00	SPR	CG	GI
0.546	13.87	B9-32	1.13	28.6	.468	11.9	5.7	.99	.75	19	4.2	19	.25	6.4	0.039	1.0	6.50	SPR	CG	Z
0.546	13.87	VV-65	1.13	28.6	.422	10.7	37	6.6	.41	11	16	69	.43	11.0	0.062	1.6	7.00	SPR	CG	N
0.546	13.87	AA-86	1.13	28.6	.366	9.3	126	22	.31	7.8	39	173	.81	20.6	0.090	2.3	9.00	SST	CG	N
0.546	13.87	10630	1.16	29.4	.488	12.4	1.3	.23	.92	23	1.2	5.4	.23	5.9	0.029	0.7	7.00	SST	C	N
0.546	13.87	H-36	1.19	30.2	.484	12.3	.62	.11	.64	16	.39	1.8	.55	14.0	0.031	0.8	17.8	MW	CG	N
0.546	13.87	A15-68	1.19	30.2	.470	11.9	4.8	.84	.77	20	3.7	16	.24	6.0	0.038	1.0	6.25	SST	CG	N
0.546	13.87	A9-57	1.19	30.2	.470	11.9	4.1	.71	.91	23	3.7	16	.27	6.8	0.038	1.0	7.00	SST	CG	N
0.546	13.87	K-55	1.19	30.2	.452	11.5	7.0	1.2	.72	18	5.0	22	.47	11.9	0.047	1.2	9.00	SST	C	N
0.546	13.87	11706	1.19	30.2	.434	11.0	20	3.5	.58	15	12	51	.45	11.4	0.056	1.4	8.00	SPR	CG	Z
0.546	13.87	W-56	1.19	30.2	.422	10.7	28	5.0	.52	13	15	65	.48	12.2	0.062	1.6	7.75	SST	CG	N
0.546	13.87	10465	1.22	31.0	.476	12.1	2.0	.34	.86	22	1.7	7.5	.36	9.1	0.035	0.9	10.3	SPR	CG	Z
0.546	13.87	I-94	1.25	31.8	.490	12.4	.52	.09	.87	22	.45	2.0	.39	9.8	0.028	0.7	12.8	SST	C	N
0.546	13.87	YY-49	1.25	31.8	.456	11.6	12	2.1	.55	14	6.5	29	.27	6.9	0.045	1.1	6.00	SPR	CG	N
0.546	13.87	RR-50	1.25	31.8	.454	11.5	11	2.0	.58	15	6.5	29	.32	8.2	0.046	1.2	6.00	SST	C	N
0.546	13.87	S-932	1.25	31.8	.452	11.5	6.9	1.2	.77	20	5.3	24	.48	12.1	0.047	1.2	9.00	SST	C	N
0.546	13.87	S-1137	1.25	31.8	.452	11.5	11	1.9	.63	16	6.9	31	.35	9.0	0.047	1.2	6.50	SST	C	N
0.546	13.87	S-2	1.25	31.8	.438	11.1	15	2.6	.66	17	9.7	43	.43	11.0	0.054	1.4	8.00	SST	CG	N
0.546	13.87	OO-99	1.25	31.8	.362	9.2	96	17	.15	3.7	14	62	1.10	28.0	0.092	2.3	12.0	SST	CG	N
0.546	13.87	S-3208	1.31	33.3	.458	11.6	8.0	1.4	.71	18	5.7	25	.34	8.7	0.044	1.1	6.75	SST	C	N
0.546	13.87	S-1593	1.34	34.1	.436	11.1	14	2.5	.73	19	10	46	.55	14.0	0.055	1.4	9.00	SST	C	N
0.546	13.87	1897	1.38	34.9	.498	12.6	.52	.09	1.1	29	.59	2.6	.23	5.8	0.024	0.6	8.50	MW	C	Z
0.546	13.87	FF-92	1.38	34.9	.472	12.0	2.0	.36	.93	24	1.9	8.5	.44	11.3	0.037	0.9	12.0	SPR	CG	N
0.546	13.87	XX-48	1.38	34.9	.472	12.0	3.9	.69	.86	22	3.4	15	.28	7.0	0.037	0.9	6.50	SST	C	N
0.546	13.87	2707	1.38	34.9	.422	10.7	30	5.2	.52	13	16	69	.51	13.0	0.062	1.6	8.25	HD	CG	Z
0.546	13.87	S-1160	1.38	34.9	.422	10.7	25	4.4	.58	15	15	65	.53	13.4	0.062	1.6	8.50	SST	CG	N
0.546	13.87	A15-26	1.38	34.9	.418	10.6	48	8.4	.36	9.1	17	76	.42	10.6	0.064	1.6	6.50	SPR	CG	GI
0.546	13.87	10142	1.38	34.9	.418	10.6	33	5.8	.52	13	17	76	.54	13.8	0.064	1.6	8.50	SPR	CG	Z
0.546	13.87	A-33	1.38	34.9	.418	10.6	27	4.7	.63	16	17	76	.64	16.3	0.064	1.6	10.0	SPR	CG	Z
0.546	13.87	QQ-45	1.38	34.9	.402	10.2	48	8.5	.47	12	23	102	.76	19.2	0.072	1.8	9.50	HD	C	Z
0.546	13.87	3627	1.38	34.9	.376	9.6	96	17	.39	9.8	37	165	.85	21.6	0.085	2.2	10.0	HD	CG	Z
0.546	13.87	I-4	1.41	35.7	.482	12.2	1.2	.22	1.0	26	1.3	5.6	.38	9.8	0.032	0.8	11.0	SPR	C	N
0.546	13.87	S-1074	1.44	36.5	.466	11.8	2.9	.51	.98	25	2.8	13	.46	11.7	0.040	1.0	10.5	SST	C	N
0.546	13.87	10759	1.44	36.5	.452	11.5	5.4	.94	.80	20	4.3	19	.63	16.1	0.047	1.2	12.5	SPR	C	Z
0.546	13.87	A14-62	1.47	37.3	.418	10.6	31	5.4	.55	14	17	76	.58	14.6	0.064	1.6	9.00	SPR	CG	GI
0.546	13.87	BB-94	1.50	38.1	.488	12.4	1.5	.25	1.2	30	1.7	7.6	.22	5.5	0.029	0.7	6.50	SST	C	N
0.546	13.87	DD-55	1.50	38.1	.486	12.3	.94	.16	1.1	29	1.1	4.8	.36	9.1	0.030	0.8	11.0	MW	C	N
0.546	13.87	S-1435	1.50	38.1	.470	11.9	4.4	.77	.83	21	3.7	16	.25	6.3	0.038	1.0	6.50	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.546	13.87	B1-62	1.50	38.1	.466	11.8	6.3	1.1	.72	18	4.6	20	.26	6.6	0.040	1.0	6.50	SPR	CG	Z
0.546	13.87	W-50	1.50	38.1	.464	11.8	3.4	.60	1.1	28	3.7	17	.41	10.4	0.041	1.0	10.0	SST	CG	N
0.546	13.87	S-1066	1.50	38.1	.438	11.1	5.9	1.0	.58	15	3.5	15	.92	23.3	0.054	1.4	17.0	SST	CG	N
0.546	13.87	10138	1.50	38.1	.422	10.7	27	4.7	.58	15	16	69	.62	15.7	0.062	1.6	9.00	HD	C	Z
0.546	13.87	H-52	1.50	38.1	.386	9.8	51	8.9	.54	14	27	122	.96	24.4	0.080	2.0	12.0	SST	CG	N
0.546	13.87	10210	1.63	41.3	.402	10.2	40	7.1	.57	14	23	102	.79	20.1	0.072	1.8	11.0	SPR	CG	Z
0.546	13.87	1591	1.63	41.3	.398	10.1	61	11	.41	10	25	110	.65	16.5	0.074	1.9	8.75	SPR	CG	Z
0.546	13.87	MM-53	1.66	42.1	.426	10.8	23	4.0	.58	15	13	59	.50	12.6	0.060	1.5	8.25	SST	CG	N
0.546	13.87	10587	1.69	42.8	.456	11.6	4.6	.81	1.2	30	5.5	24	.50	12.6	0.045	1.1	11.0	SST	CG	N
0.546	13.87	12238	1.69	42.8	.446	11.3	9.2	1.6	.90	23	8.3	37	.50	12.7	0.050	1.3	10.0	SPR	CG	Z
0.546	13.87	S-972	1.69	42.8	.388	9.9	43	7.6	.65	16	28	125	1.03	26.1	0.079	2.0	13.0	SST	CG	N
0.546	13.87	G-46	1.75	44.5	.464	11.8	1.6	.28	.93	24	1.5	6.7	.82	20.8	0.041	1.0	19.0	SST	C	N
0.546	13.87	S-78	1.75	44.5	.412	10.5	25	4.3	.74	19	18	82	.82	20.8	0.067	1.7	11.3	SST	C	N
0.546	13.87	12280	1.78	45.2	.494	12.5	.36	.06	1.4	35	.49	2.2	.42	10.6	0.026	0.7	15.0	MW	C	Z
0.546	13.87	11474	1.78	45.2	.446	11.3	9.2	1.6	.90	23	8.3	37	.55	14.0	0.050	1.3	10.0	SPR	C	Z
0.546	13.87	N-118	1.81	46.0	.376	9.6	81	14	.46	12	37	165	.98	24.8	0.085	2.2	11.5	SPR	CG	Z
0.546	13.87	12217	1.84	46.8	.472	12.0	2.6	.45	1.4	36	3.6	16	.41	10.3	0.037	0.9	10.0	SPR	C	Z
0.546	13.87	3817	1.88	47.6	.362	9.2	110	19	.41	10	45	199	1.10	28.0	0.092	2.3	12.0	HD	CG	Z
0.546	13.87	S-325	1.94	49.2	.452	11.5	3.9	.67	1.2	31	4.7	21	.71	17.9	0.047	1.2	15.0	SST	CG	N
0.546	13.87	Q-44	2.00	50.8	.466	11.8	1.7	.29	1.2	31	2.1	9.2	.76	19.3	0.040	1.0	19.0	SPR	CG	N
0.546	13.87	11650	2.00	50.8	.352	8.9	108	19	.48	12	52	231	1.46	37.0	0.097	2.5	15.0	SPR	CG	Z
0.546	13.87	12309	2.09	53.2	.354	9.0	103	18	.49	12	50	224	1.44	36.6	0.096	2.4	15.0	SPR	CG	Z
0.546	13.87	S-200	2.13	54.0	.402	10.2	40	7.0	.53	14	21	95	.79	20.1	0.072	1.8	10.0	SST	C	N
0.546	13.87	J-35	2.22	56.4	.364	9.2	73	13	.59	15	43	192	1.48	37.6	0.091	2.3	16.3	SPR	CG	N
0.546	13.87	WW-37	2.50	63.5	.470	11.9	4.6	.80	.86	22	3.9	17	.30	7.7	0.038	1.0	7.00	SPR	C	N
0.546	13.87	12049	2.56	65.1	.452	11.5	5.4	.94	1.4	35	7.4	33	.59	14.9	0.047	1.2	12.5	SPR	CG	N
0.546	13.87	UU-57	2.63	66.7	.446	11.3	5.9	1.0	1.4	36	8.3	37	.73	18.4	0.050	1.3	14.5	SPR	CG	Z
0.546	13.87	11593	2.81	71.4	.386	9.8	36	6.4	.85	22	31	138	1.52	38.6	0.080	2.0	18.0	SPR	CG	GI
0.546	13.87	2595	2.94	74.6	.434	11.0	8.0	1.4	1.4	37	12	51	.95	24.2	0.056	1.4	17.0	SPR	CG	GI
0.546	13.87	12291	3.19	81.0	.446	11.3	4.1	.72	2.0	51	8.3	37	1.05	26.7	0.050	1.3	20.0	SPR	C	N
0.546	13.87	B17-197	4.06	103.2	.412	10.5	14	2.5	1.4	34	20	87	1.36	34.5	0.067	1.7	20.3	SPR	CG	Z
0.546	13.87	A14-70	4.50	114.3	.420	10.7	8.6	1.5	1.8	45	15	68	1.43	36.4	0.063	1.6	22.8	SST	CG	N
0.546	13.87	11626	5.25	133.4	.456	11.6	1.7	.30	3.7	95	6.5	29	1.31	33.1	0.045	1.1	29.0	SPR	CG	Z
0.546	13.87	4003	19.0	482.6	.422	10.7	1.8	.31	8.8	222	16	69	6.73	170.9	0.062	1.6	107.0	HD	C	Z
0.551	14.00	B3-62	3.44	87.3	.301	7.6	245	43	.42	11	102	453	2.56	65.1	0.125	3.2	20.5	SPR	CG	N
0.562	14.27	S-209	.31	7.9	.472	12.0	25	4.4	.11	2.8	2.8	12	.20	5.1	0.045	1.1	3.50	SST	C	N
0.562	14.27	A9-35	.31	7.9	.460	11.7	58	10	.15	3.7	8.5	38	.17	4.2	0.051	1.3	3.25	SPR	CG	Z
0.562	14.27	S-221	.31	7.9	.452	11.5	72	13	.13	3.4	9.5	42	.18	4.5	0.055	1.4	3.25	SST	CG	N
0.562	14.27	2956	.34	8.7	.512	13.0	1.0	.18	.18	4.6	.19	.83	.16	4.1	0.025	0.6	5.50	MW	C	Z
0.562	14.27	JJ-38	.41	10.3	.468	11.9	36	6.4	.18	4.7	6.7	30	.20	5.1	0.047	1.2	3.25	SST	C	N
0.562	14.27	II-20	.41	10.3	.402	10.2	263	46	.09	2.2	23	101	.32	8.1	0.080	2.0	4.00	SPR	CG	N
0.562	14.27	3253	.47	11.9	.452	11.5	58	10	.18	4.7	11	47	.21	5.2	0.055	1.4	3.75	SPR	CG	Z
0.562	14.27	S-1459	.50	12.7	.518	13.2	.68	.12	.37	9.5	.25	1.1	.13	3.2	0.022	0.6	4.75	SST	C	N
0.562	14.27	JJ-8	.50	12.7	.502	12.8	3.0	.53	.34	8.7	1.0	4.6	.16	4.0	0.030	0.8	4.25	SST	C	N
0.562	14.27	K-19	.50	12.7	.478	12.1	16	2.8	.29	7.4	4.6	21	.21	5.3	0.042	1.1	4.00	SPR	C	GI
0.562	14.27	DD-89	.50	12.7	.438	11.1	99	17	.14	3.7	14	63	.22	5.5	0.062	1.6	3.50	SST	CG	N
0.562	14.27	A15-43	.53	13.5	.458	11.6	23	4.1	.27	6.9	6.3	28	.26	6.6	0.052	1.3	5.00	SST	CG	N
0.562	14.27	S-1529	.53	13.5	.446	11.3	40	7.0	.26	6.5	10	46	.28	7.0	0.058	1.5	4.75	SST	CG	N
0.562	14.27	U-61	.53	13.5	.442	11.2	75	13	.17	4.4	13	58	.23	5.7	0.060	1.5	3.75	SST	CG	N
0.562	14.27	S-436	.53	13.5	.434	11.0	113	20	.14	3.5	16	70	.22	5.7	0.064	1.6	3.50	SST	CG	N
0.562	14.27	B1-32	.59	15.1	.448	11.4	59	10	.20	5.1	12	53	.23	5.8	0.057	1.4	4.00	SPR	CG	N
0.562	14.27	S-1350	.63	15.9	.530	13.5	.17	.03	.53	13	.09	.39	.10	2.4	0.016	0.4	5.00	SST	C	N
0.562	14.27	Q-48	.63	15.9	.512	13.0	1.6	.28	.50	13	.79	3.5	.13	3.2	0.025	0.6	4.00	SST	C	N
0.562	14.27	B15-33	.63	15.9	.502	12.8	2.7	.48	.46	12	1.3	5.6	.17	4.2	0.030	0.8	4.50	SST	C	N
0.562	14.27	12685	.63	15.9	.500	12.7	3.9	.68	.47	12	1.8	8.1	.16	3.9	0.031	0.8	4.00	SST	C	N
0.562	14.27	3990	.63	15.9	.446	11.3	39	6.8	.32	8.1	12	55	.30	7.7	0.058	1.5	5.25	SPR	CG	Z
0.562	14.27	S-219	.63	15.9	.438	11.1	74	13	.19	4.9	14	63	.25	6.3	0.062	1.6	4.00	SST	CG	N
0.562	14.27	12750	.63	15.9	.438	11.1	74	13	.19	4.9	14	63	.31	7.9	0.062	1.6	4.00	SST	C	N
0.562	14.27	S-33	.66	16.7	.468	11.9	18	3.2	.37	9.4	6.7	30	.21	5.4	0.047	1.2	4.50	SST	CG	N
0.562	14.27	U-32	.66	16.7	.460	11.7	22	3.8	.37	9.4	8.0	36	.26	6.5	0.051	1.3	5.00	SST	CG	N
0.562	14.27	B-6	.66	16.7	.418	10.6	119	21	.19	4.7	22	99	.34	8.7	0.072	1.8	4.75	SPR	CG	N
0.562	14.27	S-921	.66	16.7	.376	9.6	308	54	.14	3.4	42	185	.47	11.8	0.093	2.4	5.00	SST	CG	N
0.562	14.27	S-1548	.69	17.4	.434	11.0	62	11	.25	6.4	16	70	.30	7.7	0.064	1.6	4.75	SST	CG	N
0.562	14.27	3197	.72	18.2	.498	12.6	2.2	.39	.51	13	1.1	5.1	.21	5.3	0.032	0.8	6.50	SPR	CG	Z
0.562	14.27	4189	.72	18.2	.438	11.1	49	8.5	.31	7.9	15	67	.34	8.7	0.062	1.6	5.50	HD	CG	Z
0.562	14.27	BB-68	.75	19.1	.520	13.2	.51	.09	.62	16	.32	1.4	.13	3.2	0.021	0.5	5.00	SST	C	N
0.562	14.27	S-1138	.75	19.1	.506	12.9	1.8	.32	.59	15	1.1	4.8	.16	4.1	0.028	0.7	4.75	SST	C	N
0.562	14.27	LL-84	.75	19.1	.504	12.8	.99	.17	.47	12	.46	2.1	.28	7.2	0.029	0.7	8.75	MW	C	N
0.562	14.27	S-3121	.75	19.1	.502	12.8	1.7	.29	.54	14	.91	4.0	.21	5.3	0.030	0.8	6.00	SST	C	N
0.562	14.27	S-32	.75	19.1	.478	12.1	10	1.8	.46	12	4.8	21	.20	5.0	0.042	1.1	4.67	SST	CG	N
0.562	14.27	XX-40	.75	19.1	.470	11.9	9.1	1.6	.45	11	4.1	18	.30	7.6	0.046	1.2	6.50	SST	CG	N
0.562	14.27	S-22	.75	19.1	.418	10.6	58	10	.25	6.2	14	64	.50	12.8	0.072	1.8	7.00	SST	CG	N
0.562	14.27	3975	.75	19.1	.402	10.2	175	31	.17	4.4	30	135	.40	10.2	0.080	2.0	5.00	SPR	CG	Z
0.562	14.27	B11-58	.81	20.6	.516	13.1	.64	.11	.65	17	.42	1.9	.16	4.1	0.023	0.6	6.00	MW	C	Z
0.562	14.27	Z-30	.81	20.6	.514	13.1	.56	.10	.63	16	.35	1.6	.19	4.7	0.024	0.6	6.75	SST	C	N
0.562	14.27	10649	.81	20.6	.462	11.7	17	2.9	.48	12	8.0	36	.30	7.6	0.050	1.3	6.00	SPR	CG	Z
0.562	14.27	S-87	.81	20.6	.460	11.7	21	3.7	.38	9.6	8.0	36	.31	7.8	0.051	1.3	5.00	SST	C	N
0.562	14.27	10128	.88	22.2	.454	11.5	13	2.3	.39	9.9	5.2	23	.49	12.3	0.054	1.4	9.00	SPR	CG	N
0.562	14.27	H-49	.88	22.2	.438	11.1	42	7.4	.36	9.0	15	67	.37	9.4	0.062	1.6	6.00	SPR	CG	GI
0.562	14.27	J-37	.88	22.2	.428	10.9	60	10	.32	8.1	19	85	.47	11.9	0.067	1.7	6.00	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.562	14.27	TT-66	.88	22.2	.352	8.9	398	70	.15	3.8	59	262	.63	16.0	0.105	2.7	6.00	SST	CG	N
0.562	14.27	N-136	.91	23.0	.502	12.8	.79	.14	.56	14	.44	2.0	.35	8.8	0.030	0.8	10.5	SST	C	N
0.562	14.27	2535	.91	23.0	.428	10.9	68	12	.39	9.8	26	117	.37	9.4	0.067	1.7	5.50	MW	CG	GI
0.562	14.27	10352	.94	23.8	.494	12.5	2.6	.46	.67	17	1.7	7.7	.27	6.9	0.034	0.9	7.00	SPR	C	Z
0.562	14.27	10820	.94	23.8	.482	12.2	3.3	.57	.58	15	1.9	8.4	.36	9.1	0.040	1.0	9.00	SST	CG	N
0.562	14.27	3799	.94	23.8	.478	12.1	4.0	.70	.52	13	2.1	9.2	.42	10.7	0.042	1.1	10.0	SPR	CG	Z
0.562	14.27	3315	.94	23.8	.448	11.4	17	2.9	.43	11	7.2	32	.51	13.0	0.057	1.4	9.00	SPR	CG	Z
0.562	14.27	JJ-75	.94	23.8	.442	11.2	37	6.4	.37	9.5	14	61	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.562	14.27	10217	.94	23.8	.428	10.9	60	10	.32	8.1	19	85	.40	10.2	0.067	1.7	6.00	SPR	CG	Z
0.562	14.27	3222	.97	24.6	.510	13.0	1.2	.21	.80	20	.97	4.3	.17	4.3	0.026	0.7	5.50	MW	C	Z
0.562	14.27	12660	.98	25.0	.510	13.0	1.1	.20	.81	21	.92	4.1	.18	4.5	0.026	0.7	5.75	MW	C	GI
0.562	14.27	L-19	1.00	25.4	.502	12.8	1.9	.34	.79	20	1.5	6.8	.21	5.3	0.030	0.8	6.00	MW	C	Z
0.562	14.27	10343	1.00	25.4	.494	12.5	2.6	.46	.73	18	1.9	8.5	.27	6.9	0.034	0.9	7.00	SPR	C	Z
0.562	14.27	S-1141	1.00	25.4	.494	12.5	3.0	.53	.77	20	2.3	10	.23	5.8	0.034	0.9	5.75	SST	C	N
0.562	14.27	S-1028	1.00	25.4	.492	12.5	3.2	.56	.79	20	2.5	11	.21	5.3	0.035	0.9	6.00	SST	CG	N
0.562	14.27	S-1305	1.00	25.4	.488	12.4	5.4	.95	.61	16	3.3	15	.19	4.7	0.037	0.9	5.00	SST	CG	N
0.562	14.27	Y-27	1.00	25.4	.482	12.2	7.4	1.3	.60	15	4.4	20	.22	5.6	0.040	1.0	5.50	SPR	CG	Z
0.562	14.27	S-1027	1.00	25.4	.468	11.9	11	1.9	.63	16	6.7	30	.29	7.5	0.047	1.2	6.25	SST	CG	N
0.562	14.27	3881	1.00	25.4	.466	11.8	14	2.5	.54	14	7.6	34	.29	7.3	0.048	1.2	6.00	SPR	CG	GI
0.562	14.27	S-358	1.00	25.4	.464	11.8	15	2.7	.50	13	7.6	34	.27	6.8	0.049	1.2	5.50	SST	CG	N
0.562	14.27	12294	1.00	25.4	.458	11.6	20	3.5	.46	12	9.0	40	.31	7.9	0.052	1.3	6.00	SPR	CG	Z
0.562	14.27	11747	1.00	25.4	.456	11.6	14	2.5	.58	15	8.3	37	.42	10.8	0.053	1.3	8.00	SPR	CG	Z
0.562	14.27	515	1.00	25.4	.454	11.5	22	3.8	.47	12	10	45	.40	10.1	0.054	1.4	6.33	HD	C	Z
0.562	14.27	S-3128	1.00	25.4	.454	11.5	16	2.8	.58	15	9.5	42	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.562	14.27	3578	1.00	25.4	.452	11.5	22	3.9	.64	16	14	64	.36	9.1	0.055	1.4	6.50	MW	CG	Z
0.562	14.27	A14-33	1.00	25.4	.452	11.5	21	3.6	.48	12	10	45	.35	8.8	0.055	1.4	6.33	SST	CG	N
0.562	14.27	11544	1.00	25.4	.426	10.8	57	9.9	.35	8.9	20	88	.51	13.0	0.068	1.7	6.50	SPR	CG	N
0.562	14.27	S-1242	1.00	25.4	.418	10.6	71	13	.29	7.4	21	93	.43	11.0	0.072	1.8	6.00	SST	CG	N
0.562	14.27	2750	1.00	25.4	.402	10.2	78	14	.38	9.6	29	131	.62	15.8	0.080	2.0	8.00	HD	CG	Z
0.562	14.27	10950	1.00	25.4	.400	10.2	110	19	.27	6.8	29	131	.53	13.4	0.081	2.1	6.50	SST	CG	N
0.562	14.27	S-801	1.03	26.2	.438	11.1	26	4.6	.54	14	14	63	.48	12.2	0.062	1.6	7.75	SST	CG	N
0.562	14.27	A11-50	1.06	27.0	.492	12.5	2.9	.52	.78	20	2.3	10	.28	7.1	0.035	0.9	7.00	SPR	C	Z
0.562	14.27	830	1.06	27.0	.352	8.9	318	56	.20	5.1	64	283	.81	20.7	0.105	2.7	7.75	HD	CG	Z
0.562	14.27	B14-68	1.13	28.6	.518	13.2	.43	.07	.95	24	.41	1.8	.18	4.5	0.022	0.6	7.00	MW	C	Z
0.562	14.27	O-89	1.13	28.6	.516	13.1	.51	.09	.94	24	.48	2.2	.18	4.7	0.023	0.6	7.00	MW	C	N
0.562	14.27	10047	1.13	28.6	.512	13.0	.73	.13	.93	23	.68	3.0	.20	5.1	0.025	0.6	7.00	MW	C	Z
0.562	14.27	B9-34	1.13	28.6	.478	12.1	4.5	.80	.75	19	3.4	15	.38	9.6	0.042	1.1	9.00	SPR	CG	Z
0.562	14.27	12561	1.13	28.6	.462	11.7	11	2.0	.68	17	7.5	33	.45	11.4	0.050	1.3	8.00	SPR	C	N
0.562	14.27	WW-40	1.13	28.6	.410	10.4	70	12	.37	9.5	26	116	.61	15.4	0.076	1.9	8.00	SPR	CG	Z
0.562	14.27	3871	1.13	28.6	.402	10.2	88	15	.35	8.8	30	135	.64	16.3	0.080	2.0	8.00	HD	CG	Z
0.562	14.27	DD-87	1.13	28.6	.402	10.2	131	23	.23	5.8	30	135	.48	12.2	0.080	2.0	6.00	SPR	CG	N
0.562	14.27	S-1534	1.22	31.0	.388	9.9	134	23	.27	6.9	36	161	.61	15.5	0.087	2.2	7.00	SST	CG	N
0.562	14.27	S-1369	1.25	31.8	.522	13.3	.31	.05	1.1	28	.35	1.6	.14	3.6	0.020	0.5	6.00	SST	C	N
0.562	14.27	3563	1.25	31.8	.512	13.0	.40	.07	.95	24	.38	1.7	.30	7.7	0.025	0.6	11.0	MW	C	GI
0.562	14.27	S-925	1.25	31.8	.478	12.1	4.9	.86	.88	22	4.3	19	.37	9.3	0.042	1.1	7.75	SST	C	N
0.562	14.27	S-1303	1.25	31.8	.474	12.0	7.9	1.4	.70	18	5.5	25	.28	7.0	0.044	1.1	6.25	SST	CG	N
0.562	14.27	3822	1.25	31.8	.466	11.8	10	1.8	.75	19	7.6	34	.36	9.1	0.048	1.2	7.50	SPR	CG	Z
0.562	14.27	10103	1.25	31.8	.460	11.7	12	2.1	.70	18	8.5	38	.41	10.4	0.051	1.3	8.00	SPR	CG	Z
0.562	14.27	3019	1.31	33.3	.402	10.2	70	12	.43	11	30	135	.76	19.3	0.080	2.0	9.50	SPR	CG	Z
0.562	14.27	12403	1.34	34.1	.512	13.0	.56	.10	1.1	28	.62	2.7	.24	6.0	0.025	0.6	8.50	MW	C	N
0.562	14.27	12026	1.34	34.1	.398	10.1	78	14	.41	11	33	145	.78	19.8	0.082	2.1	9.50	SPR	CG	N
0.562	14.27	Y-19	1.34	34.1	.352	8.9	262	46	.24	6.2	64	283	.95	24.0	0.105	2.7	9.00	SPR	CG	Z
0.562	14.27	1943	1.38	34.9	.512	13.0	.56	.10	1.1	29	.63	2.8	.24	6.0	0.025	0.6	8.50	MW	C	Z
0.562	14.27	10246	1.38	34.9	.510	13.0	.34	.06	.97	25	.32	1.4	.41	10.4	0.026	0.7	14.8	MW	C	Z
0.562	14.27	S-861	1.38	34.9	.460	11.7	7.9	1.4	.87	22	6.9	30	.51	13.0	0.051	1.3	10.0	SST	CG	N
0.562	14.27	3886	1.38	34.9	.452	11.5	13	2.2	.77	20	9.7	43	.61	15.4	0.055	1.4	10.0	SPR	C	Z
0.562	14.27	S-421	1.38	34.9	.436	11.1	25	4.4	.59	15	15	66	.52	13.2	0.063	1.6	8.25	SST	CG	N
0.562	14.27	29	1.38	34.9	.418	10.6	45	7.9	.49	12	22	99	.74	18.7	0.072	1.8	9.25	HD	C	Z
0.562	14.27	Q-29	1.38	34.9	.378	9.6	108	19	.37	9.5	40	180	.92	23.4	0.092	2.3	10.0	SST	CG	N
0.562	14.27	S-1691	1.41	35.7	.526	13.4	.03	.01	.87	22	.03	.12	.54	13.6	0.018	0.5	28.8	SST	C	N
0.562	14.27	Y-22	1.41	35.7	.512	13.0	.63	.11	1.2	31	.76	3.4	.20	5.1	0.025	0.6	7.00	MW	C	N
0.562	14.27	S-819	1.41	35.7	.418	10.6	38	6.6	.56	14	21	93	.70	17.8	0.072	1.8	9.75	SST	CG	N
0.562	14.27	3204	1.44	36.5	.504	12.8	.53	.09	.98	25	.52	2.3	.46	11.6	0.029	0.7	14.8	MW	C	Z
0.562	14.27	A9-29	1.44	36.5	.400	10.2	68	12	.43	11	29	131	.75	19.0	0.081	2.1	9.25	SST	CG	N
0.562	14.27	G-44	1.50	38.1	.506	12.9	.45	.08	1.1	27	.47	2.1	.45	11.4	0.028	0.7	15.0	MW	C	N
0.562	14.27	11365	1.50	38.1	.480	12.2	2.2	.38	.90	23	1.9	8.6	.60	15.4	0.041	1.0	13.8	SST	C	N
0.562	14.27	2800	1.50	38.1	.456	11.6	7.2	1.3	.76	19	5.4	24	.74	18.8	0.053	1.3	14.0	MW	CG	Z
0.562	14.27	S-1129	1.50	38.1	.442	11.2	15	2.6	.86	22	13	58	.63	16.0	0.060	1.5	10.5	SST	CG	N
0.562	14.27	3851	1.50	38.1	.438	11.1	23	4.0	.67	17	15	67	.59	15.0	0.062	1.6	9.50	HD	CG	Z
0.562	14.27	2925	1.50	38.1	.402	10.2	58	10	.52	13	30	135	.88	22.4	0.080	2.0	11.0	SPR	CG	Z
0.562	14.27	B14-62	1.56	39.7	.502	12.8	1.9	.34	1.4	34	2.6	12	.21	5.3	0.030	0.8	6.00	MW	C	N
0.562	14.27	3731	1.63	41.3	.512	13.0	.48	.08	1.4	35	.66	2.9	.26	6.7	0.025	0.6	9.50	MW	C	Z
0.562	14.27	2941	1.63	41.3	.510	13.0	.33	.06	1.2	31	.40	1.8	.41	10.5	0.026	0.7	15.0	MW	C	Z
0.562	14.27	TT-53	1.63	41.3	.460	11.7	5.3	.92	.91	23	4.8	21	.71	18.1	0.051	1.3	14.0	SST	CG	N
0.562	14.27	3983	1.63	41.3	.438	11.1	17	3.0	.88	22	15	67	.74	18.9	0.062	1.6	12.0	SPR	CG	Z
0.562	14.27	2722	1.66	42.1	.492	12.5	1.9	.33	1.3	33	2.5	11	.34	8.7	0.035	0.9	9.75	MW	CG	Z
0.562	14.27	S-115	1.66	42.1	.428	10.9	23	4.0	.77	20	18	80	.74	18.7	0.067	1.7	11.0	SST	CG	N
0.562	14.27	12593	1.69	42.8	.422	10.7	31	5.3	.67	17	21	91	.88	22.2	0.070	1.8	11.5	SPR	C	N
0.562	14.27	12333	1.72	43.6	.458	11.6	13	2.3	.68	17	9.0	40	.42	10.6	0.052	1.3	8.00	SPR	CG	Z
0.562	14.27	2873	1.75	44.5	.502	12.8	.61	.11	1.3	32	.77	3.4	.47	12.0	0.030	0.8	14.8	MW	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.562	14.27	A13-44	1.75	44.5	.478	12.1	3.4	.60	1.3	34	4.5	20	.43	10.9	0.042	1.1	10.3	SST	CG	N
0.562	14.27	B18-168	1.75	44.5	.404	10.3	52	9.1	.53	13	27	122	.83	21.1	0.079	2.0	10.5	SST	CG	N
0.562	14.27	2639	1.75	44.5	.380	9.7	94	17	.63	16	59	262	1.09	27.7	0.091	2.3	12.0	MW	CG	Z
0.562	14.27	S-170	1.78	45.2	.428	10.9	23	4.0	.77	20	18	80	.80	20.4	0.067	1.7	11.0	SST	C	N
0.562	14.27	3716	1.81	46.0	.508	12.9	.39	.07	1.4	35	.54	2.4	.43	10.9	0.027	0.7	15.0	MW	C	Z
0.562	14.27	12659	1.81	46.0	.480	12.2	1.7	.30	1.0	26	1.7	7.8	.78	19.8	0.041	1.0	19.0	SPR	CG	Z
0.562	14.27	3218	1.81	46.0	.478	12.1	3.9	.69	1.3	33	5.1	23	.47	11.9	0.042	1.1	10.0	SPR	C	Z
0.562	14.27	VV-60	1.88	47.6	.502	12.8	1.1	.19	1.6	40	1.7	7.7	.30	7.6	0.030	0.8	9.00	MW	C	Z
0.562	14.27	S-1172	1.88	47.6	.462	11.7	7.3	1.3	1.0	26	7.6	34	.50	12.7	0.050	1.3	10.0	SST	CG	N
0.562	14.27	10927	1.88	47.6	.432	11.0	21	3.8	.81	21	17	77	.83	21.1	0.065	1.7	11.8	SPR	C	Z
0.562	14.27	B2-55	1.88	47.6	.422	10.7	48	8.5	.42	11	21	91	.56	14.2	0.070	1.8	8.00	SPR	CG	N
0.562	14.27	B14-19	1.88	47.6	.384	9.8	85	15	.48	12	41	183	1.16	29.4	0.089	2.3	12.0	SPR	C	Z
0.562	14.27	12607	2.00	50.8	.490	12.4	2.1	.36	1.6	41	3.3	15	.40	10.1	0.036	0.9	10.0	MW	C	T
0.562	14.27	11748	2.00	50.8	.460	11.7	6.1	1.1	1.3	33	7.8	35	.71	18.1	0.051	1.3	14.0	SPR	CG	Z
0.562	14.27	11440	2.00	50.8	.438	11.1	15	2.6	.94	24	14	63	.74	18.9	0.062	1.6	12.0	SST	CG	N
0.562	14.27	10066	2.00	50.8	.412	10.5	39	6.9	.64	16	25	112	.90	22.9	0.075	1.9	12.0	SPR	CG	Z
0.562	14.27	B11-46	2.00	50.8	.412	10.5	33	5.8	.71	18	23	105	.94	23.8	0.075	1.9	12.5	SST	CG	N
0.562	14.27	2898	2.06	52.4	.502	12.8	.61	.11	1.6	40	.96	4.3	.47	12.0	0.030	0.8	14.8	MW	C	Z
0.562	14.27	11874	2.09	53.2	.452	11.5	7.2	1.3	1.2	31	8.8	39	.88	22.4	0.055	1.4	16.0	SPR	CG	N
0.562	14.27	B8-48	2.16	54.8	.362	9.2	112	20	.49	13	55	246	1.50	38.1	0.100	2.5	15.0	SPR	CG	N
0.562	14.27	11568	2.22	56.4	.458	11.6	7.2	1.3	1.3	32	9.0	40	.73	18.5	0.052	1.3	13.0	SPR	CG	N
0.562	14.27	3556	2.25	57.2	.426	10.8	20	3.5	1.2	32	25	111	1.00	25.5	0.068	1.7	14.8	MW	CG	Z
0.562	14.27	10337	2.31	58.7	.428	10.9	22	3.8	.88	22	19	85	.87	22.1	0.067	1.7	13.0	SPR	CG	Z
0.562	14.27	4368	2.31	58.7	.394	10.0	56	9.8	.63	16	35	155	1.16	29.3	0.084	2.1	13.8	SPR	CG	Z
0.562	14.27	S-1219	2.38	60.3	.482	12.2	1.3	.23	1.6	40	2.1	9.3	.80	20.3	0.040	1.0	19.0	SST	C	N
0.562	14.27	3969	2.38	60.3	.472	12.0	5.3	.93	1.2	30	6.3	28	.50	12.6	0.045	1.1	10.0	SPR	C	Z
0.562	14.27	887	2.38	60.3	.402	10.2	38	6.6	.81	20	30	135	1.36	34.5	0.080	2.0	16.0	HD	C	Z
0.562	14.27	10563	2.44	61.9	.388	9.9	50	8.7	.78	20	39	172	1.52	38.7	0.087	2.2	17.5	SPR	CG	Z
0.562	14.27	4372	2.44	61.9	.336	8.5	192	34	.39	10	76	337	1.75	44.5	0.113	2.9	15.5	SPR	CG	Z
0.562	14.27	11209	2.63	66.7	.502	12.8	.61	.11	2.2	55	1.3	5.8	.47	12.0	0.030	0.8	14.8	MW	C	Z
0.562	14.27	12597	2.70	68.6	.338	8.6	177	31	.42	11	74	328	1.90	48.4	0.112	2.8	16.0	HD	C	N
0.562	14.27	10308	2.75	69.9	.418	10.6	23	4.1	.95	24	22	99	1.15	29.3	0.072	1.8	16.0	SPR	CG	Z
0.562	14.27	11279	2.75	69.9	.366	9.3	74	13	.71	18	52	232	1.96	49.8	0.098	2.5	20.0	SPR	CG	Z
0.562	14.27	2987	2.94	74.6	.278	7.1	563	99	.24	6.2	138	614	2.27	57.7	0.142	3.6	16.0	SPR	CG	Z
0.562	14.27	20	3.00	76.2	.454	11.5	6.3	1.1	1.6	40	10	45	.96	24.4	0.054	1.4	16.8	HD	C	Z
0.562	14.27	11580	3.09	78.6	.448	11.4	9.1	1.6	1.3	33	12	53	.91	23.2	0.057	1.4	15.0	SPR	CG	N
0.562	14.27	S-1107	3.13	79.4	.434	11.0	9.4	1.7	1.7	42	16	70	1.28	32.5	0.064	1.6	20.0	SST	CG	N
0.562	14.27	3695	3.16	80.2	.462	11.7	3.7	.65	2.1	53	7.8	35	1.05	26.7	0.050	1.3	20.0	SPR	C	Z
0.562	14.27	12601	3.50	88.9	.384	9.8	41	7.1	1.4	35	55	246	2.14	54.3	0.089	2.3	23.0	MW	C	N
0.562	14.27	1813	3.50	88.9	.302	7.7	272	48	.40	10	109	483	2.70	68.5	0.130	3.3	20.8	SPR	CG	Z
0.562	14.27	2737	3.75	95.3	.418	10.6	14	2.4	1.6	41	22	99	1.87	47.5	0.072	1.8	26.0	SPR	CG	Z
0.562	14.27	1887	3.75	95.3	.352	8.9	109	19	.81	21	89	395	1.97	50.0	0.105	2.7	18.8	MW	CG	Z
0.562	14.27	3438	4.00	101.6	.368	9.3	58	10	.88	22	51	225	2.33	59.1	0.097	2.5	24.0	SPR	CG	Z
0.562	14.27	S-1176	4.44	112.7	.374	9.5	48	8.3	.90	23	43	191	2.07	52.5	0.094	2.4	22.0	SST	CG	N
0.562	14.27	11287	4.50	114.3	.448	11.4	4.8	.84	2.5	62	12	53	1.57	39.8	0.057	1.4	26.5	SPR	C	Z
0.562	14.27	10342	4.88	123.8	.402	10.2	18	3.1	1.7	44	30	135	2.64	67.1	0.080	2.0	32.0	SPR	C	Z
0.562	14.27	10234	5.25	133.4	.322	8.2	113	20	.79	20	90	398	3.90	99.1	0.120	3.0	32.5	SPR	CG	Z
0.562	14.27	10786	5.50	139.7	.422	10.7	7.8	1.4	2.6	67	21	91	2.73	69.3	0.070	1.8	39.0	SPR	CG	N
0.562	14.27	10385	10.0	254.0	.438	11.1	3.9	.68	3.9	100	15	67	2.91	74.0	0.062	1.6	46.0	SPR	C	Z
0.562	14.27	10296	10.0	254.0	.432	11.0	4.8	.83	3.7	93	17	77	2.99	75.9	0.065	1.7	46.0	SPR	CG	Z
0.562	14.27	4166	12.8	323.9	.460	11.7	1.3	.24	6.3	160	8.5	38	2.91	73.8	0.051	1.3	56.0	SPR	C	Z
0.562	14.27	4392	15.0	381.0	.460	11.7	1.3	.24	6.3	160	8.5	38	2.91	73.8	0.051	1.3	56.0	SPR	C	Z
0.578	14.68	L-20	.47	11.9	.494	12.5	25	4.4	.19	4.7	4.7	21	.17	4.3	0.042	1.1	3.00	SST	C	N
0.578	14.68	WW-69	.50	12.7	.516	13.1	2.0	.36	.28	7.2	.57	2.6	.22	5.5	0.031	0.8	6.00	MW	C	Z
0.578	14.68	S-1103	.50	12.7	.502	12.8	9.5	1.7	.32	8.1	3.0	13	.18	4.6	0.038	1.0	3.75	SST	C	N
0.578	14.68	BB-80	.59	15.1	.418	10.6	138	24	.19	4.9	27	119	.40	10.2	0.080	2.0	5.00	SST	CG	N
0.578	14.68	Z-99	.63	15.9	.538	13.7	.15	.03	.41	10	.06	.26	.22	5.6	0.020	0.5	11.0	MW	CG	Z
0.578	14.68	10394	.66	16.7	.410	10.4	237	42	.14	3.6	34	151	.38	9.6	0.084	2.1	4.50	SPR	CG	Z
0.578	14.68	I-41	.69	17.4	.388	9.9	320	56	.15	3.7	47	207	.50	12.7	0.095	2.4	5.25	SPR	CG	N
0.578	14.68	G-32	.75	19.1	.524	13.3	.65	.11	.48	12	.31	1.4	.27	6.9	0.027	0.7	9.00	MW	C	Z
0.578	14.68	2718	.75	19.1	.518	13.2	2.4	.41	.57	14	1.3	6.0	.18	4.6	0.030	0.8	5.00	MW	C	Z
0.578	14.68	B14-2	.75	19.1	.484	12.3	16	2.7	.45	11	7.0	31	.24	6.0	0.047	1.2	5.00	SPR	CG	N
0.578	14.68	3659	.75	19.1	.474	12.0	29	5.1	.30	7.7	8.8	39	.23	5.9	0.052	1.3	4.50	SPR	CG	GI
0.578	14.68	J-15	.81	20.6	.454	11.5	52	9.0	.29	7.3	15	66	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.578	14.68	A-45	.81	20.6	.418	10.6	104	18	.27	6.8	28	123	.48	12.2	0.080	2.0	6.00	SST	CG	N
0.578	14.68	12200	.88	22.2	.514	13.1	3.1	.54	.72	18	2.2	9.8	.16	4.1	0.032	0.8	5.00	SPR	CG	Z
0.578	14.68	12329	.88	22.2	.430	10.9	84	15	.28	7.1	24	105	.44	11.3	0.074	1.9	6.00	SPR	CG	Z
0.578	14.68	3513	.91	23.0	.460	11.7	42	7.3	.43	11	18	79	.35	9.0	0.059	1.5	5.00	MW	C	Z
0.578	14.68	A9-49	.91	23.0	.428	10.9	71	13	.34	8.7	24	109	.53	13.3	0.075	1.9	7.00	SPR	CG	Z
0.578	14.68	10929	.97	24.6	.526	13.4	1.2	.20	.81	21	.94	4.2	.16	4.0	0.026	0.7	5.00	SST	C	N
0.578	14.68	2960	1.00	25.4	.520	13.2	1.0	.18	.74	19	.76	3.4	.26	6.6	0.029	0.7	8.00	MW	C	Z
0.578	14.68	S-1064	1.00	25.4	.520	13.2	1.8	.31	.83	21	1.5	6.5	.17	4.4	0.029	0.7	5.00	SST	C	N
0.578	14.68	Y-38	1.00	25.4	.510	13.0	2.6	.46	.80	20	2.1	9.4	.20	5.2	0.034	0.9	6.00	SST	CG	N
0.578	14.68	S-1330	1.00	25.4	.508	12.9	3.3	.59	.77	20	2.6	12	.23	5.8	0.035	0.9	5.50	SST	C	N
0.578	14.68	12662	1.00	25.4	.508	12.9	4.5	.79	.79	20	3.5	16	.21	5.3	0.035	0.9	5.00	MW	C	GI
0.578	14.68	RR-63	1.00	25.4	.506	12.9	5.1	.89	.63	16	3.2	14	.22	5.5	0.036	0.9	5.00	SPR	C	Z
0.578	14.68	10826	1.00	25.4	.504	12.8	4.5	.79	.75	19	3.4	15	.25	6.4	0.037	0.9	5.75	SPR	C	Z
0.578	14.68	12740	1.00	25.4	.502	12.8	5.4	.95	.68	17	3.7	17	.25	6.3	0.038	1.0	5.50	SPR	C	Z
0.578	14.68	B3-45	1.00	25.4	.448	11.4	35	6.1	.45	11	15	69	.55	14.0	0.065	1.7	7.50	MW	C	N
0.578	14.68	Q-34	1.03	26.2	.458	11.6	24	4.2	.53	13	13	56	.42	10.7	0.060	1.5	7.00	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.578	14.68	S-1656	1.03	26.2	.456	11.6	26	4.5	.52	13	13	59	.43	10.8	0.061	1.5	7.00	SST	CG	N
0.578	14.68	11373	1.13	28.6	.496	12.6	3.3	.58	.76	19	2.5	11	.37	9.4	0.041	1.0	9.00	SST	CG	N
0.578	14.68	S-818	1.13	28.6	.428	10.9	63	11	.36	9.2	23	102	.53	13.3	0.075	1.9	7.00	SST	CG	N
0.578	14.68	10881	1.19	30.2	.398	10.1	130	23	.31	7.8	40	177	.74	18.9	0.090	2.3	8.25	SPR	CG	N
0.578	14.68	I-43	1.25	31.8	.512	13.0	2.3	.40	1.0	26	2.3	10	.23	5.9	0.033	0.8	6.00	SST	C	N
0.578	14.68	S-1041	1.25	31.8	.482	12.2	4.2	.74	.65	17	2.8	12	.60	15.2	0.048	1.2	12.5	SST	CG	N
0.578	14.68	B9-67	1.25	31.8	.444	11.3	24	4.2	.51	13	12	55	.74	18.7	0.067	1.7	10.0	SST	C	N
0.578	14.68	OO-55	1.28	32.5	.478	12.1	6.8	1.2	.78	20	5.3	24	.50	12.7	0.050	1.3	10.0	SST	CG	N
0.578	14.68	S-1498	1.31	33.3	.478	12.1	7.6	1.3	.86	22	6.5	29	.45	11.4	0.050	1.3	9.00	SST	CG	N
0.578	14.68	3112	1.31	33.3	.468	11.9	18	3.2	.56	14	10	46	.39	9.8	0.055	1.4	7.00	SPR	CG	Z
0.578	14.68	S-139	1.34	34.1	.526	13.4	.97	.17	1.2	30	1.1	5.1	.17	4.3	0.026	0.7	5.50	SST	C	N
0.578	14.68	GG-89	1.38	34.9	.450	11.4	29	5.0	.53	14	15	68	.48	12.2	0.064	1.6	7.50	SST	CG	N
0.578	14.68	WW-30	1.38	34.9	.328	8.3	539	94	.18	4.6	98	437	1.13	28.6	0.125	3.2	9.00	SPR	CG	Z
0.578	14.68	A-97	1.41	35.7	.338	8.6	443	78	.20	5.0	88	390	1.08	27.4	0.120	3.0	9.00	HD	CG	Z
0.578	14.68	10672	1.44	36.5	.438	11.1	34	5.9	.59	15	20	89	.68	17.3	0.070	1.8	9.75	SPR	CG	Z
0.578	14.68	B12-59	1.44	36.5	.396	10.1	131	23	.31	8.0	41	183	.86	22.0	0.091	2.3	8.50	SPR	C	Z
0.578	14.68	4116	1.50	38.1	.470	11.9	12	2.1	.81	21	9.8	44	.54	13.7	0.054	1.4	9.00	SPR	C	Z
0.578	14.68	S-887	1.53	38.9	.398	10.1	94	16	.39	10	37	164	.86	21.7	0.090	2.3	9.50	SST	CG	N
0.578	14.68	S-199	1.56	39.7	.488	12.4	6.2	1.1	.93	24	5.7	26	.38	9.7	0.045	1.1	7.50	SST	C	N
0.578	14.68	4321	1.63	41.3	.470	11.9	11	1.9	.92	23	9.8	44	.54	13.7	0.054	1.4	10.0	SPR	CG	Z
0.578	14.68	12209	1.63	41.3	.434	11.0	37	6.5	.58	15	22	97	.72	18.3	0.072	1.8	10.0	SPR	CG	Z
0.578	14.68	NN-56	1.69	42.8	.398	10.1	80	14	.46	12	37	164	.99	25.1	0.090	2.3	11.0	SST	CG	N
0.578	14.68	2797	1.75	44.5	.338	8.6	443	78	.20	5.0	88	390	1.08	27.4	0.120	3.0	9.00	SPR	CG	Z
0.578	14.68	3870	1.81	46.0	.488	12.4	4.1	.72	1.3	33	5.3	24	.52	13.1	0.045	1.1	11.5	SPR	CG	Z
0.578	14.68	10858	1.81	46.0	.448	11.4	17	3.0	.92	23	16	71	.76	19.4	0.065	1.7	11.8	SST	CG	N
0.578	14.68	4230	1.88	47.6	.474	12.0	8.3	1.4	1.1	27	8.8	39	.61	15.5	0.052	1.3	10.8	SPR	C	Z
0.578	14.68	12634	1.97	50.0	.506	12.9	1.9	.33	1.6	40	3.0	13	.40	10.1	0.036	0.9	10.0	MW	C	Z
0.578	14.68	12249	2.00	50.8	.484	12.3	4.3	.75	1.4	35	5.9	26	.61	15.5	0.047	1.2	13.0	SPR	CG	Z
0.578	14.68	3317	2.00	50.8	.428	10.9	36	6.3	.68	17	24	109	.90	22.9	0.075	1.9	12.0	SPR	CG	Z
0.578	14.68	M-92	2.00	50.8	.266	6.8	1259	220	.13	3.4	170	754	1.72	43.6	0.156	4.0	11.0	SPR	CG	N
0.578	14.68	11888	2.03	51.6	.430	10.9	34	5.9	.70	18	24	105	.89	22.6	0.074	1.9	12.0	SPR	CG	N
0.578	14.68	12231	2.03	51.6	.428	10.9	40	7.0	.62	16	24	109	.83	21.0	0.075	1.9	11.0	SPR	CG	Z
0.578	14.68	11317	2.13	54.0	.378	9.6	110	19	.49	13	54	240	1.40	35.6	0.100	2.5	14.0	SPR	CG	Z
0.578	14.68	10382	2.25	57.2	.496	12.6	3.5	.61	1.3	34	4.7	21	.43	10.9	0.041	1.0	9.50	SPR	C	Z
0.578	14.68	12299	2.28	57.9	.418	10.6	37	6.4	.80	20	30	131	1.20	30.5	0.080	2.0	15.0	SPR	CG	Z
0.578	14.68	12214	2.34	59.5	.478	12.1	6.1	1.1	1.3	33	7.8	35	.60	15.2	0.050	1.3	12.0	SPR	CG	Z
0.578	14.68	3200	2.38	60.3	.518	13.2	.55	.10	1.9	48	1.1	4.7	.47	12.0	0.030	0.8	14.8	MW	C	Z
0.578	14.68	10419	2.38	60.3	.444	11.3	21	3.6	.90	23	19	82	.91	23.0	0.067	1.7	12.5	SPR	C	Z
0.578	14.68	S-49	2.50	63.5	.396	10.1	53	9.3	.72	18	38	170	1.55	39.3	0.091	2.3	16.0	SST	C	N
0.578	14.68	10473	2.56	65.1	.454	11.5	9.7	1.7	1.4	37	14	62	1.12	28.3	0.062	1.6	18.0	SPR	CG	Z
0.578	14.68	12063	2.59	65.9	.482	12.2	5.1	.90	1.4	37	7.4	33	.58	14.6	0.048	1.2	12.0	SPR	CG	GI
0.578	14.68	S-1453	2.63	66.7	.434	11.0	22	3.9	.92	23	20	90	.99	25.1	0.072	1.8	13.8	SST	CG	N
0.578	14.68	11313	2.66	67.5	.434	11.0	23	4.1	.93	24	22	97	1.06	27.0	0.072	1.8	14.8	SPR	CG	Z
0.578	14.68	S-472	3.13	79.4	.516	13.1	.61	.11	2.7	68	1.6	7.3	.45	11.4	0.031	0.8	13.5	SST	C	N
0.578	14.68	2829	3.13	79.4	.484	12.3	1.6	.28	1.6	40	2.5	11	1.54	39.1	0.047	1.2	31.8	HD	C	Z
0.578	14.68	10490	3.16	80.2	.422	10.7	28	5.0	.97	25	27	122	1.33	33.7	0.078	2.0	17.0	SPR	CG	BO
0.578	14.68	10306	3.31	84.1	.368	9.3	86	15	.72	18	62	276	2.23	56.7	0.105	2.7	21.3	SPR	CG	Z
0.578	14.68	10987	3.75	95.3	.368	9.3	90	16	.69	17	62	276	2.13	54.0	0.105	2.7	20.3	HD	CG	Z
0.578	14.68	10965	3.75	95.3	.358	9.1	124	22	.55	14	69	305	2.03	51.6	0.110	2.8	18.5	HD	CG	Z
0.578	14.68	S-3041	4.75	120.7	.454	11.5	4.5	.78	2.7	69	12	54	2.05	52.0	0.062	1.6	32.0	SST	C	N
0.578	14.68	3345	5.00	127.0	.438	11.1	11	1.9	1.8	46	20	89	1.82	46.2	0.070	1.8	26.0	SPR	CG	Z
0.578	14.68	12296	5.38	136.5	.462	11.7	5.4	.94	2.3	57	12	54	1.42	36.1	0.058	1.5	23.5	SPR	C	Z
0.578	14.68	10087	5.38	136.5	.454	11.5	7.0	1.2	2.1	53	15	66	1.55	39.4	0.062	1.6	24.0	HD	C	N
0.578	14.68	12081	5.50	139.7	.454	11.5	6.2	1.1	2.4	61	15	66	1.67	42.5	0.062	1.6	27.0	SPR	CG	Z
0.578	14.68	4187	7.50	190.5	.458	11.6	4.2	.73	3.2	81	13	60	2.10	53.3	0.060	1.5	34.0	SPR	C	BO
0.578	14.68	S-3043	7.63	193.7	.454	11.5	4.2	.74	3.3	84	14	62	2.17	55.1	0.062	1.6	34.0	SST	C	N
0.578	14.68	4016	23.5	596.9	.408	10.4	5.7	1.0	6.2	156	35	157	9.56	242.9	0.085	2.2	111.5	SPR	C	Z
0.580	14.73	A9-23	.38	9.5	.568	14.4	.62	.11	.03	.69	.02	.08	.14	3.5	0.006	0.2	22.0	SST	C	N
0.590	14.99	12524	1.50	38.1	.386	9.8	255	45	.22	5.6	56	250	.74	18.8	0.102	2.6	7.25	SPR	CG	N
0.593	15.06	3789	.44	11.1	.497	12.6	13	2.4	.17	4.4	2.3	10	.26	6.7	0.048	1.2	5.50	SPR	CG	Z
0.593	15.06	N-51	.47	11.9	.499	12.7	12	2.2	.21	5.3	2.6	11	.26	6.6	0.047	1.2	5.50	SPR	CG	N
0.593	15.06	10334	.50	12.7	.459	11.7	199	35	.09	2.3	18	80	.27	6.8	0.067	1.7	3.00	SPR	C	Z
0.593	15.06	A-47	.53	13.5	.393	10.0	800	140	.07	1.7	53	235	.35	8.9	0.100	2.5	3.50	SPR	CG	GI
0.593	15.06	NN-92	.56	14.3	.523	13.3	2.4	.42	.30	7.6	.72	3.2	.26	6.7	0.035	0.9	6.50	SST	C	N
0.593	15.06	11341	.56	14.3	.503	12.8	14	2.5	.37	9.4	5.2	23	.19	4.9	0.045	1.1	4.25	SST	CG	N
0.593	15.06	I-79	.56	14.3	.483	12.3	42	7.4	.24	6.1	10	45	.22	5.6	0.055	1.4	4.00	SPR	CG	GI
0.593	15.06	3540	.59	15.1	.503	12.8	14	2.5	.35	8.8	5.0	22	.25	6.3	0.045	1.1	4.50	HD	C	Z
0.593	15.06	3586	.59	15.1	.491	12.5	20	3.6	.34	8.6	6.9	31	.26	6.5	0.051	1.3	5.00	HD	CG	Z
0.593	15.06	10784	.59	15.1	.473	12.0	41	7.2	.29	7.4	12	53	.30	7.6	0.060	1.5	5.00	SPR	CG	N
0.593	15.06	2540	.59	15.1	.449	11.4	109	19	.19	4.9	21	94	.32	8.2	0.072	1.8	4.50	SPR	CG	Z
0.593	15.06	3502	.63	15.9	.529	13.4	2.4	.43	.42	11	1.0	4.5	.21	5.3	0.032	0.8	5.50	HD	C	Z
0.593	15.06	10280	.63	15.9	.503	12.8	20	3.6	.29	7.4	6.0	27	.17	4.3	0.045	1.1	3.75	SPR	CG	Z
0.593	15.06	Y-66	.63	15.9	.503	12.8	18	3.2	.31	7.8	5.6	25	.17	4.3	0.045	1.1	3.75	SST	CG	N
0.593	15.06	G-29	.63	15.9	.485	12.3	14	2.4	.25	6.3	3.4	15	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.593	15.06	3843	.63	15.9	.483	12.3	42	7.4	.24	6.1	10	45	.22	5.6	0.055	1.4	4.00	SPR	CG	GI
0.593	15.06	11309	.63	15.9	.465	11.8	65	11	.24	6.2	16	70	.35	8.9	0.064	1.6	4.50	SPR	C	N
0.593	15.06	10538	.66	16.7	.419	10.6	231	40	.16	4.0	37	164	.41	10.5	0.087	2.2	4.75	SPR	CG	Z
0.593	15.06	S-906	.69	17.4	.453	11.5	70	12	.26	6.6	18	81	.35	8.9	0.070	1.8	5.00	SST	CG	N
0.593	15.06	N-130	.75	19.1	.517	13.1	5.2	.91	.56	14	2.9	13	.19	4.8	0.038	1.0	5.00	SST	CG	N
0.593	15.06	N-120	.75	19.1	.515	13.1	5.7	.99	.56	14	3.1	14	.20	5.0	0.039	1.0	5.00	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.593	15.06	S-828	.75	19.1	.513	13.0	8.9	1.6	.44	11	4.0	18	.21	5.2	0.040	1.0	4.00	SST	C	N
0.593	15.06	S-872	.75	19.1	.499	12.7	11	2.0	.50	13	5.7	26	.25	6.4	0.047	1.2	5.33	SST	CG	N
0.593	15.06	M-134	.75	19.1	.453	11.5	143	25	.13	3.3	18	81	.32	8.0	0.070	1.8	3.50	SST	C	N
0.593	15.06	3541	.75	19.1	.433	11.0	145	25	.28	7.0	40	179	.40	10.2	0.080	2.0	5.00	MW	CG	Z
0.593	15.06	B15-19	.78	19.8	.509	12.9	11	1.9	.46	12	4.9	22	.19	4.8	0.042	1.1	4.50	SPR	CG	N
0.593	15.06	S-943	.78	19.8	.485	12.3	17	2.9	.45	11	7.5	34	.33	8.4	0.054	1.4	6.00	SST	CG	N
0.593	15.06	S-928	.78	19.8	.465	11.8	53	9.3	.28	7.1	15	66	.30	7.6	0.064	1.6	4.67	SST	CG	N
0.593	15.06	10252	.78	19.8	.423	10.7	229	40	.15	3.8	34	153	.47	11.9	0.085	2.2	4.50	SPR	C	Z
0.593	15.06	S-62	.78	19.8	.409	10.4	484	85	.08	2.0	39	171	.32	8.2	0.092	2.3	3.50	SST	CG	N
0.593	15.06	I-46	.81	20.6	.531	13.5	2.4	.41	.63	16	1.5	6.7	.18	4.5	0.031	0.8	4.75	SST	C	N
0.593	15.06	3547	.84	21.4	.463	11.8	44	7.6	.38	9.6	17	74	.39	9.9	0.065	1.7	6.00	HD	CG	GI
0.593	15.06	2940	.84	21.4	.459	11.7	57	10	.32	8.1	18	80	.37	9.4	0.067	1.7	5.50	SPR	CG	Z
0.593	15.06	3840	.84	21.4	.449	11.4	78	14	.27	6.9	21	94	.40	10.1	0.072	1.8	5.50	SPR	CG	Z
0.593	15.06	12277	.88	22.2	.513	13.0	4.4	.76	.60	15	2.6	12	.28	7.1	0.040	1.0	7.00	SPR	CG	Z
0.593	15.06	S-1393	.88	22.2	.469	11.9	35	6.2	.38	9.8	14	60	.34	8.7	0.062	1.6	5.50	SST	CG	N
0.593	15.06	B-98	.88	22.2	.467	11.9	51	8.9	.30	7.6	15	67	.32	8.0	0.063	1.6	5.00	SPR	CG	Z
0.593	15.06	3918	.88	22.2	.449	11.4	84	15	.25	6.4	21	94	.38	9.6	0.072	1.8	5.25	HD	CG	Z
0.593	15.06	11196	.91	23.0	.463	11.8	48	8.3	.33	8.3	16	69	.34	8.7	0.065	1.7	5.25	SST	CG	N
0.593	15.06	12689	.92	23.4	.451	11.5	73	13	.39	9.8	28	126	.39	9.9	0.071	1.8	5.50	MW	CG	Z
0.593	15.06	S-3096	.94	23.8	.473	12.0	31	5.4	.40	10	12	55	.39	9.9	0.060	1.5	5.50	SST	C	N
0.593	15.06	3091	.94	23.8	.469	11.9	28	4.8	.50	13	14	61	.44	11.2	0.062	1.6	7.00	SPR	CG	Z
0.593	15.06	1923	.97	24.6	.289	7.3	2982	522	.05	1.3	156	693	.76	19.3	0.152	3.9	5.00	SPR	CG	Z
0.593	15.06	A13-58	1.00	25.4	.531	13.5	1.9	.33	.83	21	1.6	7.0	.17	4.3	0.031	0.8	5.50	SST	CG	N
0.593	15.06	10366	1.00	25.4	.519	13.2	4.5	.78	.75	19	3.3	15	.24	6.1	0.037	0.9	5.50	SPR	C	Z
0.593	15.06	GG-42	1.00	25.4	.453	11.5	61	11	.30	7.6	18	81	.39	9.8	0.070	1.8	5.50	SST	CG	N
0.593	15.06	BB-65	1.00	25.4	.443	11.3	93	16	.26	6.5	24	106	.41	10.5	0.075	1.9	5.50	SPR	CG	Z
0.593	15.06	A11-66	1.03	26.2	.531	13.5	1.9	.33	.86	22	1.6	7.3	.17	4.3	0.031	0.8	5.50	SST	CG	N
0.593	15.06	S-375	1.03	26.2	.469	11.9	25	4.3	.55	14	14	60	.43	11.0	0.062	1.6	7.00	SST	CG	N
0.593	15.06	K-46	1.13	28.6	.469	11.9	25	4.3	.55	14	14	60	.43	11.0	0.062	1.6	7.00	SST	CG	N
0.593	15.06	3536	1.13	28.6	.467	11.9	30	5.3	.68	17	21	93	.44	11.2	0.063	1.6	7.00	MW	CG	Z
0.593	15.06	3320	1.13	28.6	.449	11.4	43	7.6	.49	12	21	94	.60	15.2	0.072	1.8	8.25	HD	CG	Z
0.593	15.06	S-1362	1.13	28.6	.433	11.0	63	11	.43	11	27	120	.64	16.3	0.080	2.0	8.00	SST	CG	N
0.593	15.06	4297	1.13	28.6	.411	10.4	148	26	.27	6.9	40	179	.75	19.1	0.091	2.3	7.25	SPR	C	Z
0.593	15.06	S-1356	1.16	29.4	.433	11.0	76	13	.36	9.0	27	120	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.593	15.06	10174	1.19	30.2	.499	12.7	8.6	1.5	.79	20	6.8	30	.38	9.6	0.047	1.2	7.00	SPR	C	Z
0.593	15.06	B12-65	1.19	30.2	.457	11.6	30	5.3	.58	15	17	78	.61	15.5	0.068	1.7	9.00	SPR	CG	Z
0.593	15.06	G-60A	1.19	30.2	.433	11.0	47	8.3	.39	9.9	18	82	.80	20.3	0.080	2.0	10.0	SST	CG	N
0.593	15.06	S-295	1.19	30.2	.427	10.8	65	11	.44	11	29	128	.75	19.0	0.083	2.1	9.00	SST	CG	N
0.593	15.06	11226	1.19	30.2	.411	10.4	111	19	.36	9.2	40	179	.82	20.8	0.091	2.3	9.00	SPR	CG	Z
0.593	15.06	Q-35	1.22	31.0	.357	9.1	355	62	.21	5.3	75	332	1.00	25.5	0.118	3.0	8.50	SST	CG	N
0.593	15.06	12560	1.25	31.8	.531	13.5	1.6	.28	1.0	26	1.7	7.5	.22	5.5	0.031	0.8	6.00	SST	C	N
0.593	15.06	2719	1.25	31.8	.517	13.1	3.9	.68	.97	25	3.8	17	.29	7.2	0.038	1.0	6.50	MW	C	Z
0.593	15.06	4247	1.25	31.8	.505	12.8	6.5	1.1	.86	22	5.6	25	.35	8.9	0.044	1.1	7.00	SPR	C	Z
0.593	15.06	V-28	1.25	31.8	.449	11.4	68	12	.29	7.4	20	88	.40	10.1	0.072	1.8	5.50	SST	CG	N
0.593	15.06	KK-53	1.25	31.8	.433	11.0	62	11	.46	12	29	128	.72	18.3	0.080	2.0	9.00	SPR	CG	Z
0.593	15.06	2890	1.28	32.5	.423	10.7	95	17	.36	9.2	34	153	.68	17.3	0.085	2.2	8.00	SPR	CG	Z
0.593	15.06	10531	1.34	34.1	.469	11.9	19	3.3	.75	19	14	63	.59	15.0	0.062	1.6	9.50	SPR	CG	Z
0.593	15.06	S-237	1.38	34.9	.459	11.7	23	4.0	.74	19	17	76	.64	16.2	0.067	1.7	9.50	SST	CG	N
0.593	15.06	2686	1.41	35.7	.383	9.7	200	35	.30	7.7	61	270	1.00	25.3	0.105	2.7	9.50	HD	CG	Z
0.593	15.06	3228	1.44	36.5	.433	11.0	67	12	.43	11	29	128	.76	19.3	0.080	2.0	8.50	SPR	C	Z
0.593	15.06	10608	1.47	37.3	.463	11.8	25	4.4	.66	17	17	74	.59	14.9	0.065	1.7	9.00	SPR	CG	N
0.593	15.06	I-88	1.50	38.1	.449	11.4	34	6.0	.62	16	21	94	.72	18.3	0.072	1.8	10.0	HD	CG	Z
0.593	15.06	1691	1.50	38.1	.413	10.5	93	16	.42	11	39	173	.90	22.9	0.090	2.3	10.0	SPR	CG	Z
0.593	15.06	S-428	1.56	39.7	.501	12.7	6.1	1.1	.98	25	6.0	27	.35	8.9	0.046	1.2	7.50	SST	CG	N
0.593	15.06	S-412	1.56	39.7	.483	12.3	10	1.8	.91	23	9.5	42	.50	12.6	0.055	1.4	9.00	SST	CG	N
0.593	15.06	Q-58	1.56	39.7	.465	11.8	22	3.8	.73	18	16	70	.67	17.1	0.064	1.6	9.50	SPR	C	N
0.593	15.06	10113	1.56	39.7	.323	8.2	710	124	.16	4.1	116	515	1.22	30.9	0.135	3.4	9.00	SPR	CG	Z
0.593	15.06	3060	1.63	41.3	.513	13.0	2.4	.42	1.2	30	2.9	13	.44	11.2	0.040	1.0	11.0	SPR	CG	Z
0.593	15.06	S-856	1.63	41.3	.485	12.3	6.0	1.1	.90	23	5.4	24	.73	18.5	0.054	1.4	13.5	SST	CG	N
0.593	15.06	3268	1.63	41.3	.459	11.7	23	4.1	.77	20	18	80	.70	17.9	0.067	1.7	10.5	SPR	CG	Z
0.593	15.06	10030	1.63	41.3	.449	11.4	34	6.0	.62	16	21	94	.72	18.3	0.072	1.8	10.0	HD	CG	Z
0.593	15.06	10717	1.63	41.3	.433	11.0	47	8.3	.61	16	29	128	.90	22.9	0.080	2.0	11.3	SPR	CG	GI
0.593	15.06	3057	1.63	41.3	.383	9.7	215	38	.28	7.2	61	270	.95	24.0	0.105	2.7	9.00	SPR	CG	Z
0.593	15.06	A11-49	1.72	43.6	.457	11.6	28	4.9	.68	17	19	84	.66	16.7	0.068	1.7	9.75	SPR	CG	GI
0.593	15.06	JJ-83	1.75	44.5	.501	12.7	2.4	.43	.97	25	2.4	11	.78	19.9	0.046	1.2	16.0	SST	C	N
0.593	15.06	3500	1.75	44.5	.469	11.9	18	3.1	.81	21	14	64	.62	15.7	0.062	1.6	10.0	SPR	CG	Z
0.593	15.06	12186	1.78	45.2	.493	12.5	6.1	1.1	1.2	30	7.1	32	.61	15.6	0.050	1.3	11.3	SPR	C	Z
0.593	15.06	H-81	1.81	46.0	.517	13.1	1.6	.27	1.4	34	2.1	9.4	.46	11.6	0.038	1.0	12.0	SST	CG	N
0.593	15.06	12078	1.84	46.8	.459	11.7	27	4.6	.68	17	18	80	.64	16.2	0.067	1.7	9.50	SPR	CG	Z
0.593	15.06	3539	1.88	47.6	.529	13.4	.85	.15	1.5	37	1.2	5.5	.42	10.6	0.032	0.8	12.0	MW	C	Z
0.593	15.06	LL-68	1.94	49.2	.533	13.5	.96	.17	1.7	42	1.6	7.2	.27	6.9	0.030	0.8	8.00	SST	C	N
0.593	15.06	M-146	1.97	50.0	.489	12.4	5.8	1.0	1.3	32	7.3	33	.70	17.8	0.052	1.3	13.5	SPR	CG	N
0.593	15.06	10506	2.00	50.8	.413	10.5	76	13	.51	13	39	173	1.15	29.2	0.090	2.3	11.8	SPR	C	Z
0.593	15.06	MM-91	2.00	50.8	.413	10.5	55	9.6	.66	17	36	161	1.26	32.0	0.090	2.3	14.0	SST	CG	N
0.593	15.06	NN-87	2.00	50.8	.313	8.0	502	88	.23	5.8	115	512	1.75	44.5	0.140	3.6	12.5	SST	CG	N
0.593	15.06	S-820	2.06	52.4	.465	11.8	11	2.0	1.1	29	13	57	.93	23.6	0.064	1.6	14.5	SST	CG	N
0.593	15.06	12446	2.09	53.2	.511	13.0	3.7	.65	1.2	31	4.5	20	.39	9.9	0.041	1.0	8.50	SPR	C	N
0.593	15.06	12739	2.13	54.0	.547	13.9	.48	.08	2.0	50	.94	4.2	.17	4.4	0.023	0.6	6.50	MW	C	Z
0.593	15.06	S-1488	2.25	57.2	.531	13.5	.93	.16	1.9	49	1.8	8.0	.31	7.9	0.031	0.8	9.00	SST	C	N
0.593	15.06	WW-62	2.25	57.2	.449	11.4	26	4.6	.75	19	20	88	.79	20.1	0.072	1.8	11.0	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.593	15.06	12467	2.44	61.9	.453	11.5	24	4.2	.81	21	20	87	.84	21.3	0.070	1.8	12.0	SPR	CG	Z
0.593	15.06	3326	2.50	63.5	.449	11.4	27	4.8	.78	20	21	94	.86	21.9	0.072	1.8	12.0	HD	CG	Z
0.593	15.06	11614	2.53	64.3	.449	11.4	27	4.7	.80	20	21	94	.95	24.2	0.072	1.8	12.3	SPR	CG	GI
0.593	15.06	10783	2.56	65.1	.343	8.7	275	48	.35	8.9	96	428	1.74	44.1	0.125	3.2	14.0	SPR	CG	Z
0.593	15.06	11136	2.75	69.9	.469	11.9	9.2	1.6	1.6	40	14	64	1.15	29.1	0.062	1.6	17.5	SPR	C	Z
0.593	15.06	1695	2.75	69.9	.457	11.6	17	2.9	1.6	40	26	117	1.00	25.5	0.068	1.7	14.8	MW	CG	Z
0.593	15.06	237	2.75	69.9	.449	11.4	25	4.3	.85	22	21	94	.94	23.8	0.072	1.8	13.0	SPR	CG	Z
0.593	15.06	K-38	3.00	76.2	.499	12.7	1.5	.25	1.5	37	2.1	9.5	1.54	39.0	0.047	1.2	31.7	SPR	C	Z
0.593	15.06	S-432	3.00	76.2	.449	11.4	15	2.7	1.3	33	20	88	1.27	32.2	0.072	1.8	17.5	SST	CG	N
0.593	15.06	11729	3.00	76.2	.433	11.0	27	4.8	1.1	27	29	128	1.44	36.6	0.080	2.0	18.0	SPR	CG	GI
0.593	15.06	3090	3.00	76.2	.383	9.7	90	16	.68	17	61	270	1.97	50.0	0.105	2.7	18.8	SPR	CG	Z
0.593	15.06	11795	3.03	77.0	.451	11.5	15	2.6	1.3	34	20	90	1.35	34.3	0.071	1.8	19.0	SPR	CG	Z
0.593	15.06	2772	3.13	79.4	.499	12.7	2.0	.34	2.0	51	3.9	17	1.13	28.7	0.047	1.2	24.0	HD	CG	Z
0.593	15.06	3950	3.50	88.9	.449	11.4	27	4.8	.78	20	21	94	.86	21.9	0.072	1.8	12.0	SPR	CG	Z
0.593	15.06	11663	3.50	88.9	.445	11.3	21	3.6	1.1	28	23	102	1.26	32.0	0.074	1.9	17.0	SPR	CG	Z
0.593	15.06	10560	3.50	88.9	.393	10.0	58	10	.91	23	53	235	2.28	57.8	0.100	2.5	22.8	SPR	CG	Z
0.593	15.06	10228	4.00	101.6	.527	13.4	.49	.08	3.2	82	1.6	7.0	.76	19.3	0.033	0.8	22.0	SPR	C	Z
0.593	15.06	1611	4.00	101.6	.383	9.7	88	15	.69	17	61	270	2.00	50.7	0.105	2.7	19.0	SPR	CG	Z
0.593	15.06	10636	4.00	101.6	.367	9.3	88	15	.82	21	72	322	2.94	74.6	0.113	2.9	26.0	SPR	CG	Z
0.593	15.06	11769	4.31	109.5	.433	11.0	22	3.8	1.3	34	29	128	1.76	44.7	0.080	2.0	22.0	SPR	CG	Z
0.593	15.06	1815	5.38	136.5	.411	10.4	33	5.8	1.7	43	56	250	2.32	59.0	0.091	2.3	25.5	MW	CG	Z
0.593	15.06	1521	5.50	139.7	.411	10.4	31	5.5	1.3	33	40	179	2.46	62.4	0.091	2.3	27.0	HD	CG	Z
0.593	15.06	12178	5.75	146.1	.413	10.5	24	4.2	1.6	41	39	173	2.97	75.4	0.090	2.3	33.0	SPR	CG	Z
0.593	15.06	10681	6.00	152.4	.411	10.4	19	3.3	2.1	53	40	176	3.91	99.4	0.091	2.3	43.0	SPR	CG	Z
0.593	15.06	2902	6.25	158.8	.423	10.7	19	3.3	1.8	46	34	153	2.72	69.1	0.085	2.2	32.0	SPR	CG	Z
0.600	15.24	71711	.50	12.7	.510	13.0	23	4.1	.34	8.7	7.9	35	.16	4.0	0.045	1.1	3.50	MW	CG	N
0.600	15.24	71711S	.50	12.7	.510	13.0	20	3.5	.28	7.1	5.5	25	.16	4.0	0.045	1.1	3.50	SST	CG	N
0.600	15.24	71712	.63	16.0	.510	13.0	18	3.2	.45	12	8.2	36	.17	4.4	0.045	1.1	3.88	MW	CG	N
0.600	15.24	71712S	.63	16.0	.510	13.0	15	2.7	.36	9.2	5.5	25	.17	4.4	0.045	1.1	3.88	SST	CG	N
0.600	15.24	71729	.63	16.0	.502	12.8	28	4.9	.38	9.6	11	47	.18	4.7	0.049	1.2	3.75	MW	CG	N
0.600	15.24	71729S	.63	16.0	.502	12.8	24	4.2	.30	7.6	7.1	32	.18	4.7	0.049	1.2	3.75	SST	CG	N
0.600	15.24	71741	.63	16.0	.490	12.4	40	7.0	.35	8.8	14	62	.22	5.6	0.055	1.4	4.00	MW	CG	N
0.600	15.24	71741S	.63	16.0	.490	12.4	34	6.0	.28	7.0	9.4	42	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.600	15.24	71753	.63	16.0	.482	12.2	53	9.3	.32	8.1	17	76	.24	6.2	0.059	1.5	4.13	MW	CG	N
0.600	15.24	71753S	.63	16.0	.482	12.2	45	7.9	.26	6.5	12	51	.24	6.2	0.059	1.5	4.13	SST	CG	N
0.600	15.24	71765	.63	16.0	.474	12.0	63	11	.33	8.4	21	92	.28	7.0	0.063	1.6	4.38	MW	CG	N
0.600	15.24	71765S	.63	16.0	.474	12.0	54	9.4	.26	6.7	14	62	.28	7.0	0.063	1.6	4.38	SST	CG	N
0.600	15.24	71779	.63	16.0	.466	11.8	80	14	.31	7.9	25	110	.29	7.4	0.067	1.7	4.38	MW	CG	N
0.600	15.24	71779S	.63	16.0	.466	11.8	68	12	.25	6.3	17	75	.29	7.4	0.067	1.7	4.38	SST	CG	N
0.600	15.24	71791	.63	16.0	.456	11.6	109	19	.27	6.8	29	130	.32	8.0	0.072	1.8	4.38	MW	CG	N
0.600	15.24	71791S	.63	16.0	.456	11.6	92	16	.21	5.4	20	87	.32	8.0	0.072	1.8	4.38	SST	CG	N
0.600	15.24	71803	.63	16.0	.438	11.1	203	36	.20	5.2	41	184	.33	8.5	0.081	2.1	4.13	MW	CG	N
0.600	15.24	71803S	.63	16.0	.438	11.1	173	30	.16	4.1	28	123	.33	8.5	0.081	2.1	4.13	SST	CG	N
0.600	15.24	71819	.63	16.0	.430	10.9	263	46	.18	4.6	48	211	.35	8.9	0.085	2.2	4.13	MW	CG	N
0.600	15.24	71819S	.63	16.0	.430	10.9	223	39	.14	3.6	32	142	.35	8.9	0.085	2.2	4.13	SST	CG	N
0.600	15.24	71713	.75	19.1	.510	13.0	15	2.5	.55	14	8.0	36	.20	5.0	0.045	1.1	4.38	MW	CG	N
0.600	15.24	71713S	.75	19.1	.510	13.0	12	2.2	.45	11	5.5	25	.20	5.0	0.045	1.1	4.38	SST	CG	N
0.600	15.24	71730	.75	19.1	.502	12.8	23	4.0	.46	12	11	47	.20	5.1	0.049	1.2	4.13	MW	CG	N
0.600	15.24	71730S	.75	19.1	.502	12.8	19	3.4	.37	9.4	7.1	32	.20	5.1	0.049	1.2	4.13	SST	CG	N
0.600	15.24	71742	.75	19.1	.490	12.4	33	5.8	.42	11	14	62	.25	6.3	0.055	1.4	4.50	MW	CG	N
0.600	15.24	71742S	.75	19.1	.490	12.4	28	4.9	.34	8.5	9.4	42	.25	6.3	0.055	1.4	4.50	SST	CG	N
0.600	15.24	71754	.75	19.1	.482	12.2	42	7.4	.40	10	17	76	.27	6.9	0.059	1.5	4.63	MW	CG	N
0.600	15.24	71754S	.75	19.1	.482	12.2	36	6.3	.32	8.2	12	51	.27	6.9	0.059	1.5	4.63	SST	CG	N
0.600	15.24	71766	.75	19.1	.474	12.0	52	9.1	.40	10	21	92	.31	7.8	0.063	1.6	4.88	MW	CG	N
0.600	15.24	71766S	.75	19.1	.474	12.0	44	7.7	.32	8.1	14	62	.31	7.8	0.063	1.6	4.88	SST	CG	N
0.600	15.24	71780	.75	19.1	.466	11.8	65	11	.38	9.8	25	110	.34	8.5	0.067	1.7	5.00	MW	CG	N
0.600	15.24	71780S	.75	19.1	.466	11.8	55	9.6	.31	7.8	17	75	.34	8.5	0.067	1.7	5.00	SST	CG	N
0.600	15.24	71792	.75	19.1	.456	11.6	78	14	.36	9.2	28	126	.39	9.8	0.072	1.8	5.38	MW	CG	N
0.600	15.24	71792S	.75	19.1	.456	11.6	66	12	.30	7.5	20	87	.39	9.8	0.072	1.8	5.38	SST	CG	N
0.600	15.24	71804	.75	19.1	.438	11.1	159	28	.26	6.6	41	184	.38	9.8	0.081	2.1	4.75	MW	CG	N
0.600	15.24	71804S	.75	19.1	.438	11.1	135	24	.20	5.2	28	123	.38	9.8	0.081	2.1	4.75	SST	CG	N
0.600	15.24	71820	.75	19.1	.430	10.9	204	36	.23	5.9	48	211	.40	10.3	0.085	2.2	4.75	MW	CG	N
0.600	15.24	71820S	.75	19.1	.430	10.9	173	30	.18	4.7	32	142	.40	10.3	0.085	2.2	4.75	SST	CG	N
0.600	15.24	71835	.75	19.1	.416	10.6	292	51	.20	5.0	57	256	.44	11.1	0.092	2.3	4.75	MW	CG	N
0.600	15.24	71835S	.75	19.1	.416	10.6	248	43	.15	3.9	38	169	.44	11.1	0.092	2.3	4.75	SST	CG	N
0.600	15.24	71850	.75	19.1	.404	10.3	388	68	.18	4.5	69	307	.47	11.8	0.098	2.5	4.75	MW	CG	N
0.600	15.24	71850S	.75	19.1	.404	10.3	330	58	.14	3.5	46	203	.47	11.8	0.098	2.5	4.75	SST	CG	N
0.600	15.24	71714	.88	22.4	.510	13.0	12	2.1	.66	17	7.9	35	.22	5.6	0.045	1.1	4.88	MW	CG	N
0.600	15.24	71714S	.88	22.4	.510	13.0	10	1.8	.54	14	5.5	25	.22	5.6	0.045	1.1	4.88	SST	CG	N
0.600	15.24	71731	.88	22.4	.502	12.8	19	3.3	.55	14	11	47	.23	5.8	0.049	1.2	4.63	MW	CG	N
0.600	15.24	71731S	.88	22.4	.502	12.8	16	2.8	.44	11	7.1	32	.23	5.8	0.049	1.2	4.63	SST	CG	N
0.600	15.24	71743	.88	22.4	.490	12.4	28	4.8	.50	13	14	62	.28	7.0	0.055	1.4	5.00	MW	CG	N
0.600	15.24	71743S	.88	22.4	.490	12.4	23	4.1	.40	10	9.4	42	.28	7.0	0.055	1.4	5.00	SST	CG	N
0.600	15.24	71755	.88	22.4	.482	12.2	35	6.2	.49	12	17	76	.30	7.7	0.059	1.5	5.13	MW	CG	N
0.600	15.24	71755S	.88	22.4	.482	12.2	30	5.2	.39	9.8	12	51	.30	7.7	0.059	1.5	5.13	SST	CG	N
0.600	15.24	71767	.88	22.4	.474	12.0	45	7.8	.47	12	21	92	.33	8.4	0.063	1.6	5.25	MW	CG	N
0.600	15.24	71767S	.88	22.4	.474	12.0	38	6.6	.37	9.4	14	62	.33	8.4	0.063	1.6	5.25	SST	CG	N
0.600	15.24	71781	.88	22.4	.466	11.8	50	8.8	.49	12	24	108	.39	10.0	0.067	1.7	5.88	MW	CG	N
0.600	15.24	71781S	.88	22.4	.466	11.8	43	7.4	.40	10	17	75	.39	10.0	0.067	1.7	5.88	SST	CG	N
0.600	15.24	71793	.88	22.4	.456	11.6	68	12	.43	11	29	130	.42	10.7	0.072	1.8	5.88	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.600	15.24	71793S	.88	22.4	.456	11.6	58	10	.34	8.6	20	87	.42	10.7	0.072	1.8	5.88	SST	CG	N
0.600	15.24	71805	.88	22.4	.438	11.1	131	23	.32	8.0	41	184	.44	11.1	0.081	2.1	5.38	MW	CG	N
0.600	15.24	71805S	.88	22.4	.438	11.1	111	19	.25	6.3	28	123	.44	11.1	0.081	2.1	5.38	SST	CG	N
0.600	15.24	71821	.88	22.4	.430	10.9	166	29	.29	7.3	48	211	.45	11.3	0.085	2.2	5.25	MW	CG	N
0.600	15.24	71821S	.88	22.4	.430	10.9	141	25	.23	5.7	32	142	.45	11.3	0.085	2.2	5.25	SST	CG	N
0.600	15.24	71836	.88	22.4	.416	10.6	237	42	.24	6.2	57	256	.49	12.6	0.092	2.3	5.38	MW	CG	N
0.600	15.24	71836S	.88	22.4	.416	10.6	201	35	.19	4.8	38	169	.49	12.6	0.092	2.3	5.38	SST	CG	N
0.600	15.24	71851	.88	22.4	.404	10.3	314	55	.22	5.6	69	307	.53	13.4	0.098	2.5	5.38	MW	CG	N
0.600	15.24	71851S	.88	22.4	.404	10.3	267	47	.17	4.3	46	203	.53	13.4	0.098	2.5	5.38	SST	CG	N
0.600	15.24	71715	1.00	25.4	.510	13.0	9.9	1.7	.75	19	7.4	33	.25	6.3	0.045	1.1	5.50	MW	CG	Z
0.600	15.24	71715S	1.00	25.4	.510	13.0	8.7	1.5	.64	16	5.5	25	.24	6.1	0.045	1.1	5.38	SST	CG	N
0.600	15.24	71732	1.00	25.4	.502	12.8	16	2.8	.65	17	11	47	.25	6.4	0.049	1.2	5.13	MW	CG	N
0.600	15.24	71732S	1.00	25.4	.502	12.8	14	2.4	.52	13	7.1	32	.25	6.4	0.049	1.2	5.13	SST	CG	N
0.600	15.24	71744	1.00	25.4	.490	12.4	24	4.2	.58	15	14	62	.30	7.5	0.055	1.4	5.38	MW	CG	N
0.600	15.24	71744S	1.00	25.4	.490	12.4	20	3.6	.46	12	9.4	42	.30	7.5	0.055	1.4	5.38	SST	CG	N
0.600	15.24	71756	1.00	25.4	.482	12.2	30	5.3	.56	14	17	76	.33	8.4	0.059	1.5	5.63	MW	CG	N
0.600	15.24	71756S	1.00	25.4	.482	12.2	26	4.5	.45	11	12	51	.33	8.4	0.059	1.5	5.63	SST	CG	N
0.600	15.24	71768	1.00	25.4	.474	12.0	38	6.7	.55	14	21	92	.37	9.4	0.063	1.6	5.88	MW	CG	N
0.600	15.24	71768S	1.00	25.4	.474	12.0	32	5.7	.43	11	14	62	.37	9.4	0.063	1.6	5.88	SST	CG	N
0.600	15.24	71782	1.00	25.4	.466	11.8	45	7.9	.55	14	25	110	.42	10.6	0.067	1.7	6.25	MW	CG	N
0.600	15.24	71782S	1.00	25.4	.466	11.8	38	6.7	.44	11	17	75	.42	10.6	0.067	1.7	6.25	SST	CG	N
0.600	15.24	71794	1.00	25.4	.456	11.6	55	9.6	.51	13	28	126	.49	12.3	0.072	1.8	6.75	MW	CG	N
0.600	15.24	71794S	1.00	25.4	.456	11.6	47	8.2	.42	11	20	87	.49	12.3	0.072	1.8	6.75	SST	CG	N
0.600	15.24	71806	1.00	25.4	.438	11.1	112	20	.37	9.4	41	184	.49	12.3	0.081	2.1	6.00	MW	CG	N
0.600	15.24	71806S	1.00	25.4	.438	11.1	95	17	.29	7.4	28	123	.49	12.3	0.081	2.1	6.00	SST	CG	N
0.600	15.24	71822	1.00	25.4	.430	10.9	142	25	.33	8.5	48	211	.50	12.7	0.085	2.2	5.88	MW	CG	N
0.600	15.24	71822S	1.00	25.4	.430	10.9	121	21	.26	6.7	32	142	.50	12.7	0.085	2.2	5.88	SST	CG	N
0.600	15.24	71837	1.00	25.4	.416	10.6	202	35	.28	7.2	57	256	.54	13.7	0.092	2.3	5.88	MW	CG	N
0.600	15.24	71837S	1.00	25.4	.416	10.6	172	30	.22	5.6	38	169	.54	13.7	0.092	2.3	5.88	SST	CG	N
0.600	15.24	71852	1.00	25.4	.404	10.3	267	47	.26	6.6	69	307	.58	14.6	0.098	2.5	5.88	MW	CG	N
0.600	15.24	71852S	1.00	25.4	.404	10.3	227	40	.20	5.1	46	203	.58	14.6	0.098	2.5	5.88	SST	CG	N
0.600	15.24	71716	1.25	31.8	.510	13.0	8.0	1.4	.97	25	7.8	34	.28	7.1	0.045	1.1	6.25	MW	CG	N
0.600	15.24	71716S	1.25	31.8	.510	13.0	6.8	1.2	.81	21	5.5	25	.28	7.1	0.045	1.1	6.25	SST	CG	N
0.600	15.24	71733	1.25	31.8	.502	12.8	13	2.3	.82	21	11	47	.29	7.3	0.049	1.2	5.88	MW	CG	N
0.600	15.24	71733S	1.25	31.8	.502	12.8	11	1.9	.65	17	7.1	32	.29	7.3	0.049	1.2	5.88	SST	CG	N
0.600	15.24	71745	1.25	31.8	.490	12.4	19	3.2	.75	19	14	62	.35	8.9	0.055	1.4	6.38	MW	CG	N
0.600	15.24	71745S	1.25	31.8	.490	12.4	16	2.8	.60	15	9.4	42	.35	8.9	0.055	1.4	6.38	SST	CG	N
0.600	15.24	71757	1.25	31.8	.482	12.2	24	4.2	.71	18	17	76	.39	9.9	0.059	1.5	6.63	MW	CG	N
0.600	15.24	71757S	1.25	31.8	.482	12.2	20	3.6	.57	14	12	51	.39	9.9	0.059	1.5	6.63	SST	CG	N
0.600	15.24	71769	1.25	31.8	.474	12.0	31	5.3	.68	17	21	92	.43	10.8	0.063	1.6	6.75	MW	CG	N
0.600	15.24	71769S	1.25	31.8	.474	12.0	26	4.5	.54	14	14	62	.43	10.8	0.063	1.6	6.75	SST	CG	N
0.600	15.24	71783	1.25	31.8	.466	11.8	35	6.1	.71	18	25	110	.50	12.8	0.067	1.7	7.50	MW	CG	N
0.600	15.24	71783S	1.25	31.8	.466	11.8	30	5.2	.57	14	17	75	.50	12.8	0.067	1.7	7.50	SST	CG	N
0.600	15.24	71795	1.25	31.8	.456	11.6	45	7.9	.65	17	29	130	.57	14.4	0.072	1.8	7.88	MW	CG	N
0.600	15.24	71795S	1.25	31.8	.456	11.6	38	6.7	.51	13	20	87	.57	14.4	0.072	1.8	7.88	SST	CG	N
0.600	15.24	71807	1.25	31.8	.438	11.1	86	15	.48	12	41	184	.58	14.7	0.081	2.1	7.13	MW	CG	N
0.600	15.24	71807S	1.25	31.8	.438	11.1	73	13	.38	9.6	28	123	.58	14.7	0.081	2.1	7.13	SST	CG	N
0.600	15.24	71823	1.25	31.8	.430	10.9	109	19	.43	11	48	211	.60	15.1	0.085	2.2	7.00	MW	CG	N
0.600	15.24	71823S	1.25	31.8	.430	10.9	93	16	.34	8.7	32	142	.60	15.1	0.085	2.2	7.00	SST	CG	N
0.600	15.24	71838	1.25	31.8	.416	10.6	155	27	.37	9.4	57	256	.66	16.6	0.092	2.3	7.13	MW	CG	N
0.600	15.24	71838S	1.25	31.8	.416	10.6	131	23	.29	7.4	38	169	.66	16.6	0.092	2.3	7.13	SST	CG	N
0.600	15.24	71853	1.25	31.8	.404	10.3	204	36	.34	8.6	69	307	.70	17.7	0.098	2.5	7.13	MW	CG	N
0.600	15.24	71853S	1.25	31.8	.404	10.3	173	30	.26	6.7	46	203	.70	17.7	0.098	2.5	7.13	SST	CG	N
0.600	15.24	71717	1.38	35.1	.510	13.0	7.1	1.2	1.1	27	7.6	34	.31	7.9	0.045	1.1	6.88	MW	CG	N
0.600	15.24	71717S	1.38	35.1	.510	13.0	6.0	1.1	.92	23	5.5	25	.31	7.9	0.045	1.1	6.88	SST	CG	N
0.600	15.24	71718	1.50	38.1	.510	13.0	6.5	1.1	1.2	30	7.6	34	.33	8.3	0.045	1.1	7.25	MW	CG	N
0.600	15.24	71718S	1.50	38.1	.510	13.0	5.5	.97	1.0	25	5.5	25	.33	8.3	0.045	1.1	7.25	SST	CG	N
0.600	15.24	71719	1.50	38.1	.510	13.0	7.5	1.3	1.1	28	8.2	36	.30	7.6	0.045	1.1	6.63	MW	CG	N
0.600	15.24	71719S	1.50	38.1	.510	13.0	6.4	1.1	.87	22	5.5	25	.30	7.6	0.045	1.1	6.63	SST	CG	N
0.600	15.24	71734	1.50	38.1	.502	12.8	10	1.8	1.0	26	11	47	.34	8.6	0.049	1.2	6.88	MW	CG	N
0.600	15.24	71734S	1.50	38.1	.502	12.8	8.7	1.5	.82	21	7.1	32	.34	8.6	0.049	1.2	6.88	SST	CG	N
0.600	15.24	71746	1.50	38.1	.490	12.4	15	2.6	.93	24	14	62	.41	10.3	0.055	1.4	7.38	MW	CG	N
0.600	15.24	71746S	1.50	38.1	.490	12.4	13	2.2	.74	19	9.4	42	.41	10.3	0.055	1.4	7.38	SST	CG	N
0.600	15.24	71758	1.50	38.1	.482	12.2	19	3.4	.89	23	17	76	.46	11.6	0.059	1.5	7.75	MW	CG	N
0.600	15.24	71758S	1.50	38.1	.482	12.2	16	2.9	.71	18	12	51	.46	11.6	0.059	1.5	7.75	SST	CG	N
0.600	15.24	71770	1.50	38.1	.474	12.0	24	4.2	.86	22	21	92	.51	13.0	0.063	1.6	8.13	MW	CG	N
0.600	15.24	71770S	1.50	38.1	.474	12.0	20	3.6	.69	17	14	62	.51	13.0	0.063	1.6	8.13	SST	CG	N
0.600	15.24	71784	1.50	38.1	.466	11.8	29	5.1	.86	22	25	110	.58	14.7	0.067	1.7	8.63	MW	CG	N
0.600	15.24	71784S	1.50	38.1	.466	11.8	25	4.3	.68	17	17	75	.58	14.7	0.067	1.7	8.63	SST	CG	N
0.600	15.24	71796	1.50	38.1	.456	11.6	36	6.3	.81	21	29	130	.67	16.9	0.072	1.8	9.25	MW	CG	N
0.600	15.24	71796S	1.50	38.1	.456	11.6	31	5.4	.64	16	20	87	.67	16.9	0.072	1.8	9.25	SST	CG	N
0.600	15.24	71808	1.50	38.1	.438	11.1	70	12	.59	15	41	184	.68	17.2	0.081	2.1	8.38	MW	CG	N
0.600	15.24	71808S	1.50	38.1	.438	11.1	59	10	.47	12	28	123	.68	17.2	0.081	2.1	8.38	SST	CG	N
0.600	15.24	71824	1.50	38.1	.430	10.9	89	16	.54	14	48	211	.70	17.8	0.085	2.2	8.25	MW	CG	N
0.600	15.24	71824S	1.50	38.1	.430	10.9	75	13	.42	11	32	142	.70	17.8	0.085	2.2	8.25	SST	CG	N
0.600	15.24	71839	1.50	38.1	.416	10.6	125	22	.46	12	57	256	.76	19.3	0.092	2.3	8.25	MW	CG	N
0.600	15.24	71839S	1.50	38.1	.416	10.6	107	19	.36	9.1	38	169	.76	19.3	0.092	2.3	8.25	SST	CG	N
0.600	15.24	71854	1.50	38.1	.404	10.3	165	29	.42	11	69	307	.82	20.8	0.098	2.5	8.38	MW	CG	N
0.600	15.24	71854S	1.50	38.1	.404	10.3	140	25	.33	8.3	46	203	.82	20.8	0.098	2.5	8.38	SST	CG	N
0.600	15.24	71720	1.75	44.5	.510	13.0	5.5	.96	1.4	35	7.6	34	.37	9.4	0.045	1.1	8.25	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.600	15.24	71720S	1.75	44.5	.510	13.0	4.7	.82	1.2	30	5.5	25	.37	9.4	0.045	1.1	8.25	SST	CG	N
0.600	15.24	71735	1.75	44.5	.502	12.8	8.7	1.5	1.2	31	11	47	.38	9.6	0.049	1.2	7.75	MW	CG	N
0.600	15.24	71735S	1.75	44.5	.502	12.8	7.4	1.3	.97	25	7.1	32	.38	9.6	0.049	1.2	7.75	SST	CG	N
0.600	15.24	71747	1.75	44.5	.490	12.4	13	2.3	1.1	27	14	62	.45	11.5	0.055	1.4	8.25	MW	CG	N
0.600	15.24	71747S	1.75	44.5	.490	12.4	11	1.9	.86	22	9.4	42	.45	11.5	0.055	1.4	8.25	SST	CG	N
0.600	15.24	71759	1.75	44.5	.482	12.2	16	2.8	1.1	27	17	76	.52	13.1	0.059	1.5	8.75	MW	CG	N
0.600	15.24	71759S	1.75	44.5	.482	12.2	14	2.4	.84	21	12	51	.52	13.1	0.059	1.5	8.75	SST	CG	N
0.600	15.24	71771	1.75	44.5	.474	12.0	20	3.6	1.0	26	21	92	.57	14.6	0.063	1.6	9.13	MW	CG	N
0.600	15.24	71771S	1.75	44.5	.474	12.0	17	3.0	.81	21	14	62	.57	14.6	0.063	1.6	9.13	SST	CG	N
0.600	15.24	71785	1.75	44.5	.466	11.8	24	4.1	1.1	27	25	110	.68	17.2	0.067	1.7	10.1	MW	CG	N
0.600	15.24	71785S	1.75	44.5	.466	11.8	20	3.5	.84	21	17	75	.68	17.2	0.067	1.7	10.1	SST	CG	N
0.600	15.24	71797	1.75	44.5	.456	11.6	30	5.3	.98	25	29	130	.77	19.7	0.072	1.8	10.8	MW	CG	N
0.600	15.24	71797S	1.75	44.5	.456	11.6	26	4.5	.77	20	20	87	.77	19.7	0.072	1.8	10.8	SST	CG	N
0.600	15.24	71809	1.75	44.5	.438	11.1	59	10	.70	18	41	184	.77	19.5	0.081	2.1	9.50	MW	CG	N
0.600	15.24	71809S	1.75	44.5	.438	11.1	50	8.8	.55	14	28	123	.77	19.5	0.081	2.1	9.50	SST	CG	N
0.600	15.24	71825	1.75	44.5	.430	10.9	75	13	.64	16	48	211	.80	20.2	0.085	2.2	9.38	MW	CG	N
0.600	15.24	71825S	1.75	44.5	.430	10.9	64	11	.50	13	32	142	.80	20.2	0.085	2.2	9.38	SST	CG	N
0.600	15.24	71840	1.75	44.5	.416	10.6	105	18	.55	14	57	256	.87	22.2	0.092	2.3	9.50	MW	CG	N
0.600	15.24	71840S	1.75	44.5	.416	10.6	90	16	.43	11	38	169	.87	22.2	0.092	2.3	9.50	SST	CG	N
0.600	15.24	71855	1.75	44.5	.404	10.3	138	24	.50	13	69	307	.94	24.0	0.098	2.5	9.63	MW	CG	N
0.600	15.24	71855S	1.75	44.5	.404	10.3	118	21	.39	9.9	46	203	.94	24.0	0.098	2.5	9.63	SST	CG	N
0.600	15.24	71721	2.00	50.8	.510	13.0	5.3	.92	1.6	39	8.2	36	.38	9.7	0.045	1.1	8.50	MW	CG	N
0.600	15.24	71721S	2.00	50.8	.510	13.0	4.5	.79	1.2	31	5.5	25	.38	9.7	0.045	1.1	8.50	SST	CG	N
0.600	15.24	71736	2.00	50.8	.502	12.8	7.6	1.3	1.4	35	11	47	.42	10.6	0.049	1.2	8.50	MW	CG	N
0.600	15.24	71736S	2.00	50.8	.502	12.8	6.5	1.1	1.1	28	7.1	32	.42	10.6	0.049	1.2	8.50	SST	CG	N
0.600	15.24	71748	2.00	50.8	.490	12.4	11	2.0	1.2	32	14	62	.51	12.9	0.055	1.4	9.25	MW	CG	N
0.600	15.24	71748S	2.00	50.8	.490	12.4	9.5	1.7	.99	25	9.4	42	.51	12.9	0.055	1.4	9.25	SST	CG	N
0.600	15.24	71760	2.00	50.8	.482	12.2	14	2.5	1.2	31	17	76	.58	14.6	0.059	1.5	9.75	MW	CG	N
0.600	15.24	71760S	2.00	50.8	.482	12.2	12	2.1	.96	24	12	51	.58	14.6	0.059	1.5	9.75	SST	CG	N
0.600	15.24	71772	2.00	50.8	.474	12.0	18	3.1	1.2	30	21	92	.65	16.4	0.063	1.6	10.3	MW	CG	N
0.600	15.24	71772S	2.00	50.8	.474	12.0	15	2.6	.93	24	14	62	.65	16.4	0.063	1.6	10.3	SST	CG	N
0.600	15.24	71786	2.00	50.8	.466	11.8	21	3.7	1.2	30	25	110	.75	18.9	0.067	1.7	11.1	MW	CG	N
0.600	15.24	71786S	2.00	50.8	.466	11.8	18	3.1	.94	24	17	75	.75	18.9	0.067	1.7	11.1	SST	CG	N
0.600	15.24	71798	2.00	50.8	.456	11.6	27	4.7	1.1	28	29	130	.85	21.5	0.072	1.8	11.8	MW	CG	N
0.600	15.24	71798S	2.00	50.8	.456	11.6	23	4.0	.86	22	20	87	.85	21.5	0.072	1.8	11.8	SST	CG	N
0.600	15.24	71810	2.00	50.8	.438	11.1	51	8.9	.81	21	41	184	.87	22.1	0.081	2.1	10.8	MW	CG	N
0.600	15.24	71810S	2.00	50.8	.438	11.1	43	7.6	.64	16	28	123	.87	22.1	0.081	2.1	10.8	SST	CG	N
0.600	15.24	71826	2.00	50.8	.430	10.9	65	11	.74	19	48	211	.89	22.7	0.085	2.2	10.5	MW	CG	N
0.600	15.24	71826S	2.00	50.8	.430	10.9	55	9.6	.58	15	32	142	.89	22.7	0.085	2.2	10.5	SST	CG	N
0.600	15.24	71841	2.00	50.8	.416	10.6	91	16	.63	16	57	256	.98	24.8	0.092	2.3	10.6	MW	CG	N
0.600	15.24	71841S	2.00	50.8	.416	10.6	77	14	.49	13	38	169	.98	24.8	0.092	2.3	10.6	SST	CG	N
0.600	15.24	71856	2.00	50.8	.404	10.3	119	21	.58	15	69	307	1.05	26.8	0.098	2.5	10.8	MW	CG	N
0.600	15.24	71856S	2.00	50.8	.404	10.3	101	18	.45	11	46	203	1.05	26.8	0.098	2.5	10.8	SST	CG	N
0.600	15.24	71722	2.25	57.2	.510	13.0	4.7	.82	1.7	44	8.2	36	.42	10.7	0.045	1.1	9.38	MW	CG	N
0.600	15.24	71722S	2.25	57.2	.510	13.0	4.0	.70	1.4	35	5.5	25	.42	10.7	0.045	1.1	9.38	SST	CG	N
0.600	15.24	71737	2.25	57.2	.502	12.8	6.7	1.2	1.6	40	11	47	.47	11.8	0.049	1.2	9.50	MW	CG	N
0.600	15.24	71737S	2.25	57.2	.502	12.8	5.7	.99	1.3	32	7.1	32	.47	11.8	0.049	1.2	9.50	SST	CG	N
0.600	15.24	71749	2.25	57.2	.490	12.4	9.9	1.7	1.4	36	14	62	.56	14.3	0.055	1.4	10.3	MW	CG	N
0.600	15.24	71749S	2.25	57.2	.490	12.4	8.4	1.5	1.1	28	9.4	42	.56	14.3	0.055	1.4	10.3	SST	CG	N
0.600	15.24	71761	2.25	57.2	.482	12.2	13	2.2	1.4	35	17	76	.63	16.1	0.059	1.5	10.8	MW	CG	N
0.600	15.24	71761S	2.25	57.2	.482	12.2	11	1.9	1.1	28	12	51	.63	16.1	0.059	1.5	10.8	SST	CG	N
0.600	15.24	71773	2.25	57.2	.474	12.0	16	2.7	1.3	34	21	92	.72	18.2	0.063	1.6	11.4	MW	CG	N
0.600	15.24	71773S	2.25	57.2	.474	12.0	13	2.3	1.1	27	14	62	.72	18.2	0.063	1.6	11.4	SST	CG	N
0.600	15.24	71787	2.25	57.2	.466	11.8	18	3.2	1.3	34	25	110	.83	21.1	0.067	1.7	12.4	MW	CG	N
0.600	15.24	71787S	2.25	57.2	.466	11.8	16	2.7	1.1	27	17	75	.83	21.1	0.067	1.7	12.4	SST	CG	N
0.600	15.24	71799	2.25	57.2	.456	11.6	25	4.3	1.2	30	29	130	.91	23.1	0.072	1.8	12.6	MW	CG	N
0.600	15.24	71799S	2.25	57.2	.456	11.6	21	3.7	.94	24	20	87	.91	23.1	0.072	1.8	12.6	SST	CG	N
0.600	15.24	71811	2.25	57.2	.438	11.1	45	7.8	.92	23	41	184	.96	24.4	0.081	2.1	11.9	MW	CG	N
0.600	15.24	71811S	2.25	57.2	.438	11.1	38	6.7	.73	18	28	123	.96	24.4	0.081	2.1	11.9	SST	CG	N
0.600	15.24	71827	2.25	57.2	.430	10.9	57	9.9	.84	21	48	211	.99	25.1	0.085	2.2	11.6	MW	CG	N
0.600	15.24	71827S	2.25	57.2	.430	10.9	48	8.5	.66	17	32	142	.99	25.1	0.085	2.2	11.6	SST	CG	N
0.600	15.24	71842	2.25	57.2	.416	10.6	80	14	.72	18	57	256	1.09	27.7	0.092	2.3	11.9	MW	CG	N
0.600	15.24	71842S	2.25	57.2	.416	10.6	68	12	.56	14	38	169	1.09	27.7	0.092	2.3	11.9	SST	CG	N
0.600	15.24	71857	2.25	57.2	.404	10.3	105	18	.66	17	69	307	1.18	29.9	0.098	2.5	12.0	MW	CG	N
0.600	15.24	71857S	2.25	57.2	.404	10.3	89	16	.51	13	46	203	1.18	29.9	0.098	2.5	12.0	SST	CG	N
0.600	15.24	71723	2.50	63.5	.510	13.0	4.2	.73	2.0	50	8.2	36	.46	11.7	0.045	1.1	10.3	MW	CG	N
0.600	15.24	71723S	2.50	63.5	.510	13.0	3.5	.62	1.6	40	5.5	25	.46	11.7	0.045	1.1	10.3	SST	CG	N
0.600	15.24	71738	2.50	63.5	.502	12.8	5.9	1.0	1.8	45	11	47	.51	12.9	0.049	1.2	10.4	MW	CG	N
0.600	15.24	71738S	2.50	63.5	.502	12.8	5.0	.88	1.4	36	7.1	32	.51	12.9	0.049	1.2	10.4	SST	CG	N
0.600	15.24	71750	2.50	63.5	.490	12.4	8.9	1.6	1.6	40	14	62	.61	15.5	0.055	1.4	11.1	MW	CG	N
0.600	15.24	71750S	2.50	63.5	.490	12.4	7.6	1.3	1.2	32	9.4	42	.61	15.5	0.055	1.4	11.1	SST	CG	N
0.600	15.24	71762	2.50	63.5	.482	12.2	11	2.0	1.5	38	17	76	.69	17.6	0.059	1.5	11.8	MW	CG	N
0.600	15.24	71762S	2.50	63.5	.482	12.2	9.6	1.7	1.2	31	12	51	.69	17.6	0.059	1.5	11.8	SST	CG	N
0.600	15.24	71774	2.50	63.5	.474	12.0	14	2.5	1.5	37	21	92	.78	19.8	0.063	1.6	12.4	MW	CG	N
0.600	15.24	71774S	2.50	63.5	.474	12.0	12	2.1	1.2	30	14	62	.78	19.8	0.063	1.6	12.4	SST	CG	N
0.600	15.24	71788	2.50	63.5	.466	11.8	16	2.9	1.5	39	25	110	.92	23.4	0.067	1.7	13.8	MW	CG	N
0.600	15.24	71788S	2.50	63.5	.466	11.8	14	2.4	1.2	31	17	75	.92	23.4	0.067	1.7	13.8	SST	CG	N
0.600	15.24	71800	2.50	63.5	.456	11.6	22	3.9	1.3	34	29	130	1.00	25.4	0.072	1.8	13.9	MW	CG	N
0.600	15.24	71800S	2.50	63.5	.456	11.6	19	3.3	1.0	27	20	87	1.00	25.4	0.072	1.8	13.9	SST	CG	N
0.600	15.24	71812	2.50	63.5	.438	11.1	40	7.0	1.0	26	41	184	1.05	26.7	0.081	2.1	13.0	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.600	15.24	71812S	2.50	63.5	.438	11.1	34	6.0	.81	21	28	123	1.05	26.7	0.081	2.1	13.0	SST	CG	N
0.600	15.24	71828	2.50	63.5	.430	10.9	51	8.9	.94	24	48	211	1.09	27.8	0.085	2.2	12.9	MW	CG	N
0.600	15.24	71828S	2.50	63.5	.430	10.9	43	7.5	.74	19	32	142	1.09	27.8	0.085	2.2	12.9	SST	CG	N
0.600	15.24	71843	2.50	63.5	.416	10.6	71	12	.81	21	57	256	1.20	30.4	0.092	2.3	13.0	MW	CG	N
0.600	15.24	71843S	2.50	63.5	.416	10.6	61	11	.63	16	38	169	1.20	30.4	0.092	2.3	13.0	SST	CG	N
0.600	15.24	71858	2.50	63.5	.404	10.3	93	16	.74	19	69	307	1.30	33.0	0.098	2.5	13.3	MW	CG	N
0.600	15.24	71858S	2.50	63.5	.404	10.3	79	14	.58	15	46	203	1.30	33.0	0.098	2.5	13.3	SST	CG	N
0.600	15.24	71724	2.75	69.9	.510	13.0	3.6	.63	2.2	57	8.0	36	.52	13.3	0.045	1.1	11.6	MW	CG	N
0.600	15.24	71724S	2.75	69.9	.510	13.0	3.1	.54	1.8	46	5.5	25	.52	13.3	0.045	1.1	11.6	SST	CG	N
0.600	15.24	71739	2.75	69.9	.502	12.8	5.3	.93	2.0	51	11	47	.56	14.2	0.049	1.2	11.4	MW	CG	N
0.600	15.24	71739S	2.75	69.9	.502	12.8	4.5	.79	1.6	40	7.1	32	.56	14.2	0.049	1.2	11.4	SST	CG	N
0.600	15.24	71751	2.75	69.9	.490	12.4	8.0	1.4	1.7	44	14	62	.67	16.9	0.055	1.4	12.1	MW	CG	N
0.600	15.24	71751S	2.75	69.9	.490	12.4	6.8	1.2	1.4	35	9.4	42	.67	16.9	0.055	1.4	12.1	SST	CG	N
0.600	15.24	71763	2.75	69.9	.482	12.2	9.8	1.7	1.8	44	17	76	.78	19.9	0.059	1.5	13.3	MW	CG	N
0.600	15.24	71763S	2.75	69.9	.482	12.2	8.3	1.5	1.4	35	12	51	.78	19.9	0.059	1.5	13.3	SST	CG	N
0.600	15.24	71775	2.75	69.9	.474	12.0	13	2.3	1.6	41	21	92	.83	21.2	0.063	1.6	13.3	MW	CG	N
0.600	15.24	71775S	2.75	69.9	.474	12.0	11	1.9	1.3	32	14	62	.83	21.2	0.063	1.6	13.3	SST	CG	N
0.600	15.24	71789	2.75	69.9	.466	11.8	15	2.6	1.6	42	25	110	.99	25.1	0.067	1.7	14.8	MW	CG	N
0.600	15.24	71789S	2.75	69.9	.466	11.8	13	2.2	1.3	33	17	75	.99	25.1	0.067	1.7	14.8	SST	CG	N
0.600	15.24	71801	2.75	69.9	.456	11.6	20	3.5	1.5	37	29	130	1.09	27.7	0.072	1.8	15.1	MW	CG	N
0.600	15.24	71801S	2.75	69.9	.456	11.6	17	3.0	1.2	29	20	87	1.09	27.7	0.072	1.8	15.1	SST	CG	N
0.600	15.24	71813	2.75	69.9	.438	11.1	36	6.3	1.1	29	41	184	1.15	29.3	0.081	2.1	14.3	MW	CG	N
0.600	15.24	71813S	2.75	69.9	.438	11.1	31	5.4	.90	23	28	123	1.15	29.3	0.081	2.1	14.3	SST	CG	N
0.600	15.24	71829	2.75	69.9	.430	10.9	46	8.0	1.0	26	48	211	1.19	30.2	0.085	2.2	14.0	MW	CG	N
0.600	15.24	71829S	2.75	69.9	.430	10.9	39	6.8	.82	21	32	142	1.19	30.2	0.085	2.2	14.0	SST	CG	N
0.600	15.24	71844	2.75	69.9	.416	10.6	64	11	.89	23	57	256	1.31	33.3	0.092	2.3	14.3	MW	CG	N
0.600	15.24	71844S	2.75	69.9	.416	10.6	55	9.6	.70	18	38	169	1.31	33.3	0.092	2.3	14.3	SST	CG	N
0.600	15.24	71859	2.75	69.9	.404	10.3	84	15	.82	21	69	307	1.42	36.1	0.098	2.5	14.5	MW	CG	N
0.600	15.24	71859S	2.75	69.9	.404	10.3	71	13	.64	16	46	203	1.42	36.1	0.098	2.5	14.5	SST	CG	N
0.600	15.24	71725	3.00	76.2	.510	13.0	3.3	.58	2.4	62	8.0	36	.56	14.3	0.045	1.1	12.5	MW	CG	N
0.600	15.24	71725S	3.00	76.2	.510	13.0	2.8	.49	2.0	50	5.5	25	.56	14.3	0.045	1.1	12.5	SST	CG	N
0.600	15.24	71740	3.00	76.2	.502	12.8	4.8	.84	2.2	56	11	47	.60	15.2	0.049	1.2	12.3	MW	CG	N
0.600	15.24	71740S	3.00	76.2	.502	12.8	4.1	.72	1.7	44	7.1	32	.60	15.2	0.049	1.2	12.3	SST	CG	N
0.600	15.24	71752	3.00	76.2	.490	12.4	7.3	1.3	1.9	48	14	62	.72	18.3	0.055	1.4	13.1	MW	CG	N
0.600	15.24	71752S	3.00	76.2	.490	12.4	6.2	1.1	1.5	38	9.4	42	.72	18.3	0.055	1.4	13.1	SST	CG	N
0.600	15.24	71764	3.00	76.2	.482	12.2	9.0	1.6	1.9	48	17	76	.84	21.4	0.059	1.5	14.3	MW	CG	N
0.600	15.24	71764S	3.00	76.2	.482	12.2	7.6	1.3	1.5	39	12	51	.84	21.4	0.059	1.5	14.3	SST	CG	N
0.600	15.24	71776	3.00	76.2	.474	12.0	12	2.1	1.8	45	21	92	.91	23.0	0.063	1.6	14.4	MW	CG	N
0.600	15.24	71776S	3.00	76.2	.474	12.0	10	1.8	1.4	36	14	62	.91	23.0	0.063	1.6	14.4	SST	CG	N
0.600	15.24	71790	3.00	76.2	.466	11.8	14	2.4	1.8	46	25	110	1.06	27.0	0.067	1.7	15.9	MW	CG	N
0.600	15.24	71790S	3.00	76.2	.466	11.8	12	2.0	1.4	37	17	75	1.06	27.0	0.067	1.7	15.9	SST	CG	N
0.600	15.24	71802	3.00	76.2	.456	11.6	18	3.2	1.6	41	29	130	1.19	30.2	0.072	1.8	16.5	MW	CG	N
0.600	15.24	71802S	3.00	76.2	.456	11.6	15	2.7	1.3	33	20	87	1.19	30.2	0.072	1.8	16.5	SST	CG	N
0.600	15.24	71814	3.00	76.2	.438	11.1	33	5.8	1.3	32	41	184	1.25	31.6	0.081	2.1	15.4	MW	CG	N
0.600	15.24	71814S	3.00	76.2	.438	11.1	28	4.9	.99	25	28	123	1.25	31.6	0.081	2.1	15.4	SST	CG	N
0.600	15.24	71830	3.00	76.2	.430	10.9	42	7.3	1.1	29	48	211	1.29	32.7	0.085	2.2	15.1	MW	CG	N
0.600	15.24	71830S	3.00	76.2	.430	10.9	35	6.2	.90	23	32	142	1.29	32.7	0.085	2.2	15.1	SST	CG	N
0.600	15.24	71845	3.00	76.2	.416	10.6	59	10	.98	25	57	256	1.41	35.9	0.092	2.3	15.4	MW	CG	N
0.600	15.24	71845S	3.00	76.2	.416	10.6	50	8.7	.76	19	38	169	1.41	35.9	0.092	2.3	15.4	SST	CG	N
0.600	15.24	71860	3.00	76.2	.404	10.3	77	13	.90	23	69	307	1.53	38.9	0.098	2.5	15.6	MW	CG	N
0.600	15.24	71860S	3.00	76.2	.404	10.3	65	11	.70	18	46	203	1.53	38.9	0.098	2.5	15.6	SST	CG	N
0.600	15.24	71726	3.25	82.6	.510	13.0	2.9	.50	2.6	67	7.5	33	.63	16.0	0.045	1.1	14.0	MW	CG	N
0.600	15.24	71726S	3.25	82.6	.510	13.0	2.4	.43	2.3	58	5.5	25	.63	16.0	0.045	1.1	14.0	SST	CG	N
0.600	15.24	71727	3.25	82.6	.510	13.0	3.3	.58	2.5	63	8.2	36	.56	14.3	0.045	1.1	12.5	MW	CG	N
0.600	15.24	71727S	3.25	82.6	.510	13.0	2.8	.49	2.0	50	5.5	25	.56	14.3	0.045	1.1	12.5	SST	CG	N
0.600	15.24	71777	3.25	82.6	.474	12.0	10	1.8	2.0	52	21	92	1.03	26.2	0.063	1.6	16.4	MW	CG	N
0.600	15.24	71777S	3.25	82.6	.474	12.0	8.7	1.5	1.6	41	14	62	1.03	26.2	0.063	1.6	16.4	SST	CG	N
0.600	15.24	71815	3.25	82.6	.438	11.1	32	5.5	1.3	33	41	184	1.30	32.9	0.081	2.1	16.0	MW	CG	N
0.600	15.24	71815S	3.25	82.6	.438	11.1	27	4.7	1.0	26	28	123	1.30	32.9	0.081	2.1	16.0	SST	CG	N
0.600	15.24	71831	3.25	82.6	.430	10.9	38	6.7	1.2	32	48	211	1.39	35.4	0.085	2.2	16.4	MW	CG	N
0.600	15.24	71831S	3.25	82.6	.430	10.9	33	5.7	.98	25	32	142	1.39	35.4	0.085	2.2	16.4	SST	CG	N
0.600	15.24	71846	3.25	82.6	.416	10.6	54	9.4	1.1	27	57	256	1.53	38.8	0.092	2.3	16.6	MW	CG	N
0.600	15.24	71846S	3.25	82.6	.416	10.6	46	8.0	.83	21	38	169	1.53	38.8	0.092	2.3	16.6	SST	CG	N
0.600	15.24	71861	3.25	82.6	.404	10.3	70	12	.98	25	69	307	1.65	42.0	0.098	2.5	16.9	MW	CG	N
0.600	15.24	71861S	3.25	82.6	.404	10.3	60	10	.76	19	46	203	1.65	42.0	0.098	2.5	16.9	SST	CG	N
0.600	15.24	12675	3.50	88.9	.510	13.0	2.2	.39	2.5	63	5.5	25	.69	17.6	0.045	1.1	15.4	SST	CG	N
0.600	15.24	71728	3.50	88.9	.510	13.0	2.8	.49	2.9	73	8.1	36	.64	16.3	0.045	1.1	14.3	MW	CG	N
0.600	15.24	71728S	3.50	88.9	.510	13.0	2.4	.42	2.3	59	5.5	25	.64	16.3	0.045	1.1	14.3	SST	CG	N
0.600	15.24	71778	3.50	88.9	.474	12.0	10	1.8	2.1	52	21	92	1.04	26.4	0.063	1.6	16.5	MW	CG	N
0.600	15.24	71778S	3.50	88.9	.474	12.0	8.5	1.5	1.6	42	14	62	1.04	26.4	0.063	1.6	16.5	SST	CG	N
0.600	15.24	71816	3.50	88.9	.438	11.1	29	5.1	1.4	36	41	184	1.39	35.2	0.081	2.1	17.1	MW	CG	N
0.600	15.24	71816S	3.50	88.9	.438	11.1	25	4.3	1.1	28	28	123	1.39	35.2	0.081	2.1	17.1	SST	CG	N
0.600	15.24	71832	3.50	88.9	.430	10.9	36	6.2	1.3	34	48	211	1.49	37.8	0.085	2.2	17.5	MW	CG	N
0.600	15.24	71832S	3.50	88.9	.430	10.9	30	5.3	1.1	27	32	142	1.49	37.8	0.085	2.2	17.5	SST	CG	N
0.600	15.24	71847	3.50	88.9	.416	10.6	50	8.7	1.2	29	57	256	1.63	41.5	0.092	2.3	17.8	MW	CG	N
0.600	15.24	71847S	3.50	88.9	.416	10.6	42	7.4	.90	23	38	169	1.63	41.5	0.092	2.3	17.8	SST	CG	N
0.600	15.24	71862	3.50	88.9	.404	10.3	65	11	1.1	27	69	307	1.78	45.1	0.098	2.5	18.1	MW	CG	N
0.600	15.24	71862S	3.50	88.9	.404	10.3	55	9.7	.83	21	46	203	1.78	45.1	0.098	2.5	18.1	SST	CG	N
0.600	15.24	71817	3.75	95.3	.438	11.1	27	4.7	1.5	39	41	184	1.49	37.8	0.081	2.1	18.4	MW	CG	N
0.600	15.24	71817S	3.75	95.3	.438	11.1	23	4.0	1.2	31	28	123	1.49	37.8	0.081	2.1	18.4	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.600	15.24	71833	3.75	95.3	.430	10.9	33	5.8	1.4	37	48	211	1.58	40.2	0.085	2.2	18.6	MW	CG	N
0.600	15.24	71833S	3.75	95.3	.430	10.9	28	4.9	1.1	29	32	142	1.58	40.2	0.085	2.2	18.6	SST	CG	N
0.600	15.24	71848	3.75	95.3	.416	10.6	46	8.1	1.2	32	57	256	1.75	44.4	0.092	2.3	19.0	MW	CG	N
0.600	15.24	71848S	3.75	95.3	.416	10.6	39	6.9	.97	25	38	169	1.75	44.4	0.092	2.3	19.0	SST	CG	N
0.600	15.24	71863	3.75	95.3	.404	10.3	61	11	1.1	29	69	307	1.90	48.2	0.098	2.5	19.4	MW	CG	N
0.600	15.24	71863S	3.75	95.3	.404	10.3	51	9.0	.89	23	46	203	1.90	48.2	0.098	2.5	19.4	SST	CG	N
0.600	15.24	71818	4.00	101.6	.438	11.1	25	4.4	1.6	41	41	184	1.57	39.9	0.081	2.1	19.4	MW	CG	N
0.600	15.24	71818S	4.00	101.6	.438	11.1	22	3.8	1.3	33	28	123	1.57	39.9	0.081	2.1	19.4	SST	CG	N
0.600	15.24	71834	4.00	101.6	.430	10.9	31	5.4	1.5	39	48	211	1.69	42.9	0.085	2.2	19.9	MW	CG	N
0.600	15.24	71834S	4.00	101.6	.430	10.9	26	4.6	1.2	31	32	142	1.69	42.9	0.085	2.2	19.9	SST	CG	N
0.600	15.24	71849	4.00	101.6	.416	10.6	43	7.6	1.3	34	57	256	1.85	47.0	0.092	2.3	20.1	MW	CG	N
0.600	15.24	71849S	4.00	101.6	.416	10.6	37	6.4	1.0	26	38	169	1.85	47.0	0.092	2.3	20.1	SST	CG	N
0.600	15.24	71864	4.00	101.6	.404	10.3	57	9.9	1.2	31	69	307	2.01	51.0	0.098	2.5	20.5	MW	CG	N
0.600	15.24	71864S	4.00	101.6	.404	10.3	48	8.4	.95	24	46	203	2.01	51.0	0.098	2.5	20.5	SST	CG	N
0.609	15.47	2574	.31	7.9	.569	14.5	.56	.10	.21	5.4	.12	.53	.10	2.5	0.020	0.5	4.00	MW	C	Z
0.609	15.47	EE-76	.38	9.5	.485	12.3	130	23	.11	2.7	14	62	.25	6.3	0.062	1.6	3.00	SPR	C	Z
0.609	15.47	AA-52	.41	10.3	.549	13.9	2.4	.42	.24	6.1	.58	2.6	.17	4.2	0.030	0.8	4.50	MW	C	N
0.609	15.47	J-53	.41	10.3	.465	11.8	221	39	.09	2.2	19	86	.22	5.5	0.072	1.8	3.00	SST	CG	N
0.609	15.47	NN-100	.44	11.1	.521	13.2	18	3.1	.24	6.1	4.2	19	.20	5.0	0.044	1.1	3.50	SST	C	N
0.609	15.47	O-73	.44	11.1	.501	12.7	31	5.4	.22	5.6	6.9	31	.22	5.5	0.054	1.4	4.00	SST	CG	N
0.609	15.47	Q-37	.44	11.1	.459	11.7	130	23	.14	3.5	18	80	.30	7.6	0.075	1.9	4.00	SST	CG	N
0.609	15.47	I-100	.44	11.1	.409	10.4	1090	191	.05	1.2	52	229	.30	7.6	0.100	2.5	3.00	SPR	CG	Z
0.609	15.47	J-32	.47	11.9	.569	14.5	1.1	.20	.39	9.9	.44	1.9	.08	2.0	0.020	0.5	3.00	MW	C	N
0.609	15.47	K-41	.50	12.7	.539	13.7	5.7	1.0	.36	9.1	2.1	9.1	.14	3.6	0.035	0.9	4.00	SPR	CG	GI
0.609	15.47	WW-36	.50	12.7	.501	12.7	31	5.4	.23	5.8	7.1	32	.27	6.9	0.054	1.4	4.00	SST	C	N
0.609	15.47	UU-65	.50	12.7	.489	12.4	113	20	.11	2.9	13	57	.18	4.6	0.060	1.5	3.00	SPR	CG	Z
0.609	15.47	B15-26	.56	14.3	.509	12.9	26	4.5	.29	7.3	7.4	33	.20	5.1	0.050	1.3	4.00	SPR	CG	Z
0.609	15.47	10758	.56	14.3	.507	12.9	28	4.9	.28	7.2	7.9	35	.26	6.5	0.051	1.3	4.00	SPR	C	BO
0.609	15.47	B10-58	.63	15.9	.521	13.2	15	2.7	.34	8.6	5.1	23	.17	4.2	0.044	1.1	3.75	SST	CG	N
0.609	15.47	QQ-60	.63	15.9	.475	12.1	73	13	.24	6.2	18	78	.30	7.7	0.067	1.7	4.50	SPR	CG	Z
0.609	15.47	B17-120	.63	15.9	.385	9.8	801	140	.08	2.0	63	280	.45	11.4	0.112	2.8	4.00	SST	CG	N
0.609	15.47	Q-56	.66	16.7	.503	12.8	12	2.0	.29	7.2	3.3	15	.37	9.4	0.053	1.3	7.00	SST	CG	N
0.609	15.47	BB-98	.69	17.4	.545	13.8	1.6	.27	.46	12	.73	3.2	.22	5.7	0.032	0.8	7.00	SPR	CG	N
0.609	15.47	10618	.69	17.4	.537	13.6	6.4	1.1	.47	12	3.0	13	.18	4.6	0.036	0.9	4.00	SPR	C	Z
0.609	15.47	S-1108	.69	17.4	.489	12.4	24	4.3	.33	8.3	8.0	36	.36	9.1	0.060	1.5	6.00	SST	CG	N
0.609	15.47	10009	.69	17.5	.469	11.9	73	13	.26	6.6	19	85	.35	8.9	0.070	1.8	5.00	SPR	CG	Z
0.609	15.47	10953	.72	18.2	.523	13.3	6.8	1.2	.42	11	2.8	13	.30	7.6	0.043	1.1	6.00	SPR	C	N
0.609	15.47	2780	.75	19.1	.539	13.7	3.3	.57	.52	13	1.7	7.6	.23	5.8	0.035	0.9	5.50	HD	C	Z
0.609	15.47	N-30	.75	19.1	.525	13.3	6.2	1.1	.52	13	3.2	14	.23	5.9	0.042	1.1	5.50	SST	CG	N
0.609	15.47	PP-43	.75	19.1	.449	11.4	133	23	.21	5.4	28	125	.40	10.2	0.080	2.0	5.00	SPR	CG	Z
0.609	15.47	12258	.75	19.1	.445	11.3	127	22	.24	6.1	30	134	.45	11.5	0.082	2.1	5.50	SPR	CG	Z
0.609	15.47	2682	.75	19.1	.427	10.8	236	41	.23	5.9	55	244	.46	11.6	0.091	2.3	5.00	MW	CG	Z
0.609	15.47	S-1690	.80	20.3	.469	11.9	64	11	.28	7.1	18	79	.35	8.9	0.070	1.8	5.00	SST	CG	N
0.609	15.47	1769	.81	20.6	.549	13.9	2.4	.42	.65	16	1.6	6.9	.17	4.2	0.030	0.8	4.50	HD	C	Z
0.609	15.47	4146	.81	20.6	.439	11.2	130	23	.26	6.5	34	149	.51	13.0	0.085	2.2	6.00	SPR	CG	Z
0.609	15.47	S-1700	.82	20.9	.465	11.8	72	13	.27	6.8	19	86	.43	11.0	0.072	1.8	5.00	SST	C	N
0.609	15.47	12778	.88	22.2	.509	12.9	18	3.1	.39	9.9	7.0	31	.28	7.0	0.050	1.3	4.50	SST	C	N
0.609	15.47	J-63	.88	22.2	.499	12.7	26	4.5	.38	9.7	9.9	44	.28	7.0	0.055	1.4	5.00	SPR	C	Z
0.609	15.47	11032	.88	22.2	.463	11.8	64	11	.31	8.0	20	90	.41	10.5	0.073	1.9	5.67	SST	CG	N
0.609	15.47	S-266	.91	23.0	.499	12.7	23	4.0	.41	10	9.3	41	.33	8.4	0.055	1.4	5.00	SST	C	N
0.609	15.47	2785	.91	23.0	.497	12.6	28	4.9	.37	9.5	10	46	.34	8.5	0.056	1.4	5.00	SPR	C	Z
0.609	15.47	N-67	.94	23.8	.469	11.9	55	9.6	.35	8.8	19	85	.49	12.4	0.070	1.8	6.00	SPR	C	Z
0.609	15.47	2779	.94	23.8	.427	10.8	164	29	.34	8.5	55	244	.58	14.6	0.091	2.3	6.33	MW	CG	Z
0.609	15.47	11449	1.00	25.4	.563	14.3	.24	.04	.74	19	.17	.77	.26	6.7	0.023	0.6	10.5	MW	C	N
0.609	15.47	L-37	1.00	25.4	.539	13.7	3.8	.67	.73	18	2.8	12	.21	5.3	0.035	0.9	5.00	SPR	C	Z
0.609	15.47	3889	1.00	25.4	.519	13.2	6.6	1.2	.64	16	4.2	19	.36	9.1	0.045	1.1	7.00	SPR	C	Z
0.609	15.47	S-926	1.00	25.4	.519	13.2	7.1	1.3	.73	19	5.2	23	.27	6.9	0.045	1.1	6.00	SST	CG	N
0.609	15.47	Q-33	1.00	25.4	.475	12.1	29	5.0	.50	13	14	64	.50	12.8	0.067	1.7	7.50	SST	CG	N
0.609	15.47	B15-64	1.00	25.4	.467	11.9	59	10	.31	7.9	19	83	.39	9.9	0.071	1.8	5.50	SST	CG	N
0.609	15.47	G-48	1.00	25.4	.465	11.8	55	9.7	.37	9.5	21	92	.47	11.9	0.072	1.8	6.50	HD	CG	N
0.609	15.47	11245	1.03	26.2	.485	12.3	37	6.5	.53	13	19	87	.34	8.7	0.062	1.6	5.50	MW	CG	N
0.609	15.47	S-3209	1.06	27.0	.531	13.5	5.3	.93	.67	17	3.6	16	.23	5.9	0.039	1.0	5.00	SST	C	N
0.609	15.47	12594	1.08	27.4	.301	7.6	2020	354	.08	2.0	158	705	.96	24.5	0.154	3.9	6.25	SPR	CG	GI
0.609	15.47	10611	1.09	27.8	.535	13.6	4.1	.72	.79	20	3.3	15	.24	6.1	0.037	0.9	5.50	SPR	C	Z
0.609	15.47	S-1564	1.11	28.2	.449	11.4	53	9.3	.43	11	23	102	.68	17.3	0.080	2.0	8.50	SST	CG	N
0.609	15.47	S-259	1.13	28.6	.545	13.8	1.4	.24	.87	22	1.2	5.3	.26	6.5	0.032	0.8	7.00	SST	C	N
0.609	15.47	3107	1.13	28.6	.527	13.4	5.9	1.0	.75	19	4.4	20	.28	7.0	0.041	1.0	5.75	SPR	C	Z
0.609	15.47	B-63	1.13	28.6	.513	13.0	6.2	1.1	.69	18	4.3	19	.43	11.0	0.048	1.2	9.00	SPR	CG	Z
0.609	15.47	A12-21	1.13	28.6	.507	12.9	16	2.8	.68	17	11	49	.28	7.1	0.051	1.3	5.50	MW	CG	N
0.609	15.47	S-1332	1.13	28.6	.389	9.9	421	74	.14	3.6	60	266	.61	15.4	0.110	2.8	5.50	SST	CG	N
0.609	15.47	2803	1.16	29.4	.533	13.5	1.8	.32	.70	18	1.3	5.7	.45	11.5	0.038	1.0	11.0	HD	C	Z
0.609	15.47	NN-95	1.16	29.4	.449	11.4	88	15	.32	8.1	28	125	.52	13.2	0.080	2.0	6.50	SPR	CG	GI
0.609	15.47	XX-57	1.19	30.2	.549	13.9	1.5	.26	.99	25	1.5	6.6	.20	5.0	0.030	0.8	5.50	SST	C	N
0.609	15.47	A10-64	1.19	30.2	.509	12.9	7.3	1.3	.74	19	5.4	24	.45	11.4	0.050	1.3	9.00	SPR	CG	Z
0.609	15.47	YY-39	1.19	30.2	.465	11.8	42	7.3	.50	13	21	92	.58	14.6	0.072	1.8	8.00	SPR	CG	Z
0.609	15.47	N-77	1.22	31.0	.485	12.3	28	4.9	.47	12	13	59	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.609	15.47	12508	1.25	31.8	.513	13.0	8.6	1.5	.82	21	7.1	31	.38	9.8	0.048	1.2	7.00	SPR	C	Z
0.609	15.47	11230	1.25	31.8	.513	13.0	8.3	1.5	.85	22	7.1	31	.36	9.3	0.048	1.2	6.75	SPR	C	Z
0.609	15.47	11583	1.25	31.8	.511	13.0	12	2.1	.64	16	7.5	33	.34	8.7	0.049	1.2	6.00	SPR	CG	N
0.609	15.47	3833	1.25	31.8	.475	12.1	24	4.2	.55	14	13	59	.70	17.9	0.067	1.7	9.50	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.609	15.47	3003	1.25	31.8	.429	10.9	123	21	.31	7.9	38	169	.68	17.1	0.090	2.3	7.50	SPR	CG	Z
0.609	15.47	12134	1.25	31.8	.339	8.6	815	143	.14	3.5	113	504	1.01	25.7	0.135	3.4	7.50	SPR	CG	Z
0.609	15.47	B8-49	1.28	32.5	.553	14.0	.80	.14	1.1	28	.87	3.9	.20	5.0	0.028	0.7	7.00	SST	CG	N
0.609	15.47	3537	1.28	32.5	.399	10.1	271	47	.22	5.6	59	264	.80	20.4	0.105	2.7	7.50	SPR	CG	Z
0.609	15.47	B10-19	1.31	33.3	.501	12.7	15	2.6	.62	16	9.3	42	.42	10.6	0.054	1.4	6.75	SPR	C	N
0.609	15.47	3322	1.31	33.3	.459	11.7	37	6.5	.56	14	21	93	.75	19.1	0.075	1.9	10.0	SPR	CG	Z
0.609	15.47	B8-44	1.38	34.9	.469	11.9	44	7.7	.43	11	19	85	.49	12.4	0.070	1.8	7.00	SPR	CG	N
0.609	15.47	RR-48	1.38	34.9	.465	11.8	39	6.9	.49	12	19	86	.54	13.7	0.072	1.8	7.50	SST	CG	N
0.609	15.47	B14-64	1.44	36.5	.501	12.7	14	2.5	.65	17	9.3	42	.38	9.6	0.054	1.4	7.00	SPR	CG	Z
0.609	15.47	S-1192	1.44	36.5	.425	10.8	118	21	.32	8.1	38	167	.69	17.5	0.092	2.3	7.50	SST	CG	N
0.609	15.47	LL-92	1.50	38.1	.527	13.4	3.9	.68	1.1	29	4.4	20	.36	9.1	0.041	1.0	7.75	SPR	C	GI
0.609	15.47	S-1406	1.50	38.1	.521	13.2	3.2	.57	1.1	27	3.4	15	.44	11.2	0.044	1.1	10.0	SST	CG	N
0.609	15.47	S-1311	1.50	38.1	.501	12.7	11	2.0	.78	20	8.8	39	.41	10.3	0.054	1.4	7.50	SST	CG	N
0.609	15.47	S-938	1.50	38.1	.501	12.7	9.6	1.7	.92	23	8.8	39	.46	11.7	0.054	1.4	8.50	SST	CG	N
0.609	15.47	11310	1.50	38.1	.489	12.4	13	2.3	.87	22	12	51	.63	16.0	0.060	1.5	10.5	SPR	CG	Z
0.609	15.47	Q-60	1.50	38.1	.451	11.5	32	5.6	.51	13	16	72	.99	25.1	0.079	2.0	12.5	SST	CG	N
0.609	15.47	S-485	1.53	38.9	.519	13.2	5.2	.91	1.1	27	5.5	24	.34	8.6	0.045	1.1	7.50	SST	CG	N
0.609	15.47	11653	1.53	38.9	.449	11.4	33	5.8	.41	10	14	61	1.12	28.4	0.080	2.0	14.0	SPR	CG	Z
0.609	15.47	YY-30	1.56	39.7	.503	12.8	11	1.9	.80	20	8.8	39	.48	12.1	0.053	1.3	8.00	SPR	C	Z
0.609	15.47	A15-67	1.56	39.7	.403	10.2	147	26	.38	9.7	56	250	1.08	27.5	0.103	2.6	10.5	SPR	CG	Z
0.609	15.47	S-1143	1.63	41.3	.501	12.7	8.3	1.5	1.1	27	8.8	39	.51	13.0	0.054	1.4	9.50	SST	CG	N
0.609	15.47	11511	1.63	41.3	.467	11.9	29	5.1	.68	17	20	88	.78	19.8	0.071	1.8	10.0	SPR	CG	Z
0.609	15.47	10189	1.63	41.3	.427	10.8	71	12	.53	14	38	168	1.09	27.7	0.091	2.3	12.0	SPR	CG	GI
0.609	15.47	10846	1.63	41.3	.369	9.4	323	57	.24	6.0	77	341	1.08	27.4	0.120	3.0	9.00	SST	CG	N
0.609	15.47	S-1213	1.63	41.3	.289	7.3	1293	226	.12	3.1	156	693	1.44	36.6	0.160	4.1	9.00	SST	CG	N
0.609	15.47	B10-15	1.66	42.1	.499	12.7	9.7	1.7	1.0	26	9.9	44	.61	15.4	0.055	1.4	10.0	SPR	C	Z
0.609	15.47	2537	1.69	42.8	.513	13.0	3.9	.69	1.1	27	4.2	19	.62	15.8	0.048	1.2	13.0	SPR	CG	GI
0.609	15.47	S-885	1.69	42.8	.365	9.3	355	62	.23	5.7	80	357	1.07	27.1	0.122	3.1	8.75	SST	CG	N
0.609	15.47	11581	1.75	44.5	.489	12.4	14	2.5	.91	23	13	57	.66	16.8	0.060	1.5	10.0	SPR	CG	N
0.609	15.47	S-494	1.75	44.5	.465	11.8	24	4.2	.80	20	19	86	.79	20.1	0.072	1.8	11.0	SST	CG	N
0.609	15.47	1517	1.75	44.5	.413	10.5	114	20	.43	11	49	216	1.05	26.8	0.098	2.5	10.8	SPR	CG	Z
0.609	15.47	JJ-78	1.81	46.0	.545	13.8	.98	.17	1.5	37	1.4	6.4	.35	8.9	0.032	0.8	10.0	SPR	C	Z
0.609	15.47	11886	1.84	46.8	.445	11.3	49	8.6	.61	16	30	134	.90	22.9	0.082	2.1	11.0	SPR	CG	N
0.609	15.47	11939	1.84	46.8	.409	10.4	91	16	.44	11	40	179	1.40	35.6	0.100	2.5	14.0	SPR	CG	Z
0.609	15.47	12510	1.84	46.8	.483	12.3	16	2.8	1.1	28	18	78	.74	18.8	0.063	1.6	10.8	MW	C	N
0.609	15.47	12256	1.88	47.6	.419	10.6	108	19	.41	10	44	198	.95	24.1	0.095	2.4	10.0	SPR	CG	Z
0.609	15.47	S-24	2.00	50.8	.519	13.2	3.6	.63	1.5	38	5.4	24	.50	12.6	0.045	1.1	10.0	SST	C	N
0.609	15.47	S-277	2.00	50.8	.439	11.2	57	9.9	.55	14	31	140	.85	21.6	0.085	2.2	10.0	SST	CG	N
0.609	15.47	11792	2.00	50.8	.421	10.7	82	14	.53	13	43	192	1.13	28.7	0.094	2.4	12.0	SPR	CG	Z
0.609	15.47	10564	2.03	51.6	.505	12.8	6.2	1.1	1.3	34	8.4	37	.61	15.5	0.052	1.3	11.8	SPR	CG	Z
0.609	15.47	10961	2.13	54.0	.561	14.2	.50	.09	1.9	49	.97	4.3	.19	4.7	0.024	0.6	6.75	MW	C	Z
0.609	15.47	11689	2.25	57.2	.501	12.7	7.9	1.4	1.2	30	9.3	42	.59	15.1	0.054	1.4	11.0	SPR	CG	Z
0.609	15.47	11487	2.25	57.2	.399	10.1	105	18	.57	14	59	264	1.68	42.7	0.105	2.7	15.0	SPR	CG	Z
0.609	15.47	10501	2.28	57.9	.463	11.8	27	4.6	.81	21	22	96	.88	22.3	0.073	1.9	12.0	SPR	CG	Z
0.609	15.47	B14-45	2.34	59.5	.409	10.4	91	16	.57	14	52	229	1.40	35.6	0.100	2.5	14.0	SPR	CG	Z
0.609	15.47	S-74	2.38	60.3	.339	8.6	487	85	.21	5.3	102	454	1.35	34.3	0.135	3.4	10.0	SST	CG	N
0.609	15.47	S-3255	2.41	61.1	.519	13.2	3.9	.68	1.4	36	5.5	24	.43	10.9	0.045	1.1	9.50	SST	CG	N
0.609	15.47	10711	2.41	61.1	.373	9.5	235	41	.34	8.6	80	356	1.42	36.0	0.118	3.0	12.0	SPR	CG	Z
0.609	15.47	VV-56	2.50	63.5	.525	13.3	1.9	.34	1.9	49	3.7	16	.59	14.9	0.042	1.1	13.0	SST	C	N
0.609	15.47	11622	2.50	63.5	.519	13.2	3.3	.58	1.8	45	5.8	26	.54	13.7	0.045	1.1	12.0	SPR	CG	GI
0.609	15.47	B2-63	2.50	63.5	.485	12.3	12	2.1	1.6	41	19	86	.87	22.0	0.062	1.6	13.0	MW	C	Z
0.609	15.47	11249	2.50	63.5	.413	10.5	71	12	.69	17	49	216	1.57	39.8	0.098	2.5	16.0	SPR	CG	Z
0.609	15.47	11657	2.53	64.3	.399	10.1	171	30	.35	8.8	59	264	1.05	26.7	0.105	2.7	10.0	SPR	CG	Z
0.609	15.47	11958	2.59	65.9	.531	13.5	1.0	.17	1.8	45	1.8	7.9	.82	20.8	0.039	1.0	20.0	SPR	C	Z
0.609	15.47	11790	2.59	65.9	.461	11.7	28	4.9	.80	20	22	100	.89	22.6	0.074	1.9	12.0	SPR	CG	Z
0.609	15.47	WW-50	2.75	69.9	.529	13.4	2.2	.38	1.8	45	3.9	17	.44	11.2	0.040	1.0	10.0	SST	C	N
0.609	15.47	4105	2.75	69.9	.527	13.4	1.8	.32	2.1	54	3.9	18	.62	15.6	0.041	1.0	14.0	SPR	C	Z
0.609	15.47	2867	2.75	69.9	.471	12.0	16	2.8	1.7	42	27	119	1.03	26.1	0.069	1.8	15.0	MW	CG	Z
0.609	15.47	11840	2.78	70.6	.467	11.9	21	3.7	.93	24	20	88	.92	23.4	0.071	1.8	13.0	SPR	CG	Z
0.609	15.47	12142	2.88	73.0	.525	13.3	1.1	.19	1.8	45	1.9	8.5	1.09	27.7	0.042	1.1	25.0	SPR	C	Z
0.609	15.47	3660	3.25	82.6	.525	13.3	2.5	.44	1.9	48	4.8	21	.49	12.5	0.042	1.1	11.8	SPR	CG	Z
0.609	15.47	10769	3.25	82.6	.485	12.3	11	1.9	1.3	32	14	62	.85	21.7	0.062	1.6	13.8	SPR	CG	GI
0.609	15.47	11556	3.38	85.7	.559	14.2	.28	.05	3.1	77	.86	3.8	.33	8.3	0.025	0.6	12.0	MW	C	Z
0.609	15.47	2710	3.50	88.9	.513	13.0	2.7	.47	2.6	66	7.0	31	.91	23.2	0.048	1.2	18.0	HD	C	Z
0.609	15.47	S-215	3.50	88.9	.485	12.3	7.1	1.2	1.9	48	13	59	1.12	28.3	0.062	1.6	18.0	SST	CG	N
0.609	15.47	10863	3.50	88.9	.427	10.8	43	7.5	.91	23	39	175	1.68	42.8	0.091	2.3	18.5	SPR	CG	N
0.609	15.47	3199	3.53	89.7	.513	13.0	2.5	.45	2.6	65	6.5	29	.96	24.4	0.048	1.2	19.0	SPR	C	Z
0.609	15.47	3280	3.75	95.3	.465	11.8	11	1.9	1.9	49	20	90	1.84	46.6	0.072	1.8	25.5	HD	CG	GI
0.609	15.47	TT-65	3.75	95.3	.427	10.8	28	4.9	1.3	33	36	162	2.18	55.5	0.091	2.3	24.0	SST	CG	N
0.609	15.47	3311	4.13	104.8	.399	10.1	80	14	.74	19	59	264	2.10	53.3	0.105	2.7	19.0	SPR	CG	Z
0.609	15.47	S-61	4.38	111.1	.439	11.2	15	2.6	1.6	41	24	107	2.76	70.2	0.085	2.2	32.5	SST	CG	N
0.609	15.47	2796	4.50	114.3	.415	10.5	36	6.4	1.8	45	65	289	2.72	69.0	0.097	2.5	28.0	MW	CG	Z
0.609	15.47	3162	4.50	114.3	.415	10.5	40	6.9	1.2	30	47	210	2.52	64.1	0.097	2.5	26.0	SPR	CG	Z
0.609	15.47	11585	4.53	115.1	.421	10.7	34	6.0	1.3	32	43	192	2.54	64.5	0.094	2.4	26.0	SPR	CG	N
0.609	15.47	1811	4.88	123.8	.427	10.8	28	4.8	2.0	51	55	244	2.62	66.4	0.091	2.3	27.8	MW	C	Z
0.609	15.47	3805	5.00	127.0	.485	12.3	4.3	.76	3.0	75	13	57	2.05	52.0	0.062	1.6	32.0	HD	C	Z
0.609	15.47	12323	7.34	186.5	.467	11.9	4.6	.81	3.6	91	16	73	3.76	95.6	0.071	1.8	53.0	SPR	CG	Z
0.609	15.47	S-228	8.50	215.9	.497	12.6	1.7	.30	5.8	147	9.8	44	2.58	65.4	0.056	1.4	45.0	SST	C	N
0.625	15.88	S-175	.28	7.1	.501	12.7	106	18	.10	2.4	10	45	.19	4.7	0.062	1.6	3.00	SST	CG	N
0.625	15.88	S-391	.38	9.5	.567	14.4	3.3	.59	.25	6.4	.84	3.7	.12	3.1	0.029	0.7	3.25	SST	C	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.625	15.88	H-24	.41	10.3	.515	13.1	62	11	.15	3.7	9.0	40	.17	4.2	0.055	1.4	3.00	SST	CG	N
0.625	15.88	K-31	.44	11.1	.529	13.4	12	2.0	.20	5.0	2.3	10	.24	6.1	0.048	1.2	5.00	SST	CG	N
0.625	15.88	PP-47	.44	11.1	.465	11.8	364	64	.08	1.9	27	122	.24	6.1	0.080	2.0	3.00	SPR	CG	Z
0.625	15.88	3506	.53	13.5	.569	14.5	4.2	.73	.42	11	1.7	7.7	.11	2.8	0.028	0.7	3.00	MW	C	Z
0.625	15.88	2511	.53	13.5	.517	13.1	33	5.7	.26	6.6	8.6	38	.27	6.9	0.054	1.4	4.00	HD	C	GI
0.625	15.88	B-97	.53	13.5	.481	12.2	131	23	.15	3.9	20	90	.27	6.9	0.072	1.8	3.75	HD	CG	N
0.625	15.88	11369	.59	15.1	.571	14.5	.67	.12	.38	9.7	.26	1.1	.21	5.3	0.027	0.7	6.75	SST	C	N
0.625	15.88	4320	.63	15.9	.563	14.3	4.2	.74	.49	12	2.1	9.1	.14	3.5	0.031	0.8	3.50	MW	C	Z
0.625	15.88	10123	.63	15.9	.497	12.6	39	6.8	.27	6.9	11	47	.35	8.9	0.064	1.6	5.50	SPR	CG	Z
0.625	15.88	B9-39	.66	16.7	.521	13.2	19	3.3	.40	10	7.4	33	.26	6.6	0.052	1.3	5.00	SPR	CG	N
0.625	15.88	XX-56	.69	17.4	.545	13.8	8.0	1.4	.47	12	3.8	17	.20	5.1	0.040	1.0	4.00	SST	C	N
0.625	15.88	A9-66	.72	18.2	.561	14.2	2.3	.41	.57	14	1.3	5.9	.15	3.8	0.032	0.8	4.75	SST	CG	N
0.625	15.88	522	.75	19.1	.543	13.8	10	1.8	.42	11	4.3	19	.21	5.2	0.041	1.0	4.00	HD	C	Z
0.625	15.88	918	.75	19.1	.543	13.8	6.8	1.2	.50	13	3.4	15	.25	6.2	0.041	1.0	5.00	HD	C	Z
0.625	15.88	CC-24	.75	19.1	.525	13.3	16	2.8	.46	12	7.3	32	.25	6.4	0.050	1.3	5.00	SPR	CG	Z
0.625	15.88	S-766	.75	19.1	.515	13.1	27	4.8	.33	8.4	9.0	40	.29	7.3	0.055	1.4	4.25	SST	C	N
0.625	15.88	S-286	.75	19.1	.481	12.2	50	8.7	.32	8.1	16	70	.43	11.0	0.072	1.8	6.00	SST	CG	N
0.625	15.88	10279	.75	19.1	.465	11.8	182	32	.15	3.8	27	122	.32	8.1	0.080	2.0	4.00	SPR	CG	Z
0.625	15.88	4205	.75	19.1	.415	10.5	414	73	.14	3.6	58	258	.53	13.3	0.105	2.7	5.00	SPR	CG	Z
0.625	15.88	S-58	.78	19.8	.501	12.7	69	12	.19	4.7	13	57	.22	5.5	0.062	1.6	3.50	SST	CG	N
0.625	15.88	K-59	.78	19.8	.445	11.3	154	27	.24	6.1	37	165	.54	13.7	0.090	2.3	6.00	SPR	CG	N
0.625	15.88	A11-43	.81	20.6	.519	13.2	23	4.0	.35	8.9	8.1	36	.23	5.8	0.053	1.3	4.33	SST	CG	N
0.625	15.88	S-826	.81	20.6	.425	10.8	247	43	.19	4.8	47	208	.55	14.0	0.100	2.5	5.50	SST	CG	N
0.625	15.88	10888	.84	21.4	.589	15.0	.17	.03	.73	18	.12	.55	.12	3.0	0.018	0.5	5.50	SST	C	N
0.625	15.88	S-68	.88	22.2	.549	13.9	4.7	.82	.69	17	3.2	14	.18	4.6	0.038	1.0	4.75	SST	CG	N
0.625	15.88	2831	.88	22.2	.531	13.5	7.3	1.3	.50	13	3.6	16	.38	9.6	0.047	1.2	7.00	HD	C	Z
0.625	15.88	B12-58	.88	22.2	.515	13.1	14	2.5	.49	12	7.0	31	.39	9.8	0.055	1.4	7.00	SPR	CG	Z
0.625	15.88	3911	.88	22.2	.501	12.7	30	5.2	.46	12	14	61	.37	9.4	0.062	1.6	6.00	HD	CG	Z
0.625	15.88	3192	.88	22.2	.439	11.2	238	42	.17	4.4	41	182	.47	11.8	0.093	2.4	5.00	SPR	CG	Z
0.625	15.88	10982	.88	22.2	.431	10.9	219	38	.20	5.0	43	190	.53	13.6	0.097	2.5	5.50	SST	CG	N
0.625	15.88	A9-69	.91	23.0	.543	13.8	7.4	1.3	.58	15	4.3	19	.19	4.9	0.041	1.0	4.75	SPR	CG	Z
0.625	15.88	W-30	.94	23.8	.551	14.0	1.5	.26	.49	13	.73	3.2	.44	11.3	0.037	0.9	11.0	SPR	C	Z
0.625	15.88	AA-75	.94	23.8	.505	12.8	28	4.8	.45	11	12	55	.35	8.8	0.060	1.5	5.75	SPR	CG	N
0.625	15.88	3129	.97	24.6	.563	14.3	2.1	.37	.78	20	1.7	7.3	.19	4.7	0.031	0.8	5.00	MW	C	Z
0.625	15.88	3031	1.00	25.4	.539	13.7	5.5	.97	.68	17	3.8	17	.32	8.2	0.043	1.1	6.50	SPR	C	Z
0.625	15.88	2799	1.00	25.4	.533	13.5	13	2.3	.46	12	6.1	27	.21	5.3	0.046	1.2	4.50	SPR	CG	GI
0.625	15.88	B11-59	1.00	25.4	.529	13.4	11	2.0	.61	15	6.9	31	.26	6.7	0.048	1.2	5.50	SPR	CG	N
0.625	15.88	11456	1.00	25.4	.521	13.2	14	2.4	.58	15	8.1	36	.36	9.2	0.052	1.3	6.00	SPR	C	Z
0.625	15.88	N-53	1.00	25.4	.517	13.1	13	2.3	.62	16	8.2	36	.38	9.6	0.054	1.4	7.00	SPR	CG	GI
0.625	15.88	S-767	1.00	25.4	.515	13.1	19	3.3	.48	12	9.0	40	.34	8.7	0.055	1.4	5.25	SST	C	N
0.625	15.88	12121	1.00	25.4	.509	12.9	11	2.0	.36	9.2	4.0	18	.64	16.2	0.058	1.5	10.0	SPR	C	Z
0.625	15.88	S-770	1.00	25.4	.499	12.7	32	5.6	.43	11	14	60	.41	10.4	0.063	1.6	5.50	SST	C	N
0.625	15.88	EE-40	1.00	25.4	.485	12.3	50	8.8	.37	9.4	19	83	.42	10.7	0.070	1.8	6.00	SPR	CG	N
0.625	15.88	S-367	1.00	25.4	.481	12.2	50	8.7	.38	9.7	19	84	.43	11.0	0.072	1.8	6.00	SST	CG	N
0.625	15.88	944	1.00	25.4	.465	11.8	121	21	.23	5.8	27	122	.48	12.2	0.080	2.0	5.00	HD	C	Z
0.625	15.88	2745	1.00	25.4	.455	11.6	159	28	.29	7.3	46	204	.43	10.8	0.085	2.2	5.00	MW	CG	Z
0.625	15.88	10354	1.03	26.2	.471	12.0	51	9.0	.42	11	21	94	.62	15.6	0.077	2.0	8.00	SPR	CG	Z
0.625	15.88	BB-88	1.06	27.0	.547	13.9	3.3	.58	.79	20	2.6	12	.27	6.9	0.039	1.0	7.00	SPR	CG	Z
0.625	15.88	B15-24	1.06	27.0	.535	13.6	10	1.8	.56	14	5.7	25	.23	5.7	0.045	1.1	5.00	SPR	CG	N
0.625	15.88	S-1451	1.06	27.0	.509	12.9	14	2.5	.63	16	8.8	39	.44	11.0	0.058	1.5	7.50	SST	CG	N
0.625	15.88	L-64	1.06	27.0	.491	12.5	28	4.9	.53	13	15	65	.54	13.6	0.067	1.7	8.00	SPR	CG	N
0.625	15.88	12289	1.06	27.0	.435	11.0	157	28	.28	7.0	43	193	.67	16.9	0.095	2.4	7.00	SPR	CG	GI
0.625	15.88	3856	1.06	27.0	.371	9.4	757	133	.13	3.2	96	429	.76	19.4	0.127	3.2	6.00	SPR	CG	Z
0.625	15.88	12469	1.09	27.8	.495	12.6	27	4.7	.59	15	16	70	.49	12.4	0.065	1.7	7.50	SPR	CG	Z
0.625	15.88	10747	1.09	27.8	.415	10.5	220	39	.24	6.2	54	239	.74	18.7	0.105	2.7	7.00	SST	CG	N
0.625	15.88	4317	1.13	28.6	.575	14.6	.58	.10	.94	24	.54	2.4	.19	4.8	0.025	0.6	6.50	MW	C	T
0.625	15.88	S-1588	1.13	28.6	.507	12.9	14	2.5	.65	17	9.3	41	.47	12.0	0.059	1.5	8.00	SST	CG	N
0.625	15.88	S-890	1.13	28.6	.491	12.5	26	4.6	.61	16	16	72	.50	12.8	0.067	1.7	7.50	SST	CG	N
0.625	15.88	S-1423	1.13	28.6	.481	12.2	33	5.8	.55	14	18	81	.58	14.6	0.072	1.8	8.00	SST	CG	N
0.625	15.88	12190	1.13	28.6	.425	10.8	136	24	.28	7.0	37	166	.85	21.6	0.100	2.5	8.50	SPR	CG	Z
0.625	15.88	L-50	1.13	28.6	.415	10.5	355	62	.16	4.2	58	258	.58	14.7	0.105	2.7	5.50	SPR	CG	Z
0.625	15.88	2972	1.16	29.4	.551	14.0	1.4	.24	.73	19	1.0	4.5	.43	10.8	0.037	0.9	11.5	SPR	CG	Z
0.625	15.88	12137	1.16	29.4	.525	13.3	12	2.1	.61	16	7.3	32	.30	7.6	0.050	1.3	6.00	SPR	CG	Z
0.625	15.88	3980	1.16	29.4	.329	8.4	1338	234	.11	2.7	143	637	1.00	25.4	0.148	3.8	6.75	SPR	CG	N
0.625	15.88	S-117	1.19	30.2	.561	14.2	1.3	.22	.93	24	1.2	5.3	.26	6.5	0.032	0.8	7.00	SST	C	N
0.625	15.88	10750	1.19	30.2	.537	13.6	5.5	.96	.88	22	4.8	22	.31	7.8	0.044	1.1	7.00	SPR	CG	Z
0.625	15.88	B15-58	1.19	30.2	.537	13.6	4.2	.74	.81	21	3.4	15	.37	9.5	0.044	1.1	8.50	SPR	CG	Z
0.625	15.88	NN-52	1.19	30.2	.485	12.3	45	7.8	.39	9.9	17	77	.42	10.7	0.070	1.8	6.00	SST	CG	N
0.625	15.88	S-1055	1.19	30.2	.481	12.2	29	5.2	.56	14	16	73	.63	16.0	0.072	1.8	8.75	SST	CG	N
0.625	15.88	B11-60	1.22	31.0	.501	12.7	30	5.2	.46	12	14	61	.37	9.4	0.062	1.6	6.00	SPR	CG	Z
0.625	15.88	12267	1.25	31.8	.545	13.8	6.1	1.1	.65	17	4.0	18	.20	5.1	0.040	1.0	5.00	SPR	CG	Z
0.625	15.88	2757	1.25	31.8	.523	13.3	10	1.8	.84	21	8.7	39	.41	10.4	0.051	1.3	7.00	MW	C	Z
0.625	15.88	10050	1.25	31.8	.515	13.1	14	2.4	.71	18	9.6	43	.40	10.1	0.055	1.4	7.25	SPR	CG	Z
0.625	15.88	S-768	1.25	31.8	.515	13.1	15	2.5	.62	16	9.0	40	.40	10.1	0.055	1.4	6.25	SST	C	N
0.625	15.88	1915	1.25	31.8	.511	13.0	19	3.4	.55	14	11	48	.41	10.5	0.057	1.4	6.25	SPR	C	Z
0.625	15.88	1909	1.25	31.8	.501	12.7	24	4.2	.58	15	14	61	.43	11.0	0.062	1.6	7.00	SPR	CG	Z
0.625	15.88	S-771	1.25	31.8	.499	12.7	23	4.1	.58	15	14	60	.49	12.4	0.063	1.6	6.75	SST	C	N
0.625	15.88	10121	1.25	31.8	.497	12.6	27	4.8	.55	14	15	67	.51	13.0	0.064	1.6	7.00	HD	C	Z
0.625	15.88	12768	1.25	31.8	.475	12.1	61	11	.52	13	32	141	.56	14.3	0.075	1.9	6.50	MW	C	Z
0.625	15.88	10620	1.25	31.8	.443	11.3	118	21	.33	8.3	38	171	.68	17.3	0.091	2.3	7.50	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.625	15.88	3137	1.25	31.8	.431	10.9	173	30	.27	6.8	46	205	.68	17.2	0.097	2.5	7.00	SPR	CG	Z
0.625	15.88	A10-41	1.25	31.8	.349	8.9	860	151	.14	3.5	118	525	1.00	25.4	0.138	3.5	7.25	SPR	CG	Z
0.625	15.88	B6-14	1.28	32.5	.487	12.4	38	6.6	.49	13	19	83	.48	12.3	0.069	1.8	7.00	SPR	CG	N
0.625	15.88	B18-146	1.28	32.5	.437	11.1	150	26	.28	7.1	42	188	.66	16.7	0.094	2.4	7.00	SPR	CG	GI
0.625	15.88	B11-64	1.31	33.3	.501	12.7	40	6.9	.35	8.8	14	61	.31	7.9	0.062	1.6	5.00	SPR	CG	N
0.625	15.88	11838	1.34	34.1	.517	13.1	11	1.9	.83	21	9.1	41	.43	11.0	0.054	1.4	8.00	SPR	CG	Z
0.625	15.88	10632	1.38	34.9	.481	12.2	29	5.2	.67	17	20	88	.70	17.8	0.072	1.8	9.75	SPR	CG	Z
0.625	15.88	3818	1.38	34.9	.431	10.9	133	23	.35	8.8	46	205	.82	20.9	0.097	2.5	8.50	SPR	CG	Z
0.625	15.88	G-41	1.38	34.9	.415	10.5	178	31	.33	8.3	58	258	.95	24.0	0.105	2.7	9.00	SPR	CG	N
0.625	15.88	3879	1.44	36.5	.551	14.0	1.5	.26	.99	25	1.5	6.5	.44	11.3	0.037	0.9	11.0	SPR	C	Z
0.625	15.88	A10-59	1.44	36.5	.481	12.2	29	5.0	.71	18	20	90	.72	18.3	0.072	1.8	10.0	SPR	CG	Z
0.625	15.88	S-1225	1.44	36.5	.455	11.6	64	11	.48	12	31	137	.72	18.4	0.085	2.2	8.50	SST	CG	N
0.625	15.88	10452	1.47	37.3	.477	12.1	32	5.6	.68	17	22	97	.74	18.8	0.074	1.9	10.0	SPR	CG	Z
0.625	15.88	11473	1.50	38.1	.555	14.1	1.4	.25	1.1	29	1.7	7.4	.36	9.1	0.035	0.9	9.25	MW	C	T
0.625	15.88	523	1.50	38.1	.543	13.8	3.4	.60	1.1	29	3.8	17	.37	9.4	0.041	1.0	8.00	HD	C	Z
0.625	15.88	S-1186	1.50	38.1	.531	13.5	5.3	.92	1.1	27	5.7	25	.42	10.7	0.047	1.2	8.00	SST	C	N
0.625	15.88	4213	1.50	38.1	.529	13.4	6.9	1.2	1.0	25	6.9	31	.42	10.7	0.048	1.2	7.75	SPR	C	Z
0.625	15.88	S-769	1.50	38.1	.515	13.1	12	2.1	.77	20	9.0	40	.45	11.5	0.055	1.4	7.25	SST	C	N
0.625	15.88	S-772	1.50	38.1	.499	12.7	19	3.4	.70	18	14	60	.55	14.0	0.063	1.6	7.75	SST	C	N
0.625	15.88	S-773	1.50	38.1	.481	12.2	32	5.6	.59	15	19	84	.67	16.9	0.072	1.8	8.25	SST	C	N
0.625	15.88	XX-58	1.50	38.1	.481	12.2	28	5.0	.67	17	19	84	.65	16.5	0.072	1.8	9.00	SST	CG	N
0.625	15.88	11304	1.50	38.1	.451	11.5	82	14	.40	10	33	146	.76	19.3	0.087	2.2	7.75	SST	C	N
0.625	15.88	11445	1.50	38.1	.435	11.0	157	28	.39	9.8	61	270	.67	16.9	0.095	2.4	7.00	MW	CG	Z
0.625	15.88	3917	1.63	41.3	.529	13.4	3.6	.63	.95	24	3.4	15	.67	17.1	0.048	1.2	13.0	HD	C	Z
0.625	15.88	3252	1.63	41.3	.465	11.8	40	7.1	.68	17	27	122	.88	22.4	0.080	2.0	11.0	HD	CG	Z
0.625	15.88	11688	1.69	42.8	.531	13.5	3.5	.61	1.1	28	3.8	17	.59	14.9	0.047	1.2	12.5	SPR	CG	Z
0.625	15.88	4128	1.69	42.8	.445	11.3	103	18	.36	9.2	37	165	.81	20.6	0.090	2.3	8.00	SPR	C	Z
0.625	15.88	3887	1.69	42.8	.355	9.0	541	95	.21	5.2	111	494	1.28	32.6	0.135	3.4	9.50	SPR	CG	Z
0.625	15.88	4125	1.75	44.5	.481	12.2	33	5.7	.62	16	20	90	.72	18.3	0.072	1.8	9.00	SPR	C	Z
0.625	15.88	S-774	1.75	44.5	.481	12.2	26	4.6	.71	18	19	84	.76	19.2	0.072	1.8	9.50	SST	C	N
0.625	15.88	882	1.75	44.5	.443	11.3	72	13	.53	14	38	171	1.09	27.7	0.091	2.3	11.0	HD	C	Z
0.625	15.88	S-3259	1.78	45.2	.565	14.4	1.2	.21	1.4	34	1.7	7.4	.18	4.6	0.030	0.8	6.00	SST	CG	N
0.625	15.88	B18-134	1.78	45.2	.329	8.4	794	139	.15	3.9	122	541	1.63	41.4	0.148	3.8	10.0	SPR	CG	N
0.625	15.88	S-1568	1.81	46.0	.497	12.6	15	2.7	.93	24	14	63	.64	16.3	0.064	1.6	10.0	SST	CG	N
0.625	15.88	11124	1.81	46.0	.443	11.3	66	12	.58	15	38	171	1.16	29.5	0.091	2.3	11.8	HD	C	Z
0.625	15.88	3209	1.84	46.8	.443	11.3	65	11	.59	15	38	171	1.09	27.7	0.091	2.3	12.0	SPR	CG	Z
0.625	15.88	4295	1.88	47.6	.531	13.5	8.1	1.4	.80	20	6.5	29	.31	7.8	0.047	1.2	6.50	SPR	CG	Z
0.625	15.88	B32-32	1.91	48.4	.483	12.3	19	3.3	.95	24	18	81	.85	21.6	0.071	1.8	12.0	SST	CG	N
0.625	15.88	11852	2.00	50.8	.567	14.4	.87	.15	1.8	45	1.6	6.9	.22	5.5	0.029	0.7	7.50	MW	CG	N
0.625	15.88	S-775	2.00	50.8	.481	12.2	23	4.0	.83	21	19	84	.85	21.5	0.072	1.8	10.8	SST	C	N
0.625	15.88	B8-28	2.00	50.8	.475	12.1	29	5.0	.79	20	23	101	.86	21.9	0.075	1.9	11.5	SPR	CG	N
0.625	15.88	12272	2.09	53.2	.501	12.7	13	2.3	1.0	26	14	61	.68	17.3	0.062	1.6	11.0	SPR	CG	Z
0.625	15.88	11767	2.09	53.2	.465	11.8	33	5.8	.83	21	27	122	1.04	26.4	0.080	2.0	13.0	SPR	CG	Z
0.625	15.88	11295	2.19	55.6	.459	11.7	37	6.5	.82	21	31	136	1.12	28.5	0.083	2.1	13.5	SPR	CG	Z
0.625	15.88	B18-153	2.22	56.4	.425	10.8	81	14	.62	16	50	224	1.43	36.2	0.100	2.5	14.3	SPR	CG	Z
0.625	15.88	S-1470	2.25	57.2	.559	14.2	1.4	.25	1.5	39	2.2	9.8	.23	5.9	0.033	0.8	7.00	SST	CG	N
0.625	15.88	4260	2.25	57.2	.501	12.7	13	2.3	1.0	26	14	61	.74	18.9	0.062	1.6	11.0	SPR	C	Z
0.625	15.88	916	2.25	57.2	.481	12.2	20	3.5	1.0	26	20	90	1.04	26.5	0.072	1.8	13.5	HD	C	Z
0.625	15.88	2672	2.25	57.2	.415	10.5	113	20	.51	13	58	258	1.37	34.7	0.105	2.7	13.0	SPR	CG	Z
0.625	15.88	11438	2.25	57.2	.401	10.2	134	23	.50	13	68	300	1.62	41.2	0.112	2.8	14.5	SPR	CG	Z
0.625	15.88	S-809	2.31	58.7	.355	9.0	483	85	.21	5.3	100	445	1.37	34.8	0.135	3.4	10.0	SST	CG	N
0.625	15.88	47	2.38	60.3	.415	10.5	104	18	.56	14	58	258	1.47	37.3	0.105	2.7	14.0	HD	CG	Z
0.625	15.88	Q-42	2.44	61.9	.483	12.3	16	2.8	1.2	31	19	86	1.17	29.8	0.071	1.8	15.5	SPR	C	N
0.625	15.88	2512	2.44	61.9	.415	10.5	124	22	.65	17	81	361	1.37	34.7	0.105	2.7	12.0	MW	C	Z
0.625	15.88	2838	2.44	61.9	.381	9.7	209	37	.58	15	120	535	1.71	43.4	0.122	3.1	14.0	MW	CG	Z
0.625	15.88	S-776	2.50	63.5	.481	12.2	18	3.1	1.1	27	19	84	1.03	26.1	0.072	1.8	13.3	SST	C	N
0.625	15.88	1787	2.50	63.5	.465	11.8	29	5.1	.94	24	27	122	1.24	31.5	0.080	2.0	14.5	SPR	C	Z
0.625	15.88	23	2.50	63.5	.465	11.8	32	5.7	.85	22	27	122	1.14	29.0	0.080	2.0	13.3	HD	C	Z
0.625	15.88	12279	2.50	63.5	.453	11.5	36	6.3	.95	24	34	151	1.38	35.0	0.086	2.2	16.0	SPR	CG	Z
0.625	15.88	S-1371	2.50	63.5	.329	8.4	460	81	.28	7.1	129	574	2.07	52.6	0.148	3.8	14.0	SST	CG	N
0.625	15.88	S-871	2.53	64.3	.463	11.8	32	5.6	.84	21	27	119	1.01	25.7	0.081	2.1	12.5	SST	CG	N
0.625	15.88	1791	2.53	64.3	.329	8.4	508	89	.39	9.8	196	871	2.15	54.5	0.148	3.8	14.5	MW	CG	Z
0.625	15.88	11654	2.56	65.1	.495	12.6	12	2.1	1.3	33	16	70	.98	24.8	0.065	1.7	14.0	SPR	C	Z
0.625	15.88	S-91	2.63	66.7	.375	9.5	212	37	.40	10	84	374	1.69	42.9	0.125	3.2	13.5	SST	CG	N
0.625	15.88	21	2.75	69.9	.517	13.1	5.8	1.0	1.6	40	9.1	41	.77	19.6	0.054	1.4	13.3	HD	C	Z
0.625	15.88	1607	2.75	69.9	.515	13.1	4.4	.78	1.7	43	7.6	34	1.05	26.5	0.055	1.4	18.0	SPR	C	Z
0.625	15.88	3246	2.75	69.9	.481	12.2	18	3.1	1.1	29	20	90	1.08	27.4	0.072	1.8	15.0	SPR	CG	Z
0.625	15.88	51	2.75	69.9	.385	9.8	162	28	.51	13	82	366	1.95	49.5	0.120	3.0	16.3	HD	CG	Z
0.625	15.88	B9-65	2.81	71.4	.415	10.5	72	13	.74	19	54	239	1.81	46.0	0.105	2.7	17.3	SST	CG	N
0.625	15.88	11181	2.88	73.0	.529	13.4	3.6	.63	1.9	48	6.9	31	.62	15.8	0.048	1.2	13.0	SPR	CG	Z
0.625	15.88	12135	2.88	73.0	.475	12.1	20	3.4	1.2	30	23	101	1.20	30.5	0.075	1.9	16.0	SPR	CG	Z
0.625	15.88	S-1681	3.00	76.2	.565	14.4	.80	.14	2.1	53	1.7	7.4	.24	6.1	0.030	0.8	8.00	SST	CG	N
0.625	15.88	1906	3.00	76.2	.531	13.5	4.0	.71	1.6	41	6.5	29	.56	14.3	0.047	1.2	11.0	SPR	C	Z
0.625	15.88	11340	3.00	76.2	.501	12.7	9.2	1.6	1.5	38	14	61	.99	25.2	0.062	1.6	15.0	HD	C	Z
0.625	15.88	19	3.00	76.2	.465	11.8	26	4.6	1.0	26	27	122	1.34	34.0	0.080	2.0	15.8	HD	C	Z
0.625	15.88	3499	3.00	76.2	.465	11.8	24	4.2	1.1	29	27	122	1.44	36.6	0.080	2.0	17.0	HD	C	Z
0.625	15.88	3694	3.13	79.4	.513	13.0	5.9	1.0	1.7	44	10	45	.84	21.3	0.056	1.4	15.0	SPR	CG	Z
0.625	15.88	3797	3.13	79.4	.395	10.0	118	21	.61	16	73	324	2.07	52.6	0.115	2.9	18.0	SPR	CG	Z
0.625	15.88	2528	3.19	81.0	.461	11.7	29	5.1	1.4	36	41	184	1.31	33.3	0.082	2.1	16.0	MW	CG	Z
0.625	15.88	S-3132	3.25	82.6	.415	10.5	64	11	.85	21	54	239	2.00	50.7	0.105	2.7	19.0	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.625	15.88	2596	3.50	88.9	.573	14.6	.31	.05	3.2	80	.97	4.3	.34	8.6	0.026	0.7	12.0	MW	C	T
0.625	15.88	4156	3.50	88.9	.531	13.5	3.8	.67	1.7	43	6.5	29	.59	14.9	0.047	1.2	11.5	HD	C	GI
0.625	15.88	2820	3.50	88.9	.399	10.1	97	17	1.0	25	97	430	2.26	57.4	0.113	2.9	20.0	MW	CG	Z
0.625	15.88	12107	3.50	88.9	.389	9.9	122	21	.64	16	78	349	2.30	58.4	0.118	3.0	19.5	SPR	CG	Z
0.625	15.88	S-1037	3.75	95.3	.375	9.5	122	21	.69	18	84	374	2.75	69.9	0.125	3.2	22.0	SST	CG	N
0.625	15.88	12314	4.00	101.6	.515	13.1	5.9	1.0	1.6	41	9.6	43	.83	21.0	0.055	1.4	14.0	HD	C	Z
0.625	15.88	S-364	4.19	106.4	.465	11.8	18	3.1	1.5	37	26	114	1.60	40.6	0.080	2.0	20.0	SST	CG	N
0.625	15.88	S-419	4.50	114.3	.449	11.4	16	2.8	1.6	42	26	116	2.86	72.6	0.088	2.2	32.5	SST	CG	N
0.625	15.88	925	4.50	114.3	.415	10.5	65	11	.89	23	58	258	2.31	58.7	0.105	2.7	21.0	HD	C	Z
0.625	15.88	1899	4.81	122.2	.449	11.4	24	4.3	2.1	53	51	225	2.18	55.3	0.088	2.2	24.8	MW	CG	Z
0.625	15.88	12419	4.84	123.0	.443	11.3	27	4.7	1.4	36	38	171	2.37	60.1	0.091	2.3	26.0	SPR	CG	N
0.625	15.88	12441	4.94	125.4	.441	11.2	27	4.7	1.5	38	40	176	2.62	66.6	0.092	2.3	27.5	SPR	C	N
0.625	15.88	874	5.00	127.0	.443	11.3	24	4.2	1.6	41	38	171	2.64	67.0	0.091	2.3	29.0	HD	CG	Z
0.625	15.88	3803	5.00	127.0	.441	11.2	25	4.4	1.6	40	40	176	2.76	70.1	0.092	2.3	29.0	SPR	CG	Z
0.625	15.88	870	5.00	127.0	.415	10.5	41	7.1	1.4	36	58	258	3.43	87.1	0.105	2.7	32.7	HD	CG	Z
0.625	15.88	1657	6.00	152.4	.517	13.1	2.8	.49	3.2	82	9.1	41	1.42	36.0	0.054	1.4	25.3	SPR	C	Z
0.625	15.88	3334	6.00	152.4	.481	12.2	5.8	1.0	3.0	77	17	77	2.99	75.9	0.072	1.8	41.5	HD	CG	GI
0.625	15.88	1944	7.00	177.8	.455	11.6	15	2.6	2.2	56	33	146	2.98	75.6	0.085	2.2	34.0	SPR	C	Z
0.625	15.88	888	9.00	228.6	.465	11.8	8.4	1.5	3.3	83	27	122	3.72	94.5	0.080	2.0	45.5	HD	C	Z
0.625	15.88	10542	9.50	241.3	.477	12.1	6.1	1.1	3.6	91	22	97	3.33	84.6	0.074	1.9	44.0	SPR	C	Z
0.625	15.88	10150	9.75	247.7	.443	11.3	15	2.5	2.6	67	38	171	4.32	109.8	0.091	2.3	46.5	SPR	C	Z
0.625	15.88	4143	11.9	301.6	.481	12.2	4.0	.70	5.0	128	20	90	4.32	109.7	0.072	1.8	59.0	HD	C	Z
0.625	15.88	881	12.0	304.8	.501	12.7	2.1	.36	6.7	169	14	61	3.78	96.1	0.062	1.6	60.0	HD	C	Z
0.625	15.88	878	12.0	304.8	.481	12.2	3.5	.62	5.7	145	20	90	4.86	123.4	0.072	1.8	66.0	HD	C	Z
0.625	15.88	876	12.0	304.8	.465	11.8	6.2	1.1	4.4	112	27	122	4.92	125.0	0.080	2.0	60.0	HD	C	Z
0.625	15.88	S-3045	15.0	381.0	.491	12.5	1.9	.34	8.4	214	16	72	5.19	131.9	0.067	1.7	77.0	SST	CG	N
0.640	16.26	S-105	.34	8.7	.582	14.8	3.1	.54	.22	5.6	.68	3.0	.12	3.1	0.029	0.7	3.25	SST	C	N
0.640	16.26	B10-13	.38	9.5	.508	12.9	57	10	.09	2.4	5.4	24	.28	7.1	0.066	1.7	4.25	SST	CG	N
0.640	16.26	O-70	.41	10.3	.516	13.1	110	19	.12	3.1	13	60	.19	4.7	0.062	1.6	3.00	SPR	CG	Z
0.640	16.26	S-1187	.41	10.3	.506	12.9	134	23	.12	3.0	16	70	.20	5.1	0.067	1.7	3.00	SST	CG	N
0.640	16.26	3181	.44	11.1	.512	13.0	126	22	.12	3.0	15	65	.19	4.9	0.064	1.6	3.00	SPR	CG	GI
0.640	16.26	10124	.50	12.7	.516	13.1	55	9.6	.19	4.8	10	46	.31	7.9	0.062	1.6	4.00	HD	C	Z
0.640	16.26	B15-27	.50	12.7	.500	12.7	110	19	.15	3.9	17	76	.25	6.2	0.070	1.8	3.50	SST	CG	N
0.640	16.26	3248	.63	15.9	.564	14.3	9.2	1.6	.37	9.3	3.4	15	.17	4.3	0.038	1.0	3.50	SPR	C	Z
0.640	16.26	S-1106	.63	15.9	.560	14.2	3.7	.65	.35	8.8	1.3	5.7	.28	7.1	0.040	1.0	6.00	SST	C	N
0.640	16.26	QQ-61	.69	17.4	.522	13.3	44	7.8	.26	6.6	12	51	.30	7.5	0.059	1.5	4.00	SPR	C	GI
0.640	16.26	3221	.69	17.4	.518	13.2	51	9.0	.25	6.3	13	57	.24	6.2	0.061	1.5	4.00	SPR	CG	GI
0.640	16.26	10595	.69	17.4	.430	10.9	368	64	.14	3.6	53	234	.50	12.7	0.105	2.7	4.75	SST	CG	N
0.640	16.26	S-889	.75	19.1	.542	13.8	9.2	1.6	.46	12	4.2	19	.29	7.3	0.049	1.2	6.00	SST	CG	N
0.640	16.26	KK-30	.75	19.1	.540	13.7	22	3.8	.32	8.2	7.1	32	.20	5.1	0.050	1.3	4.00	SPR	CG	Z
0.640	16.26	S-1428	.75	19.1	.430	10.9	397	70	.13	3.4	53	234	.47	12.0	0.105	2.7	4.50	SST	CG	N
0.640	16.26	BB-96	.84	21.4	.490	12.4	37	6.4	.24	6.2	8.9	40	.60	15.2	0.075	1.9	8.00	SST	CG	N
0.640	16.26	10134	.88	22.2	.512	13.0	42	7.4	.35	8.9	15	65	.32	8.1	0.064	1.6	5.00	SPR	CG	Z
0.640	16.26	10789	.88	22.2	.470	11.9	111	19	.27	6.9	30	134	.47	11.9	0.085	2.2	5.50	SST	CG	N
0.640	16.26	GG-94	.94	23.8	.532	13.5	13	2.3	.61	16	8.1	36	.32	8.2	0.054	1.4	6.00	SST	CG	N
0.640	16.26	MM-52	.94	23.8	.520	13.2	32	5.6	.38	9.7	12	54	.30	7.6	0.060	1.5	5.00	SPR	CG	Z
0.640	16.26	S-3197	.94	23.8	.468	11.9	117	21	.27	6.7	31	138	.47	12.0	0.086	2.2	5.50	SST	CG	N
0.640	16.26	10787	.97	24.6	.470	11.9	110	19	.29	7.4	32	143	.51	13.0	0.085	2.2	6.00	SPR	CG	N
0.640	16.26	UU-53	1.00	25.4	.550	14.0	7.0	1.2	.69	17	4.8	21	.32	8.0	0.045	1.1	6.00	SPR	C	Z
0.640	16.26	3144	1.00	25.4	.546	13.9	5.2	.91	.55	14	2.9	13	.45	11.3	0.047	1.2	8.50	SPR	C	Z
0.640	16.26	H-30	1.00	25.4	.528	13.4	18	3.1	.56	14	9.9	44	.34	8.5	0.056	1.4	6.00	SPR	CG	Z
0.640	16.26	2763	1.00	25.4	.474	12.0	175	31	.24	6.1	42	186	.44	11.1	0.083	2.1	4.25	MW	C	Z
0.640	16.26	S-1571	1.00	25.4	.468	11.9	126	22	.25	6.3	31	138	.45	11.5	0.086	2.2	5.25	SST	CG	N
0.640	16.26	A15-35	1.03	26.2	.548	13.9	11	1.9	.51	13	5.6	25	.21	5.3	0.046	1.2	4.50	SST	CG	N
0.640	16.26	GG-48	1.03	26.2	.520	13.2	19	3.3	.61	16	12	52	.42	10.7	0.060	1.5	7.00	SPR	CG	BO
0.640	16.26	2669	1.13	28.6	.396	10.1	688	120	.12	3.1	84	376	.77	19.6	0.122	3.1	5.33	SPR	C	Z
0.640	16.26	B7-58	1.16	29.4	.558	14.2	6.9	1.2	.61	16	4.2	19	.24	6.0	0.041	1.0	4.75	SPR	C	N
0.640	16.26	11901	1.16	29.4	.552	14.0	7.8	1.4	.66	17	5.2	23	.23	5.9	0.044	1.1	5.25	SPR	CG	N
0.640	16.26	A14-68	1.19	30.2	.548	13.9	8.4	1.5	.66	17	5.6	25	.29	7.3	0.046	1.2	5.25	SST	C	N
0.640	16.26	A14-69	1.19	30.2	.530	13.5	19	3.4	.46	12	8.8	39	.28	7.0	0.055	1.4	5.00	SST	CG	N
0.640	16.26	S-1248	1.19	30.2	.506	12.9	27	4.7	.59	15	16	70	.47	11.9	0.067	1.7	7.00	SST	CG	N
0.640	16.26	10240	1.25	31.8	.538	13.7	24	4.2	.32	8.0	7.5	33	.26	6.5	0.051	1.3	4.00	SPR	C	Z
0.640	16.26	11158	1.25	31.8	.528	13.4	18	3.1	.56	14	9.9	44	.34	8.5	0.056	1.4	6.00	SPR	CG	Z
0.640	16.26	10408	1.25	31.8	.516	13.1	31	5.5	.43	11	13	60	.34	8.7	0.062	1.6	5.50	SPR	CG	Z
0.640	16.26	3387	1.25	31.8	.480	12.2	56	9.8	.48	12	27	120	.64	16.3	0.080	2.0	8.00	SPR	CG	Z
0.640	16.26	A14-41	1.28	32.5	.530	13.5	18	3.1	.54	14	9.4	42	.32	8.0	0.055	1.4	5.75	SPR	CG	N
0.640	16.26	10559	1.31	33.3	.536	13.6	15	2.6	.54	14	8.0	35	.29	7.3	0.052	1.3	5.50	SPR	CG	Z
0.640	16.26	2705	1.36	34.5	.440	11.2	228	40	.22	5.5	49	220	.60	15.2	0.100	2.5	6.00	SPR	CG	Z
0.640	16.26	S-411	1.38	34.9	.530	13.5	9.1	1.6	.92	23	8.4	37	.45	11.5	0.055	1.4	8.25	SST	CG	N
0.640	16.26	G-59	1.38	34.9	.480	12.2	42	7.3	.60	15	25	112	.72	18.3	0.080	2.0	9.00	SST	CG	N
0.640	16.26	A13-47	1.44	36.5	.528	13.4	13	2.3	.70	18	9.3	41	.43	11.0	0.056	1.4	6.75	SST	C	N
0.640	16.26	B6-67	1.47	37.3	.560	14.2	4.9	.85	.81	20	3.9	17	.26	6.6	0.040	1.0	5.50	SPR	C	N
0.640	16.26	10082	1.50	38.1	.516	13.1	20	3.5	.67	17	13	60	.47	11.8	0.062	1.6	7.50	HD	CG	GI
0.640	16.26	10418	1.50	38.1	.480	12.2	42	7.3	.64	16	27	120	.80	20.3	0.080	2.0	10.0	SPR	CG	Z
0.640	16.26	3894	1.50	38.1	.480	12.2	48	8.4	.56	14	27	120	.72	18.3	0.080	2.0	9.00	HD	CG	Z
0.640	16.26	Q-50	1.50	38.1	.452	11.5	73	13	.42	11	30	135	1.08	27.5	0.094	2.4	11.5	SPR	CG	N
0.640	16.26	3738	1.50	38.1	.450	11.4	80	14	.46	12	37	163	1.05	26.5	0.095	2.4	11.0	SPR	CG	Z
0.640	16.26	Q-9	1.53	38.9	.572	14.5	2.0	.36	1.2	32	2.5	11	.21	5.4	0.034	0.9	6.25	SPR	CG	Z
0.640	16.26	B11-45	1.56	39.7	.390	9.9	321	56	.28	7.2	90	402	1.25	31.8	0.125	3.2	10.0	SPR	CG	Z
0.640	16.26	11732	1.59	40.5	.574	14.6	1.5	.27	1.4	35	2.1	9.2	.23	5.9	0.033	0.8	7.00	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.640	16.26	3001	1.63	41.3	.560	14.2	2.9	.51	1.3	33	3.8	17	.32	8.0	0.040	1.0	7.88	SPR	C	Z
0.640	16.26	A15-47	1.63	41.3	.556	14.1	3.7	.65	1.1	29	4.2	19	.34	8.5	0.042	1.1	7.00	SST	C	N
0.640	16.26	1553	1.75	44.5	.590	15.0	.44	.08	1.5	39	.67	3.0	.21	5.4	0.025	0.6	7.50	MW	C	Z
0.640	16.26	B17-157	1.75	44.5	.514	13.1	18	3.2	.77	20	14	62	.54	13.6	0.063	1.6	8.50	SPR	CG	N
0.640	16.26	10617	1.81	46.0	.530	13.5	5.3	.92	.96	24	5.0	22	.85	21.7	0.055	1.4	14.5	SPR	C	Z
0.640	16.26	MM-85	1.81	46.0	.380	9.7	344	60	.29	7.2	98	437	1.43	36.3	0.130	3.3	11.0	SPR	CG	Z
0.640	16.26	11797	1.84	46.8	.540	13.7	5.5	.96	1.3	33	7.1	32	.50	12.7	0.050	1.3	10.0	SPR	CG	Z
0.640	16.26	S-1206	1.88	47.6	.558	14.2	1.6	.29	1.3	34	2.2	9.8	.53	13.5	0.041	1.0	12.0	SST	C	N
0.640	16.26	A15-65	2.00	50.8	.558	14.2	2.1	.37	1.6	40	3.3	15	.41	10.4	0.041	1.0	10.0	SST	CG	N
0.640	16.26	10335	2.00	50.8	.546	13.9	3.2	.56	1.4	36	4.5	20	.59	14.9	0.047	1.2	12.5	SPR	CG	Z
0.640	16.26	11750	2.00	50.8	.516	13.1	12	2.1	1.1	28	13	60	.68	17.3	0.062	1.6	11.0	SPR	CG	Z
0.640	16.26	12580	2.00	50.8	.480	12.2	36	6.3	.74	19	27	120	.98	24.9	0.080	2.0	11.3	SPR	C	N
0.640	16.26	4316	2.13	54.0	.530	13.5	8.2	1.4	1.1	29	9.4	42	.55	14.0	0.055	1.4	10.0	SPR	CG	Z
0.640	16.26	S-321	2.19	55.6	.316	8.0	956	167	.16	4.1	156	693	1.66	42.2	0.162	4.1	10.3	SST	CG	N
0.640	16.26	3808	2.25	57.2	.430	10.9	104	18	.55	14	57	253	1.61	40.8	0.105	2.7	14.0	SPR	C	Z
0.640	16.26	LL-96	2.38	60.3	.480	12.2	30	5.2	.85	22	25	112	.96	24.4	0.080	2.0	12.0	SST	CG	N
0.640	16.26	2926	2.47	62.7	.532	13.5	6.1	1.1	1.5	37	8.9	40	.65	16.5	0.054	1.4	12.0	SPR	CG	Z
0.640	16.26	RR-11	2.50	63.5	.568	14.4	1.3	.23	2.1	53	2.7	12	.41	10.5	0.036	0.9	10.5	SPR	C	Z
0.640	16.26	10522	2.63	66.7	.516	13.1	10	1.8	1.3	34	13	60	.81	20.5	0.062	1.6	13.0	SPR	CG	Z
0.640	16.26	11374	2.63	66.7	.496	12.6	20	3.5	.91	23	18	82	.81	20.6	0.072	1.8	11.3	SST	CG	N
0.640	16.26	11596	2.69	68.2	.370	9.4	278	49	.39	10	109	485	2.20	56.0	0.135	3.4	15.3	SPR	CG	Z
0.640	16.26	2624	2.91	73.8	.430	10.9	71	12	.80	20	57	253	2.00	50.7	0.105	2.7	18.0	HD	C	Z
0.640	16.26	S-805	2.94	74.6	.558	14.2	1.6	.27	2.4	61	3.7	17	.55	14.1	0.041	1.0	12.5	SST	C	N
0.640	16.26	12455	3.00	76.2	.480	12.2	24	4.2	1.1	29	27	120	1.36	34.5	0.080	2.0	16.0	SPR	C	Z
0.640	16.26	S-3037	3.25	82.6	.430	10.9	58	10	.90	23	53	234	2.10	53.3	0.105	2.7	19.0	SST	C	N
0.640	16.26	10414	3.31	84.1	.430	10.9	67	12	.85	22	57	253	2.00	50.7	0.105	2.7	19.0	SPR	CG	Z
0.640	16.26	11800	3.50	88.9	.526	13.4	7.7	1.3	1.4	35	10	46	.74	18.8	0.057	1.4	12.0	SPR	C	Z
0.640	16.26	10771	4.00	101.6	.478	12.1	18	3.1	1.6	40	28	124	1.78	45.3	0.081	2.1	22.0	SPR	CG	GI
0.640	16.26	3437	4.50	114.3	.530	13.5	3.9	.68	2.4	62	9.4	42	1.10	27.9	0.055	1.4	19.0	SPR	C	Z
0.640	16.26	3154	4.50	114.3	.480	12.2	19	3.3	1.4	36	27	120	1.57	40.0	0.080	2.0	19.8	SPR	CG	Z
0.640	16.26	1593	4.88	123.8	.400	10.2	92	16	.87	22	81	358	3.00	76.2	0.120	3.0	25.0	SPR	CG	Z
0.640	16.26	3332	6.00	152.4	.496	12.6	5.2	.91	2.9	73	15	66	3.13	79.6	0.072	1.8	42.5	HD	C	Z
0.640	16.26	1531	8.00	203.2	.500	12.7	5.6	.98	3.2	82	18	81	2.54	64.5	0.070	1.8	35.3	SPR	C	Z
0.640	16.26	11691	9.75	247.7	.458	11.6	13	2.3	2.8	71	38	167	4.23	107.5	0.091	2.3	46.5	SPR	CG	GI
0.640	16.26	10152	11.0	279.4	.570	14.5	.28	.05	9.5	241	2.6	12	1.33	33.8	0.035	0.9	37.0	SPR	C	Z
0.653	16.59	12682	.69	17.4	.527	13.4	32	5.6	.31	7.8	9.9	44	.38	9.6	0.063	1.6	5.00	SST	C	N
0.656	16.66	10241	.34	8.7	.496	12.6	411	72	.06	1.6	26	117	.22	5.6	0.080	2.0	2.75	SPR	CG	Z
0.656	16.66	B4-70	.38	9.5	.600	15.2	3.1	.54	.26	6.7	.82	3.6	.11	2.8	0.028	0.7	3.00	SST	C	N
0.656	16.66	3645	.38	9.5	.574	14.6	17	3.1	.21	5.4	3.7	16	.16	4.2	0.041	1.0	3.00	HD	C	Z
0.656	16.66	II-97	.44	11.1	.574	14.6	15	2.7	.25	6.4	3.9	17	.16	4.2	0.041	1.0	3.00	SST	C	N
0.656	16.66	1763	.47	11.9	.562	14.3	18	3.1	.25	6.2	4.3	19	.22	5.7	0.047	1.2	3.75	HD	C	Z
0.656	16.66	S-883	.53	13.5	.546	13.9	28	4.9	.31	7.8	8.6	38	.21	5.4	0.055	1.4	4.00	SST	CG	N
0.656	16.66	12266	.56	14.3	.556	14.1	17	3.0	.35	8.8	6.0	27	.22	5.5	0.050	1.3	4.25	SPR	CG	Z
0.656	16.66	A-48	.66	16.7	.296	7.5	13992	2450	.02	.40	218	968	.54	13.7	0.180	4.6	3.00	HD	CG	Z
0.656	16.66	OO-48	.69	17.4	.576	14.6	5.2	.92	.45	11	2.3	10	.24	6.1	0.040	1.0	5.00	SPR	C	GI
0.656	16.66	A11-28	.69	17.4	.560	14.2	15	2.6	.41	10	6.2	27	.19	4.9	0.048	1.2	4.00	SST	CG	N
0.656	16.66	S-1264	.69	17.4	.474	12.0	136	24	.19	4.7	25	113	.50	12.7	0.091	2.3	5.50	SST	CG	N
0.656	16.66	S-1210	.75	19.1	.574	14.6	7.6	1.3	.51	13	3.9	17	.21	5.2	0.041	1.0	4.00	SST	C	N
0.656	16.66	I-59	.75	19.1	.564	14.3	8.2	1.4	.52	13	4.3	19	.23	5.8	0.046	1.2	5.00	SST	CG	N
0.656	16.66	S-1403	.75	19.1	.532	13.5	44	7.7	.28	7.1	12	55	.25	6.3	0.062	1.6	4.00	SST	CG	N
0.656	16.66	A15-69	.75	19.1	.504	12.8	67	12	.32	8.0	21	94	.40	10.1	0.076	1.9	5.25	SST	CG	N
0.656	16.66	S-1135	.81	20.6	.592	15.0	2.4	.42	.64	16	1.5	6.9	.17	4.3	0.032	0.8	4.25	SST	C	N
0.656	16.66	S-479	.81	20.6	.544	13.8	24	4.3	.37	9.5	9.1	41	.24	6.2	0.056	1.4	4.25	SST	CG	N
0.656	16.66	B11-57	.84	21.4	.520	13.2	60	11	.28	7.2	17	76	.31	7.8	0.068	1.7	4.50	SPR	CG	Z
0.656	16.66	A14-64	1.00	25.4	.568	14.4	8.3	1.5	.57	14	4.8	21	.20	5.0	0.044	1.1	4.50	SST	CG	N
0.656	16.66	A14-52	1.00	25.4	.542	13.8	26	4.5	.40	10	10	45	.27	6.9	0.057	1.4	4.75	SPR	CG	GI
0.656	16.66	S-135	1.00	25.4	.512	13.0	42	7.4	.43	11	18	80	.50	12.8	0.072	1.8	6.00	SST	C	N
0.656	16.66	A14-63	1.03	26.2	.562	14.3	12	2.2	.50	13	6.2	27	.21	5.4	0.047	1.2	4.50	SPR	CG	GI
0.656	16.66	S-1391	1.03	26.2	.474	12.0	106	18	.32	8.2	34	152	.59	15.0	0.091	2.3	6.50	SST	CG	N
0.656	16.66	S-1102	1.06	27.0	.576	14.6	4.2	.74	.81	21	3.4	15	.25	6.4	0.040	1.0	5.25	SST	C	N
0.656	16.66	B9-57	1.06	27.0	.572	14.5	4.3	.75	.79	20	3.4	15	.27	6.9	0.042	1.1	6.50	SPR	CG	N
0.656	16.66	H-9	1.13	28.6	.562	14.3	10	1.8	.60	15	6.2	27	.24	6.0	0.047	1.2	5.00	SPR	CG	GI
0.656	16.66	10327	1.13	28.6	.548	13.9	12	2.2	.70	18	8.7	39	.41	10.3	0.054	1.4	6.50	SPR	C	Z
0.656	16.66	S-269	1.13	28.6	.548	13.9	13	2.3	.63	16	8.2	36	.36	9.3	0.054	1.4	5.75	SST	C	N
0.656	16.66	11228	1.13	28.6	.526	13.4	33	5.8	.45	12	15	67	.37	9.5	0.065	1.7	5.75	SPR	CG	Z
0.656	16.66	1601	1.13	28.6	.476	12.1	87	15	.41	10	35	156	.72	18.3	0.090	2.3	8.00	SPR	CG	Z
0.656	16.66	Y-26	1.13	28.6	.406	10.3	1172	205	.08	1.9	89	394	.50	12.7	0.125	3.2	4.00	SPR	CG	Z
0.656	16.66	10453	1.19	30.2	.522	13.3	30	5.2	.55	14	16	73	.45	11.5	0.067	1.7	6.75	SPR	CG	Z
0.656	16.66	B12-5	1.25	31.8	.548	13.9	14	2.5	.62	16	8.7	39	.32	8.2	0.054	1.4	6.00	SPR	CG	N
0.656	16.66	S-425	1.28	32.5	.548	13.9	13	2.4	.61	15	8.2	36	.30	7.7	0.054	1.4	5.75	SST	CG	N
0.656	16.66	B1-64	1.28	32.5	.540	13.7	19	3.3	.56	14	11	48	.41	10.3	0.058	1.5	6.00	SPR	C	Z
0.656	16.66	10794	1.31	33.3	.564	14.3	7.2	1.3	.76	19	5.4	24	.25	6.4	0.046	1.2	5.50	SST	CG	N
0.656	16.66	4330	1.31	33.3	.536	13.6	12	2.1	.74	19	8.7	39	.57	14.5	0.060	1.5	9.50	SPR	CG	Z
0.656	16.66	11566	1.34	34.1	.496	12.6	56	9.8	.47	12	26	117	.68	17.3	0.080	2.0	7.50	SPR	CG	N
0.656	16.66	11420	1.38	34.9	.512	13.0	43	7.5	.45	11	19	86	.54	13.7	0.072	1.8	6.50	SPR	C	Z
0.656	16.66	10264	1.38	34.9	.466	11.8	111	19	.38	9.6	42	185	.86	21.7	0.095	2.4	8.00	SPR	C	Z
0.656	16.66	10712	1.41	35.7	.612	15.5	.29	.05	1.2	32	.36	1.6	.17	4.2	0.022	0.6	6.50	MW	C	Z
0.656	16.66	11129	1.41	35.7	.592	15.0	2.1	.36	1.0	25	2.1	9.2	.19	4.9	0.032	0.8	5.00	HD	C	Z
0.656	16.66	10960	1.41	35.7	.590	15.0	1.7	.29	1.2	30	1.9	8.6	.24	6.1	0.033	0.8	6.25	SPR	C	N
0.656	16.66	A15-56	1.47	37.3	.572	14.5	4.9	.86	.85	21	4.1	18	.23	5.9	0.042	1.1	5.50	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.656	16.66	10807	1.47	37.3	.564	14.3	4.2	.73	1.1	28	4.6	21	.37	9.3	0.046	1.2	8.00	SST	CG	N
0.656	16.66	B15-42	1.50	38.1	.532	13.5	10	1.8	.76	19	7.7	34	.74	18.9	0.062	1.6	12.0	SPR	CG	Z
0.656	16.66	S-171	1.50	38.1	.446	11.3	121	21	.43	11	52	229	1.00	25.3	0.105	2.7	9.50	SST	CG	N
0.656	16.66	S-1402	1.50	38.1	.430	10.9	318	56	.19	4.8	61	270	.68	17.2	0.113	2.9	6.00	SST	CG	N
0.656	16.66	B8-36	1.53	38.9	.456	11.6	99	17	.45	12	45	199	.95	24.1	0.100	2.5	9.50	SST	CG	N
0.656	16.66	2608	1.53	38.9	.432	11.0	201	35	.32	8.2	65	288	1.01	25.6	0.112	2.8	9.00	SPR	CG	Z
0.656	16.66	12305	1.63	41.3	.446	11.3	116	20	.47	12	55	243	1.16	29.3	0.105	2.7	11.0	SPR	CG	Z
0.656	16.66	10196	1.69	42.8	.612	15.5	.20	.03	1.5	37	.29	1.3	.22	5.5	0.022	0.6	8.75	MW	C	Z
0.656	16.66	10663	1.69	42.8	.606	15.4	.34	.06	1.4	37	.50	2.2	.24	6.0	0.025	0.6	8.50	MW	C	N
0.656	16.66	1715	1.75	44.5	.600	15.2	.55	.10	1.5	38	.81	3.6	.27	6.8	0.028	0.7	8.50	MW	C	Z
0.656	16.66	4186	1.75	44.5	.562	14.3	5.2	.91	1.2	30	6.2	27	.42	10.7	0.047	1.2	8.00	SPR	C	Z
0.656	16.66	A14-12	1.75	44.5	.396	10.1	316	55	.27	7.0	87	385	1.27	32.2	0.130	3.3	9.75	SST	CG	N
0.656	16.66	10157	1.78	45.2	.354	9.0	967	169	.15	3.7	142	634	1.21	30.7	0.151	3.8	8.00	SPR	CG	GI
0.656	16.66	S-1148	1.88	47.6	.432	11.0	122	21	.48	12	59	263	1.34	34.1	0.112	2.8	12.0	SST	CG	N
0.656	16.66	11882	1.91	48.4	.560	14.2	6.8	1.2	.97	25	6.6	29	.34	8.5	0.048	1.2	7.00	SPR	CG	N
0.656	16.66	11723	1.97	50.0	.552	14.0	7.9	1.4	.98	25	7.8	35	.42	10.6	0.052	1.3	8.00	SPR	CG	Z
0.656	16.66	B18-179	2.00	50.8	.576	14.6	1.7	.31	1.6	41	2.8	12	.40	10.2	0.040	1.0	10.0	SST	CG	N
0.656	16.66	4256	2.00	50.8	.560	14.2	6.5	1.1	1.0	26	6.6	29	.40	10.1	0.048	1.2	7.25	SPR	C	Z
0.656	16.66	11682	2.03	51.6	.530	13.5	12	2.1	1.1	29	14	61	.69	17.6	0.063	1.6	11.0	SPR	CG	Z
0.656	16.66	3130	2.06	52.4	.530	13.5	12	2.1	1.1	28	14	61	.69	17.4	0.063	1.6	11.0	SPR	CG	Z
0.656	16.66	2656	2.25	57.2	.546	13.9	6.2	1.1	1.5	38	9.2	41	.65	16.4	0.055	1.4	11.8	SPR	CG	Z
0.656	16.66	N-124	2.50	63.5	.574	14.6	1.9	.33	2.0	52	3.9	17	.45	11.5	0.041	1.0	10.0	SST	C	N
0.656	16.66	2514	2.53	64.3	.548	13.9	6.8	1.2	1.8	45	12	54	.55	14.1	0.054	1.4	10.3	MW	CG	Z
0.656	16.66	S-1121	2.63	66.7	.574	14.6	1.9	.33	2.0	52	3.9	17	.45	11.5	0.041	1.0	10.0	SST	C	N
0.656	16.66	11616	2.84	72.2	.414	10.5	161	28	.50	13	81	359	1.88	47.6	0.121	3.1	14.5	SPR	CG	Z
0.656	16.66	1635	2.88	73.0	.496	12.6	32	5.7	.81	21	26	117	1.00	25.4	0.080	2.0	11.5	SPR	C	Z
0.656	16.66	10997	3.06	77.8	.446	11.3	87	15	.64	16	56	247	1.47	37.3	0.105	2.7	14.0	HD	CG	Z
0.656	16.66	S-3179	3.31	84.1	.446	11.3	50	8.8	1.0	26	52	229	2.10	53.3	0.105	2.7	20.0	SST	CG	N
0.656	16.66	S-1525	3.50	88.9	.594	15.1	.29	.05	2.9	74	.83	3.7	.60	15.4	0.031	0.8	18.5	SST	C	N
0.656	16.66	11393	3.50	88.9	.562	14.3	2.3	.40	2.7	69	6.1	27	.79	20.0	0.047	1.2	15.8	HD	C	GI
0.656	16.66	11811	3.59	91.3	.428	10.9	85	15	.80	20	68	303	2.28	57.9	0.114	2.9	20.0	SPR	CG	Z
0.656	16.66	3337	4.00	101.6	.542	13.8	6.4	1.1	1.6	40	10	45	.80	20.3	0.057	1.4	13.0	SPR	C	Z
0.656	16.66	2684	4.94	125.4	.532	13.5	4.6	.80	2.9	73	13	58	1.57	39.8	0.062	1.6	24.3	HD	C	Z
0.656	16.66	4265	6.00	152.4	.532	13.5	2.7	.47	3.5	88	9.2	41	2.54	64.6	0.062	1.6	40.0	SPR	C	Z
0.656	16.66	1883	6.50	165.1	.532	13.5	3.4	.59	3.9	98	13	58	2.05	52.0	0.062	1.6	32.0	HD	C	Z
0.656	16.66	2805	6.63	168.3	.340	8.6	227	40	.71	18	161	717	5.37	136.4	0.158	4.0	34.0	HD	CG	Z
0.656	16.66	1825	7.75	196.9	.332	8.4	261	46	.66	17	172	767	5.43	137.8	0.162	4.1	33.5	HD	CG	Z
0.656	16.66	10289	9.50	241.3	.512	13.0	4.9	.86	3.9	100	19	86	3.06	77.7	0.072	1.8	41.5	SPR	C	Z
0.656	16.66	12116	11.1	281.8	.474	12.0	9.6	1.7	3.8	97	37	163	5.37	136.4	0.091	2.3	59.0	SPR	CG	Z
0.656	16.66	4019	18.5	469.9	.522	13.3	2.0	.35	8.2	209	16	73	4.96	125.9	0.067	1.7	73.0	HD	C	BO
0.660	16.76	71865	.63	16.0	.562	14.3	23	4.1	.41	10	9.6	43	.17	4.4	0.049	1.2	3.50	MW	CG	N
0.660	16.76	71865S	.63	16.0	.562	14.3	20	3.5	.33	8.3	6.5	29	.17	4.4	0.049	1.2	3.50	SST	CG	N
0.660	16.76	71877	.63	16.0	.550	14.0	36	6.3	.35	8.9	13	56	.20	5.1	0.055	1.4	3.63	MW	CG	N
0.660	16.76	71877S	.63	16.0	.550	14.0	31	5.4	.28	7.1	8.6	38	.20	5.1	0.055	1.4	3.63	SST	CG	N
0.660	16.76	71889	.63	16.0	.534	13.6	56	9.7	.34	8.6	19	84	.24	6.2	0.063	1.6	3.88	MW	CG	N
0.660	16.76	71889S	.63	16.0	.534	13.6	47	8.3	.27	6.9	13	57	.24	6.2	0.063	1.6	3.88	SST	CG	N
0.660	16.76	71901	.63	16.0	.526	13.4	71	12	.32	8.2	23	101	.27	6.8	0.067	1.7	4.00	MW	CG	N
0.660	16.76	71901S	.63	16.0	.526	13.4	60	11	.26	6.5	15	68	.27	6.8	0.067	1.7	4.00	SST	CG	N
0.660	16.76	71913	.63	16.0	.516	13.1	94	16	.28	7.2	27	119	.29	7.3	0.072	1.8	4.00	MW	CG	N
0.660	16.76	71913S	.63	16.0	.516	13.1	80	14	.22	5.7	18	80	.29	7.3	0.072	1.8	4.00	SST	CG	N
0.660	16.76	71866	.75	19.1	.562	14.3	18	3.2	.53	13	9.6	43	.20	5.0	0.049	1.2	4.00	MW	CG	N
0.660	16.76	71866S	.75	19.1	.562	14.3	15	2.7	.42	11	6.5	29	.20	5.0	0.049	1.2	4.00	SST	CG	N
0.660	16.76	71878	.75	19.1	.550	14.0	29	5.1	.44	11	13	56	.22	5.6	0.055	1.4	4.00	MW	CG	N
0.660	16.76	71878S	.75	19.1	.550	14.0	25	4.3	.35	8.9	8.6	38	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.660	16.76	71890	.75	19.1	.534	13.6	45	7.8	.43	11	19	84	.28	7.0	0.063	1.6	4.38	MW	CG	N
0.660	16.76	71890S	.75	19.1	.534	13.6	38	6.6	.34	8.6	13	57	.28	7.0	0.063	1.6	4.38	SST	CG	N
0.660	16.76	71902	.75	19.1	.526	13.4	56	9.9	.40	10	23	101	.30	7.7	0.067	1.7	4.50	MW	CG	N
0.660	16.76	71902S	.75	19.1	.526	13.4	48	8.4	.32	8.1	15	68	.30	7.7	0.067	1.7	4.50	SST	CG	N
0.660	16.76	71914	.75	19.1	.516	13.1	75	13	.36	9.1	27	119	.32	8.2	0.072	1.8	4.50	MW	CG	N
0.660	16.76	71914S	.75	19.1	.516	13.1	63	11	.28	7.2	18	80	.32	8.2	0.072	1.8	4.50	SST	CG	N
0.660	16.76	71867	.88	22.4	.562	14.3	15	2.7	.63	16	9.6	43	.21	5.4	0.049	1.2	4.38	MW	CG	N
0.660	16.76	71867S	.88	22.4	.562	14.3	13	2.3	.50	13	6.5	29	.21	5.4	0.049	1.2	4.38	SST	CG	N
0.660	16.76	71879	.88	22.4	.550	14.0	24	4.2	.53	13	13	56	.25	6.3	0.055	1.4	4.50	MW	CG	N
0.660	16.76	71879S	.88	22.4	.550	14.0	20	3.6	.42	11	8.6	38	.25	6.3	0.055	1.4	4.50	SST	CG	N
0.660	16.76	71891	.88	22.4	.534	13.6	37	6.5	.51	13	19	84	.31	7.8	0.063	1.6	4.88	MW	CG	N
0.660	16.76	71891S	.88	22.4	.534	13.6	32	5.5	.41	10	13	57	.31	7.8	0.063	1.6	4.88	SST	CG	N
0.660	16.76	71903	.88	22.4	.526	13.4	47	8.2	.48	12	23	101	.34	8.5	0.067	1.7	5.00	MW	CG	N
0.660	16.76	71903S	.88	22.4	.526	13.4	40	7.0	.39	9.8	15	68	.34	8.5	0.067	1.7	5.00	SST	CG	N
0.660	16.76	71915	.88	22.4	.516	13.1	62	11	.43	11	27	119	.37	9.4	0.072	1.8	5.13	MW	CG	N
0.660	16.76	71915S	.88	22.4	.516	13.1	53	9.2	.34	8.7	18	80	.37	9.4	0.072	1.8	5.13	SST	CG	N
0.660	16.76	71868	1.00	25.4	.562	14.3	13	2.3	.73	19	9.6	43	.23	5.9	0.049	1.2	4.75	MW	CG	N
0.660	16.76	71868S	1.00	25.4	.562	14.3	11	2.0	.58	15	6.5	29	.23	5.9	0.049	1.2	4.75	SST	CG	N
0.660	16.76	71880	1.00	25.4	.550	14.0	21	3.6	.61	15	13	56	.27	6.8	0.055	1.4	4.88	MW	CG	N
0.660	16.76	71880S	1.00	25.4	.550	14.0	18	3.1	.49	12	8.6	38	.27	6.8	0.055	1.4	4.88	SST	CG	N
0.660	16.76	71892	1.00	25.4	.534	13.6	32	5.6	.60	15	19	84	.34	8.6	0.063	1.6	5.38	MW	CG	N
0.660	16.76	71892S	1.00	25.4	.534	13.6	27	4.7	.47	12	13	57	.34	8.6	0.063	1.6	5.38	SST	CG	N
0.660	16.76	71904	1.00	25.4	.526	13.4	40	7.0	.57	14	23	101	.37	9.4	0.067	1.7	5.50	MW	CG	N
0.660	16.76	71904S	1.00	25.4	.526	13.4	34	6.0	.45	11	15	68	.37	9.4	0.067	1.7	5.50	SST	CG	N
0.660	16.76	71916	1.00	25.4	.516	13.1	53	9.3	.51	13	27	119	.41	10.3	0.072	1.8	5.63	MW	CG	N
0.660	16.76	71916S	1.00	25.4	.516	13.1	45	7.9	.40	10	18	80	.41	10.3	0.072	1.8	5.63	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None





COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.660	16.76	71869	1.25	31.8	.562	14.3	10	1.8	.93	24	9.6	43	.27	6.8	0.049	1.2	5.50	MW	CG	N
0.660	16.76	71869S	1.25	31.8	.562	14.3	8.8	1.5	.74	19	6.5	29	.27	6.8	0.049	1.2	5.50	SST	CG	N
0.660	16.76	71881	1.25	31.8	.550	14.0	16	2.8	.78	20	13	56	.31	7.9	0.055	1.4	5.63	MW	CG	N
0.660	16.76	71881S	1.25	31.8	.550	14.0	14	2.4	.62	16	8.6	38	.31	7.9	0.055	1.4	5.63	SST	CG	N
0.660	16.76	71893	1.25	31.8	.534	13.6	25	4.3	.77	19	19	84	.39	10.0	0.063	1.6	6.25	MW	CG	N
0.660	16.76	71893S	1.25	31.8	.534	13.6	21	3.7	.61	16	13	57	.39	10.0	0.063	1.6	6.25	SST	CG	N
0.660	16.76	71905	1.25	31.8	.526	13.4	31	5.4	.73	19	23	101	.44	11.1	0.067	1.7	6.50	MW	CG	N
0.660	16.76	71905S	1.25	31.8	.526	13.4	26	4.6	.58	15	15	68	.44	11.1	0.067	1.7	6.50	SST	CG	N
0.660	16.76	71917	1.25	31.8	.516	13.1	41	7.2	.65	17	27	119	.48	12.1	0.072	1.8	6.63	MW	CG	N
0.660	16.76	71917S	1.25	31.8	.516	13.1	35	6.1	.52	13	18	80	.48	12.1	0.072	1.8	6.63	SST	CG	N
0.660	16.76	71870	1.50	38.1	.562	14.3	8.5	1.5	1.1	29	9.6	43	.31	7.8	0.049	1.2	6.25	MW	CG	N
0.660	16.76	71870S	1.50	38.1	.562	14.3	7.2	1.3	.90	23	6.5	29	.31	7.8	0.049	1.2	6.25	SST	CG	N
0.660	16.76	71882	1.50	38.1	.550	14.0	13	2.3	.95	24	13	56	.36	9.1	0.055	1.4	6.50	MW	CG	N
0.660	16.76	71882S	1.50	38.1	.550	14.0	11	2.0	.76	19	8.6	38	.36	9.1	0.055	1.4	6.50	SST	CG	N
0.660	16.76	71894	1.50	38.1	.534	13.6	20	3.5	.94	24	19	84	.46	11.6	0.063	1.6	7.25	MW	CG	N
0.660	16.76	71894S	1.50	38.1	.534	13.6	17	3.0	.75	19	13	57	.46	11.6	0.063	1.6	7.25	SST	CG	N
0.660	16.76	71906	1.50	38.1	.526	13.4	26	4.5	.89	23	23	101	.50	12.8	0.067	1.7	7.50	MW	CG	N
0.660	16.76	71906S	1.50	38.1	.526	13.4	22	3.8	.71	18	15	68	.50	12.8	0.067	1.7	7.50	SST	CG	N
0.660	16.76	71918	1.50	38.1	.516	13.1	34	5.9	.80	20	27	119	.55	13.9	0.072	1.8	7.63	MW	CG	N
0.660	16.76	71918S	1.50	38.1	.516	13.1	28	5.0	.63	16	18	80	.55	13.9	0.072	1.8	7.63	SST	CG	N
0.660	16.76	71871	1.75	44.5	.562	14.3	7.2	1.3	1.3	34	9.6	43	.34	8.7	0.049	1.2	7.00	MW	CG	N
0.660	16.76	71871S	1.75	44.5	.562	14.3	6.1	1.1	1.1	27	6.5	29	.34	8.7	0.049	1.2	7.00	SST	CG	N
0.660	16.76	71883	1.75	44.5	.550	14.0	11	2.0	1.1	28	13	56	.40	10.1	0.055	1.4	7.25	MW	CG	N
0.660	16.76	71883S	1.75	44.5	.550	14.0	9.6	1.7	.89	23	8.6	38	.40	10.1	0.055	1.4	7.25	SST	CG	N
0.660	16.76	71895	1.75	44.5	.534	13.6	17	3.0	1.1	28	19	84	.52	13.2	0.063	1.6	8.25	MW	CG	N
0.660	16.76	71895S	1.75	44.5	.534	13.6	15	2.5	.88	22	13	57	.52	13.2	0.063	1.6	8.25	SST	CG	N
0.660	16.76	71907	1.75	44.5	.526	13.4	22	3.8	1.1	27	23	101	.57	14.5	0.067	1.7	8.50	MW	CG	N
0.660	16.76	71907S	1.75	44.5	.526	13.4	18	3.2	.84	21	15	68	.57	14.5	0.067	1.7	8.50	SST	CG	N
0.660	16.76	71919	1.75	44.5	.516	13.1	28	4.9	.95	24	27	119	.63	16.0	0.072	1.8	8.75	MW	CG	N
0.660	16.76	71919S	1.75	44.5	.516	13.1	24	4.2	.75	19	18	80	.63	16.0	0.072	1.8	8.75	SST	CG	N
0.660	16.76	71872	2.00	50.8	.562	14.3	6.3	1.1	1.5	39	9.6	43	.39	9.8	0.049	1.2	7.88	MW	CG	N
0.660	16.76	71872S	2.00	50.8	.562	14.3	5.3	.93	1.2	31	6.5	29	.39	9.8	0.049	1.2	7.88	SST	CG	N
0.660	16.76	71884	2.00	50.8	.550	14.0	9.8	1.7	1.3	33	13	56	.44	11.2	0.055	1.4	8.00	MW	CG	N
0.660	16.76	71884S	2.00	50.8	.550	14.0	8.3	1.5	1.0	26	8.6	38	.44	11.2	0.055	1.4	8.00	SST	CG	N
0.660	16.76	71896	2.00	50.8	.534	13.6	15	2.6	1.3	32	19	84	.58	14.8	0.063	1.6	9.25	MW	CG	N
0.660	16.76	71896S	2.00	50.8	.534	13.6	13	2.2	1.0	26	13	57	.58	14.8	0.063	1.6	9.25	SST	CG	N
0.660	16.76	71908	2.00	50.8	.526	13.4	19	3.3	1.2	31	23	101	.64	16.2	0.067	1.7	9.50	MW	CG	N
0.660	16.76	71908S	2.00	50.8	.526	13.4	16	2.8	.97	25	15	68	.64	16.2	0.067	1.7	9.50	SST	CG	N
0.660	16.76	71920	2.00	50.8	.516	13.1	25	4.3	1.1	28	27	119	.70	17.8	0.072	1.8	9.75	MW	CG	N
0.660	16.76	71920S	2.00	50.8	.516	13.1	21	3.6	.86	22	18	80	.70	17.8	0.072	1.8	9.75	SST	CG	N
0.660	16.76	71873	2.25	57.2	.562	14.3	5.5	.96	1.7	44	9.6	43	.42	10.7	0.049	1.2	8.63	MW	CG	N
0.660	16.76	71873S	2.25	57.2	.562	14.3	4.7	.82	1.4	35	6.5	29	.42	10.7	0.049	1.2	8.63	SST	CG	N
0.660	16.76	71885	2.25	57.2	.550	14.0	8.6	1.5	1.5	37	13	56	.49	12.4	0.055	1.4	8.88	MW	CG	N
0.660	16.76	71885S	2.25	57.2	.550	14.0	7.3	1.3	1.2	30	8.6	38	.49	12.4	0.055	1.4	8.88	SST	CG	N
0.660	16.76	71897	2.25	57.2	.534	13.6	13	2.3	1.4	37	19	84	.64	16.2	0.063	1.6	10.1	MW	CG	N
0.660	16.76	71897S	2.25	57.2	.534	13.6	11	1.9	1.2	29	13	57	.64	16.2	0.063	1.6	10.1	SST	CG	N
0.660	16.76	71909	2.25	57.2	.526	13.4	17	2.9	1.4	35	23	101	.70	17.7	0.067	1.7	10.4	MW	CG	N
0.660	16.76	71909S	2.25	57.2	.526	13.4	14	2.5	1.1	28	15	68	.70	17.7	0.067	1.7	10.4	SST	CG	N
0.660	16.76	71921	2.25	57.2	.516	13.1	22	3.8	1.2	32	27	119	.78	19.9	0.072	1.8	10.9	MW	CG	N
0.660	16.76	71921S	2.25	57.2	.516	13.1	18	3.2	.98	25	18	80	.78	19.9	0.072	1.8	10.9	SST	CG	N
0.660	16.76	71874	2.50	63.5	.562	14.3	5.0	.87	1.9	49	9.6	43	.46	11.7	0.049	1.2	9.38	MW	CG	N
0.660	16.76	71874S	2.50	63.5	.562	14.3	4.2	.74	1.5	39	6.5	29	.46	11.7	0.049	1.2	9.38	SST	CG	N
0.660	16.76	71886	2.50	63.5	.550	14.0	7.8	1.4	1.6	42	13	56	.53	13.4	0.055	1.4	9.63	MW	CG	N
0.660	16.76	71886S	2.50	63.5	.550	14.0	6.6	1.2	1.3	33	8.6	38	.53	13.4	0.055	1.4	9.63	SST	CG	N
0.660	16.76	71898	2.50	63.5	.534	13.6	12	2.0	1.6	41	19	84	.70	17.8	0.063	1.6	11.1	MW	CG	N
0.660	16.76	71898S	2.50	63.5	.534	13.6	9.9	1.7	1.3	33	13	57	.70	17.8	0.063	1.6	11.1	SST	CG	N
0.660	16.76	71910	2.50	63.5	.526	13.4	15	2.6	1.5	39	23	101	.77	19.6	0.067	1.7	11.5	MW	CG	N
0.660	16.76	71910S	2.50	63.5	.526	13.4	12	2.2	1.2	31	15	68	.77	19.6	0.067	1.7	11.5	SST	CG	N
0.660	16.76	71922	2.50	63.5	.516	13.1	19	3.4	1.4	35	27	119	.86	21.7	0.072	1.8	11.9	MW	CG	N
0.660	16.76	71922S	2.50	63.5	.516	13.1	16	2.9	1.1	28	18	80	.86	21.7	0.072	1.8	11.9	SST	CG	N
0.660	16.76	71875	2.75	69.9	.562	14.3	4.5	.79	2.1	54	9.6	43	.50	12.6	0.049	1.2	10.1	MW	CG	N
0.660	16.76	71875S	2.75	69.9	.562	14.3	3.8	.67	1.7	43	6.5	29	.50	12.6	0.049	1.2	10.1	SST	CG	N
0.660	16.76	71887	2.75	69.9	.550	14.0	7.0	1.2	1.8	46	13	56	.58	14.7	0.055	1.4	10.5	MW	CG	N
0.660	16.76	71887S	2.75	69.9	.550	14.0	6.0	1.0	1.4	37	8.6	38	.58	14.7	0.055	1.4	10.5	SST	CG	N
0.660	16.76	71899	2.75	69.9	.534	13.6	11	1.9	1.8	45	19	84	.76	19.2	0.063	1.6	12.0	MW	CG	N
0.660	16.76	71899S	2.75	69.9	.534	13.6	9.0	1.6	1.4	36	13	57	.76	19.2	0.063	1.6	12.0	SST	CG	N
0.660	16.76	71911	2.75	69.9	.526	13.4	13	2.3	1.7	43	23	101	.84	21.3	0.067	1.7	12.5	MW	CG	N
0.660	16.76	71911S	2.75	69.9	.526	13.4	11	2.0	1.4	35	15	68	.84	21.3	0.067	1.7	12.5	SST	CG	N
0.660	16.76	71923	2.75	69.9	.516	13.1	18	3.1	1.5	39	27	119	.93	23.5	0.072	1.8	12.9	MW	CG	N
0.660	16.76	71923S	2.75	69.9	.516	13.1	15	2.6	1.2	31	18	80	.93	23.5	0.072	1.8	12.9	SST	CG	N
0.660	16.76	71876	3.00	76.2	.562	14.3	4.1	.72	2.3	60	9.6	43	.53	13.5	0.049	1.2	10.9	MW	CG	N
0.660	16.76	71876S	3.00	76.2	.562	14.3	3.5	.61	1.9	47	6.5	29	.53	13.5	0.049	1.2	10.9	SST	CG	N
0.660	16.76	71888	3.00	76.2	.550	14.0	6.4	1.1	2.0	50	13	56	.62	15.7	0.055	1.4	11.3	MW	CG	N
0.660	16.76	71888S	3.00	76.2	.550	14.0	5.4	.95	1.6	40	8.6	38	.62	15.7	0.055	1.4	11.3	SST	CG	N
0.660	16.76	71900	3.00	76.2	.534	13.6	9.7	1.7	2.0	50	19	84	.82	20.8	0.063	1.6	13.0	MW	CG	N
0.660	16.76	71900S	3.00	76.2	.534	13.6	8.2	1.4	1.6	40	13	57	.82	20.8	0.063	1.6	13.0	SST	CG	N
0.660	16.76	71912	3.00	76.2	.526	13.4	12	2.1	1.9	48	23	101	.90	23.0	0.067	1.7	13.5	MW	CG	N
0.660	16.76	71912S	3.00	76.2	.526	13.4	10	1.8	1.5	38	15	68	.90	23.0	0.067	1.7	13.5	SST	CG	N
0.660	16.76	71924	3.00	76.2	.516	13.1	16	2.8	1.7	43	27	119	1.01	25.6	0.072	1.8	14.0	MW	CG	N
0.660	16.76	71924S	3.00	76.2	.516	13.1	14	2.4	1.3	34	18	80	1.01	25.6	0.072	1.8	14.0	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.671	17.04	B9-6	.38	9.5	.589	15.0	16	2.8	.21	5.4	3.4	15	.16	4.2	0.041	1.0	3.00	SPR	C	Z
0.671	17.04	10520	.38	9.5	.511	13.0	380	67	.07	1.7	26	114	.22	5.6	0.080	2.0	2.75	SPR	CG	Z
0.671	17.04	N-80	.41	10.3	.461	11.7	838	147	.06	1.5	51	225	.32	8.0	0.105	2.7	3.00	SST	CG	N
0.671	17.04	B10-21	.47	11.9	.575	14.6	28	4.9	.22	5.5	6.0	27	.19	4.9	0.048	1.2	3.00	SST	C	N
0.671	17.04	S-21	.59	15.1	.601	15.3	2.5	.43	.38	9.7	.95	4.2	.21	5.3	0.035	0.9	5.00	SST	C	N
0.671	17.04	1865	.59	15.1	.527	13.4	90	16	.23	5.9	21	93	.36	9.1	0.072	1.8	4.00	MW	C	Z
0.671	17.04	S-924	.75	19.1	.575	14.6	13	2.3	.47	12	6.0	27	.20	5.0	0.048	1.2	4.00	SST	CG	N
0.671	17.04	S-1452	.75	19.1	.527	13.4	52	9.1	.34	8.6	18	79	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.671	17.04	2911	.81	20.6	.489	12.4	238	42	.15	3.8	36	160	.38	9.5	0.091	2.3	4.00	SPR	CG	Z
0.671	17.04	K-59A	.88	22.2	.543	13.8	31	5.4	.46	12	14	63	.42	10.6	0.064	1.6	5.50	SPR	C	Z
0.671	17.04	N-127	.88	22.2	.487	12.4	134	24	.26	6.5	34	153	.51	12.9	0.092	2.3	5.50	SST	CG	N
0.671	17.04	XX-19	.94	23.8	.561	14.2	9.4	1.6	.44	11	4.2	18	.50	12.6	0.055	1.4	8.00	SPR	C	Z
0.671	17.04	10010	1.06	27.0	.527	13.4	42	7.4	.45	11	19	84	.52	13.3	0.072	1.8	6.25	HD	C	Z
0.671	17.04	B7-70	1.09	27.8	.603	15.3	1.5	.26	.86	22	1.3	5.7	.24	6.0	0.034	0.9	7.00	SPR	CG	N
0.671	17.04	10467	1.13	28.6	.611	15.5	1.0	.18	.91	23	.94	4.2	.22	5.5	0.030	0.8	6.25	MW	C	Z
0.671	17.04	RR-66	1.13	28.6	.563	14.3	9.1	1.6	.75	19	6.8	30	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.671	17.04	BB-66	1.13	28.6	.511	13.0	51	8.9	.48	12	24	107	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.671	17.04	3758	1.13	28.6	.451	11.5	207	36	.27	6.9	56	251	.85	21.7	0.110	2.8	7.75	SPR	CG	Z
0.671	17.04	10725	1.19	30.2	.537	13.6	33	5.8	.49	12	16	72	.40	10.2	0.067	1.7	6.00	SPR	CG	GI
0.671	17.04	11316	1.19	30.2	.511	13.0	63	11	.41	10	26	114	.52	13.2	0.080	2.0	6.50	SPR	CG	Z
0.671	17.04	S-784	1.25	31.8	.589	15.0	3.5	.62	1.0	26	3.5	16	.25	6.2	0.041	1.0	6.00	SST	CG	N
0.671	17.04	2999	1.25	31.8	.563	14.3	11	1.9	.78	20	8.5	38	.36	9.3	0.054	1.4	6.75	SPR	CG	Z
0.671	17.04	J-38	1.25	31.8	.563	14.3	9.5	1.7	.84	21	8.0	36	.36	9.3	0.054	1.4	6.75	SST	CG	N
0.671	17.04	4270	1.25	31.8	.555	14.1	8.6	1.5	.60	15	5.1	23	.65	16.6	0.058	1.5	10.3	SPR	C	Z
0.671	17.04	3275	1.25	31.8	.487	12.4	106	19	.35	8.9	37	165	.74	18.7	0.092	2.3	7.00	SPR	C	Z
0.671	17.04	12582	1.30	32.9	.475	12.1	141	25	.32	8.0	45	199	.78	19.9	0.098	2.5	7.00	SPR	C	N
0.671	17.04	10837	1.44	36.5	.607	15.4	1.3	.22	1.2	30	1.5	6.8	.24	6.1	0.032	0.8	6.50	SPR	C	Z
0.671	17.04	4262	1.44	36.5	.527	13.4	40	7.0	.47	12	19	84	.47	11.9	0.072	1.8	6.50	SPR	CG	Z
0.671	17.04	S-786	1.50	38.1	.563	14.3	9.1	1.6	.88	22	8.0	36	.43	11.0	0.054	1.4	7.00	SST	C	N
0.671	17.04	2577	1.50	38.1	.561	14.2	8.3	1.5	1.0	26	8.5	38	.48	12.2	0.055	1.4	8.75	MW	CG	GI
0.671	17.04	2858	1.50	38.1	.561	14.2	8.3	1.5	1.0	26	8.5	38	.48	12.2	0.055	1.4	8.75	MW	CG	GI
0.671	17.04	2693	1.50	38.1	.527	13.4	31	5.5	.84	21	26	117	.56	14.2	0.072	1.8	7.75	MW	CG	GI
0.671	17.04	S-1468	1.50	38.1	.511	13.0	41	7.2	.58	15	24	107	.64	16.3	0.080	2.0	8.00	SST	CG	N
0.671	17.04	10701	1.50	38.1	.489	12.4	72	13	.50	13	36	160	.82	20.8	0.091	2.3	9.00	SPR	CG	Z
0.671	17.04	B10-69	1.56	39.7	.601	15.3	1.3	.23	1.3	32	1.6	7.3	.30	7.6	0.035	0.9	8.50	SPR	CG	Z
0.671	17.04	O-116	1.56	39.7	.563	14.3	5.8	1.0	.91	23	5.3	24	.65	16.5	0.054	1.4	11.0	SPR	C	Z
0.671	17.04	10757	1.56	39.7	.467	11.9	109	19	.46	12	50	223	.99	25.3	0.102	2.6	9.75	SPR	CG	N
0.671	17.04	11703	1.59	40.5	.561	14.2	9.4	1.6	.96	24	9.0	40	.44	11.2	0.055	1.4	8.00	SPR	CG	Z
0.671	17.04	3319	1.63	41.3	.511	13.0	29	5.0	.67	17	19	84	.96	24.4	0.080	2.0	12.0	SPR	CG	Z
0.671	17.04	S-104	1.69	42.8	.431	10.9	226	40	.31	7.9	71	314	1.08	27.4	0.120	3.0	9.00	SST	CG	N
0.671	17.04	B2-61	1.73	43.9	.563	14.3	12	2.0	.74	19	8.5	38	.41	10.3	0.054	1.4	6.50	SPR	C	GI
0.671	17.04	S-13	1.75	44.5	.577	14.7	4.6	.80	1.2	31	5.7	25	.40	10.1	0.047	1.2	7.50	SST	C	N
0.671	17.04	3893	1.75	44.5	.543	13.8	13	2.4	1.0	26	14	63	.70	17.9	0.064	1.6	10.0	SPR	C	Z
0.671	17.04	3698	1.81	46.0	.559	14.2	7.6	1.3	1.2	30	9.1	40	.62	15.6	0.056	1.4	10.0	SPR	C	Z
0.671	17.04	10682	1.84	46.8	.447	11.4	167	29	.38	9.7	64	283	1.09	27.7	0.112	2.8	9.75	SPR	CG	Z
0.671	17.04	10545	1.84	46.8	.441	11.2	183	32	.37	9.5	69	305	1.15	29.2	0.115	2.9	10.0	SPR	CG	Z
0.671	17.04	25	1.88	47.6	.511	13.0	30	5.3	.86	22	26	114	1.00	25.4	0.080	2.0	11.5	HD	C	Z
0.671	17.04	10357	1.88	47.6	.431	10.9	210	37	.37	9.4	77	344	1.26	32.0	0.120	3.0	10.5	SPR	CG	Z
0.671	17.04	S-1541	1.91	48.4	.583	14.8	1.9	.33	1.4	35	2.6	12	.53	13.4	0.044	1.1	12.0	SST	CG	N
0.671	17.04	S-360	1.91	48.4	.511	13.0	31	5.4	.78	20	24	107	.80	20.3	0.080	2.0	10.0	SST	CG	N
0.671	17.04	12518	1.94	49.2	.447	11.4	162	28	.39	10	64	283	1.23	31.3	0.112	2.8	10.0	SPR	C	N
0.671	17.04	S-64	2.00	50.8	.577	14.7	3.3	.59	1.6	39	5.2	23	.45	11.3	0.047	1.2	9.50	SST	CG	N
0.671	17.04	12086	2.00	50.8	.541	13.7	8.0	1.4	.93	24	7.4	33	1.07	27.2	0.065	1.7	16.5	SPR	CG	Z
0.671	17.04	12183	2.03	51.6	.517	13.1	24	4.2	.95	24	23	102	.92	23.5	0.077	2.0	12.0	SPR	CG	GI
0.671	17.04	10235	2.13	54.0	.445	11.3	135	24	.48	12	65	290	1.36	34.4	0.113	2.9	12.0	SPR	CG	GI
0.671	17.04	3036	2.22	56.4	.547	13.9	9.4	1.6	1.4	35	13	57	.74	18.9	0.062	1.6	12.0	SPR	CG	Z
0.671	17.04	B-20	2.31	58.7	.581	14.8	2.5	.44	1.8	46	4.5	20	.52	13.1	0.045	1.1	11.5	HD	CG	Z
0.671	17.04	12598	2.50	63.5	.581	14.8	2.7	.47	2.0	51	5.4	24	.50	12.6	0.045	1.1	11.0	MW	CG	N
0.671	17.04	11662	2.53	64.3	.563	14.3	5.2	.91	1.6	42	8.5	38	.65	16.5	0.054	1.4	12.0	SPR	CG	Z
0.671	17.04	S-808	2.56	65.1	.419	10.6	166	29	.49	12	81	361	1.73	44.0	0.126	3.2	13.8	SST	CG	N
0.671	17.04	4209	2.58	65.5	.569	14.5	8.2	1.4	.88	22	7.2	32	.41	10.4	0.051	1.3	7.00	SPR	CG	N
0.671	17.04	10562	2.91	73.8	.483	12.3	44	7.7	.90	23	40	176	1.53	38.8	0.094	2.4	15.3	SPR	C	Z
0.671	17.04	11744	3.00	76.2	.551	14.0	7.1	1.2	1.6	42	12	52	.87	22.1	0.060	1.5	13.5	SPR	C	Z
0.671	17.04	S-1363	3.31	84.1	.589	15.0	1.3	.24	2.8	71	3.8	17	.51	13.0	0.041	1.0	12.5	SST	CG	N
0.671	17.04	2613	3.50	88.9	.541	13.7	7.4	1.3	2.0	51	15	65	1.15	29.1	0.065	1.7	17.5	HD	CG	Z
0.671	17.04	11351	4.25	108.0	.611	15.5	.24	.04	3.7	14	.89	3.9	.16	4.0	0.030	0.8	18	SST	C	N
0.671	17.04	12013	5.00	127.0	.577	14.7	1.3	.22	4.0	101	5.1	23	1.03	26.3	0.047	1.2	22.0	SST	CG	N
0.671	17.04	11988	6.13	155.6	.575	14.6	1.0	.18	4.5	115	4.7	21	1.61	40.8	0.048	1.2	32.5	SPR	C	GI
0.671	17.04	1709	7.00	177.8	.511	13.0	8.8	1.5	2.9	74	26	114	2.76	70.1	0.080	2.0	34.5	SPR	CG	Z
0.671	17.04	12065	8.41	213.5	.551	14.0	7.2	1.3	1.6	41	12	52	.86	21.8	0.060	1.5	13.3	SPR	C	Z
0.687	17.45	S-334	.47	11.9	.637	16.2	1.3	.24	.36	9.2	.49	2.2	.11	2.7	0.025	0.6	3.25	SST	C	N
0.687	17.45	S-3120	.56	14.3	.639	16.2	.25	.04	.35	8.9	.09	.39	.21	5.3	0.024	0.6	7.75	SST	C	N
0.687	17.45	QQ-43	.63	15.9	.527	13.4	132	23	.19	4.9	25	112	.32	8.1	0.080	2.0	4.00	SPR	CG	Z
0.687	17.45	A-12	.63	15.9	.521	13.2	155	27	.18	4.6	28	125	.33	8.4	0.083	2.1	4.00	HD	CG	Z
0.687	17.45	K-52	.69	17.4	.579	14.7	19	3.4	.43	11	8.3	37	.24	6.2	0.054	1.4	4.50	SPR	CG	N
0.687	17.45	W-48	.72	18.2	.611	15.5	3.9	.68	.51	13	2.0	8.8	.21	5.3	0.038	1.0	4.50	SST	C	N
0.687	17.45	S-168	.72	18.2	.585	14.9	17	2.9	.39	10	6.6	29	.20	5.2	0.051	1.3	4.00	SST	CG	N
0.687	17.45	Q-57	.75	19.1	.607	15.4	3.9	.69	.51	13	2.0	8.9	.24	6.1	0.040	1.0	5.00	SST	C	N
0.687	17.45	2975	.75	19.1	.593	15.1	8.9	1.6	.52	13	4.6	20	.24	6.0	0.047	1.2	5.00	SPR	CG	Z
0.687	17.45	3250	.75	19.1	.589	15.0	16	2.8	.42	11	6.7	30	.25	6.2	0.049	1.2	4.00	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.687	17.45	I-52	.75	19.1	.503	12.8	163	29	.22	5.7	36	162	.46	11.7	0.092	2.3	5.00	SPR	CG	Z
0.687	17.45	S-1110	.81	20.6	.623	15.8	2.3	.41	.65	17	1.5	6.8	.16	4.1	0.032	0.8	4.00	SST	C	N
0.687	17.45	11348	.81	20.6	.579	14.7	11	2.0	.50	13	5.7	25	.31	7.9	0.054	1.4	5.75	SST	CG	N
0.687	17.45	2845	.81	20.6	.577	14.7	17	2.9	.53	13	8.8	39	.28	7.2	0.055	1.4	5.13	HD	CG	Z
0.687	17.45	S-1610	.81	20.6	.541	13.7	39	6.8	.37	9.5	15	65	.44	11.1	0.073	1.9	6.00	SST	CG	N
0.687	17.45	3849	.88	22.2	.571	14.5	20	3.5	.51	13	10	46	.36	9.2	0.058	1.5	5.25	SPR	C	Z
0.687	17.45	S-1299	.88	22.2	.553	14.0	38	6.7	.39	9.8	15	66	.32	8.1	0.067	1.7	4.75	SST	CG	N
0.687	17.45	Z-10	.91	23.0	.601	15.3	4.6	.81	.65	16	3.0	13	.26	6.6	0.043	1.1	6.00	SPR	CG	N
0.687	17.45	DD-40	.94	23.8	.627	15.9	1.0	.18	.73	18	.75	3.3	.21	5.3	0.030	0.8	6.00	MW	C	N
0.687	17.45	3949	.94	23.8	.563	14.3	18	3.2	.46	12	8.4	37	.48	12.2	0.062	1.6	6.75	SPR	C	Z
0.687	17.45	S-800	.97	24.6	.617	15.7	2.3	.40	.79	20	1.8	8.0	.18	4.4	0.035	0.9	5.00	SST	CG	N
0.687	17.45	12332	.97	24.6	.605	15.4	7.5	1.3	.52	13	3.9	18	.21	5.2	0.041	1.0	4.00	SPR	C	Z
0.687	17.45	11105	1.00	25.4	.617	15.7	3.1	.55	.81	21	2.5	11	.19	4.9	0.035	0.9	4.50	MW	C	Z
0.687	17.45	3654	1.00	25.4	.595	15.1	6.1	1.1	.72	18	4.4	20	.28	7.0	0.046	1.2	6.00	SPR	CG	Z
0.687	17.45	11345	1.00	25.4	.579	14.7	8.5	1.5	.62	16	5.3	24	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.687	17.45	3349	1.00	25.4	.573	14.6	14	2.5	.59	15	8.4	37	.41	10.5	0.057	1.4	6.25	HD	C	Z
0.687	17.45	3350	1.00	25.4	.571	14.5	15	2.5	.57	14	8.2	37	.44	11.0	0.058	1.5	6.50	SPR	C	Z
0.687	17.45	12148	1.00	25.4	.501	12.7	128	22	.29	7.4	38	167	.56	14.2	0.093	2.4	6.00	SPR	CG	Z
0.687	17.45	3943	1.00	25.4	.363	9.2	2281	399	.07	1.9	167	742	.81	20.6	0.162	4.1	5.00	SPR	CG	Z
0.687	17.45	MM-93	1.00	25.4	.307	7.8	5087	891	.05	1.2	244	1084	.95	24.1	0.190	4.8	5.00	SPR	CG	N
0.687	17.45	1950	1.03	26.2	.603	15.3	8.3	1.5	.51	13	4.2	19	.21	5.3	0.042	1.1	4.00	SPR	C	Z
0.687	17.45	AA-82	1.03	26.2	.547	13.9	43	7.6	.37	9.3	16	71	.42	10.7	0.070	1.8	5.00	SST	C	N
0.687	17.45	B5-38	1.09	27.8	.605	15.4	6.7	1.2	.59	15	3.9	18	.22	5.5	0.041	1.0	4.25	SPR	C	N
0.687	17.45	S-1291	1.13	28.6	.579	14.7	14	2.4	.56	14	7.8	35	.27	6.9	0.054	1.4	5.00	SST	CG	N
0.687	17.45	4117	1.13	28.6	.527	13.4	66	12	.38	9.7	25	112	.48	12.2	0.080	2.0	6.00	SPR	CG	Z
0.687	17.45	4221	1.13	28.6	.519	13.2	82	14	.36	9.0	29	129	.50	12.8	0.084	2.1	6.00	SPR	CG	Z
0.687	17.45	10079	1.13	28.6	.431	10.9	631	111	.14	3.7	91	406	.70	17.9	0.128	3.3	5.50	SPR	CG	Z
0.687	17.45	K-15	1.19	30.2	.579	14.7	7.1	1.2	.70	18	5.0	22	.49	12.3	0.054	1.4	8.00	SST	C	N
0.687	17.45	11312	1.19	30.2	.511	13.0	95	17	.33	8.3	31	139	.51	12.9	0.088	2.2	5.75	SST	CG	N
0.687	17.45	S-1624	1.22	31.0	.607	15.4	3.0	.53	.98	25	2.9	13	.24	6.1	0.040	1.0	6.00	SST	CG	N
0.687	17.45	11707	1.22	31.0	.569	14.5	13	2.2	.78	20	9.9	44	.44	11.2	0.059	1.5	7.50	SPR	CG	Z
0.687	17.45	S-961	1.22	31.0	.561	14.2	20	3.5	.61	15	12	55	.38	9.6	0.063	1.6	6.00	SST	CG	N
0.687	17.45	3114	1.25	31.8	.579	14.7	11	1.9	.75	19	8.3	37	.40	10.1	0.054	1.4	6.25	SPR	C	Z
0.687	17.45	Z-41	1.25	31.8	.579	14.7	8.4	1.5	.87	22	7.3	33	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.687	17.45	S-1471	1.25	31.8	.563	14.3	19	3.3	.62	16	12	52	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.687	17.45	I-32	1.25	31.8	.559	14.2	20	3.5	.69	18	14	61	.45	11.4	0.064	1.6	7.00	SPR	CG	Z
0.687	17.45	10295	1.25	31.8	.557	14.1	28	5.0	.51	13	14	64	.37	9.5	0.065	1.7	5.75	SPR	CG	Z
0.687	17.45	505	1.25	31.8	.543	13.8	39	6.8	.47	12	18	82	.52	13.3	0.072	1.8	6.25	HD	C	Z
0.687	17.45	B8-58	1.25	31.8	.537	13.6	35	6.2	.55	14	20	87	.53	13.3	0.075	1.9	7.00	SST	CG	N
0.687	17.45	28	1.25	31.8	.505	12.8	89	16	.40	10	35	157	.75	19.1	0.091	2.3	7.25	HD	C	Z
0.687	17.45	11192	1.31	33.3	.505	12.8	67	12	.49	13	33	146	.82	20.8	0.091	2.3	9.00	HD	CG	Z
0.687	17.45	11680	1.31	33.3	.461	11.7	248	43	.26	6.5	64	284	.79	20.1	0.113	2.9	7.00	SPR	CG	Z
0.687	17.45	12025	1.34	34.1	.481	12.2	162	28	.31	7.9	50	225	.82	20.9	0.103	2.6	7.00	SPR	C	Z
0.687	17.45	11367	1.38	34.9	.527	13.4	41	7.1	.58	15	24	105	.62	15.7	0.080	2.0	7.75	SST	CG	N
0.687	17.45	EE-94	1.38	34.9	.447	11.4	327	57	.23	5.9	76	337	.84	21.3	0.120	3.0	7.00	SPR	CG	Z
0.687	17.45	S-267	1.44	36.5	.623	15.8	.67	.12	1.2	29	.77	3.4	.29	7.3	0.032	0.8	9.00	SST	CG	N
0.687	17.45	S-950	1.44	36.5	.601	15.3	3.8	.66	1.1	29	4.2	19	.27	6.8	0.043	1.1	6.25	SST	CG	N
0.687	17.45	S-1004	1.50	38.1	.607	15.4	2.4	.41	1.2	31	2.9	13	.28	7.1	0.040	1.0	7.00	SST	CG	N
0.687	17.45	S-1357	1.50	38.1	.605	15.4	4.0	.71	.91	23	3.7	16	.22	5.5	0.041	1.0	5.25	SST	CG	N
0.687	17.45	S-1424	1.50	38.1	.585	14.9	8.2	1.4	.80	20	6.6	29	.36	9.1	0.051	1.3	6.00	SST	C	N
0.687	17.45	2734	1.50	38.1	.561	14.2	21	3.6	.88	22	18	81	.41	10.4	0.063	1.6	6.50	MW	CG	GI
0.687	17.45	S-1387	1.50	38.1	.553	14.0	21	3.7	.70	18	15	66	.47	11.9	0.067	1.7	7.00	SST	CG	N
0.687	17.45	B9-49	1.50	38.1	.551	14.0	26	4.5	.63	16	16	73	.48	12.1	0.068	1.7	7.00	SPR	CG	N
0.687	17.45	11537	1.50	38.1	.543	13.8	28	4.8	.67	17	18	82	.65	16.5	0.072	1.8	8.00	SPR	C	Z
0.687	17.45	11649	1.50	38.1	.537	13.6	33	5.8	.63	16	21	93	.60	15.2	0.075	1.9	8.00	SPR	CG	GI
0.687	17.45	11611	1.50	38.1	.517	13.1	69	12	.44	11	30	134	.68	17.3	0.085	2.2	7.00	SPR	CG	Z
0.687	17.45	A-64	1.50	38.1	.477	12.1	118	21	.45	11	53	237	1.00	25.3	0.105	2.7	9.50	SPR	CG	N
0.687	17.45	2910	1.50	38.1	.447	11.4	252	44	.30	7.7	76	337	1.02	25.9	0.120	3.0	8.50	SPR	CG	Z
0.687	17.45	S-276	1.50	38.1	.447	11.4	219	38	.32	8.0	69	308	1.02	25.9	0.120	3.0	8.50	SST	CG	N
0.687	17.45	KK-75	1.53	38.9	.507	12.9	42	7.3	.81	21	34	152	.70	17.7	0.090	2.3	7.75	PB	CG	N
0.687	17.45	1917	1.56	39.7	.497	12.6	87	15	.46	12	40	178	.81	20.5	0.095	2.4	8.50	SPR	CG	Z
0.687	17.45	12172	1.63	41.3	.567	14.4	7.6	1.3	.91	23	6.8	30	.72	18.3	0.060	1.5	12.0	SPR	CG	Z
0.687	17.45	B9-54	1.63	41.3	.545	13.8	31	5.5	.57	14	18	79	.57	14.4	0.071	1.8	7.00	SPR	C	N
0.687	17.45	S-3107	1.63	41.3	.503	12.8	61	11	.56	14	34	150	.92	23.4	0.092	2.3	9.00	SST	C	N
0.687	17.45	12099	1.63	41.3	.475	12.1	103	18	.46	12	47	210	1.17	29.6	0.106	2.7	11.0	SPR	CG	Z
0.687	17.45	AA-62	1.63	41.3	.427	10.8	380	67	.24	6.2	93	412	1.07	27.2	0.130	3.3	8.25	SPR	CG	N
0.687	17.45	11559	1.69	42.8	.565	14.4	12	2.0	1.0	26	12	53	.61	15.5	0.061	1.5	9.00	SPR	CG	Z
0.687	17.45	10872	1.75	44.5	.619	15.7	1.1	.20	1.4	37	1.7	7.4	.31	7.8	0.034	0.9	8.00	SPR	C	Z
0.687	17.45	11865	1.75	44.5	.571	14.5	8.0	1.4	1.2	29	9.2	41	.59	15.1	0.058	1.5	9.25	SST	C	N
0.687	17.45	S-71	1.81	46.0	.503	12.8	54	9.5	.62	16	34	150	.92	23.4	0.092	2.3	10.0	SST	CG	N
0.687	17.45	10416	1.81	46.0	.391	9.9	734	129	.18	4.6	133	593	1.18	30.1	0.148	3.8	8.00	SPR	CG	N
0.687	17.45	B2-65	1.84	46.7	.527	13.4	41	7.1	.62	16	25	112	.76	19.3	0.080	2.0	8.50	SPR	CL	N
0.687	17.45	11111	1.88	47.6	.505	12.8	36	6.3	.42	11	15	67	1.46	37.0	0.091	2.3	15.0	HD	C	Z
0.687	17.45	12596	1.91	48.4	.583	14.8	4.4	.78	1.3	32	5.6	25	.64	16.2	0.052	1.3	11.3	MW	C	N
0.687	17.45	S-1620	1.91	48.4	.521	13.2	34	6.0	.77	19	26	117	.83	21.1	0.083	2.1	10.0	SST	CG	N
0.687	17.45	I-60	1.94	49.2	.563	14.3	9.5	1.7	1.2	32	12	52	.62	15.7	0.062	1.6	10.0	SST	CG	N
0.687	17.45	10468	1.94	49.2	.503	12.8	49	8.6	.74	19	36	161	1.20	30.4	0.092	2.3	12.0	SPR	C	Z
0.687	17.45	12595	2.00	50.8	.593	15.1	2.7	.48	1.4	37	4.0	18	.55	14.0	0.047	1.2	11.8	MW	CG	N
0.687	17.45	2580	2.00	50.8	.579	14.7	6.9	1.2	1.5	38	10	46	.49	12.3	0.054	1.4	9.00	MW	CG	Z
0.687	17.45	GG-79	2.00	50.8	.547	13.9	10	1.8	.88	22	9.2	41	1.12	28.4	0.070	1.8	16.0	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.687	17.45	12220	2.00	50.8	.525	13.3	46	8.1	.56	14	26	116	.73	18.5	0.081	2.1	8.00	SPR	C	Z
0.687	17.45	3022	2.06	52.4	.477	12.1	104	18	.51	13	53	237	1.21	30.7	0.105	2.7	10.5	SPR	C	Z
0.687	17.45	3039	2.13	54.0	.567	14.4	9.4	1.7	1.2	31	11	51	.60	15.2	0.060	1.5	10.0	SPR	CG	Z
0.687	17.45	3097	2.13	54.0	.527	13.4	38	6.6	.67	17	25	112	.72	18.3	0.080	2.0	9.00	SPR	CG	Z
0.687	17.45	3964	2.19	55.6	.573	14.6	6.7	1.2	1.4	37	9.8	43	.63	15.9	0.057	1.4	11.0	SPR	CG	Z
0.687	17.45	S-3138	2.25	57.2	.567	14.4	8.2	1.4	1.3	33	11	48	.60	15.2	0.060	1.5	10.0	SST	CG	N
0.687	17.45	10012	2.25	57.2	.531	13.5	39	6.9	.60	15	23	104	.70	17.8	0.078	2.0	8.00	SPR	C	Z
0.687	17.45	S-59	2.28	57.9	.535	13.6	19	3.3	1.1	28	20	90	.91	23.2	0.076	1.9	12.0	SST	CG	N
0.687	17.45	10411	2.38	60.3	.579	14.7	9.6	1.7	.86	22	8.3	37	.38	9.6	0.054	1.4	7.00	SPR	CG	Z
0.687	17.45	B8-43	2.38	60.3	.569	14.5	4.5	.78	1.4	36	6.4	28	.94	24.0	0.059	1.5	16.0	SST	CG	N
0.687	17.45	11984	2.38	60.3	.511	13.0	43	7.5	.77	20	33	148	1.00	25.3	0.088	2.2	11.3	SPR	CG	Z
0.687	17.45	11972	2.41	61.1	.565	14.4	6.8	1.2	1.6	39	10	47	.85	21.7	0.061	1.5	14.0	SPR	CG	Z
0.687	17.45	11296	2.50	63.5	.611	15.5	.93	.16	1.9	49	1.8	8.1	.56	14.2	0.038	1.0	13.8	MW	C	Z
0.687	17.45	S-372	2.50	63.5	.575	14.6	4.6	.80	1.8	45	8.2	37	.71	18.0	0.056	1.4	12.7	SST	CG	N
0.687	17.45	S-1592	2.50	63.5	.573	14.6	4.9	.86	1.8	45	8.7	39	.73	18.5	0.057	1.4	12.8	SST	CG	N
0.687	17.45	11687	2.50	63.5	.569	14.5	8.3	1.4	1.3	33	11	48	.62	15.7	0.059	1.5	10.5	SPR	CG	Z
0.687	17.45	12022	2.50	63.5	.559	14.2	9.1	1.6	1.5	39	14	61	.83	21.1	0.064	1.6	13.0	SPR	CG	Z
0.687	17.45	2739	2.50	63.5	.417	10.6	270	47	.38	9.7	103	458	1.69	42.9	0.135	3.4	12.5	SPR	CG	Z
0.687	17.45	S-3250	2.53	64.3	.571	14.5	3.4	.60	1.4	36	4.9	22	1.10	28.0	0.058	1.5	19.0	SST	CG	N
0.687	17.45	B17-165	2.53	64.3	.543	13.8	12	2.1	1.4	35	16	72	1.15	29	0.072	1.8	16.0	HD	CG	N
0.687	17.45	10654	2.59	65.9	.569	14.5	4.5	.78	1.6	42	7.3	33	.94	24.0	0.059	1.5	16.0	SST	CG	N
0.687	17.45	2998	2.66	67.5	.623	15.8	.44	.08	2.2	55	.95	4.2	.49	12.4	0.032	0.8	14.3	MW	C	Z
0.687	17.45	12282	2.69	68.2	.603	15.3	2.8	.49	1.5	39	4.2	19	.38	9.6	0.042	1.1	8.00	SPR	C	Z
0.687	17.45	3674	2.69	68.2	.495	12.6	46	8.1	.89	23	41	183	1.42	36.0	0.096	2.4	14.8	SPR	CG	Z
0.687	17.45	10556	2.75	69.9	.601	15.3	1.9	.34	2.3	57	4.4	19	.50	12.6	0.043	1.1	11.5	SPR	CG	Z
0.687	17.45	DD-86	2.75	69.9	.547	13.9	11	1.9	1.5	37	16	71	.98	24.9	0.070	1.8	14.0	SST	CG	N
0.687	17.45	12221	2.78	70.6	.515	13.1	40	7.0	.77	20	31	138	.95	24.0	0.086	2.2	11.0	SPR	CG	Z
0.687	17.45	12416	2.91	73.8	.529	13.4	26	4.6	.93	23	24	108	.99	25.1	0.079	2.0	11.5	SPR	C	N
0.687	17.45	4375	2.97	75.4	.505	12.8	33	5.8	1.1	27	35	157	1.46	37.0	0.091	2.3	16.0	SPR	CG	Z
0.687	17.45	18	3.00	76.2	.593	15.1	3.0	.52	2.0	50	5.9	26	.56	14.3	0.047	1.2	11.0	HD	C	Z
0.687	17.45	3353	3.00	76.2	.543	13.8	12	2.2	1.5	38	18	82	1.19	30.2	0.072	1.8	15.5	HD	C	Z
0.687	17.45	12023	3.25	82.6	.555	14.1	8.4	1.5	1.8	45	15	67	1.02	26.0	0.066	1.7	15.5	SPR	CG	Z
0.687	17.45	3206	3.31	84.1	.613	15.6	.70	.12	2.7	68	1.9	8.4	.63	16.0	0.037	0.9	16.0	SPR	C	Z
0.687	17.45	3089	3.31	84.1	.593	15.1	1.8	.32	2.5	63	4.4	20	.84	21.3	0.047	1.2	17.0	SPR	C	Z
0.687	17.45	11416	3.38	85.7	.605	15.4	1.7	.30	2.3	58	3.9	18	.48	12.2	0.041	1.0	10.8	HD	C	Z
0.687	17.45	506	3.63	92.1	.543	13.8	10	1.8	1.8	45	18	82	1.37	34.7	0.072	1.8	18.0	HD	C	Z
0.687	17.45	35	4.00	101.6	.477	12.1	42	7.3	1.3	33	53	237	2.44	62.0	0.105	2.7	23.3	HD	CG	Z
0.687	17.45	12187	4.41	111.9	.527	13.4	16	2.9	1.5	39	25	112	1.44	36.6	0.080	2.0	18.0	SPR	CG	Z
0.687	17.45	3925	4.50	114.3	.577	14.7	4.7	.83	1.9	47	8.8	39	.77	19.6	0.055	1.4	13.0	SPR	C	Z
0.687	17.45	11529	4.63	117.5	.571	14.5	3.9	.68	2.6	67	10	46	1.15	29.1	0.058	1.5	18.8	SPR	CG	Z
0.687	17.45	10707	4.63	117.5	.543	13.8	7.2	1.3	2.6	65	18	82	1.80	45.7	0.072	1.8	25.0	SPR	CG	Z
0.687	17.45	11821	5.25	133.4	.507	12.9	15	2.6	2.3	59	34	152	2.88	73.2	0.090	2.3	32.0	SPR	CG	Z
0.687	17.45	358	5.75	146.1	.543	13.8	6.4	1.1	2.9	73	18	82	2.07	52.6	0.072	1.8	27.8	HD	C	Z
0.687	17.45	364	6.00	152.4	.543	13.8	6.2	1.1	3.0	76	18	82	2.16	54.9	0.072	1.8	29.0	HD	C	Z
0.687	17.45	2836	6.56	166.7	.537	13.6	6.0	1.1	3.9	100	24	105	2.63	66.7	0.075	1.9	35.0	MW	CG	GI
0.687	17.45	3961	9.50	241.3	.543	13.8	4.4	.78	4.2	106	18	82	2.92	74.1	0.072	1.8	39.5	SPR	C	Z
0.687	17.45	12592	12.1	308.0	.425	10.8	38	6.7	2.5	62	95	421	8.65	219.6	0.131	3.3	66.0	SPR	CG	Z
0.687	17.45	3384	16.0	406.4	.563	14.3	1.6	.28	7.7	196	13	56	3.50	89.0	0.062	1.6	55.5	HD	C	Z
0.687	17.45	512	16.0	406.4	.563	14.3	1.3	.23	9.5	241	13	56	4.28	108.7	0.062	1.6	68.0	HD	C	Z
0.690	17.53	71925	.69	17.5	.588	14.9	107	19	.09	2.3	9.7	43	.12	3.1	0.051	1.3	2.38	MW	CG	N
0.690	17.53	71925S	.69	17.5	.588	14.9	91	16	.07	1.8	6.6	29	.12	3.1	0.051	1.3	2.38	SST	CG	N
0.703	17.86	JJ-55	.50	12.7	.635	16.1	4.5	.78	.36	9.0	1.6	7.1	.14	3.7	0.034	0.9	3.25	SST	C	N
0.703	17.86	Q-53	.50	12.7	.635	16.1	2.5	.43	.32	8.2	.80	3.5	.18	4.5	0.034	0.9	4.25	SST	C	N
0.703	17.86	S-489	.50	12.7	.621	15.8	4.1	.71	.25	6.5	1.0	4.6	.25	6.2	0.041	1.0	5.00	SST	C	N
0.703	17.86	K-12	.50	12.7	.503	12.8	656	115	.07	1.8	45	202	.30	7.6	0.100	2.5	3.00	SPR	CG	N
0.703	17.86	MM-41	.53	13.5	.603	15.3	19	3.3	.32	8.1	6.1	27	.18	4.4	0.050	1.3	3.50	SST	CG	N
0.703	17.86	S-795	.59	15.1	.609	15.5	11	1.9	.41	10	4.4	19	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.703	17.86	4144	.63	15.9	.605	15.4	9.9	1.7	.33	8.4	3.3	15	.29	7.5	0.049	1.2	5.00	SPR	C	Z
0.703	17.86	I-62	.63	15.9	.595	15.1	19	3.4	.39	10	7.7	34	.22	5.5	0.054	1.4	4.00	SST	CG	N
0.703	17.86	OO-68	.66	16.7	.443	11.3	1091	191	.08	2.1	91	404	.52	13.2	0.130	3.3	4.00	SPR	CG	Z
0.703	17.86	QQ-42	.69	17.4	.643	16.3	.95	.17	.48	12	.46	2.0	.21	5.3	0.030	0.8	6.00	MW	C	Z
0.703	17.86	Q-64	.69	17.4	.621	15.8	5.0	.87	.46	12	2.3	10	.23	5.7	0.041	1.0	4.50	SST	C	N
0.703	17.86	PP-79	.69	17.4	.559	14.2	53	9.4	.32	8.0	17	75	.32	8.2	0.072	1.8	4.50	SST	CG	N
0.703	17.86	3846	.75	19.1	.645	16.4	.83	.15	.55	14	.45	2.0	.20	5.2	0.029	0.7	6.00	MW	C	Z
0.703	17.86	4224	.75	19.1	.623	15.8	4.2	.74	.55	14	2.3	10	.20	5.1	0.040	1.0	5.00	SPR	CG	Z
0.703	17.86	3880	.75	19.1	.579	14.7	40	7.1	.30	7.7	12	54	.31	7.9	0.062	1.6	4.00	HD	C	Z
0.703	17.86	2516	.75	19.1	.557	14.1	82	14	.32	8.2	26	117	.29	7.4	0.073	1.9	4.00	MW	CG	Z
0.703	17.86	EE-70	.75	19.1	.463	11.8	534	93	.13	3.2	68	302	.54	13.7	0.120	3.0	4.50	SST	CG	N
0.703	17.86	10427	.78	19.8	.653	16.6	.72	.13	.64	16	.46	2.1	.14	3.5	0.025	0.6	4.50	MW	C	Z
0.703	17.86	XX-53	.81	20.6	.579	14.7	18	3.1	.35	8.8	6.2	28	.47	11.8	0.062	1.6	6.50	SPR	C	Z
0.703	17.86	12216	.84	21.4	.621	15.8	7.0	1.2	.55	14	3.8	17	.21	5.2	0.041	1.0	4.00	SPR	C	Z
0.703	17.86	11429	.88	22.2	.503	12.8	166	29	.25	6.4	42	187	.55	14.0	0.100	2.5	5.50	SST	CG	N
0.703	17.86	H-32	1.00	25.4	.629	16.0	1.4	.25	.71	18	1.0	4.5	.29	7.3	0.037	0.9	7.75	SST	CG	N
0.703	17.86	K-21	1.00	25.4	.621	15.8	6.1	1.1	.59	15	3.6	16	.16	4.2	0.041	1.0	4.00	SST	CG	N
0.703	17.86	S-368	1.00	25.4	.559	14.2	27	4.7	.50	13	13	59	.50	12.8	0.072	1.8	7.00	SST	CG	N
0.703	17.86	3590	1.00	25.4	.521	13.2	108	19	.32	8.1	34	153	.55	13.9	0.091	2.3	6.00	HD	CG	Z
0.703	17.86	3916	1.00	25.4	.519	13.2	113	20	.32	8.0	36	158	.55	14.0	0.092	2.3	6.00	SPR	CG	Z
0.703	17.86	H-14	1.03	26.2	.541	13.7	38	6.7	.38	9.7	15	65	.65	16.5	0.081	2.1	8.00	SST	CG	N
0.703	17.86	11739	1.03	26.2	.519	13.2	150	26	.24	6.0	36	158	.55	14.0	0.092	2.3	5.00	SPR	C	Z
0.703	17.86	LL-62	1.03	26.2	.443	11.3	546	96	.17	4.2	91	404	.78	19.8	0.130	3.3	6.00	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.703	17.86	10471	1.06	27.0	.507	12.9	141	25	.30	7.7	43	190	.61	15.6	0.098	2.5	6.25	SPR	CG	Z
0.703	17.86	10526	1.06	27.0	.391	9.9	1300	228	.11	2.9	148	658	.94	23.8	0.156	4.0	6.00	SPR	CG	N
0.703	17.86	11760	1.09	27.8	.453	11.5	428	75	.20	5.0	84	372	.78	19.8	0.125	3.2	6.25	SPR	CG	Z
0.703	17.86	2575	1.09	27.8	.443	11.3	513	90	.25	6.3	127	565	.81	20.7	0.130	3.3	6.25	MW	CG	Z
0.703	17.86	B15-23	1.13	28.6	.575	14.6	26	4.6	.51	13	13	60	.35	8.9	0.064	1.6	5.50	SPR	CG	N
0.703	17.86	S-12	1.13	28.6	.573	14.6	14	2.5	.61	15	8.7	39	.52	13.2	0.065	1.7	8.00	SST	CG	N
0.703	17.86	S-1247	1.13	28.6	.533	13.5	65	11	.42	11	28	123	.53	13.5	0.085	2.2	6.25	SST	CG	N
0.703	17.86	2644	1.13	28.6	.453	11.5	485	85	.17	4.4	84	372	.72	18.3	0.125	3.2	5.75	SPR	CG	Z
0.703	17.86	A10-46	1.13	28.6	.427	10.8	680	119	.16	4.0	108	478	.86	21.9	0.138	3.5	6.25	SPR	CG	Z
0.703	17.86	2573	1.19	30.2	.639	16.2	1.2	.22	.96	24	1.2	5.3	.22	5.7	0.032	0.8	6.00	HD	C	Z
0.703	17.86	11878	1.19	30.2	.601	15.3	6.2	1.1	.83	21	5.2	23	.36	9.1	0.051	1.3	7.00	SST	CG	N
0.703	17.86	11293	1.19	30.2	.533	13.5	79	14	.37	9.4	29	131	.51	13.0	0.085	2.2	6.00	SPR	CG	Z
0.703	17.86	3951	1.25	31.8	.613	15.6	6.9	1.2	.74	19	5.1	23	.23	5.7	0.045	1.1	5.00	SPR	CG	Z
0.703	17.86	AA-69	1.25	31.8	.543	13.8	62	11	.37	9.5	23	103	.44	11.2	0.080	2.0	5.50	SST	CG	N
0.703	17.86	2676	1.25	31.8	.517	13.1	118	21	.43	11	51	229	.65	16.5	0.093	2.4	6.00	MW	C	Z
0.703	17.86	B11-66	1.25	31.8	.453	11.5	428	75	.20	5.0	84	372	.78	19.8	0.125	3.2	6.25	SPR	CG	Z
0.703	17.86	11943	1.28	32.5	.567	14.4	30	5.3	.54	14	16	72	.41	10.4	0.068	1.7	6.00	SPR	CG	Z
0.703	17.86	10139	1.31	33.3	.569	14.5	28	4.9	.55	14	15	68	.47	11.9	0.067	1.7	6.00	SPR	C	Z
0.703	17.86	10920	1.31	33.3	.513	13.0	83	15	.47	12	39	174	.78	19.9	0.095	2.4	8.25	SPR	CG	Z
0.703	17.86	3164	1.34	34.1	.575	14.6	15	2.7	.77	19	12	53	.58	14.6	0.064	1.6	8.00	SPR	C	Z
0.703	17.86	S-1680	1.41	35.7	.623	15.8	2.6	.46	1.1	28	2.9	13	.29	7.4	0.040	1.0	6.25	SST	C	N
0.703	17.86	10631	1.41	35.7	.619	15.7	2.7	.48	1.1	28	3.1	14	.29	7.5	0.042	1.1	7.00	SST	CG	N
0.703	17.86	11378	1.41	35.7	.559	14.2	24	4.2	.71	18	17	75	.56	14.2	0.072	1.8	7.75	SST	CG	N
0.703	17.86	3517	1.44	36.5	.559	14.2	24	4.1	.76	19	18	80	.61	15.5	0.072	1.8	8.50	HD	CG	Z
0.703	17.86	AA-76	1.44	36.5	.483	12.3	168	29	.34	8.7	58	258	.88	22.4	0.110	2.8	8.00	SPR	CG	N
0.703	17.86	A10-67	1.50	38.1	.631	16.0	1.8	.32	1.2	32	2.3	10	.25	6.4	0.036	0.9	6.00	SST	C	N
0.703	17.86	A15-62	1.50	38.1	.617	15.7	4.7	.82	.89	23	4.2	18	.23	5.7	0.043	1.1	5.25	SST	CG	N
0.703	17.86	11675	1.50	38.1	.583	14.8	14	2.5	.79	20	11	49	.42	10.7	0.060	1.5	7.00	SPR	CG	GI
0.703	17.86	S-1289	1.50	38.1	.579	14.7	16	2.7	.74	19	12	51	.40	10.2	0.062	1.6	6.50	SST	CG	N
0.703	17.86	B12-60	1.50	38.1	.571	14.5	22	3.9	.66	17	15	66	.51	13.0	0.066	1.7	6.75	SPR	C	Z
0.703	17.86	S-1309	1.50	38.1	.569	14.5	20	3.4	.74	19	14	64	.47	11.9	0.067	1.7	7.00	SST	CG	N
0.703	17.86	12141	1.50	38.1	.569	14.5	23	3.9	.68	17	15	68	.47	11.9	0.067	1.7	7.00	SPR	CG	Z
0.703	17.86	3581	1.50	38.1	.559	14.2	29	5.1	.86	22	25	112	.52	13.3	0.072	1.8	7.25	MW	CG	Z
0.703	17.86	GG-100	1.50	38.1	.553	14.0	17	2.9	.45	11	7.5	33	1.05	26.7	0.075	1.9	13.0	SPR	C	GI
0.703	17.86	1711	1.50	38.1	.521	13.2	123	22	.28	7.1	34	153	.50	12.7	0.091	2.3	5.50	SPR	CG	Z
0.703	17.86	3559	1.50	38.1	.507	12.9	92	16	.65	17	60	266	.83	21.2	0.098	2.5	8.50	MW	CG	Z
0.703	17.86	3813	1.63	41.3	.519	13.2	56	9.9	.63	16	36	158	.92	23.4	0.092	2.3	10.0	SPR	CG	Z
0.703	17.86	S-1000	1.66	42.1	.641	16.3	.67	.12	1.4	36	.96	4.2	.24	6.1	0.031	0.8	7.75	SST	CG	N
0.703	17.86	S-251	1.75	44.5	.519	13.2	49	8.6	.67	17	33	147	.92	23.4	0.092	2.3	10.0	SST	CG	N
0.703	17.86	S-280	1.78	45.2	.521	13.2	48	8.3	.67	17	32	142	.91	23.1	0.091	2.3	10.0	SST	CG	N
0.703	17.86	4263	1.81	46.0	.579	14.7	10	1.8	1.1	29	11	51	.68	17.3	0.062	1.6	10.0	SPR	C	Z
0.703	17.86	12501	1.86	47.2	.543	13.8	36	6.3	.68	17	25	110	.78	19.8	0.080	2.0	8.75	SPR	C	N
0.703	17.86	12557	1.91	48.4	.545	13.8	14	2.5	.39	9.8	5.5	24	1.52	38.6	0.079	2.0	18.3	MW	C	N
0.703	17.86	4348	1.94	49.2	.521	13.2	49	8.6	.70	18	34	153	.98	24.8	0.091	2.3	10.8	SPR	CG	Z
0.703	17.86	4373	1.94	49.2	.521	13.2	51	8.9	.68	17	34	153	.96	24.3	0.091	2.3	10.5	SPR	CG	Z
0.703	17.86	10573	1.97	50.0	.573	14.6	12	2.1	1.1	28	13	59	.60	15.3	0.065	1.7	9.25	SST	CG	N
0.703	17.86	NN-96	2.00	50.8	.503	12.8	105	18	.43	11	45	202	.83	21.0	0.100	2.5	8.25	SPR	CG	Z
0.703	17.86	3462	2.13	54.0	.543	13.8	35	6.1	.71	18	25	110	.80	20.3	0.080	2.0	9.00	HD	C	Z
0.703	17.86	3422	2.19	55.6	.463	11.8	201	35	.37	9.4	74	331	1.26	32.0	0.120	3.0	9.50	SPR	C	Z
0.703	17.86	3672	2.22	56.4	.557	14.1	18	3.2	1.0	26	19	84	.80	20.4	0.073	1.9	11.0	SPR	CG	Z
0.703	17.86	S-1495	2.38	60.3	.579	14.7	5.8	1.0	1.5	38	8.8	39	.87	22.0	0.062	1.6	14.0	SST	CG	N
0.703	17.86	12335	2.53	64.3	.583	14.8	7.0	1.2	1.6	40	11	49	.78	19.8	0.060	1.5	12.0	SPR	C	Z
0.703	17.86	10415	2.56	65.1	.477	12.1	114	20	.55	14	63	278	1.36	34.4	0.113	2.9	12.0	SPR	CG	Z
0.703	17.86	12274	2.69	68.2	.577	14.7	7.9	1.4	1.6	42	13	57	.82	20.8	0.063	1.6	13.0	SPR	CG	Z
0.703	17.86	3063	2.72	69.0	.513	13.0	41	7.2	.96	24	39	174	1.40	35.6	0.095	2.4	14.8	SPR	CG	Z
0.703	17.86	GG-43	2.75	69.9	.643	16.3	.34	.06	2.4	61	.81	3.6	.36	9.1	0.030	0.8	12.0	SST	CG	N
0.703	17.86	12039	2.84	72.2	.543	13.8	22	3.9	1.1	28	25	110	1.04	26.4	0.080	2.0	13.0	SPR	CG	Z
0.703	17.86	10523	3.06	77.8	.583	14.8	5.3	.93	2.1	53	11	49	.92	23.2	0.060	1.5	15.3	SPR	CG	GI
0.703	17.86	S-1200	3.38	85.7	.559	14.2	7.9	1.4	2.0	51	16	70	1.37	34.7	0.072	1.8	19.0	SST	CG	N
0.703	17.86	11274	3.50	88.9	.521	13.2	36	6.3	.96	24	34	153	1.27	32.4	0.091	2.3	14.0	SPR	CG	Z
0.703	17.86	11273	3.50	88.9	.507	12.9	33	5.8	1.3	33	43	190	1.96	49.8	0.098	2.5	20.0	SPR	CG	Z
0.703	17.86	11344	3.50	88.9	.407	10.3	336	59	.39	9.9	131	582	2.07	52.6	0.148	3.8	14.0	SPR	CG	Z
0.703	17.86	11725	4.13	104.8	.613	15.6	2.3	.40	2.2	56	5.1	23	.50	12.6	0.045	1.1	11.0	SPR	CG	GI
0.703	17.86	3052	4.13	104.8	.579	14.7	5.0	.88	2.4	62	12	54	1.12	28.3	0.062	1.6	18.0	SPR	CG	Z
0.703	17.86	12450	4.13	104.8	.493	12.5	50	8.7	1.1	27	52	233	1.94	49.3	0.105	2.7	18.5	SPR	CG	Z
0.703	17.86	10446	4.25	108.0	.463	11.8	66	12	1.1	29	74	331	2.97	75.4	0.120	3.0	24.8	SPR	CG	Z
0.703	17.86	12283	4.41	111.9	.553	14.0	9.2	1.6	2.2	56	20	91	1.65	41.9	0.075	1.9	22.0	SPR	CG	Z
0.703	17.86	S-3013	4.50	114.3	.563	14.3	7.6	1.3	2.0	52	16	69	1.23	31.1	0.070	1.8	17.5	SST	CG	N
0.703	17.86	3481	6.00	152.4	.583	14.8	3.9	.68	2.9	73	11	49	1.26	32.0	0.060	1.5	20.0	SPR	C	Z
0.703	17.86	10270	6.00	152.4	.391	9.9	198	35	.75	19	148	658	4.41	111.9	0.156	4.0	28.3	SPR	CG	Z
0.703	17.86	12171	8.13	206.4	.489	12.4	22	3.9	2.5	63	55	246	4.49	114.1	0.107	2.7	42.0	SPR	CG	Z
0.703	17.86	3705	8.75	222.3	.573	14.6	2.4	.43	5.8	147	14	63	2.83	71.8	0.065	1.7	42.5	SPR	C	Z
0.710	18.03	12806	.63	15.9	.526	13.4	218	38	.16	4.1	35	157	.37	9.3	0.092	2.3	4.00	SPR	C	Z
0.718	18.24	B2-48	.41	10.3	.666	16.9	3.4	.60	.27	7.0	.95	4.2	.09	2.3	0.026	0.7	2.50	SST	C	N
0.718	18.24	S-1381	.44	11.1	.616	15.6	14	2.5	.23	5.9	3.3	15	.20	5.2	0.051	1.3	4.00	SST	CG	N
0.718	18.24	S-20	.50	12.7	.592	15.0	70	12	.17	4.3	12	53	.25	6.4	0.063	1.6	3.00	SST	C	N
0.718	18.24	S-216	.50	12.7	.532	13.5	192	34	.13	3.3	25	109	.37	9.4	0.093	2.4	4.00	SST	CG	N
0.718	18.24	HH-91	.59	15.1	.612	15.5	17	3.0	.38	9.7	6.5	29	.21	5.4	0.053	1.3	4.00	SST	CG	N
0.718	18.24	KK-80	.59	15.1	.606	15.4	32	5.7	.27	6.9	8.9	40	.20	5.0	0.056	1.4	3.50	SPR	CG	Z
0.718	18.24	MM-79	.63	15.9	.638	16.2	4.2	.73	.45	11	1.9	8.3	.18	4.6	0.040	1.0	4.50	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.718	18.24	MM-71	.63	15.9	.578	14.7	75	13	.20	5.2	15	68	.25	6.2	0.070	1.8	3.50	SST	CG	N
0.718	18.24	1945	.66	16.7	.612	15.5	19	3.4	.39	9.9	7.5	34	.27	6.7	0.053	1.3	4.00	SPR	C	Z
0.718	18.24	12261	.66	16.7	.612	15.5	17	3.0	.39	9.9	6.7	30	.27	6.7	0.053	1.3	4.00	SST	C	N
0.718	18.24	S-125	.66	16.7	.532	13.5	120	21	.17	4.3	20	90	.49	12.4	0.093	2.4	5.25	SST	CG	N
0.718	18.24	3750	.69	17.4	.590	15.0	25	4.3	.27	6.9	6.7	30	.42	10.6	0.064	1.6	5.50	HD	C	Z
0.718	18.24	S-3142	.69	17.4	.536	13.6	199	35	.16	4.0	31	140	.43	11.0	0.091	2.3	3.75	SST	C	N
0.718	18.24	S-3180	.75	19.1	.636	16.2	5.7	1.0	.59	15	3.3	15	.16	4.2	0.041	1.0	4.00	SST	CG	N
0.718	18.24	W-38	.75	19.1	.634	16.1	4.2	.73	.54	14	2.3	10	.21	5.3	0.042	1.1	5.00	SST	CG	N
0.718	18.24	QQ-31	.75	19.1	.616	15.6	5.7	1.0	.34	8.7	1.9	8.7	.41	10.4	0.051	1.3	7.00	SST	C	N
0.718	18.24	11458	.75	19.1	.574	14.6	51	8.9	.33	8.3	17	74	.40	10.1	0.072	1.8	4.50	SST	C	N
0.718	18.24	A9-38	.81	20.6	.634	16.1	6.4	1.1	.59	15	3.8	17	.21	5.3	0.042	1.1	4.00	SST	C	N
0.718	18.24	A14-47	.81	20.6	.478	12.1	612	107	.11	2.8	67	296	.48	12.2	0.120	3.0	4.00	SST	CG	N
0.718	18.24	12729	.87	22.0	.638	16.2	4.1	.72	.67	17	2.8	12	.20	5.0	0.040	1.0	4.88	MW	CG	BO
0.718	18.24	S-1364	.88	22.2	.594	15.1	24	4.2	.47	12	11	50	.29	7.5	0.062	1.6	4.75	SST	CG	N
0.718	18.24	10233	.88	22.2	.574	14.6	25	4.4	.32	8.1	7.9	35	.56	14.2	0.072	1.8	7.75	SPR	CG	Z
0.718	18.24	S-1082	1.00	25.4	.638	16.2	2.9	.51	.74	19	2.2	9.7	.26	6.6	0.040	1.0	5.50	SST	C	N
0.718	18.24	A12-41	1.00	25.4	.628	16.0	6.4	1.1	.73	19	4.7	21	.27	6.9	0.045	1.1	5.00	MW	C	Z
0.718	18.24	RR-33	1.00	25.4	.618	15.7	7.5	1.3	.65	17	4.9	22	.35	8.9	0.050	1.3	6.00	SPR	C	Z
0.718	18.24	S-878	1.00	25.4	.610	15.5	11	2.0	.67	17	7.5	33	.28	7.2	0.054	1.4	5.25	SST	CG	N
0.718	18.24	3973	1.00	25.4	.574	14.6	48	8.4	.37	9.4	18	79	.43	11.0	0.072	1.8	5.00	SPR	C	Z
0.718	18.24	CC-80	1.00	25.4	.546	13.9	98	17	.28	7.2	28	124	.41	10.4	0.086	2.2	4.75	SST	CG	N
0.718	18.24	S-1260	1.03	26.2	.636	16.2	3.3	.57	.81	20	2.6	12	.23	5.7	0.041	1.0	5.50	SST	CG	N
0.718	18.24	S-3077	1.13	28.6	.614	15.6	7.7	1.4	.81	21	6.3	28	.31	7.9	0.052	1.3	6.00	SST	CG	N
0.718	18.24	10907	1.16	29.4	.628	16.0	3.4	.60	.84	21	2.9	13	.32	8.0	0.045	1.1	7.00	SST	CG	N
0.718	18.24	S-246	1.22	31.0	.624	15.8	5.0	.88	.89	23	4.5	20	.33	8.4	0.047	1.2	6.00	SST	C	N
0.718	18.24	S-430	1.22	31.0	.608	15.4	6.9	1.2	.80	20	5.5	25	.42	10.7	0.055	1.4	7.67	SST	CG	N
0.718	18.24	QQ-44	1.25	31.8	.534	13.6	56	9.8	.38	9.6	21	94	.87	22.2	0.092	2.3	9.50	SPR	CG	Z
0.718	18.24	S-1034	1.31	33.3	.634	16.1	4.2	.73	.90	23	3.8	17	.25	6.4	0.042	1.1	5.00	SST	C	N
0.718	18.24	3792	1.31	33.3	.614	15.6	7.9	1.4	.90	23	7.1	32	.34	8.6	0.052	1.3	6.50	SPR	CG	GI
0.718	18.24	B11-4	1.31	33.3	.594	15.1	11	1.9	.75	19	8.1	36	.56	14.2	0.062	1.6	9.00	SPR	CG	N
0.718	18.24	M-145	1.31	33.3	.572	14.5	43	7.6	.42	11	18	82	.47	12.1	0.073	1.9	5.50	SPR	C	GI
0.718	18.24	S-69	1.34	34.1	.610	15.5	14	2.4	.55	14	7.5	33	.25	6.4	0.054	1.4	4.67	SST	CG	N
0.718	18.24	B10-56	1.38	34.9	.618	15.7	7.5	1.3	.84	21	6.3	28	.30	7.6	0.050	1.3	6.00	SPR	CG	N
0.718	18.24	KK-56	1.38	34.9	.578	14.7	23	4.0	.71	18	16	73	.53	13.3	0.070	1.8	7.50	SPR	CG	N
0.718	18.24	3993	1.38	34.9	.478	12.1	199	35	.30	7.5	59	261	1.08	27.4	0.120	3.0	9.00	SPR	CG	Z
0.718	18.24	Q-51	1.41	35.7	.568	14.4	31	5.4	.64	16	20	89	.56	14.3	0.075	1.9	7.50	SPR	CG	N
0.718	18.24	B9-62	1.50	38.1	.622	15.8	6.3	1.1	.95	24	6.0	27	.34	8.5	0.048	1.2	6.00	SPR	C	N
0.718	18.24	S-48	1.50	38.1	.594	15.1	11	1.9	1.0	26	11	49	.50	12.6	0.062	1.6	8.00	SST	CG	N
0.718	18.24	S-3252	1.50	38.1	.446	11.3	443	77	.21	5.2	91	406	.95	24.2	0.136	3.5	7.00	SST	CG	N
0.718	18.24	B6-54	1.59	40.5	.654	16.6	.93	.16	1.4	35	1.3	5.7	.22	5.7	0.032	0.8	7.00	SPR	CG	Z
0.718	18.24	10565	1.59	40.5	.488	12.4	118	21	.24	6.1	28	127	1.35	34.3	0.115	2.9	11.8	SPR	CG	Z
0.718	18.24	S-1431	1.63	41.3	.636	16.2	2.4	.42	1.3	34	3.2	14	.28	7.0	0.041	1.0	6.75	SST	CG	N
0.718	18.24	11252	1.63	41.3	.528	13.4	59	10	.65	16	38	171	.88	22.3	0.095	2.4	9.25	SPR	CG	N
0.718	18.24	3829	1.63	41.3	.508	12.9	101	18	.51	13	51	228	1.00	25.3	0.105	2.7	9.50	SPR	CG	Z
0.718	18.24	11612	1.63	41.3	.458	11.6	274	48	.25	6.5	70	311	1.37	34.8	0.130	3.3	9.50	SPR	CG	Z
0.718	18.24	10633	1.69	42.8	.622	15.8	3.6	.63	1.2	31	4.4	19	.48	12.2	0.048	1.2	9.00	SPR	C	Z
0.718	18.24	10070	1.69	42.8	.394	10.0	1047	183	.15	3.9	161	718	1.22	30.9	0.162	4.1	7.50	SPR	CG	Z
0.718	18.24	S-370	1.75	44.5	.654	16.6	.90	.16	1.5	38	1.4	6.1	.24	6.1	0.032	0.8	6.50	SST	C	N
0.718	18.24	S-285	1.75	44.5	.636	16.2	1.1	.20	1.3	32	1.4	6.4	.49	12.5	0.041	1.0	12.0	SST	CG	N
0.718	18.24	S-849	1.81	46.0	.574	14.6	12	2.2	.95	24	12	53	.86	21.9	0.072	1.8	12.0	SST	CG	N
0.718	18.24	10209	1.81	46.0	.354	9.0	1517	266	.14	3.5	212	941	1.59	40.5	0.182	4.6	8.75	SPR	CG	Z
0.718	18.24	11588	1.88	47.6	.598	15.2	10	1.8	1.1	28	11	48	.57	14.5	0.060	1.5	8.50	SPR	CG	Z
0.718	18.24	2946	1.88	47.6	.584	14.8	17	3.1	.86	22	15	67	.60	15.3	0.067	1.7	8.00	SPR	C	Z
0.718	18.24	11756	1.91	48.4	.524	13.3	71	12	.58	15	41	181	.92	23.4	0.097	2.5	9.50	SPR	CG	Z
0.718	18.24	10599	1.94	49.2	.530	13.5	54	9.5	.68	17	37	165	.99	25.1	0.094	2.4	10.5	SPR	CG	Z
0.718	18.24	YY-33	2.00	50.8	.628	16.0	2.4	.42	1.6	39	3.7	17	.45	11.4	0.045	1.1	9.00	SST	C	N
0.718	18.24	S-1440	2.00	50.8	.584	14.8	13	2.3	1.1	28	14	63	.60	15.3	0.067	1.7	9.00	SST	CG	N
0.718	18.24	10257	2.00	50.8	.536	13.6	53	9.3	.63	16	34	150	.96	24.3	0.091	2.3	9.50	SPR	C	Z
0.718	18.24	A15-53	2.00	50.8	.528	13.4	57	10	.62	16	36	158	.90	22.9	0.095	2.4	9.50	SST	CG	N
0.718	18.24	A13-33	2.03	51.6	.582	14.8	15	2.6	1.0	26	15	66	.60	15.1	0.068	1.7	8.75	SST	CG	N
0.718	18.24	2778	2.06	52.4	.568	14.4	25	4.4	1.1	28	28	124	.73	18.6	0.075	1.9	8.75	MW	C	Z
0.718	18.24	10867	2.13	54.0	.594	15.1	13	2.2	.96	24	12	53	.50	12.6	0.062	1.6	8.00	SPR	CG	GI
0.718	18.24	4367	2.13	54.0	.584	14.8	11	1.9	1.4	34	15	67	.77	19.6	0.067	1.7	11.5	SPR	CG	Z
0.718	18.24	B9-56	2.13	54.0	.556	14.1	27	4.8	.86	22	23	104	.79	20.1	0.081	2.1	9.75	SST	CG	N
0.718	18.24	2651	2.19	55.6	.488	12.4	104	18	.62	16	65	287	1.50	38.0	0.115	2.9	13.0	SPR	CG	Z
0.718	18.24	S-1630	2.22	56.4	.636	16.2	1.5	.27	1.8	46	2.8	13	.39	9.9	0.041	1.0	9.50	SST	CG	N
0.718	18.24	12625	2.22	56.4	.494	12.5	92	16	.65	16	60	266	1.46	37.0	0.112	2.8	13.0	SPR	CG	Z
0.718	18.24	B11-53	2.31	58.7	.588	14.9	12	2.2	1.1	29	14	61	.62	15.7	0.065	1.7	9.50	SPR	CG	N
0.718	18.24	3386	2.38	60.3	.574	14.6	14	2.5	1.2	31	18	79	.86	21.9	0.072	1.8	12.0	SPR	CG	Z
0.718	18.24	11575	2.50	63.5	.526	13.4	39	6.8	.96	24	38	167	1.54	39.0	0.096	2.4	15.0	SPR	CG	N
0.718	18.24	N-121	2.53	64.3	.572	14.5	17	3.0	1.1	28	18	82	.80	20.4	0.073	1.9	11.0	SPR	CG	N
0.718	18.24	3739	2.56	65.1	.558	14.2	23	4.0	1.1	27	24	107	.96	24.4	0.080	2.0	12.0	SPR	CG	Z
0.718	18.24	S-3164	2.63	66.7	.628	16.0	1.1	.18	1.8	45	1.9	8.3	.86	21.7	0.045	1.1	18.0	SST	C	N
0.718	18.24	1707	2.63	66.7	.570	14.5	18	3.1	1.1	27	19	85	.81	20.7	0.074	1.9	11.0	SPR	CG	Z
0.718	18.24	S-1469	2.75	69.9	.594	15.1	7.5	1.3	1.5	38	11	50	.67	16.9	0.062	1.6	10.8	SST	CG	N
0.718	18.24	10721	3.00	76.2	.478	12.1	100	17	.73	19	73	325	1.92	48.8	0.120	3.0	16.0	SPR	CG	Z
0.718	18.24	B9-51	3.25	82.6	.578	14.7	12	2.1	1.3	34	16	73	.88	22.2	0.070	1.8	12.5	SPR	CG	N
0.718	18.24	2509	3.38	85.7	.534	13.6	23	4.1	1.5	38	35	155	1.84	46.7	0.092	2.3	20.0	HD	CG	Z
0.718	18.24	10396	3.41	86.5	.536	13.6	32	5.6	1.1	27	34	150	1.32	33.5	0.091	2.3	14.5	SPR	CG	Z
0.718	18.24	313	3.50	88.9	.636	16.2	1.5	.27	2.4	62	3.8	17	.47	12.0	0.041	1.0	10.5	HD	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.718	18.24	4277	3.50	88.9	.578	14.7	11	1.9	1.5	38	16	73	.95	24.0	0.070	1.8	13.5	SPR	CG	Z
0.718	18.24	11660	3.53	89.7	.512	13.0	56	9.7	.87	22	49	216	1.49	37.9	0.103	2.6	14.5	SPR	CG	Z
0.718	18.24	S-3243	3.84	97.6	.576	14.6	9.2	1.6	1.7	44	16	71	1.07	27.1	0.071	1.8	15.0	SST	CG	N
0.718	18.24	2894	4.50	114.3	.574	14.6	7.7	1.4	2.3	58	18	79	1.48	37.5	0.072	1.8	20.5	SPR	CG	Z
0.718	18.24	S-3026	4.50	114.3	.562	14.3	13	2.2	1.7	42	21	93	1.33	33.7	0.078	2.0	16.0	SST	C	N
0.718	18.24	12637	4.81	122.2	.656	16.7	.30	.05	4.3	110	1.3	5.7	.47	11.8	0.031	0.8	14.0	SST	C	N
0.718	18.24	B8-66	5.13	130.2	.562	14.3	11	1.9	2.1	53	22	100	1.72	43.6	0.078	2.0	21.0	SPR	C	N
0.718	18.24	S-997	5.75	146.1	.640	16.3	.42	.07	4.8	121	2.0	8.8	.98	25.0	0.039	1.0	24.3	SST	C	N
0.718	18.24	10698	6.25	158.8	.432	11.0	99	17	1.2	30	117	520	4.86	123.5	0.143	3.6	34.0	SPR	CG	Z
0.719	18.26	U-84	.61	15.5	.637	16.2	2.5	.44	.34	8.7	.86	3.8	.27	6.8	0.041	1.0	6.50	SST		
0.720	18.29	71926	.63	16.0	.610	15.5	31	5.4	.38	9.7	12	52	.19	4.9	0.055	1.4	3.50	MW	CG	N
0.720	18.29	71926S	.63	16.0	.610	15.5	26	4.6	.30	7.7	7.9	35	.19	4.9	0.055	1.4	3.50	SST	CG	N
0.720	18.29	71951	.63	16.0	.594	15.1	47	8.2	.37	9.5	17	78	.24	6.0	0.063	1.6	3.75	MW	CG	N
0.720	18.29	71951S	.63	16.0	.594	15.1	40	7.0	.30	7.5	12	53	.24	6.0	0.063	1.6	3.75	SST	CG	N
0.720	18.29	71927	.75	19.1	.610	15.5	23	4.0	.51	13	12	52	.22	5.6	0.055	1.4	4.00	MW	CG	N
0.720	18.29	71927S	.75	19.1	.610	15.5	20	3.4	.40	10	7.9	35	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.720	18.29	71938	.75	19.1	.602	15.3	33	5.8	.44	11	14	64	.23	5.8	0.059	1.5	3.88	MW	CG	N
0.720	18.29	71938S	.75	19.1	.602	15.3	28	4.9	.35	8.8	9.7	43	.23	5.8	0.059	1.5	3.88	SST	CG	N
0.720	18.29	71952	.75	19.1	.594	15.1	33	5.8	.47	12	16	70	.28	7.0	0.063	1.6	4.38	MW	CG	N
0.720	18.29	71952S	.75	19.1	.594	15.1	28	4.9	.42	11	12	53	.28	7.0	0.063	1.6	4.38	SST	CG	N
0.720	18.29	71963	.75	19.1	.590	15.0	44	7.6	.44	11	19	85	.27	6.8	0.065	1.7	4.13	MW	CG	N
0.720	18.29	71963S	.75	19.1	.590	15.0	37	6.5	.35	8.9	13	58	.27	6.8	0.065	1.7	4.13	SST	CG	N
0.720	18.29	71976	.75	19.1	.586	14.9	50	8.8	.42	11	21	93	.28	7.0	0.067	1.7	4.13	MW	CG	N
0.720	18.29	71976S	.75	19.1	.586	14.9	43	7.4	.33	8.5	14	63	.28	7.0	0.067	1.7	4.13	SST	CG	N
0.720	18.29	71991	.75	19.1	.584	14.8	50	8.7	.44	11	22	97	.29	7.3	0.068	1.7	4.25	MW	CG	N
0.720	18.29	71991S	.75	19.1	.584	14.8	42	7.4	.35	8.9	15	66	.29	7.3	0.068	1.7	4.25	SST	CG	N
0.720	18.29	72014	.75	19.1	.576	14.6	67	12	.37	9.3	25	110	.30	7.5	0.072	1.8	4.13	MW	CG	N
0.720	18.29	72014S	.75	19.1	.576	14.6	57	10	.29	7.4	17	74	.30	7.5	0.072	1.8	4.13	SST	CG	N
0.720	18.29	72029	.75	19.1	.560	14.2	92	16	.37	9.3	34	150	.36	9.1	0.080	2.0	4.50	MW	CG	N
0.720	18.29	72029S	.75	19.1	.560	14.2	78	14	.29	7.3	23	100	.36	9.1	0.080	2.0	4.50	SST	CG	N
0.720	18.29	72057	.75	19.1	.558	14.2	104	18	.34	8.6	35	155	.34	8.7	0.081	2.1	4.25	MW	CG	N
0.720	18.29	72057S	.75	19.1	.558	14.2	88	15	.27	6.8	23	104	.34	8.7	0.081	2.1	4.25	SST	CG	N
0.720	18.29	72070	.75	19.1	.550	14.0	139	24	.29	7.3	40	179	.35	8.9	0.085	2.2	4.13	MW	CG	N
0.720	18.29	72070S	.75	19.1	.550	14.0	118	21	.23	5.8	27	120	.35	8.9	0.085	2.2	4.13	SST	CG	N
0.720	18.29	72097	.75	19.1	.528	13.4	239	42	.23	5.9	55	245	.40	10.1	0.096	2.4	4.13	MW	CG	N
0.720	18.29	72097S	.75	19.1	.528	13.4	203	36	.18	4.6	37	163	.40	10.1	0.096	2.4	4.13	SST	CG	N
0.720	18.29	72110	.75	19.1	.510	13.0	355	62	.20	5.1	72	318	.43	11.0	0.105	2.7	4.13	MW	CG	N
0.720	18.29	72110S	.75	19.1	.510	13.0	301	53	.16	4.0	47	211	.43	11.0	0.105	2.7	4.13	SST	CG	N
0.720	18.29	72123	.75	19.1	.496	12.6	469	82	.18	4.5	83	371	.46	11.7	0.112	2.8	4.13	MW	CG	N
0.720	18.29	72123S	.75	19.1	.496	12.6	398	70	.14	3.5	54	242	.46	11.7	0.112	2.8	4.13	SST	CG	N
0.720	18.29	71928	.88	22.4	.610	15.5	20	3.5	.58	15	12	52	.23	5.9	0.055	1.4	4.25	MW	CG	N
0.720	18.29	71928S	.88	22.4	.610	15.5	17	3.0	.46	12	7.9	35	.23	5.9	0.055	1.4	4.25	SST	CG	N
0.720	18.29	71939	.88	22.4	.602	15.3	27	4.8	.53	13	14	64	.25	6.4	0.059	1.5	4.25	MW	CG	N
0.720	18.29	71939S	.88	22.4	.602	15.3	23	4.1	.42	11	9.7	43	.25	6.4	0.059	1.5	4.25	SST	CG	N
0.720	18.29	71953	.88	22.4	.594	15.1	28	4.9	.57	15	16	71	.31	7.8	0.063	1.6	4.88	MW	CG	N
0.720	18.29	71953S	.88	22.4	.594	15.1	24	4.2	.50	13	12	53	.31	7.8	0.063	1.6	4.88	SST	CG	N
0.720	18.29	71964	.88	22.4	.590	15.0	37	6.4	.52	13	19	85	.29	7.4	0.065	1.7	4.50	MW	CG	N
0.720	18.29	71964S	.88	22.4	.590	15.0	31	5.4	.42	11	13	58	.29	7.4	0.065	1.7	4.50	SST	CG	N
0.720	18.29	71977	.88	22.4	.586	14.9	40	7.0	.52	13	21	93	.31	7.9	0.067	1.7	4.63	MW	CG	N
0.720	18.29	71977S	.88	22.4	.586	14.9	34	6.0	.42	11	14	63	.31	7.9	0.067	1.7	4.63	SST	CG	N
0.720	18.29	71993	.88	22.4	.584	14.8	41	7.2	.53	13	22	97	.31	8.0	0.068	1.7	4.63	MW	CG	N
0.720	18.29	71993S	.88	22.4	.584	14.8	35	6.2	.42	11	15	66	.31	8.0	0.068	1.7	4.63	SST	CG	N
0.720	18.29	72015	.88	22.4	.576	14.6	48	8.4	.51	13	25	110	.36	9.1	0.072	1.8	5.00	MW	CG	N
0.720	18.29	72015S	.88	22.4	.576	14.6	41	7.1	.41	10	17	74	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.720	18.29	72031	.88	22.4	.560	14.2	76	13	.44	11	34	150	.40	10.2	0.080	2.0	5.00	MW	CG	N
0.720	18.29	72031S	.88	22.4	.560	14.2	65	11	.35	8.9	23	100	.40	10.2	0.080	2.0	5.00	SST	CG	N
0.720	18.29	72058	.88	22.4	.558	14.2	82	14	.42	11	35	155	.39	10.0	0.081	2.1	4.88	MW	CG	N
0.720	18.29	72058S	.88	22.4	.558	14.2	70	12	.33	8.5	23	104	.39	10.0	0.081	2.1	4.88	SST	CG	N
0.720	18.29	72071	.88	22.4	.550	14.0	114	20	.35	9.0	40	179	.39	10.0	0.085	2.2	4.63	MW	CG	N
0.720	18.29	72071S	.88	22.4	.550	14.0	97	17	.28	7.1	27	120	.39	10.0	0.085	2.2	4.63	SST	CG	N
0.720	18.29	72098	.88	22.4	.528	13.4	194	34	.28	7.2	55	245	.44	11.3	0.096	2.4	4.63	MW	CG	N
0.720	18.29	72098S	.88	22.4	.528	13.4	165	29	.22	5.6	37	163	.44	11.3	0.096	2.4	4.63	SST	CG	N
0.720	18.29	72111	.88	22.4	.510	13.0	286	50	.25	6.4	72	318	.49	12.3	0.105	2.7	4.63	MW	CG	N
0.720	18.29	72111S	.88	22.4	.510	13.0	243	43	.20	5.0	47	211	.49	12.3	0.105	2.7	4.63	SST	CG	N
0.720	18.29	72124	.88	22.4	.496	12.6	374	66	.22	5.7	83	371	.53	13.5	0.112	2.8	4.75	MW	CG	N
0.720	18.29	72124S	.88	22.4	.496	12.6	318	56	.17	4.3	54	242	.53	13.5	0.112	2.8	4.75	SST	CG	N
0.720	18.29	71929	1.00	25.4	.610	15.5	19	3.2	.63	16	12	52	.24	6.1	0.055	1.4	4.38	MW	CG	N
0.720	18.29	71929S	1.00	25.4	.610	15.5	16	2.8	.50	13	7.9	35	.24	6.1	0.055	1.4	4.38	SST	CG	N
0.720	18.29	71940	1.00	25.4	.602	15.3	24	4.1	.61	16	14	64	.27	6.9	0.059	1.5	4.63	MW	CG	N
0.720	18.29	71940S	1.00	25.4	.602	15.3	20	3.5	.49	12	9.7	43	.27	6.9	0.059	1.5	4.63	SST	CG	N
0.720	18.29	71954	1.00	25.4	.594	15.1	24	4.2	.66	17	16	71	.34	8.6	0.063	1.6	5.38	MW	CG	N
0.720	18.29	71954S	1.00	25.4	.594	15.1	20	3.6	.58	15	12	53	.34	8.6	0.063	1.6	5.38	SST	CG	N
0.720	18.29	71965	1.00	25.4	.590	15.0	31	5.4	.62	16	19	85	.33	8.3	0.065	1.7	5.00	MW	CG	N
0.720	18.29	71965S	1.00	25.4	.590	15.0	26	4.6	.49	13	13	58	.33	8.3	0.065	1.7	5.00	SST	CG	N
0.720	18.29	71978	1.00	25.4	.586	14.9	33	5.8	.63	16	21	93	.34	8.7	0.067	1.7	5.13	MW	CG	N
0.720	18.29	71978S	1.00	25.4	.586	14.9	28	4.9	.50	13	14	63	.34	8.7	0.067	1.7	5.13	SST	CG	N
0.720	18.29	71995	1.00	25.4	.584	14.8	35	6.2	.62	16	22	97	.35	8.9	0.068	1.7	5.13	MW	CG	N
0.720	18.29	71995S	1.00	25.4	.584	14.8	30	5.3	.49	12	15	66	.35	8.9	0.068	1.7	5.13	SST	CG	N
0.720	18.29	72016	1.00	25.4	.576	14.6	42	7.4	.59	15	25	110	.39	9.8	0.072	1.8	5.38	MW	CG	N
0.720	18.29	72016S	1.00	25.4	.576	14.6	36	6.3	.46	12	17	74	.39	9.8	0.072	1.8	5.38	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.720	18.29	72033	1.00	25.4	.560	14.2	65	11	.52	13	34	150	.44	11.2	0.080	2.0	5.50	MW	CG	N
0.720	18.29	72033S	1.00	25.4	.560	14.2	55	9.6	.41	10	23	100	.44	11.2	0.080	2.0	5.50	SST	CG	N
0.720	18.29	72034	1.00	25.4	.560	14.2	108	19	.31	7.9	34	150	.33	8.4	0.080	2.0	4.13	MW	CG	N
0.720	18.29	72034S	1.00	25.4	.560	14.2	92	16	.25	6.3	23	100	.33	8.4	0.080	2.0	4.13	SST	CG	N
0.720	18.29	72059	1.00	25.4	.558	14.2	71	12	.49	13	35	155	.44	11.1	0.081	2.1	5.38	MW	CG	N
0.720	18.29	72059S	1.00	25.4	.558	14.2	60	11	.39	9.9	23	104	.44	11.1	0.081	2.1	5.38	SST	CG	N
0.720	18.29	72072	1.00	25.4	.550	14.0	97	17	.41	11	40	179	.43	10.8	0.085	2.2	5.00	MW	CG	N
0.720	18.29	72072S	1.00	25.4	.550	14.0	82	14	.33	8.3	27	120	.43	10.8	0.085	2.2	5.00	SST	CG	N
0.720	18.29	72099	1.00	25.4	.528	13.4	165	29	.33	8.5	55	245	.48	12.2	0.096	2.4	5.00	MW	CG	N
0.720	18.29	72099S	1.00	25.4	.528	13.4	140	25	.26	6.6	37	163	.48	12.2	0.096	2.4	5.00	SST	CG	N
0.720	18.29	72112	1.00	25.4	.510	13.0	243	42	.30	7.5	72	318	.54	13.7	0.105	2.7	5.13	MW	CG	N
0.720	18.29	72112S	1.00	25.4	.510	13.0	206	36	.23	5.8	47	211	.54	13.7	0.105	2.7	5.13	SST	CG	N
0.720	18.29	72125	1.00	25.4	.496	12.6	315	55	.26	6.7	83	371	.59	14.9	0.112	2.8	5.25	MW	CG	N
0.720	18.29	72125S	1.00	25.4	.496	12.6	268	47	.20	5.2	54	242	.59	14.9	0.112	2.8	5.25	SST	CG	N
0.720	18.29	71930	1.25	31.8	.610	15.5	15	2.5	.80	20	12	52	.28	7.2	0.055	1.4	5.13	MW	CG	N
0.720	18.29	71930S	1.25	31.8	.610	15.5	12	2.2	.64	16	7.9	35	.28	7.2	0.055	1.4	5.13	SST	CG	N
0.720	18.29	71941	1.25	31.8	.602	15.3	18	3.2	.78	20	14	64	.31	7.9	0.059	1.5	5.25	MW	CG	N
0.720	18.29	71941S	1.25	31.8	.602	15.3	16	2.7	.63	16	9.7	43	.31	7.9	0.059	1.5	5.25	SST	CG	N
0.720	18.29	71955	1.25	31.8	.594	15.1	19	3.3	.86	22	16	71	.39	10.0	0.063	1.6	6.25	MW	CG	N
0.720	18.29	71955S	1.25	31.8	.594	15.1	16	2.8	.74	19	12	53	.39	10.0	0.063	1.6	6.25	SST	CG	N
0.720	18.29	71966	1.25	31.8	.590	15.0	24	4.2	.79	20	19	85	.37	9.5	0.065	1.7	5.75	MW	CG	N
0.720	18.29	71966S	1.25	31.8	.590	15.0	21	3.6	.63	16	13	58	.37	9.5	0.065	1.7	5.75	SST	CG	N
0.720	18.29	71979	1.25	31.8	.586	14.9	27	4.7	.77	20	21	93	.39	10.0	0.067	1.7	5.88	MW	CG	N
0.720	18.29	71979S	1.25	31.8	.586	14.9	23	4.0	.62	16	14	63	.39	10.0	0.067	1.7	5.88	SST	CG	N
0.720	18.29	71997	1.25	31.8	.584	14.8	28	4.8	.79	20	22	97	.41	10.4	0.068	1.7	6.00	MW	CG	N
0.720	18.29	71997S	1.25	31.8	.584	14.8	23	4.1	.63	16	15	66	.41	10.4	0.068	1.7	6.00	SST	CG	N
0.720	18.29	72017	1.25	31.8	.576	14.6	34	6.0	.73	18	25	110	.44	11.2	0.072	1.8	6.13	MW	CG	N
0.720	18.29	72017S	1.25	31.8	.576	14.6	29	5.1	.57	15	17	74	.44	11.2	0.072	1.8	6.13	SST	CG	N
0.720	18.29	72036	1.25	31.8	.560	14.2	50	8.7	.68	17	34	150	.52	13.2	0.080	2.0	6.50	MW	CG	N
0.720	18.29	72036S	1.25	31.8	.560	14.2	42	7.4	.53	14	23	100	.52	13.2	0.080	2.0	6.50	SST	CG	N
0.720	18.29	72037	1.25	31.8	.560	14.2	83	14	.41	10	34	150	.38	9.7	0.080	2.0	4.75	MW	CG	N
0.720	18.29	72037S	1.25	31.8	.560	14.2	70	12	.32	8.2	23	100	.38	9.7	0.080	2.0	4.75	SST	CG	N
0.720	18.29	72060	1.25	31.8	.558	14.2	54	9.5	.64	16	35	155	.52	13.1	0.081	2.1	6.38	MW	CG	N
0.720	18.29	72060S	1.25	31.8	.558	14.2	46	8.1	.51	13	23	104	.52	13.1	0.081	2.1	6.38	SST	CG	N
0.720	18.29	72073	1.25	31.8	.550	14.0	75	13	.54	14	40	179	.50	12.7	0.085	2.2	5.88	MW	CG	N
0.720	18.29	72073S	1.25	31.8	.550	14.0	63	11	.43	11	27	120	.50	12.7	0.085	2.2	5.88	SST	CG	N
0.720	18.29	72100	1.25	31.8	.528	13.4	126	22	.44	11	55	245	.58	14.6	0.096	2.4	6.00	MW	CG	N
0.720	18.29	72100S	1.25	31.8	.528	13.4	107	19	.34	8.7	37	163	.58	14.6	0.096	2.4	6.00	SST	CG	N
0.720	18.29	72113	1.25	31.8	.510	13.0	184	32	.39	9.9	72	318	.64	16.3	0.105	2.7	6.13	MW	CG	N
0.720	18.29	72113S	1.25	31.8	.510	13.0	157	27	.30	7.7	47	211	.64	16.3	0.105	2.7	6.13	SST	CG	N
0.720	18.29	72126	1.25	31.8	.496	12.6	238	42	.35	8.9	83	371	.70	17.8	0.112	2.8	6.25	MW	CG	N
0.720	18.29	72126S	1.25	31.8	.496	12.6	203	35	.27	6.8	54	242	.70	17.8	0.112	2.8	6.25	SST	CG	N
0.720	18.29	71931	1.50	38.1	.610	15.5	12	2.0	1.0	26	12	52	.32	8.2	0.055	1.4	5.88	MW	CG	N
0.720	18.29	71931S	1.50	38.1	.610	15.5	9.8	1.7	.81	21	7.9	35	.32	8.2	0.055	1.4	5.88	SST	CG	N
0.720	18.29	71942	1.50	38.1	.602	15.3	15	2.6	.96	24	14	64	.35	9.0	0.059	1.5	6.00	MW	CG	N
0.720	18.29	71942S	1.50	38.1	.602	15.3	13	2.2	.76	19	9.7	43	.35	9.0	0.059	1.5	6.00	SST	CG	N
0.720	18.29	71956	1.50	38.1	.594	15.1	15	2.6	1.0	26	16	69	.46	11.8	0.063	1.6	7.38	MW	CG	N
0.720	18.29	71956S	1.50	38.1	.594	15.1	13	2.2	.93	24	12	53	.46	11.8	0.063	1.6	7.38	SST	CG	N
0.720	18.29	71967	1.50	38.1	.590	15.0	20	3.5	.96	24	19	85	.43	10.9	0.065	1.7	6.63	MW	CG	N
0.720	18.29	71967S	1.50	38.1	.590	15.0	17	3.0	.77	19	13	58	.43	10.9	0.065	1.7	6.63	SST	CG	N
0.720	18.29	71980	1.50	38.1	.586	14.9	22	3.9	.95	24	21	93	.45	11.5	0.067	1.7	6.75	MW	CG	N
0.720	18.29	71980S	1.50	38.1	.586	14.9	19	3.3	.76	19	14	63	.45	11.5	0.067	1.7	6.75	SST	CG	N
0.720	18.29	71999	1.50	38.1	.584	14.8	22	3.9	.97	25	22	97	.48	12.1	0.068	1.7	7.00	MW	CG	N
0.720	18.29	71999S	1.50	38.1	.584	14.8	19	3.3	.78	20	15	66	.48	12.1	0.068	1.7	7.00	SST	CG	N
0.720	18.29	72018	1.50	38.1	.576	14.6	26	4.6	.95	24	25	110	.54	13.7	0.072	1.8	7.50	MW	CG	N
0.720	18.29	72018S	1.50	38.1	.576	14.6	22	3.9	.75	19	17	74	.54	13.7	0.072	1.8	7.50	SST	CG	N
0.720	18.29	72039	1.50	38.1	.560	14.2	41	7.1	.83	21	34	150	.60	15.2	0.080	2.0	7.50	MW	CG	N
0.720	18.29	72039S	1.50	38.1	.560	14.2	34	6.0	.66	17	23	100	.60	15.2	0.080	2.0	7.50	SST	CG	N
0.720	18.29	72040	1.50	38.1	.560	14.2	67	12	.50	13	34	150	.43	10.9	0.080	2.0	5.38	MW	CG	N
0.720	18.29	72040S	1.50	38.1	.560	14.2	57	10	.40	10	23	100	.43	10.9	0.080	2.0	5.38	SST	CG	N
0.720	18.29	72061	1.50	38.1	.558	14.2	44	7.7	.79	20	35	155	.60	15.2	0.081	2.1	7.38	MW	CG	N
0.720	18.29	72061S	1.50	38.1	.558	14.2	38	6.6	.62	16	23	104	.60	15.2	0.081	2.1	7.38	SST	CG	N
0.720	18.29	72074	1.50	38.1	.550	14.0	61	11	.66	17	40	179	.58	14.8	0.085	2.2	6.88	MW	CG	N
0.720	18.29	72074S	1.50	38.1	.550	14.0	51	9.0	.52	13	27	120	.58	14.8	0.085	2.2	6.88	SST	CG	N
0.720	18.29	72101	1.50	38.1	.528	13.4	102	18	.54	14	55	245	.66	16.8	0.096	2.4	6.88	MW	CG	N
0.720	18.29	72101S	1.50	38.1	.528	13.4	87	15	.42	11	37	163	.66	16.8	0.096	2.4	6.88	SST	CG	N
0.720	18.29	72114	1.50	38.1	.510	13.0	149	26	.48	12	72	318	.74	18.7	0.105	2.7	7.00	MW	CG	N
0.720	18.29	72114S	1.50	38.1	.510	13.0	126	22	.38	9.5	47	211	.74	18.7	0.105	2.7	7.00	SST	CG	N
0.720	18.29	72127	1.50	38.1	.496	12.6	192	34	.44	11	83	371	.81	20.6	0.112	2.8	7.25	MW	CG	N
0.720	18.29	72127S	1.50	38.1	.496	12.6	163	29	.33	8.5	54	242	.81	20.6	0.112	2.8	7.25	SST	CG	N
0.720	18.29	71932	1.75	44.5	.610	15.5	9.1	1.6	1.3	33	12	52	.38	9.6	0.055	1.4	6.88	MW	CG	N
0.720	18.29	71932S	1.75	44.5	.610	15.5	7.7	1.4	1.0	26	7.9	35	.38	9.6	0.055	1.4	6.88	SST	CG	N
0.720	18.29	71943	1.75	44.5	.602	15.3	13	2.2	1.1	29	14	64	.40	10.1	0.059	1.5	6.75	MW	CG	N
0.720	18.29	71943S	1.75	44.5	.602	15.3	11	1.9	.90	23	9.7	43	.40	10.1	0.059	1.5	6.75	SST	CG	N
0.720	18.29	71957	1.75	44.5	.594	15.1	13	2.3	1.2	31	16	72	.51	13.0	0.063	1.6	8.13	MW	CG	N
0.720	18.29	71957S	1.75	44.5	.594	15.1	11	1.9	1.1	27	12	53	.51	13.0	0.063	1.6	8.13	SST	CG	N
0.720	18.29	71968	1.75	44.5	.590	15.0	17	2.9	1.2	29	19	85	.49	12.4	0.065	1.7	7.50	MW	CG	N
0.720	18.29	71968S	1.75	44.5	.590	15.0	14	2.5	.92	23	13	58	.49	12.4	0.065	1.7	7.50	SST	CG	N
0.720	18.29	71981	1.75	44.5	.586	14.9	18	3.2	1.2	29	21	93	.52	13.2	0.067	1.7	7.75	MW	CG	N
0.720	18.29	71981S	1.75	44.5	.586	14.9	15	2.7	.93	24	14	63	.52	13.2	0.067	1.7	7.75	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.720	18.29	72001	1.75	44.5	.584	14.8	19	3.3	1.1	29	22	97	.54	13.6	0.068	1.7	7.88	MW	CG	N
0.720	18.29	72001S	1.75	44.5	.584	14.8	16	2.8	.92	23	15	66	.54	13.6	0.068	1.7	7.88	SST	CG	N
0.720	18.29	72019	1.75	44.5	.576	14.6	22	3.9	1.1	29	25	110	.61	15.5	0.072	1.8	8.50	MW	CG	N
0.720	18.29	72019S	1.75	44.5	.576	14.6	19	3.3	.89	22	17	74	.61	15.5	0.072	1.8	8.50	SST	CG	N
0.720	18.29	72042	1.75	44.5	.560	14.2	34	6.0	.98	25	34	150	.69	17.5	0.080	2.0	8.63	MW	CG	N
0.720	18.29	72042S	1.75	44.5	.560	14.2	29	5.1	.78	20	23	100	.69	17.5	0.080	2.0	8.63	SST	CG	N
0.720	18.29	72062	1.75	44.5	.558	14.2	37	6.5	.93	24	35	155	.68	17.2	0.081	2.1	8.38	MW	CG	N
0.720	18.29	72062S	1.75	44.5	.558	14.2	32	5.6	.74	19	23	104	.68	17.2	0.081	2.1	8.38	SST	CG	N
0.720	18.29	72075	1.75	44.5	.550	14.0	51	8.9	.79	20	40	179	.66	16.7	0.085	2.2	7.75	MW	CG	N
0.720	18.29	72075S	1.75	44.5	.550	14.0	43	7.6	.62	16	27	120	.66	16.7	0.085	2.2	7.75	SST	CG	N
0.720	18.29	72084	1.75	44.5	.538	13.7	56	9.8	.84	21	47	210	.82	20.8	0.091	2.3	9.00	MW	CG	N
0.720	18.29	72084S	1.75	44.5	.538	13.7	48	8.4	.65	17	31	139	.82	20.8	0.091	2.3	9.00	SST	CG	N
0.720	18.29	72102	1.75	44.5	.528	13.4	86	15	.65	16	55	245	.76	19.2	0.096	2.4	7.88	MW	CG	N
0.720	18.29	72102S	1.75	44.5	.528	13.4	73	13	.50	13	37	163	.76	19.2	0.096	2.4	7.88	SST	CG	N
0.720	18.29	72115	1.75	44.5	.510	13.0	124	22	.58	15	72	318	.84	21.3	0.105	2.7	8.00	MW	CG	N
0.720	18.29	72115S	1.75	44.5	.510	13.0	106	19	.45	11	47	211	.84	21.3	0.105	2.7	8.00	SST	CG	N
0.720	18.29	72128	1.75	44.5	.496	12.6	160	28	.52	13	83	371	.92	23.5	0.112	2.8	8.25	MW	CG	N
0.720	18.29	72128S	1.75	44.5	.496	12.6	136	24	.40	10	54	242	.92	23.5	0.112	2.8	8.25	SST	CG	N
0.720	18.29	71933	2.00	50.8	.610	15.5	8.5	1.5	1.4	35	12	52	.40	10.1	0.055	1.4	7.25	MW	CG	N
0.720	18.29	71933S	2.00	50.8	.610	15.5	7.2	1.3	1.1	28	7.9	35	.40	10.1	0.055	1.4	7.25	SST	CG	N
0.720	18.29	71944	2.00	50.8	.602	15.3	11	1.9	1.3	33	14	64	.44	11.2	0.059	1.5	7.50	MW	CG	N
0.720	18.29	71944S	2.00	50.8	.602	15.3	9.4	1.6	1.0	26	9.7	43	.44	11.2	0.059	1.5	7.50	SST	CG	N
0.720	18.29	71958	2.00	50.8	.594	15.1	11	1.9	1.4	36	16	69	.58	14.8	0.063	1.6	9.25	MW	CG	N
0.720	18.29	71958S	2.00	50.8	.594	15.1	9.4	1.6	1.3	32	12	53	.58	14.8	0.063	1.6	9.25	SST	CG	N
0.720	18.29	71969	2.00	50.8	.590	15.0	14	2.5	1.3	34	19	85	.54	13.8	0.065	1.7	8.38	MW	CG	N
0.720	18.29	71969S	2.00	50.8	.590	15.0	12	2.1	1.1	27	13	58	.54	13.8	0.065	1.7	8.38	SST	CG	N
0.720	18.29	71982	2.00	50.8	.586	14.9	16	2.7	1.3	34	21	93	.59	14.9	0.067	1.7	8.75	MW	CG	N
0.720	18.29	71982S	2.00	50.8	.586	14.9	13	2.3	1.1	27	14	63	.59	14.9	0.067	1.7	8.75	SST	CG	N
0.720	18.29	72003	2.00	50.8	.584	14.8	16	2.9	1.3	34	22	97	.60	15.1	0.068	1.7	8.75	MW	CG	N
0.720	18.29	72003S	2.00	50.8	.584	14.8	14	2.4	1.1	27	15	66	.60	15.1	0.068	1.7	8.75	SST	CG	N
0.720	18.29	72020	2.00	50.8	.576	14.6	20	3.5	1.2	31	25	110	.66	16.7	0.072	1.8	9.13	MW	CG	N
0.720	18.29	72020S	2.00	50.8	.576	14.6	17	3.0	.97	25	17	74	.66	16.7	0.072	1.8	9.13	SST	CG	N
0.720	18.29	72044	2.00	50.8	.560	14.2	30	5.2	1.1	29	34	150	.77	19.6	0.080	2.0	9.63	MW	CG	N
0.720	18.29	72044S	2.00	50.8	.560	14.2	25	4.4	.90	23	23	100	.77	19.6	0.080	2.0	9.63	SST	CG	N
0.720	18.29	72063	2.00	50.8	.558	14.2	32	5.6	1.1	28	35	155	.76	19.3	0.081	2.1	9.38	MW	CG	N
0.720	18.29	72063S	2.00	50.8	.558	14.2	27	4.8	.86	22	23	104	.76	19.3	0.081	2.1	9.38	SST	CG	N
0.720	18.29	72076	2.00	50.8	.550	14.0	44	7.7	.91	23	40	179	.73	18.6	0.085	2.2	8.63	MW	CG	N
0.720	18.29	72076S	2.00	50.8	.550	14.0	37	6.5	.72	18	27	120	.73	18.6	0.085	2.2	8.63	SST	CG	N
0.720	18.29	72086	2.00	50.8	.538	13.7	49	8.5	.97	25	47	210	.92	23.4	0.091	2.3	10.1	MW	CG	N
0.720	18.29	72086S	2.00	50.8	.538	13.7	41	7.2	.76	19	31	139	.92	23.4	0.091	2.3	10.1	SST	CG	N
0.720	18.29	72103	2.00	50.8	.528	13.4	74	13	.75	19	55	245	.85	21.6	0.096	2.4	8.88	MW	CG	N
0.720	18.29	72103S	2.00	50.8	.528	13.4	63	11	.58	15	37	163	.85	21.6	0.096	2.4	8.88	SST	CG	N
0.720	18.29	72116	2.00	50.8	.510	13.0	107	19	.67	17	72	318	.95	24.0	0.105	2.7	9.00	MW	CG	N
0.720	18.29	72116S	2.00	50.8	.510	13.0	91	16	.52	13	47	211	.95	24.0	0.105	2.7	9.00	SST	CG	N
0.720	18.29	72129	2.00	50.8	.496	12.6	138	24	.61	15	83	371	1.04	26.3	0.112	2.8	9.25	MW	CG	N
0.720	18.29	72129S	2.00	50.8	.496	12.6	117	21	.47	12	54	242	1.04	26.3	0.112	2.8	9.25	SST	CG	N
0.720	18.29	71934	2.25	57.2	.610	15.5	7.5	1.3	1.5	39	12	52	.44	11.2	0.055	1.4	8.00	MW	CG	N
0.720	18.29	71934S	2.25	57.2	.610	15.5	6.4	1.1	1.2	31	7.9	35	.44	11.2	0.055	1.4	8.00	SST	CG	N
0.720	18.29	71945	2.25	57.2	.602	15.3	9.7	1.7	1.5	38	14	64	.49	12.4	0.059	1.5	8.25	MW	CG	N
0.720	18.29	71945S	2.25	57.2	.602	15.3	8.2	1.4	1.2	30	9.7	43	.49	12.4	0.059	1.5	8.25	SST	CG	N
0.720	18.29	71959	2.25	57.2	.594	15.1	11	1.9	1.6	40	17	78	.58	14.8	0.063	1.6	9.25	MW	CG	N
0.720	18.29	71959S	2.25	57.2	.594	15.1	9.4	1.6	1.3	32	12	53	.58	14.8	0.063	1.6	9.25	SST	CG	N
0.720	18.29	71970	2.25	57.2	.590	15.0	13	2.2	1.5	38	19	85	.60	15.3	0.065	1.7	9.25	MW	CG	N
0.720	18.29	71970S	2.25	57.2	.590	15.0	11	1.9	1.2	30	13	58	.60	15.3	0.065	1.7	9.25	SST	CG	N
0.720	18.29	71983	2.25	57.2	.586	14.9	14	2.5	1.4	37	21	93	.62	15.7	0.067	1.7	9.25	MW	CG	N
0.720	18.29	71983S	2.25	57.2	.586	14.9	12	2.2	1.2	29	14	63	.62	15.7	0.067	1.7	9.25	SST	CG	N
0.720	18.29	72005	2.25	57.2	.584	14.8	15	2.5	1.5	38	22	97	.65	16.6	0.068	1.7	9.63	MW	CG	N
0.720	18.29	72005S	2.25	57.2	.584	14.8	12	2.2	1.2	30	15	66	.65	16.6	0.068	1.7	9.63	SST	CG	N
0.720	18.29	72021	2.25	57.2	.576	14.6	18	3.2	1.4	35	25	110	.71	18.1	0.072	1.8	9.88	MW	CG	N
0.720	18.29	72021S	2.25	57.2	.576	14.6	15	2.7	1.1	27	17	74	.71	18.1	0.072	1.8	9.88	SST	CG	N
0.720	18.29	72046	2.25	57.2	.560	14.2	26	4.6	1.3	33	34	150	.85	21.6	0.080	2.0	10.6	MW	CG	N
0.720	18.29	72046S	2.25	57.2	.560	14.2	22	3.9	1.0	26	23	100	.85	21.6	0.080	2.0	10.6	SST	CG	N
0.720	18.29	72064	2.25	57.2	.558	14.2	28	5.0	1.2	31	35	155	.84	21.3	0.081	2.1	10.4	MW	CG	N
0.720	18.29	72064S	2.25	57.2	.558	14.2	24	4.2	.97	25	23	104	.84	21.3	0.081	2.1	10.4	SST	CG	N
0.720	18.29	72077	2.25	57.2	.550	14.0	39	6.8	1.0	26	40	179	.82	20.8	0.085	2.2	9.63	MW	CG	N
0.720	18.29	72077S	2.25	57.2	.550	14.0	33	5.8	.82	21	27	120	.82	20.8	0.085	2.2	9.63	SST	CG	N
0.720	18.29	72088	2.25	57.2	.538	13.7	43	7.5	1.1	28	47	210	1.02	26.0	0.091	2.3	11.3	MW	CG	N
0.720	18.29	72088S	2.25	57.2	.538	13.7	36	6.3	.86	22	31	139	1.02	26.0	0.091	2.3	11.3	SST	CG	N
0.720	18.29	72104	2.25	57.2	.528	13.4	65	11	.85	22	55	245	.94	23.8	0.096	2.4	9.75	MW	CG	N
0.720	18.29	72104S	2.25	57.2	.528	13.4	55	9.6	.66	17	37	163	.94	23.8	0.096	2.4	9.75	SST	CG	N
0.720	18.29	72117	2.25	57.2	.510	13.0	94	16	.76	19	72	318	1.05	26.7	0.105	2.7	10.0	MW	CG	N
0.720	18.29	72117S	2.25	57.2	.510	13.0	80	14	.59	15	47	211	1.05	26.7	0.105	2.7	10.0	SST	CG	N
0.720	18.29	72130	2.25	57.2	.496	12.6	121	21	.69	18	83	371	1.16	29.5	0.112	2.8	10.4	MW	CG	N
0.720	18.29	72130S	2.25	57.2	.496	12.6	103	18	.53	13	54	242	1.16	29.5	0.112	2.8	10.4	SST	CG	N
0.720	18.29	71935	2.50	63.5	.610	15.5	6.8	1.2	1.7	44	12	52	.47	12.0	0.055	1.4	8.63	MW	CG	N
0.720	18.29	71935S	2.50	63.5	.610	15.5	5.7	1.0	1.4	35	7.9	35	.47	12.0	0.055	1.4	8.63	SST	CG	N
0.720	18.29	71946	2.50	63.5	.602	15.3	8.7	1.5	1.6	42	14	64	.52	13.3	0.059	1.5	8.88	MW	CG	N
0.720	18.29	71946S	2.50	63.5	.602	15.3	7.4	1.3	1.3	33	9.7	43	.52	13.3	0.059	1.5	8.88	SST	CG	N
0.720	18.29	71960	2.50	63.5	.594	15.1	9.9	1.7	1.8	45	17	78	.64	16.2	0.063	1.6	10.1	MW	CG	N
0.720	18.29	71960S	2.50	63.5	.594	15.1	8.4	1.5	1.4	36	12	53	.64	16.2	0.063	1.6	10.1	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.720	18.29	71971	2.50	63.5	.590	15.0	11	2.0	1.7	43	19	85	.66	16.7	0.065	1.7	10.1	MW	CG	N
0.720	18.29	71971S	2.50	63.5	.590	15.0	9.6	1.7	1.4	34	13	58	.66	16.7	0.065	1.7	10.1	SST	CG	N
0.720	18.29	71984	2.50	63.5	.586	14.9	14	2.4	1.5	39	21	93	.65	16.6	0.067	1.7	9.75	MW	CG	N
0.720	18.29	71984S	2.50	63.5	.586	14.9	11	2.0	1.2	31	14	63	.65	16.6	0.067	1.7	9.75	SST	CG	N
0.720	18.29	72007	2.50	63.5	.584	14.8	13	2.3	1.7	43	22	97	.71	18.1	0.068	1.7	10.5	MW	CG	N
0.720	18.29	72007S	2.50	63.5	.584	14.8	11	1.9	1.3	34	15	66	.71	18.1	0.068	1.7	10.5	SST	CG	N
0.720	18.29	72022	2.50	63.5	.576	14.6	16	2.8	1.5	39	25	110	.78	19.9	0.072	1.8	10.9	MW	CG	N
0.720	18.29	72022S	2.50	63.5	.576	14.6	14	2.4	1.2	31	17	74	.78	19.9	0.072	1.8	10.9	SST	CG	N
0.720	18.29	72048	2.50	63.5	.560	14.2	23	4.1	1.5	37	34	150	.93	23.6	0.080	2.0	11.6	MW	CG	N
0.720	18.29	72048S	2.50	63.5	.560	14.2	20	3.5	1.1	29	23	100	.93	23.6	0.080	2.0	11.6	SST	CG	N
0.720	18.29	72065	2.50	63.5	.558	14.2	25	4.4	1.4	35	35	155	.92	23.4	0.081	2.1	11.4	MW	CG	N
0.720	18.29	72065S	2.50	63.5	.558	14.2	21	3.8	1.1	28	23	104	.92	23.4	0.081	2.1	11.4	SST	CG	N
0.720	18.29	72078	2.50	63.5	.550	14.0	35	6.1	1.2	30	40	179	.89	22.7	0.085	2.2	10.5	MW	CG	N
0.720	18.29	72078S	2.50	63.5	.550	14.0	29	5.1	.92	23	27	120	.89	22.7	0.085	2.2	10.5	SST	CG	N
0.720	18.29	72090	2.50	63.5	.538	13.7	38	6.7	1.2	32	47	210	1.13	28.6	0.091	2.3	12.4	MW	CG	N
0.720	18.29	72090S	2.50	63.5	.538	13.7	32	5.7	.97	25	31	139	1.13	28.6	0.091	2.3	12.4	SST	CG	N
0.720	18.29	72105	2.50	63.5	.528	13.4	58	10	.96	24	55	245	1.03	26.2	0.096	2.4	10.8	MW	CG	N
0.720	18.29	72105S	2.50	63.5	.528	13.4	49	8.6	.75	19	37	163	1.03	26.2	0.096	2.4	10.8	SST	CG	N
0.720	18.29	72118	2.50	63.5	.510	13.0	84	15	.86	22	72	318	1.16	29.3	0.105	2.7	11.0	MW	CG	N
0.720	18.29	72118S	2.50	63.5	.510	13.0	71	12	.67	17	47	211	1.16	29.3	0.105	2.7	11.0	SST	CG	N
0.720	18.29	72131	2.50	63.5	.496	12.6	107	19	.78	20	83	371	1.27	32.4	0.112	2.8	11.4	MW	CG	N
0.720	18.29	72131S	2.50	63.5	.496	12.6	91	16	.60	15	54	242	1.27	32.4	0.112	2.8	11.4	SST	CG	N
0.720	18.29	71936	2.75	69.9	.610	15.5	6.2	1.1	1.9	48	12	52	.51	12.9	0.055	1.4	9.25	MW	CG	N
0.720	18.29	71936S	2.75	69.9	.610	15.5	5.2	.92	1.5	38	7.9	35	.51	12.9	0.055	1.4	9.25	SST	CG	N
0.720	18.29	71948	2.75	69.9	.602	15.3	7.2	1.3	2.0	51	14	64	.61	15.5	0.059	1.5	10.4	MW	CG	N
0.720	18.29	71948S	2.75	69.9	.602	15.3	6.1	1.1	1.6	40	9.7	43	.61	15.5	0.059	1.5	10.4	SST	CG	N
0.720	18.29	71961	2.75	69.9	.594	15.1	8.9	1.6	2.0	50	17	78	.69	17.6	0.063	1.6	11.0	MW	CG	N
0.720	18.29	71961S	2.75	69.9	.594	15.1	7.6	1.3	1.6	40	12	53	.69	17.6	0.063	1.6	11.0	SST	CG	N
0.720	18.29	71972	2.75	69.9	.590	15.0	10	1.8	1.9	48	19	85	.72	18.4	0.065	1.7	11.1	MW	CG	N
0.720	18.29	71972S	2.75	69.9	.590	15.0	8.5	1.5	1.5	39	13	58	.72	18.4	0.065	1.7	11.1	SST	CG	N
0.720	18.29	72009	2.75	69.9	.584	14.8	12	2.0	1.9	47	22	97	.78	19.9	0.068	1.7	11.5	MW	CG	N
0.720	18.29	72009S	2.75	69.9	.584	14.8	9.9	1.7	1.5	38	15	66	.78	19.9	0.068	1.7	11.5	SST	CG	N
0.720	18.29	72023	2.75	69.9	.576	14.6	15	2.6	1.7	43	25	110	.84	21.3	0.072	1.8	11.6	MW	CG	N
0.720	18.29	72023S	2.75	69.9	.576	14.6	12	2.2	1.3	34	17	74	.84	21.3	0.072	1.8	11.6	SST	CG	N
0.720	18.29	72050	2.75	69.9	.560	14.2	21	3.7	1.6	41	34	150	1.02	25.9	0.080	2.0	12.8	MW	CG	N
0.720	18.29	72050S	2.75	69.9	.560	14.2	18	3.1	1.3	32	23	100	1.02	25.9	0.080	2.0	12.8	SST	CG	N
0.720	18.29	72066	2.75	69.9	.558	14.2	23	4.0	1.5	39	35	155	1.00	25.5	0.081	2.1	12.4	MW	CG	N
0.720	18.29	72066S	2.75	69.9	.558	14.2	19	3.4	1.2	31	23	104	1.00	25.5	0.081	2.1	12.4	SST	CG	N
0.720	18.29	72079	2.75	69.9	.550	14.0	31	5.5	1.3	33	40	179	.97	24.6	0.085	2.2	11.4	MW	CG	N
0.720	18.29	72079S	2.75	69.9	.550	14.0	27	4.6	1.0	26	27	120	.97	24.6	0.085	2.2	11.4	SST	CG	N
0.720	18.29	72092	2.75	69.9	.538	13.7	34	6.0	1.4	35	47	210	1.23	31.2	0.091	2.3	13.5	MW	CG	N
0.720	18.29	72092S	2.75	69.9	.538	13.7	29	5.1	1.1	27	31	139	1.23	31.2	0.091	2.3	13.5	SST	CG	N
0.720	18.29	72106	2.75	69.9	.528	13.4	52	9.1	1.1	27	55	245	1.12	28.3	0.096	2.4	11.6	MW	CG	N
0.720	18.29	72106S	2.75	69.9	.528	13.4	44	7.8	.83	21	37	163	1.12	28.3	0.096	2.4	11.6	SST	CG	N
0.720	18.29	72119	2.75	69.9	.510	13.0	75	13	.95	24	72	318	1.26	32.0	0.105	2.7	12.0	MW	CG	N
0.720	18.29	72119S	2.75	69.9	.510	13.0	64	11	.74	19	47	211	1.26	32.0	0.105	2.7	12.0	SST	CG	N
0.720	18.29	72132	2.75	69.9	.496	12.6	97	17	.86	22	83	371	1.39	35.2	0.112	2.8	12.4	MW	CG	N
0.720	18.29	72132S	2.75	69.9	.496	12.6	82	14	.66	17	54	242	1.39	35.2	0.112	2.8	12.4	SST	CG	N
0.720	18.29	71937	3.00	76.2	.610	15.5	5.6	.98	2.1	53	12	52	.55	14.0	0.055	1.4	10.0	MW	CG	N
0.720	18.29	71937S	3.00	76.2	.610	15.5	4.8	.83	1.7	42	7.9	35	.55	14.0	0.055	1.4	10.0	SST	CG	N
0.720	18.29	71950	3.00	76.2	.602	15.3	6.6	1.2	2.2	55	14	64	.66	16.7	0.059	1.5	11.1	MW	CG	N
0.720	18.29	71950S	3.00	76.2	.602	15.3	5.6	.98	1.7	44	9.7	43	.66	16.7	0.059	1.5	11.1	SST	CG	N
0.720	18.29	71962	3.00	76.2	.594	15.1	8.1	1.4	2.2	55	17	78	.75	19.0	0.063	1.6	11.9	MW	CG	N
0.720	18.29	71962S	3.00	76.2	.594	15.1	6.9	1.2	1.7	44	12	53	.75	19.0	0.063	1.6	11.9	SST	CG	N
0.720	18.29	71973	3.00	76.2	.590	15.0	9.1	1.6	2.1	53	19	85	.78	19.8	0.065	1.7	12.0	MW	CG	N
0.720	18.29	71973S	3.00	76.2	.590	15.0	7.8	1.4	1.7	42	13	58	.78	19.8	0.065	1.7	12.0	SST	CG	N
0.720	18.29	71985	3.00	76.2	.586	14.9	11	1.8	2.0	51	21	93	.80	20.2	0.067	1.7	11.9	MW	CG	N
0.720	18.29	71985S	3.00	76.2	.586	14.9	8.9	1.6	1.6	40	14	63	.80	20.2	0.067	1.7	11.9	SST	CG	N
0.720	18.29	72011	3.00	76.2	.584	14.8	11	1.9	2.0	52	22	97	.84	21.4	0.068	1.7	12.4	MW	CG	N
0.720	18.29	72011S	3.00	76.2	.584	14.8	9.1	1.6	1.6	41	15	66	.84	21.4	0.068	1.7	12.4	SST	CG	N
0.720	18.29	72024	3.00	76.2	.576	14.6	13	2.3	1.9	47	25	110	.91	23.1	0.072	1.8	12.6	MW	CG	N
0.720	18.29	72024S	3.00	76.2	.576	14.6	11	2.0	1.5	37	17	74	.91	23.1	0.072	1.8	12.6	SST	CG	N
0.720	18.29	72052	3.00	76.2	.560	14.2	19	3.3	1.8	45	34	150	1.10	27.9	0.080	2.0	13.8	MW	CG	N
0.720	18.29	72052S	3.00	76.2	.560	14.2	16	2.8	1.4	35	23	100	1.10	27.9	0.080	2.0	13.8	SST	CG	N
0.720	18.29	72067	3.00	76.2	.558	14.2	21	3.6	1.7	43	35	155	1.08	27.5	0.081	2.1	13.4	MW	CG	N
0.720	18.29	72067S	3.00	76.2	.558	14.2	18	3.1	1.3	34	23	104	1.08	27.5	0.081	2.1	13.4	SST	CG	N
0.720	18.29	72080	3.00	76.2	.550	14.0	28	5.0	1.4	36	40	179	1.04	26.4	0.085	2.2	12.3	MW	CG	N
0.720	18.29	72080S	3.00	76.2	.550	14.0	24	4.2	1.1	28	27	120	1.04	26.4	0.085	2.2	12.3	SST	CG	N
0.720	18.29	72094	3.00	76.2	.538	13.7	31	5.5	1.5	38	47	210	1.33	33.8	0.091	2.3	14.6	MW	CG	N
0.720	18.29	72094S	3.00	76.2	.538	13.7	27	4.7	1.2	30	31	139	1.33	33.8	0.091	2.3	14.6	SST	CG	N
0.720	18.29	72107	3.00	76.2	.528	13.4	47	8.3	1.2	30	55	245	1.21	30.8	0.096	2.4	12.6	MW	CG	N
0.720	18.29	72107S	3.00	76.2	.528	13.4	40	7.1	.91	23	37	163	1.21	30.8	0.096	2.4	12.6	SST	CG	N
0.720	18.29	72120	3.00	76.2	.510	13.0	69	12	1.0	26	72	318	1.35	34.3	0.105	2.7	12.9	MW	CG	N
0.720	18.29	72120S	3.00	76.2	.510	13.0	58	10	.81	21	47	211	1.35	34.3	0.105	2.7	12.9	SST	CG	N
0.720	18.29	72133	3.00	76.2	.496	12.6	88	15	.95	24	83	371	1.50	38.0	0.112	2.8	13.4	MW	CG	N
0.720	18.29	72133S	3.00	76.2	.496	12.6	75	13	.73	18	54	242	1.50	38.0	0.112	2.8	13.4	SST	CG	N
0.720	18.29	71986	3.25	82.6	.586	14.9	9.2	1.6	2.3	58	21	93	.89	22.5	0.067	1.7	13.3	MW	CG	N
0.720	18.29	71986S	3.25	82.6	.586	14.9	7.8	1.4	1.8	46	14	63	.89	22.5	0.067	1.7	13.3	SST	CG	N
0.720	18.29	71988	3.25	82.6	.586	14.9	11	1.9	2.0	50	21	93	.79	20.0	0.067	1.7	11.8	MW	CG	N
0.720	18.29	71988S	3.25	82.6	.586	14.9	9.1	1.6	1.6	40	14	63	.79	20.0	0.067	1.7	11.8	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.720	18.29	72025	3.25	82.6	.576	14.6	13	2.3	1.9	48	25	110	.93	23.5	0.072	1.8	12.9	MW	CG	N
0.720	18.29	72025S	3.25	82.6	.576	14.6	11	1.9	1.5	38	17	74	.93	23.5	0.072	1.8	12.9	SST	CG	N
0.720	18.29	71975	3.50	88.9	.590	15.0	7.8	1.4	2.5	62	19	85	.89	22.7	0.065	1.7	13.8	MW	CG	N
0.720	18.29	71975S	3.50	88.9	.590	15.0	6.6	1.2	2.0	50	13	58	.89	22.7	0.065	1.7	13.8	SST	CG	N
0.720	18.29	71987	3.50	88.9	.586	14.9	8.5	1.5	2.5	62	21	93	.95	24.2	0.067	1.7	14.3	MW	CG	N
0.720	18.29	71987S	3.50	88.9	.586	14.9	7.2	1.3	2.0	50	14	63	.95	24.2	0.067	1.7	14.3	SST	CG	N
0.720	18.29	71989	3.50	88.9	.586	14.9	10	1.8	2.1	53	21	93	.83	21.1	0.067	1.7	12.4	MW	CG	N
0.720	18.29	71989S	3.50	88.9	.586	14.9	8.5	1.5	1.7	42	14	63	.83	21.1	0.067	1.7	12.4	SST	CG	N
0.720	18.29	72013	3.50	88.9	.584	14.8	9.1	1.6	2.4	61	22	97	.96	24.4	0.068	1.7	14.1	MW	CG	N
0.720	18.29	72013S	3.50	88.9	.584	14.8	7.7	1.4	1.9	49	15	66	.96	24.4	0.068	1.7	14.1	SST	CG	N
0.720	18.29	72026	3.50	88.9	.576	14.6	11	2.0	2.2	56	25	110	1.05	26.7	0.072	1.8	14.6	MW	CG	N
0.720	18.29	72026S	3.50	88.9	.576	14.6	9.6	1.7	1.7	44	17	74	1.05	26.7	0.072	1.8	14.6	SST	CG	N
0.720	18.29	72054	3.50	88.9	.560	14.2	16	2.9	2.1	52	34	150	1.26	32.0	0.080	2.0	15.8	MW	CG	N
0.720	18.29	72054S	3.50	88.9	.560	14.2	14	2.4	1.6	41	23	100	1.26	32.0	0.080	2.0	15.8	SST	CG	N
0.720	18.29	72068	3.50	88.9	.558	14.2	18	3.1	2.0	50	35	155	1.26	31.9	0.081	2.1	15.5	MW	CG	N
0.720	18.29	72068S	3.50	88.9	.558	14.2	15	2.6	1.6	40	23	104	1.26	31.9	0.081	2.1	15.5	SST	CG	N
0.720	18.29	72081	3.50	88.9	.550	14.0	24	4.2	1.7	42	40	179	1.20	30.5	0.085	2.2	14.1	MW	CG	N
0.720	18.29	72081S	3.50	88.9	.550	14.0	21	3.6	1.3	33	27	120	1.20	30.5	0.085	2.2	14.1	SST	CG	N
0.720	18.29	72096	3.50	88.9	.538	13.7	27	4.7	1.8	45	47	210	1.54	39.0	0.091	2.3	16.9	MW	CG	N
0.720	18.29	72096S	3.50	88.9	.538	13.7	23	4.0	1.4	35	31	139	1.54	39.0	0.091	2.3	16.9	SST	CG	N
0.720	18.29	72108	3.50	88.9	.528	13.4	40	7.1	1.4	35	55	245	1.39	35.4	0.096	2.4	14.5	MW	CG	N
0.720	18.29	72108S	3.50	88.9	.528	13.4	34	6.0	1.1	27	37	163	1.39	35.4	0.096	2.4	14.5	SST	CG	N
0.720	18.29	72121	3.50	88.9	.510	13.0	58	10	1.2	31	72	318	1.56	39.7	0.105	2.7	14.9	MW	CG	N
0.720	18.29	72121S	3.50	88.9	.510	13.0	49	8.7	.96	24	47	211	1.56	39.7	0.105	2.7	14.9	SST	CG	N
0.720	18.29	72134	3.50	88.9	.496	12.6	75	13	1.1	28	83	371	1.74	44.1	0.112	2.8	15.5	MW	CG	N
0.720	18.29	72134S	3.50	88.9	.496	12.6	63	11	.86	22	54	242	1.74	44.1	0.112	2.8	15.5	SST	CG	N
0.720	18.29	72027	4.00	101.6	.576	14.6	9.9	1.7	2.5	64	25	110	1.18	29.9	0.072	1.8	16.4	MW	CG	N
0.720	18.29	72027S	4.00	101.6	.576	14.6	8.4	1.5	2.0	50	17	74	1.18	29.9	0.072	1.8	16.4	SST	CG	N
0.720	18.29	72056	4.00	101.6	.560	14.2	14	2.5	2.4	61	34	150	1.43	36.3	0.080	2.0	17.9	MW	CG	N
0.720	18.29	72056S	4.00	101.6	.560	14.2	12	2.1	1.9	48	23	100	1.43	36.3	0.080	2.0	17.9	SST	CG	N
0.720	18.29	72069	4.00	101.6	.558	14.2	15	2.7	2.3	58	35	155	1.42	36.0	0.081	2.1	17.5	MW	CG	N
0.720	18.29	72069S	4.00	101.6	.558	14.2	13	2.3	1.8	46	23	104	1.42	36.0	0.081	2.1	17.5	SST	CG	N
0.720	18.29	72082	4.00	101.6	.550	14.0	21	3.7	1.9	49	40	179	1.36	34.5	0.085	2.2	16.0	MW	CG	N
0.720	18.29	72082S	4.00	101.6	.550	14.0	18	3.1	1.5	38	27	120	1.36	34.5	0.085	2.2	16.0	SST	CG	N
0.720	18.29	72109	4.00	101.6	.528	13.4	35	6.1	1.6	40	55	245	1.57	39.9	0.096	2.4	16.4	MW	CG	N
0.720	18.29	72109S	4.00	101.6	.528	13.4	30	5.2	1.2	31	37	163	1.57	39.9	0.096	2.4	16.4	SST	CG	N
0.720	18.29	72122	4.00	101.6	.510	13.0	51	8.8	1.4	36	72	318	1.77	45.0	0.105	2.7	16.9	MW	CG	N
0.720	18.29	72122S	4.00	101.6	.510	13.0	43	7.5	1.1	28	47	211	1.77	45.0	0.105	2.7	16.9	SST	CG	N
0.720	18.29	72135	4.00	101.6	.496	12.6	65	11	1.3	33	83	371	1.96	49.8	0.112	2.8	17.5	MW	CG	N
0.720	18.29	72135S	4.00	101.6	.496	12.6	55	9.6	.99	25	54	242	1.96	49.8	0.112	2.8	17.5	SST	CG	N
0.734	18.64	XX-36	.50	12.7	.626	15.9	19	3.4	.28	7.2	5.5	25	.22	5.5	0.054	1.4	4.00	SPR	CG	Z
0.734	18.64	S-3203	.56	14.3	.544	13.8	265	46	.13	3.3	35	155	.33	8.4	0.095	2.4	3.50	SST	CG	N
0.734	18.64	B-64	.63	15.9	.664	16.9	5.5	.96	.39	10	2.2	9.6	.14	3.6	0.035	0.9	3.00	SST	C	N
0.734	18.64	AA-54	.63	15.9	.574	14.6	107	19	.21	5.3	22	99	.30	7.6	0.080	2.0	3.75	SST	CG	N
0.734	18.64	II-67	.66	16.7	.614	15.6	18	3.2	.30	7.5	5.3	24	.36	9.1	0.060	1.5	5.00	SST	C	N
0.734	18.64	S-1220	.69	17.4	.524	13.3	305	53	.15	3.9	47	207	.42	10.7	0.105	2.7	4.00	SST	CG	N
0.734	18.64	S-1319	.69	17.4	.494	12.5	640	112	.10	2.6	65	291	.45	11.4	0.120	3.0	3.75	SST	CG	N
0.734	18.64	NN-98	.72	18.2	.614	15.6	15	2.7	.36	9.1	5.4	24	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.734	18.64	S-164	.72	18.2	.574	14.6	93	16	.24	6.0	22	99	.40	10.2	0.080	2.0	4.00	SST	C	N
0.734	18.64	CC-99	.75	19.1	.694	17.6	.08	.01	.56	14	.05	.21	.19	4.8	0.020	0.5	8.50	SST	C	N
0.734	18.64	BB-75	.75	19.1	.656	16.7	2.9	.50	.52	13	1.5	6.6	.23	5.9	0.039	1.0	5.00	SST	C	N
0.734	18.64	A10-62	.75	19.1	.654	16.6	3.3	.58	.55	14	1.8	8.1	.20	5.1	0.040	1.0	5.00	SST	CG	N
0.734	18.64	S-1475	.75	19.1	.646	16.4	3.6	.62	.44	11	1.6	7.0	.31	7.8	0.044	1.1	6.00	SST	C	N
0.734	18.64	11176	.75	19.1	.638	16.2	14	2.4	.40	10	5.5	25	.22	5.5	0.048	1.2	3.50	SST	C	N
0.734	18.64	3867	.75	19.1	.630	16.0	17	2.9	.42	11	7.0	31	.26	6.6	0.052	1.3	4.00	SPR	C	Z
0.734	18.64	B12-38	.75	19.1	.606	15.4	29	5.1	.38	9.7	11	50	.37	9.3	0.064	1.6	4.75	SPR	C	Z
0.734	18.64	S-3085	.88	22.2	.600	15.2	34	5.9	.41	10	14	62	.30	7.7	0.067	1.7	4.50	SST	CG	N
0.734	18.64	S-1343	.88	22.2	.574	14.6	46	8.0	.40	10	18	80	.48	12.2	0.080	2.0	6.00	SST	CG	N
0.734	18.64	V-26	.94	23.8	.650	16.5	4.5	.79	.69	17	3.1	14	.25	6.4	0.042	1.1	5.00	SPR	C	GI
0.734	18.64	S-310	1.00	25.4	.600	15.2	28	5.0	.49	12	14	62	.34	8.5	0.067	1.7	5.00	SST	CG	N
0.734	18.64	3796	1.00	25.4	.590	15.0	44	7.8	.39	9.9	17	77	.36	9.1	0.072	1.8	5.00	HD	CG	GI
0.734	18.64	S-340	1.09	27.8	.380	9.7	2069	362	.09	2.2	180	800	.97	24.7	0.177	4.5	5.50	SST	CG	N
0.734	18.64	S-1373	1.13	28.6	.508	12.9	213	37	.26	6.6	55	244	.79	20.1	0.113	2.9	6.00	SST	CG	N
0.734	18.64	S-403	1.16	29.4	.636	16.2	4.4	.77	.81	20	3.5	16	.35	8.9	0.049	1.2	7.00	SST	CG	N
0.734	18.64	11820	1.19	30.2	.562	14.3	72	13	.40	10	29	130	.52	13.1	0.086	2.2	6.00	SPR	CG	Z
0.734	18.64	S-263	1.19	30.2	.494	12.5	228	40	.29	7.3	65	291	.84	21.3	0.120	3.0	7.00	SST	CG	N
0.734	18.64	11704	1.22	31.0	.654	16.6	3.1	.55	.96	24	3.0	13	.26	6.6	0.040	1.0	5.50	SPR	C	Z
0.734	18.64	11549	1.31	33.3	.634	16.1	5.6	.98	.91	23	5.1	23	.40	10.2	0.050	1.3	7.00	SPR	C	Z
0.734	18.64	A11-55	1.31	33.3	.604	15.3	8.4	1.5	.60	15	5.0	22	.72	18.2	0.065	1.7	11.0	SST	CG	N
0.734	18.64	3740	1.31	33.3	.534	13.6	107	19	.41	10	44	194	.73	18.4	0.100	2.5	7.25	SPR	CG	Z
0.734	18.64	10517	1.38	34.9	.642	16.3	6.6	1.2	1.1	28	7.2	32	.23	5.8	0.046	1.2	5.00	MW	CG	N
0.734	18.64	11186	1.38	34.9	.570	14.5	41	7.1	.62	16	25	113	.64	16.1	0.082	2.1	7.75	SPR	CG	Z
0.734	18.64	2668	1.41	35.7	.626	15.9	8.4	1.5	.93	24	7.8	35	.41	10.5	0.054	1.4	7.00	SPR	C	Z
0.734	18.64	10671	1.47	37.3	.656	16.7	1.4	.24	1.1	27	1.5	6.5	.40	10.2	0.039	1.0	9.25	SPR	C	N
0.734	18.64	S-51	1.50	38.1	.646	16.4	3.2	.55	1.2	30	3.7	16	.33	8.4	0.044	1.1	6.50	SST	C	N
0.734	18.64	10080	1.50	38.1	.624	15.8	12	2.1	.69	17	8.2	37	.30	7.7	0.055	1.4	5.50	SPR	CG	GI
0.734	18.64	S-330	1.50	38.1	.622	15.8	8.8	1.5	.93	24	8.2	36	.42	10.7	0.056	1.4	6.50	SST	C	N
0.734	18.64	B14-53	1.50	38.1	.614	15.6	13	2.4	.74	19	10	45	.36	9.1	0.060	1.5	6.00	SST	CG	N
0.734	18.64	11554	1.50	38.1	.574	14.6	35	6.1	.67	17	24	105	.72	18.3	0.080	2.0	8.00	SPR	CG	Z
0.734	18.64	4351	1.50	38.1	.570	14.5	39	6.8	.65	17	25	113	.66	16.7	0.082	2.1	8.00	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.734	18.64	3436	1.50	38.1	.410	10.4	1058	185	.15	3.8	159	706	1.13	28.8	0.162	4.1	7.00	SPR	CG	Z
0.734	18.64	12046	1.59	40.5	.524	13.3	83	14	.49	12	41	180	1.10	28.0	0.105	2.7	10.5	SPR	CG	Z
0.734	18.64	S-96	1.63	41.3	.652	16.6	2.2	.39	1.3	33	2.9	13	.32	8.1	0.041	1.0	6.75	SST	C	N
0.734	18.64	O-67	1.63	41.3	.652	16.6	1.1	.19	1.1	29	1.2	5.3	.49	12.5	0.041	1.0	12.0	SST	CG	N
0.734	18.64	12102	1.66	42.1	.652	16.6	2.4	.42	1.4	35	3.3	15	.27	6.8	0.041	1.0	6.50	SST	CG	N
0.734	18.64	10810	1.66	42.1	.548	13.9	54	9.5	.65	16	35	157	.88	22.5	0.093	2.4	9.50	SPR	CG	N
0.734	18.64	S-1636	1.72	43.6	.652	16.6	1.1	.19	1.2	31	1.3	5.9	.49	12.5	0.041	1.0	12.0	SST	CG	N
0.734	18.64	4237	1.75	44.5	.646	16.4	3.3	.57	1.4	35	4.6	20	.35	8.9	0.044	1.1	7.00	SPR	C	N
0.734	18.64	2893	1.75	44.5	.606	15.4	11	2.0	1.1	29	13	57	.58	14.6	0.064	1.6	9.00	SPR	CG	Z
0.734	18.64	A-42	1.75	44.5	.584	14.8	26	4.6	.74	19	20	87	.60	15.2	0.075	1.9	8.00	SPR	CG	N
0.734	18.64	3347	1.88	47.6	.594	15.1	18	3.2	.88	22	16	71	.60	15.1	0.070	1.8	8.50	SPR	CG	Z
0.734	18.64	S-248	1.91	48.4	.550	14.0	35	6.0	.80	20	28	123	1.10	28.0	0.092	2.3	12.0	SST	CG	N
0.734	18.64	S-417	2.00	50.8	.552	14.0	33	5.9	.92	23	31	137	1.06	26.9	0.091	2.3	11.8	SST	CG	N
0.734	18.64	10530	2.06	52.4	.590	15.0	16	2.7	1.1	28	17	77	.83	21.0	0.072	1.8	10.5	SPR	C	Z
0.734	18.64	11693	2.09	53.2	.610	15.5	7.6	1.3	1.4	35	11	47	.70	17.7	0.062	1.6	11.3	SPR	CG	Z
0.734	18.64	10981	2.19	55.6	.590	15.0	15	2.6	1.1	28	16	72	.72	18.3	0.072	1.8	10.0	SST	CG	N
0.734	18.64	S-493	2.34	59.5	.532	13.5	53	9.3	.79	20	42	185	1.18	29.9	0.101	2.6	11.7	SST	CG	N
0.734	18.64	10871	2.44	61.9	.558	14.2	36	6.2	.88	22	31	139	.97	24.6	0.088	2.2	11.0	SPR	CG	N
0.734	18.64	10886	2.50	63.5	.614	15.6	6.1	1.1	1.8	45	11	47	.72	18.3	0.060	1.5	12.0	SPR	CG	Z
0.734	18.64	1663	2.63	66.7	.574	14.6	16	2.8	1.3	34	22	97	1.28	32.5	0.080	2.0	15.0	SPR	C	Z
0.734	18.64	S-1224	2.69	68.2	.626	15.9	2.8	.49	1.9	49	5.4	24	.76	19.2	0.054	1.4	14.0	SST	CG	N
0.734	18.64	3365	2.75	69.9	.610	15.5	7.0	1.2	1.7	43	12	52	.81	20.5	0.062	1.6	12.0	SPR	C	GI
0.734	18.64	S-1503	2.94	74.6	.646	16.4	.85	.15	2.1	54	1.8	8.0	.83	21.0	0.044	1.1	18.8	SST	CG	N
0.734	18.64	2747	2.94	74.6	.464	11.8	185	32	.53	13	97	434	1.89	48.0	0.135	3.4	14.0	SPR	CG	Z
0.734	18.64	11333	3.00	76.2	.578	14.7	18	3.2	1.2	30	22	98	1.03	26.3	0.078	2.0	12.3	HD	C	Z
0.734	18.64	B18-181	3.00	76.2	.554	14.1	17	3.0	1.2	30	21	93	1.80	45.7	0.090	2.3	20.0	SST	CG	N
0.734	18.64	B11-44	3.25	82.6	.622	15.8	6.5	1.1	1.3	34	8.7	39	.56	14.2	0.056	1.4	9.00	SPR	C	N
0.734	18.64	3753	3.50	88.9	.650	16.5	1.6	.28	2.5	63	4.0	18	.48	12.3	0.042	1.1	10.5	SPR	C	Z
0.734	18.64	4126	3.50	88.9	.640	16.3	1.6	.28	2.7	69	4.4	19	.78	19.7	0.047	1.2	15.5	HD	C	Z
0.734	18.64	12723	3.50	88.9	.616	15.6	4.0	.71	2.6	65	10	46	.94	24.0	0.059	1.5	16.0	MW	CG	GI
0.734	18.64	4190	3.50	88.9	.604	15.3	9.5	1.7	1.4	36	14	60	.72	18.2	0.065	1.7	11.0	SPR	CG	Z
0.734	18.64	1555	3.50	88.9	.590	15.0	10	1.8	1.7	43	17	77	1.15	29.3	0.072	1.8	15.0	SPR	C	Z
0.734	18.64	S-1430	3.56	90.5	.574	14.6	8.3	1.5	1.6	40	13	58	2.00	50.8	0.080	2.0	24.0	SST	C	N
0.734	18.64	3876	3.69	93.6	.584	14.8	11	1.9	1.8	47	20	87	1.28	32.4	0.075	1.9	17.0	SPR	CG	Z
0.734	18.64	11937	4.63	117.5	.538	13.7	25	4.3	1.7	43	41	183	2.25	57.3	0.098	2.5	23.0	SPR	CG	Z
0.734	18.64	11540	5.00	127.0	.614	15.6	3.6	.63	3.0	76	11	47	1.20	30.5	0.060	1.5	19.0	SPR	C	Z
0.734	18.64	11392	6.13	155.6	.484	12.3	55	9.7	1.5	37	81	358	3.75	95.3	0.125	3.2	30.0	SPR	CG	Z
0.734	18.64	11885	6.31	160.3	.528	13.4	23	4.1	2.0	52	48	212	3.04	77.2	0.103	2.6	29.5	SPR	CG	N
0.734	18.64	12609	6.38	161.9	.708	18.0	.55	9.7	2.0	51	112	497	3.75	95	0.013	0.3	30	MW	C	N
0.734	18.64	4158	11.5	292.1	.534	13.6	13	2.3	3.3	85	44	194	4.60	116.8	0.100	2.5	45.0	SPR	C	Z
0.750	19.05	B4-20	.50	12.7	.650	16.5	21	3.7	.29	7.4	6.1	27	.16	4.1	0.050	1.3	3.25	SPR	CG	N
0.750	19.05	2518	.50	12.7	.642	16.3	24	4.2	.31	7.9	7.5	33	.19	4.8	0.054	1.4	3.50	HD	CG	Z
0.750	19.05	B2-57	.56	14.3	.688	17.5	2.9	.50	.43	11	1.2	5.5	.13	3.4	0.031	0.8	3.25	MW	C	Z
0.750	19.05	S-1345	.56	14.3	.674	17.1	2.9	.51	.39	9.9	1.1	5.0	.17	4.3	0.038	1.0	4.50	SST	CG	N
0.750	19.05	OO-84	.56	14.3	.650	16.5	9.5	1.7	.27	7.0	2.6	12	.29	7.3	0.050	1.3	4.75	SPR	C	Z
0.750	19.05	CC-79	.56	14.3	.590	15.0	98	17	.24	6.0	23	103	.32	8.1	0.080	2.0	4.00	SPR	CG	N
0.750	19.05	B15-66	.59	15.1	.670	17.0	4.1	.72	.41	10	1.7	7.6	.18	4.6	0.040	1.0	4.50	SPR	CG	N
0.750	19.05	2665	.59	15.1	.586	14.9	193	34	.13	3.3	25	111	.26	6.5	0.082	2.1	3.25	SPR	CG	Z
0.750	19.05	S-238	.63	15.9	.550	14.0	182	32	.18	4.4	32	142	.45	11.4	0.100	2.5	4.50	SST	CG	N
0.750	19.05	12559	.70	17.9	.610	15.5	40	7.0	.37	9.4	15	66	.33	8.5	0.070	1.8	4.75	SPR	CG	N
0.750	19.05	S-1321	.75	19.1	.656	16.7	8.8	1.5	.52	13	4.5	20	.24	6.0	0.047	1.2	4.00	SST	C	N
0.750	19.05	12581	.75	19.1	.650	16.5	13	2.3	.46	12	6.1	27	.25	6.4	0.050	1.3	4.00	SPR	C	N
0.750	19.05	KK-93	.75	19.1	.636	16.2	13	2.3	.44	11	5.7	25	.31	8.0	0.057	1.4	5.50	SPR	CG	N
0.750	19.05	GG-64	.75	19.1	.430	10.9	2294	402	.07	1.7	151	671	.64	16.3	0.160	4.1	4.00	SPR	CG	N
0.750	19.05	10140	.81	20.6	.616	15.6	45	8.0	.32	8.1	14	64	.27	6.8	0.067	1.7	4.00	SPR	CG	Z
0.750	19.05	S-1301	.88	22.2	.642	16.3	16	2.8	.46	12	7.2	32	.22	5.5	0.054	1.4	4.00	SST	C	N
0.750	19.05	A14-67	.88	22.2	.636	16.2	23	4.0	.39	10	9.0	40	.23	5.8	0.057	1.4	4.00	SPR	CG	GI
0.750	19.05	10448	.88	22.2	.606	15.4	41	7.2	.41	10	17	76	.36	9.1	0.072	1.8	5.00	SPR	CG	Z
0.750	19.05	2590	.89	22.6	.590	15.0	39	6.9	.33	8.4	13	57	.56	14.2	0.080	2.0	7.00	HD	CG	Z
0.750	19.05	12584	.91	23.0	.510	13.0	397	70	.18	4.5	70	313	.60	15.2	0.120	3.0	5.00	SPR	CG	N
0.750	19.05	N-137	.94	23.8	.672	17.1	2.3	.41	.70	18	1.6	7.2	.23	5.9	0.039	1.0	6.00	SPR	C	N
0.750	19.05	B15-40	.94	23.8	.658	16.7	6.7	1.2	.72	18	4.8	21	.22	5.5	0.046	1.2	4.75	SPR	CG	Z
0.750	19.05	B1-65	.94	23.8	.624	15.8	25	4.3	.46	12	11	51	.35	8.8	0.063	1.6	4.50	SST	CG	N
0.750	19.05	3033	.94	23.8	.540	13.7	326	57	.15	3.8	49	219	.42	10.7	0.105	2.7	4.00	SPR	CG	Z
0.750	19.05	2602	.97	24.6	.646	16.4	7.3	1.3	.64	16	4.7	21	.33	8.3	0.052	1.3	6.25	HD	CG	Z
0.750	19.05	S-3115	1.00	25.4	.668	17.0	5.0	.87	.68	17	3.4	15	.21	5.2	0.041	1.0	4.00	SST	C	N
0.750	19.05	11493	1.00	25.4	.642	16.3	18	3.2	.42	11	7.6	34	.27	6.9	0.054	1.4	4.00	SPR	CG	Z
0.750	19.05	WW-70	1.00	25.4	.638	16.2	21	3.7	.40	10	8.5	38	.28	7.1	0.056	1.4	4.00	SPR	C	Z
0.750	19.05	3957	1.00	25.4	.626	15.9	14	2.4	.58	15	8.0	36	.42	10.6	0.062	1.6	6.75	SPR	CG	Z
0.750	19.05	S-976	1.00	25.4	.624	15.8	27	4.7	.42	11	11	51	.27	6.8	0.063	1.6	4.25	SST	CG	N
0.750	19.05	10577	1.00	25.4	.608	15.4	39	6.8	.42	11	16	73	.43	10.8	0.071	1.8	5.00	SPR	C	Z
0.750	19.05	889	1.00	25.4	.590	15.0	59	10	.39	10	23	103	.51	12.9	0.080	2.0	5.33	HD	C	Z
0.750	19.05	3318	1.00	25.4	.540	13.7	217	38	.23	5.8	49	219	.53	13.3	0.105	2.7	5.00	SPR	CG	Z
0.750	19.05	3827	1.00	25.4	.536	13.6	236	41	.22	5.6	52	232	.54	13.6	0.107	2.7	5.00	SPR	CG	N
0.750	19.05	KK-55	1.00	25.4	.530	13.5	203	36	.25	6.2	50	222	.61	15.4	0.110	2.8	5.50	SST	CG	N
0.750	19.05	S-344	1.00	25.4	.510	13.0	346	61	.19	4.7	64	285	.60	15.2	0.120	3.0	5.00	SST	CG	N
0.750	19.05	S-307	1.00	25.4	.500	12.7	357	63	.20	5.1	72	321	.69	17.5	0.125	3.2	5.50	SST	CG	N
0.750	19.05	B1-47	1.03	26.2	.640	16.3	15	2.6	.51	13	7.6	34	.29	7.5	0.055	1.4	4.33	SST	C	N
0.750	19.05	S-1259	1.03	26.2	.626	15.9	14	2.5	.66	17	9.3	42	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.750	19.05	S-884	1.03	26.2	.538	13.7	201	35	.23	5.9	47	209	.53	13.5	0.106	2.7	5.00	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; **HD** - Hard Drawn; **OT** - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.750	19.05	B1-67	1.09	27.8	.640	16.3	14	2.5	.57	14	8.1	36	.26	6.6	0.055	1.4	4.75	SPR	CG	N
0.750	19.05	B8-39	1.09	27.8	.570	14.5	94	16	.34	8.5	31	140	.50	12.6	0.090	2.3	5.50	SPR	CG	Z
0.750	19.05	B17-185	1.09	27.8	.400	10.2	2364	414	.08	2.1	193	860	.88	22.2	0.175	4.4	5.00	SPR	CG	N
0.750	19.05	S-948	1.11	28.2	.510	13.0	352	62	.18	4.6	64	285	.60	15.2	0.120	3.0	5.00	SST	CG	N
0.750	19.05	12248	1.13	28.6	.644	16.4	11	2.0	.65	16	7.2	32	.27	6.7	0.053	1.3	5.00	SPR	CG	Z
0.750	19.05	11371	1.13	28.6	.608	15.4	15	2.6	.49	12	7.2	32	.64	16.2	0.071	1.8	9.00	SST	CG	N
0.750	19.05	B17-183	1.13	28.6	.590	15.0	44	7.6	.53	14	23	103	.52	13.2	0.080	2.0	6.50	SPR	CG	Z
0.750	19.05	HH-72	1.13	28.6	.550	14.0	88	15	.40	10	35	157	.73	18.4	0.100	2.5	7.25	SST	CG	N
0.750	19.05	3479	1.13	28.6	.500	12.7	479	84	.16	4.2	79	352	.63	15.9	0.125	3.2	5.00	HD	CG	Z
0.750	19.05	11701	1.13	28.6	.496	12.6	387	68	.21	5.4	83	368	.76	19.4	0.127	3.2	6.00	SPR	CG	Z
0.750	19.05	S-1448	1.13	28.6	.480	12.2	446	78	.19	4.9	86	383	.81	20.6	0.135	3.4	6.00	SST	CG	N
0.750	19.05	B17-121	1.16	29.4	.620	15.7	23	4.0	.58	15	13	59	.36	9.1	0.065	1.7	5.50	SPR	CG	N
0.750	19.05	10933	1.19	30.2	.626	15.9	16	2.9	.71	18	12	51	.43	11.0	0.062	1.6	6.00	SPR	C	N
0.750	19.05	HH-7	1.19	30.2	.570	14.5	73	13	.40	10	29	130	.54	13.7	0.090	2.3	6.00	SST	CG	N
0.750	19.05	S-1537	1.19	30.2	.514	13.1	192	34	.32	8.1	61	272	.83	21.0	0.118	3.0	7.00	SST	CG	N
0.750	19.05	12198	1.22	31.0	.570	14.5	55	9.6	.50	13	27	121	.72	18.3	0.090	2.3	8.00	SPR	CG	Z
0.750	19.05	S-392	1.25	31.8	.626	15.9	16	2.8	.67	17	11	48	.40	10.2	0.062	1.6	5.50	SST	C	N
0.750	19.05	S-1287	1.25	31.8	.616	15.6	23	4.0	.60	15	14	61	.37	9.4	0.067	1.7	5.50	SST	CG	N
0.750	19.05	EE-73	1.25	31.8	.590	15.0	36	6.2	.65	17	23	103	.60	15.2	0.080	2.0	7.50	SPR	CG	Z
0.750	19.05	KK-72	1.25	31.8	.530	13.5	146	26	.37	9.5	55	243	.83	21.0	0.110	2.8	7.50	SPR	CG	N
0.750	19.05	B1-69	1.28	32.5	.614	15.6	28	4.8	.55	14	15	67	.37	9.5	0.068	1.7	5.50	SPR	CG	N
0.750	19.05	S-1634	1.31	33.3	.688	17.5	1.1	.18	1.2	29	1.2	5.4	.16	3.9	0.031	0.8	5.00	SST	CG	N
0.750	19.05	10637	1.31	33.3	.622	15.8	23	4.0	.55	14	13	56	.40	10.2	0.064	1.6	5.25	SPR	C	Z
0.750	19.05	4284	1.31	33.3	.616	15.6	19	3.4	.76	19	14	64	.45	11.5	0.067	1.7	6.75	SPR	CG	Z
0.750	19.05	12259	1.31	33.3	.616	15.6	18	3.2	.80	20	14	64	.47	11.9	0.067	1.7	7.00	SPR	CG	Z
0.750	19.05	11798	1.34	34.1	.652	16.6	6.0	1.1	1.0	25	6.0	27	.34	8.7	0.049	1.2	6.00	SPR	C	N
0.750	19.05	12230	1.34	34.1	.608	15.4	26	4.5	.63	16	16	73	.46	11.7	0.071	1.8	6.50	SPR	CG	Z
0.750	19.05	12224	1.38	34.9	.650	16.5	6.5	1.1	.93	24	6.1	27	.30	7.6	0.050	1.3	6.00	SPR	CG	N
0.750	19.05	S-439	1.38	34.9	.640	16.3	7.7	1.4	.98	25	7.6	34	.36	9.1	0.055	1.4	6.50	SST	CG	N
0.750	19.05	3064	1.38	34.9	.256	6.5	12936	2265	.03	.84	427	1901	1.30	32.9	0.247	6.3	5.25	SPR	CG	Z
0.750	19.05	A11-64	1.41	35.7	.648	16.5	6.3	1.1	.96	24	6.1	27	.31	7.8	0.051	1.3	6.00	SST	CG	N
0.750	19.05	B7-51	1.41	35.7	.640	16.3	10	1.8	.77	20	8.1	36	.32	8.0	0.055	1.4	5.75	SPR	CG	Z
0.750	19.05	B18-173	1.44	36.5	.630	16.0	13	2.2	.78	20	9.8	44	.36	9.1	0.060	1.5	6.00	SST	CG	N
0.750	19.05	3824	1.44	36.5	.626	15.9	16	2.9	.71	18	12	51	.37	9.4	0.062	1.6	6.00	HD	CG	Z
0.750	19.05	11516	1.50	38.1	.682	17.3	.87	.15	1.2	30	1.0	4.6	.31	7.8	0.034	0.9	8.00	SPR	C	Z
0.750	19.05	12551	1.50	38.1	.626	15.9	12	2.1	.97	25	12	51	.53	13.4	0.062	1.6	7.50	HD	C	N
0.750	19.05	S-777	1.50	38.1	.624	15.8	14	2.5	.79	20	11	51	.46	11.6	0.063	1.6	6.25	SST	C	N
0.750	19.05	S-868	1.50	38.1	.624	15.8	15	2.6	.77	20	11	51	.39	9.8	0.063	1.6	6.00	SST	CG	N
0.750	19.05	12269	1.50	38.1	.620	15.7	18	3.1	.70	18	12	55	.46	11.6	0.065	1.7	6.00	SST	C	N
0.750	19.05	S-780	1.50	38.1	.606	15.4	24	4.2	.66	17	16	71	.54	13.7	0.072	1.8	6.50	SST	C	N
0.750	19.05	M-104	1.50	38.1	.572	14.5	48	8.4	.66	17	32	141	.76	19.2	0.089	2.3	8.50	SPR	CG	Z
0.750	19.05	11504	1.50	38.1	.570	14.5	77	14	.41	10	31	140	.65	16.6	0.090	2.3	6.25	SPR	CG	Z
0.750	19.05	3165	1.50	38.1	.506	12.9	206	36	.36	9.1	74	328	1.01	25.6	0.122	3.1	8.25	SPR	CG	Z
0.750	19.05	3352	1.63	41.3	.630	16.0	10	1.8	1.0	26	10	46	.51	13.0	0.060	1.5	7.50	SPR	C	Z
0.750	19.05	GG-78	1.63	41.3	.530	13.5	115	20	.48	12	55	243	.99	25.1	0.110	2.8	9.00	SPR	CG	Z
0.750	19.05	FF-30	1.63	41.3	.490	12.4	278	49	.28	7.1	77	344	.98	24.8	0.130	3.3	7.50	SST	CG	N
0.750	19.05	11946	1.72	43.6	.490	12.4	287	50	.30	7.6	86	382	1.04	26.4	0.130	3.3	8.00	SPR	CG	Z
0.750	19.05	2855	1.75	44.5	.684	17.4	.71	.12	1.4	36	1.0	4.5	.31	8.0	0.033	0.8	8.50	HD	C	GI
0.750	19.05	10199	1.75	44.5	.634	16.1	7.0	1.2	1.2	31	8.6	38	.52	13.3	0.058	1.5	9.00	SPR	CG	Z
0.750	19.05	2743	1.75	44.5	.630	16.0	11	2.0	.92	23	10	46	.48	12.2	0.060	1.5	7.00	SPR	C	Z
0.750	19.05	S-778	1.75	44.5	.624	15.8	12	2.1	.93	24	11	51	.50	12.8	0.063	1.6	7.00	SST	C	N
0.750	19.05	S-781	1.75	44.5	.606	15.4	20	3.4	.81	21	16	71	.61	15.5	0.072	1.8	7.50	SST	C	N
0.750	19.05	A11-37	1.81	46.0	.614	15.6	27	4.8	.52	13	14	63	.35	8.9	0.068	1.7	5.00	SST	CG	N
0.750	19.05	S-1325	1.81	46.0	.500	12.7	156	27	.46	12	72	321	1.25	31.8	0.125	3.2	10.0	SST	CG	N
0.750	19.05	12247	1.84	46.8	.624	15.8	11	1.9	1.1	29	12	54	.60	15.2	0.063	1.6	8.50	SPR	C	Z
0.750	19.05	DD-92	1.88	47.6	.650	16.5	3.5	.61	1.4	36	4.9	22	.48	12.1	0.050	1.3	9.50	SPR	CG	GI
0.750	19.05	EE-62	1.88	47.6	.610	15.5	17	3.0	.93	24	16	70	.60	15.1	0.070	1.8	8.50	SPR	CG	Z
0.750	19.05	B18-198	1.91	48.4	.590	15.0	25	4.4	.92	23	23	103	.86	21.8	0.080	2.0	9.75	SPR	C	GI
0.750	19.05	11495	1.94	49.2	.568	14.4	57	10	.57	14	32	145	.82	20.8	0.091	2.3	8.00	SPR	CG	Z
0.750	19.05	11595	1.94	49.2	.538	13.7	80	14	.63	16	51	226	1.22	31.0	0.106	2.7	10.5	SPR	CG	Z
0.750	19.05	S-951	1.97	50.0	.642	16.3	4.0	.70	1.4	36	5.7	26	.53	13.5	0.054	1.4	10.0	SST	CG	N
0.750	19.05	1585	2.00	50.8	.692	17.6	.24	.04	1.6	40	.38	1.7	.41	10.5	0.029	0.7	13.3	MW	C	Z
0.750	19.05	3340	2.00	50.8	.686	17.4	.65	.11	1.7	43	1.1	4.9	.30	7.5	0.032	0.8	8.25	MW	C	Z
0.750	19.05	12228	2.00	50.8	.654	16.6	3.2	.55	1.5	39	4.8	21	.48	12.2	0.048	1.2	9.00	SPR	C	Z
0.750	19.05	10735	2.00	50.8	.640	16.3	4.9	.86	1.5	37	7.1	32	.55	14.0	0.055	1.4	10.0	SPR	CG	Z
0.750	19.05	10226	2.00	50.8	.626	15.9	10	1.8	1.1	29	12	51	.53	13.4	0.062	1.6	8.50	SPR	CG	Z
0.750	19.05	S-779	2.00	50.8	.624	15.8	11	1.8	1.1	27	11	51	.55	14.0	0.063	1.6	7.75	SST	C	N
0.750	19.05	S-782	2.00	50.8	.606	15.4	17	2.9	.96	24	16	71	.68	17.4	0.072	1.8	8.50	SST	C	N
0.750	19.05	66	2.00	50.8	.590	15.0	25	4.4	.92	23	23	103	.78	19.8	0.080	2.0	9.75	HD	CG	Z
0.750	19.05	11280	2.09	53.2	.540	13.7	72	13	.68	17	49	219	1.16	29.3	0.105	2.7	11.0	SPR	CG	Z
0.750	19.05	S-1353	2.13	54.0	.662	16.8	1.7	.29	1.6	42	2.7	12	.48	12.3	0.044	1.1	10.0	SST	C	N
0.750	19.05	11394	2.13	54.0	.606	15.4	12	2.2	1.3	32	16	70	.86	21.9	0.072	1.8	12.0	SPR	CG	Z
0.750	19.05	S-3228	2.13	54.0	.592	15.0	19	3.4	1.1	27	21	93	.83	21.1	0.079	2.0	10.5	SST	CG	N
0.750	19.05	12070	2.13	54.0	.582	14.8	81	14	.33	8.4	27	119	.42	10.7	0.084	2.1	5.00	SPR	CG	Z
0.750	19.05	S-1036	2.13	54.0	.558	14.2	40	7.0	.88	22	35	157	1.10	28.0	0.096	2.4	11.5	SST	CG	N
0.750	19.05	S-415	2.19	55.6	.624	15.8	9.2	1.6	1.2	31	11	51	.54	13.8	0.063	1.6	8.75	SST	CG	N
0.750	19.05	S-1583	2.19	55.6	.540	13.7	83	14	.55	14	46	203	.95	24.0	0.105	2.7	9.00	SST	CG	N
0.750	19.05	S-1418	2.25	57.2	.656	16.7	2.7	.47	1.9	47	5.0	22	.40	10.1	0.047	1.2	8.50	SST	CG	N
0.750	19.05	10344	2.31	58.7	.540	13.7	65	11	.76	19	49	219	1.26	32.0	0.105	2.7	12.0	SPR	CG	Z
0.750	19.05	B10-70	2.34	59.5	.642	16.3	6.0	1.1	1.3	32	7.6	34	.43	11.0	0.054	1.4	8.00	SPR	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.750	19.05	A13-29	2.38	60.3	.640	16.3	5.8	1.0	1.3	33	7.6	34	.44	11.2	0.055	1.4	8.00	SST	CG	N
0.750	19.05	12254	2.38	60.3	.630	16.0	5.7	.99	1.7	42	9.4	42	.72	18.3	0.060	1.5	12.0	SPR	CG	Z
0.750	19.05	11920	2.41	61.1	.674	17.1	.74	.13	2.0	50	1.4	6.4	.46	11.6	0.038	1.0	12.0	SST	CG	N
0.750	19.05	S-490	2.50	63.5	.680	17.3	.29	.05	1.8	45	.50	2.2	.74	18.7	0.035	0.9	20.0	SST	C	N
0.750	19.05	11875	2.50	63.5	.672	17.1	.77	.14	2.0	50	1.5	6.7	.55	13.9	0.039	1.0	14.0	SPR	CG	N
0.750	19.05	RR-53	2.50	63.5	.670	17.0	.75	.13	1.9	48	1.4	6.3	.60	15.2	0.040	1.0	14.0	SST	C	N
0.750	19.05	S-1271	2.50	63.5	.626	15.9	7.6	1.3	1.4	36	11	48	.65	16.5	0.062	1.6	9.50	SST	C	N
0.750	19.05	S-783	2.50	63.5	.606	15.4	13	2.3	1.2	31	16	71	.81	20.6	0.072	1.8	10.3	SST	C	N
0.750	19.05	11758	2.50	63.5	.542	13.8	59	10	.81	21	48	213	1.40	35.7	0.104	2.6	12.5	SPR	C	Z
0.750	19.05	48	2.50	63.5	.540	13.7	59	10	.83	21	49	219	1.37	34.7	0.105	2.7	13.0	HD	CG	Z
0.750	19.05	50	2.50	63.5	.480	12.2	195	34	.49	12	96	426	1.69	42.9	0.135	3.4	12.5	HD	CG	Z
0.750	19.05	12451	2.59	65.9	.536	13.6	81	14	.64	16	52	232	1.15	29.2	0.107	2.7	10.8	SPR	CG	N
0.750	19.05	3472	2.63	66.7	.550	14.0	50	8.7	.86	22	43	190	1.35	34.3	0.100	2.5	12.5	SPR	C	Z
0.750	19.05	1873	2.69	68.2	.590	15.0	15	2.6	1.4	36	21	94	1.28	32.5	0.080	2.0	15.0	HD	C	Z
0.750	19.05	4362	2.69	68.2	.540	13.7	55	9.7	.89	23	49	219	1.44	36.7	0.105	2.7	13.8	SPR	CG	Z
0.750	19.05	12199	2.75	69.9	.640	16.3	4.4	.76	1.9	47	8.1	36	.66	16.8	0.055	1.4	11.0	SPR	C	Z
0.750	19.05	3959	2.75	69.9	.580	14.7	26	4.5	1.1	28	28	123	1.02	25.9	0.085	2.2	12.0	SPR	CG	Z
0.750	19.05	12079	2.78	70.6	.616	15.6	8.3	1.4	1.8	44	14	64	.87	22.1	0.067	1.7	13.0	SPR	CG	GI
0.750	19.05	12696	2.81	71.4	.678	17.2	.72	.13	2.4	61	1.7	7.7	.40	10.1	0.036	0.9	10.0	SST	C	N
0.750	19.05	10602	3.00	76.2	.654	16.6	2.8	.48	2.1	53	5.8	26	.53	13.4	0.048	1.2	10.0	SPR	C	Z
0.750	19.05	S-316	3.00	76.2	.648	16.5	1.8	.31	2.1	54	3.8	17	.87	22.0	0.051	1.3	16.0	SST	C	N
0.750	19.05	S-888	3.00	76.2	.626	15.9	5.2	.90	2.1	53	11	48	.81	20.5	0.062	1.6	13.0	SST	CG	N
0.750	19.05	4219	3.00	76.2	.624	15.8	7.0	1.2	1.7	44	12	54	.82	20.8	0.063	1.6	12.0	SPR	C	Z
0.750	19.05	4255	3.00	76.2	.540	13.7	54	9.5	.91	23	49	219	1.58	40.0	0.105	2.7	14.0	SPR	C	Z
0.750	19.05	44	3.13	79.4	.568	14.4	25	4.4	1.3	33	32	145	1.52	38.7	0.091	2.3	15.8	HD	C	Z
0.750	19.05	11467	3.25	82.6	.580	14.7	16	2.7	1.7	43	27	119	1.55	39.4	0.085	2.2	18.3	SPR	CG	Z
0.750	19.05	831	3.25	82.6	.540	13.7	44	7.7	1.1	28	49	219	1.86	47.3	0.105	2.7	16.8	HD	C	Z
0.750	19.05	3869	3.25	82.6	.500	12.7	82	14	.81	21	67	297	2.44	61.9	0.125	3.2	19.5	SPR	CG	Z
0.750	19.05	10084	3.38	85.7	.638	16.2	3.3	.58	2.5	65	8.5	38	.83	21.0	0.056	1.4	14.8	SPR	CG	GI
0.750	19.05	11377	3.47	88.1	.626	15.9	5.5	.96	2.0	50	11	48	.84	21.3	0.062	1.6	12.5	SST	C	N
0.750	19.05	10061	3.50	88.9	.642	16.3	3.5	.60	2.2	56	7.6	34	.68	17.1	0.054	1.4	12.5	SPR	CG	GI
0.750	19.05	890	3.50	88.9	.590	15.0	14	2.4	1.7	43	23	103	1.38	35.1	0.080	2.0	16.3	HD	C	Z
0.750	19.05	11406	3.50	88.9	.590	15.0	12	2.1	1.8	46	22	97	1.40	35.6	0.080	2.0	16.5	SST	C	N
0.750	19.05	40	3.50	88.9	.568	14.4	22	3.9	1.5	37	32	145	1.68	42.8	0.091	2.3	17.5	HD	C	Z
0.750	19.05	1863	3.50	88.9	.554	14.1	31	5.4	1.3	33	40	179	1.81	46.1	0.098	2.5	17.5	SPR	C	Z
0.750	19.05	12306	3.50	88.9	.520	13.2	65	11	.95	24	62	276	1.96	49.7	0.115	2.9	17.0	SPR	CG	Z
0.750	19.05	41	3.50	88.9	.480	12.2	135	24	.71	18	96	426	2.33	59.1	0.135	3.4	17.3	HD	CG	Z
0.750	19.05	11169	3.56	90.5	.500	12.7	74	13	.87	22	64	287	2.69	68.3	0.125	3.2	21.5	SPR	CG	Z
0.750	19.05	4175	3.63	92.1	.634	16.1	4.1	.72	2.3	59	9.4	42	.87	22.1	0.058	1.5	14.0	SPR	C	Z
0.750	19.05	2781	3.69	93.6	.458	11.6	242	42	.49	13	120	532	2.08	52.8	0.146	3.7	14.3	SPR	CG	Z
0.750	19.05	12255	3.84	97.6	.678	17.2	.66	.12	3.4	87	2.3	10	.43	11.0	0.036	0.9	12.0	SPR	CG	Z
0.750	19.05	3700	3.88	98.4	.558	14.2	26	4.6	1.5	37	38	169	1.80	45.7	0.096	2.4	18.8	SPR	CG	GI
0.750	19.05	12553	4.06	103.1	.590	15.0	14	2.4	1.7	44	23	103	1.32	33.5	0.080	2.0	16.5	SPR	CG	N
0.750	19.05	12250	4.13	104.8	.678	17.2	.66	.12	3.7	94	2.4	11	.43	11.0	0.036	0.9	12.0	SPR	CG	Z
0.750	19.05	11737	4.25	108.0	.568	14.4	17	3.0	1.9	48	32	145	2.00	50.9	0.091	2.3	22.0	SPR	CG	Z
0.750	19.05	12193	4.34	110.3	.578	14.7	18	3.1	1.6	41	29	128	1.46	37.1	0.086	2.2	17.0	SPR	CG	GI
0.750	19.05	3932	4.50	114.3	.616	15.6	4.7	.82	3.1	78	14	63	1.44	36.6	0.067	1.7	21.5	SPR	CG	Z
0.750	19.05	11749	4.50	114.3	.608	15.4	6.5	1.1	2.5	64	16	73	1.49	37.9	0.071	1.8	20.0	SPR	C	Z
0.750	19.05	11782	4.59	116.7	.612	15.5	6.7	1.2	2.4	60	16	70	1.21	30.7	0.069	1.8	17.5	SPR	CG	N
0.750	19.05	10816	4.69	119.0	.654	16.6	1.9	.33	3.1	78	5.8	26	.66	16.8	0.048	1.2	13.8	SPR	CG	GI
0.750	19.05	10060	4.75	120.7	.626	15.9	5.6	.97	2.9	73	16	71	.85	21.7	0.062	1.6	13.8	MW	CG	Z
0.750	19.05	1773	4.75	120.7	.620	15.7	8.4	1.5	1.6	40	13	59	.81	20.7	0.065	1.7	11.5	SPR	C	Z
0.750	19.05	11683	4.75	120.7	.620	15.7	8.4	1.5	1.6	40	13	59	.81	20.6	0.065	1.7	11.5	SPR	C	Z
0.750	19.05	3971	4.88	123.8	.590	15.0	10	1.8	2.3	59	23	103	1.72	43.7	0.080	2.0	21.5	SPR	CG	Z
0.750	19.05	854	5.00	127.0	.480	12.2	93	16	1.0	26	96	426	3.24	82.3	0.135	3.4	24.0	HD	CG	Z
0.750	19.05	12064	5.13	130.2	.602	15.3	6.3	1.1	2.9	74	18	82	1.78	45.1	0.074	1.9	24.0	SPR	CG	Z
0.750	19.05	S-1174	5.25	133.4	.590	15.0	8.1	1.4	2.7	68	22	97	1.84	46.7	0.080	2.0	23.0	SST	CG	N
0.750	19.05	11816	6.00	152.4	.602	15.3	5.8	1.0	3.2	81	18	82	1.92	48.9	0.074	1.9	26.0	SPR	CG	GI
0.750	19.05	875	6.00	152.4	.568	14.4	13	2.2	2.6	66	32	145	2.78	70.5	0.091	2.3	29.5	HD	C	Z
0.750	19.05	871	6.00	152.4	.540	13.7	23	4.0	2.2	55	49	219	3.20	81.3	0.105	2.7	30.5	HD	CG	Z
0.750	19.05	827	6.00	152.4	.510	13.0	40	7.0	1.8	45	70	313	3.84	97.5	0.120	3.0	32.0	HD	CG	Z
0.750	19.05	3122	6.25	158.8	.606	15.4	5.3	.92	3.2	82	17	76	1.91	48.5	0.072	1.8	25.5	SPR	C	Z
0.750	19.05	11413	6.25	158.8	.568	14.4	12	2.2	2.6	66	32	145	2.80	71.1	0.091	2.3	29.8	HD	C	Z
0.750	19.05	3051	6.38	161.9	.540	13.7	25	4.3	2.0	51	49	219	2.97	75.3	0.105	2.7	28.3	SPR	CG	Z
0.750	19.05	11545	7.50	190.5	.568	14.4	8.8	1.5	3.7	93	32	144	3.82	97.1	0.091	2.3	41.0	SPR	CG	Z
0.750	19.05	2905	7.56	192.1	.558	14.2	15	2.6	2.5	64	38	169	2.98	75.6	0.096	2.4	31.0	SPR	CG	Z
0.750	19.05	11845	8.31	211.1	.506	12.9	31	5.4	2.2	55	67	299	4.76	120.9	0.122	3.1	39.0	SST	CG	N
0.750	19.05	11427	10.0	254.0	.540	13.7	11	1.9	4.2	106	45	200	5.83	148.0	0.105	2.7	55.5	SST	CG	N
0.750	19.05	11855	10.2	258.7	.540	13.7	12	2.1	4.1	104	49	219	5.88	149.4	0.105	2.7	56.0	SPR	CG	N
0.750	19.05	3126	11.4	288.9	.553	14.1	11	1.9	3.8	97	41	181	4.34	110.3	0.098	2.5	44.8	SPR	CG	Z
0.750	19.05	288	12.0	304.8	.626	15.9	1.5	.27	7.5	191	12	51	2.82	71.7	0.062	1.6	44.5	HD	C	Z
0.750	19.05	879	12.0	304.8	.606	15.4	2.6	.45	6.6	167	17	76	3.67	93.3	0.072	1.8	50.0	HD	C	Z
0.750	19.05	877	12.0	304.8	.590	15.0	3.8	.66	6.2	156	23	103	4.40	111.8	0.080	2.0	54.0	HD	C	Z
0.750	19.05	S-3035	13.4	339.7	.540	13.7	8.0	1.4	5.7	145	46	203	7.67	194.7	0.105	2.7	73.0	SST	CG	N
0.750	19.05	3042	13.8	349.3	.540	13.7	12	2.0	4.2	108	49	219	6.20	157.4	0.105	2.7	58.0	SPR	C	Z
0.765	19.43	12602	.56	14.3	.701	17.8	3.1	.54	.43	11	1.3	5.8	.14	3.5	0.032	0.8	3.25	MW	C	T
0.765	19.43	10443	.63	15.9	.709	18.0	1.1	.19	.49	12	.54	2.4	.14	3.6	0.028	0.7	4.00	MW	C	Z
0.765	19.43	S-454	.63	15.9	.689	17.5	2.4	.41	.44	11	1.0	4.6	.19	4.7	0.038	1.0	5.00	SST	CG	N
0.765	19.43	10925	.63	15.9	.555	14.1	270	47	.17	4.2	45	200	.42	10.7	0.105	2.7	4.00	SST	CG	N
0.765	19.43	12244	.66	16.7	.701	17.8	1.3	.22	.46	12	.59	2.6	.19	4.9	0.032	0.8	5.00	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.765	19.43	3812	.69	17.4	.605	15.4	73	13	.31	7.9	23	101	.36	9.1	0.080	2.0	4.50	SPR	CG	Z
0.765	19.43	S-873	.81	20.6	.703	17.9	1.6	.28	.69	18	1.1	4.9	.12	3.1	0.031	0.8	4.00	SST	CG	N
0.765	19.43	1589	.88	22.2	.681	17.3	4.3	.75	.63	16	2.7	12	.24	6.1	0.042	1.1	4.75	SPR	C	Z
0.765	19.43	UU-70	.88	22.2	.621	15.8	34	5.9	.46	12	16	70	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.765	19.43	12577	.91	23.0	.565	14.4	244	43	.24	6.1	59	261	.40	10.2	0.100	2.5	4.00	MW	CG	N
0.765	19.43	XX-61	1.00	25.4	.683	17.3	3.6	.62	.75	19	2.7	12	.25	6.2	0.041	1.0	5.00	SPR	C	Z
0.765	19.43	2848	1.00	25.4	.643	16.3	11	2.0	.57	15	6.5	29	.43	10.8	0.061	1.5	7.00	HD	CG	Z
0.765	19.43	S-30	1.00	25.4	.605	15.4	46	8.0	.47	12	21	95	.44	11.2	0.080	2.0	5.50	SST	CG	N
0.765	19.43	S-302	1.00	25.4	.525	13.3	276	48	.23	5.8	63	280	.66	16.8	0.120	3.0	5.50	SST	CG	N
0.765	19.43	HH-76	1.00	25.4	.485	12.3	502	88	.16	4.1	80	357	.84	21.3	0.140	3.6	6.00	SST	CG	N
0.765	19.43	S-3245	1.03	26.2	.685	17.4	4.3	.75	.72	18	3.1	14	.16	4.1	0.040	1.0	4.00	SST	CG	N
0.765	19.43	3682	1.06	27.0	.671	17.0	5.8	1.0	.82	21	4.8	21	.25	6.3	0.047	1.2	5.25	SPR	CG	Z
0.765	19.43	S-1150	1.13	28.6	.525	13.3	322	56	.20	5.0	63	280	.60	15.2	0.120	3.0	5.00	SST	CG	N
0.765	19.43	S-385	1.16	29.4	.695	17.7	1.3	.23	.96	24	1.3	5.7	.20	5.0	0.035	0.9	6.00	SST	C	N
0.765	19.43	3152	1.16	29.4	.551	14.0	165	29	.31	7.9	51	228	.64	16.3	0.107	2.7	6.00	SPR	CG	Z
0.765	19.43	S-187	1.25	31.8	.665	16.9	3.3	.58	.83	21	2.7	12	.43	10.8	0.050	1.3	8.50	SST	CG	N
0.765	19.43	S-1320	1.25	31.8	.641	16.3	7.9	1.4	.71	18	5.6	25	.54	13.8	0.062	1.6	8.75	SST	CG	N
0.765	19.43	B11-26	1.25	31.8	.635	16.1	23	4.0	.56	14	13	58	.34	8.7	0.065	1.7	5.25	SPR	CG	N
0.765	19.43	B12-20	1.25	31.8	.545	13.8	187	33	.29	7.3	54	239	.66	16.8	0.110	2.8	6.00	SPR	CG	Z
0.765	19.43	3771	1.25	31.8	.495	12.6	477	84	.20	5.0	94	419	.81	20.6	0.135	3.4	6.00	SPR	CG	Z
0.765	19.43	12146	1.31	33.3	.585	14.9	51	9.0	.59	15	30	135	.72	18.3	0.090	2.3	8.00	SPR	CG	Z
0.765	19.43	11599	1.41	35.7	.691	17.6	2.1	.37	1.2	30	2.5	11	.23	5.9	0.037	0.9	5.33	SPR	C	Z
0.765	19.43	12122	1.41	35.7	.603	15.3	39	6.8	.61	16	24	105	.57	14.4	0.081	2.1	7.00	SPR	CG	Z
0.765	19.43	S-423	1.41	35.7	.525	13.3	172	30	.37	9.3	63	280	.92	23.2	0.120	3.0	7.75	SST	CG	N
0.765	19.43	2853	1.44	36.5	.663	16.8	5.3	.94	1.1	27	5.8	26	.36	9.1	0.051	1.3	7.00	SPR	CG	Z
0.765	19.43	S-1623	1.47	37.3	.625	15.9	18	3.2	.79	20	14	64	.56	14.2	0.070	1.8	7.00	SST	CG	N
0.765	19.43	S-222	1.50	38.1	.695	17.7	1.2	.21	1.3	32	1.5	6.7	.25	6.2	0.035	0.9	6.00	SST	C	N
0.765	19.43	10915	1.50	38.1	.665	16.9	2.8	.49	.91	23	2.6	11	.59	14.9	0.050	1.3	10.8	SPR	C	N
0.765	19.43	S-1298	1.50	38.1	.629	16.0	18	3.1	.79	20	14	62	.44	11.1	0.068	1.7	6.50	SST	CG	N
0.765	19.43	S-438	1.50	38.1	.621	15.8	17	2.9	.92	23	16	69	.58	14.6	0.072	1.8	8.00	SST	CG	N
0.765	19.43	S-253	1.56	39.7	.525	13.3	164	29	.38	9.7	63	280	.96	24.4	0.120	3.0	8.00	SST	CG	N
0.765	19.43	4304	1.63	41.3	.583	14.8	61	11	.52	13	32	142	.66	16.8	0.091	2.3	7.25	SPR	CG	Z
0.765	19.43	3411	1.63	41.3	.555	14.1	111	19	.44	11	48	215	.79	20.0	0.105	2.7	7.50	SPR	CG	GI
0.765	19.43	NN-80	1.63	41.3	.505	12.8	211	37	.36	9.2	76	338	1.14	28.9	0.130	3.3	8.75	SST	CG	N
0.765	19.43	CC-70	1.75	44.5	.585	14.9	23	4.0	.49	12	11	49	1.26	32.0	0.090	2.3	14.0	SST	CG	N
0.765	19.43	11410	1.81	46.0	.525	13.3	153	27	.45	11	69	307	1.11	28.2	0.120	3.0	9.25	SPR	CG	Z
0.765	19.43	4148	2.00	50.8	.641	16.3	6.8	1.2	1.3	32	8.5	38	.74	18.9	0.062	1.6	11.0	HD	C	Z
0.765	19.43	12164	2.00	50.8	.601	15.3	27	4.8	.90	23	24	109	.86	21.9	0.082	2.1	9.50	SPR	C	Z
0.765	19.43	S-308	2.00	50.8	.515	13.1	212	37	.33	8.5	71	315	.94	23.8	0.125	3.2	7.50	SST	CG	N
0.765	19.43	11803	2.09	53.2	.579	14.7	59	10	.58	15	34	151	.74	18.9	0.093	2.4	8.00	SPR	CG	Z
0.765	19.43	S-433	2.19	55.6	.641	16.3	8.2	1.4	1.3	33	11	47	.60	15.2	0.062	1.6	8.75	SST	CG	N
0.765	19.43	S-909	2.44	61.9	.603	15.3	18	3.2	1.2	30	22	98	.90	22.9	0.081	2.1	11.0	SST	CG	N
0.765	19.43	11713	2.47	62.7	.523	13.3	105	18	.67	17	71	315	1.57	40.0	0.121	3.1	13.0	SPR	CG	Z
0.765	19.43	3439	2.69	68.2	.577	14.7	41	7.2	.85	22	35	156	1.13	28.7	0.094	2.4	11.0	SPR	C	Z
0.765	19.43	B8-53	2.72	69.0	.655	16.6	4.6	.80	1.7	44	7.9	35	.55	14.0	0.055	1.4	10.0	SPR	CG	N
0.765	19.43	11712	3.09	78.6	.553	14.0	79	14	.63	16	50	222	1.17	29.6	0.106	2.7	10.0	SPR	C	Z
0.765	19.43	10731	3.31	84.1	.669	17.0	1.2	.20	2.4	60	2.8	12	.95	24.1	0.048	1.2	19.8	SPR	CG	Z
0.765	19.43	11916	3.53	89.7	.555	14.1	34	6.0	1.3	33	45	200	1.86	47.3	0.105	2.7	17.8	SST	CG	N
0.765	19.43	3171	3.56	90.5	.635	16.1	6.4	1.1	2.0	52	13	58	.89	22.7	0.065	1.7	13.8	SPR	CG	Z
0.765	19.43	3929	3.75	95.3	.661	16.8	2.6	.46	2.5	65	6.7	30	.73	18.5	0.052	1.3	13.0	SPR	C	Z
0.765	19.43	10322	4.13	104.8	.425	10.8	326	57	.54	14	176	782	3.32	84.2	0.170	4.3	19.5	SPR	CG	Z
0.765	19.43	S-3220	4.50	114.3	.639	16.2	3.4	.60	3.3	83	11	50	1.20	30.4	0.063	1.6	19.0	SST	CG	N
0.765	19.43	S-457	4.63	117.5	.621	15.8	6.5	1.1	2.4	61	16	70	1.26	32.0	0.072	1.8	17.5	SST	CG	N
0.765	19.43	11859	4.69	119.0	.579	14.7	18	3.1	1.9	49	34	151	2.05	52.0	0.093	2.4	22.0	SPR	CG	N
0.765	19.43	3291	5.50	139.7	.601	15.3	15	2.6	1.7	43	24	109	1.31	33.3	0.082	2.1	16.0	SPR	CG	Z
0.765	19.43	12185	7.75	196.9	.549	13.9	22	3.8	2.4	62	53	234	3.67	93.3	0.108	2.7	34.0	SPR	CG	N
0.765	19.43	11828	8.00	203.2	.643	16.3	2.2	.38	4.7	118	10	45	1.54	39.1	0.061	1.5	25.3	SST	CG	N
0.765	19.43	3030	8.00	203.2	.615	15.6	6.2	1.1	3.1	78	19	84	1.84	46.7	0.075	1.9	24.5	SPR	CG	GI
0.781	19.84	Q-63	.44	11.1	.651	16.5	61	11	.20	5.0	12	53	.20	5.0	0.065	1.7	3.00	SST	CG	N
0.781	19.84	PP-8	.50	12.7	.541	13.7	1032	181	.07	1.7	68	302	.36	9.1	0.120	3.0	3.00	SPR	CG	N
0.781	19.84	2619	.69	17.4	.687	17.4	10	1.8	.51	13	5.2	23	.18	4.5	0.047	1.2	3.75	HD	CG	Z
0.781	19.84	12319	.72	18.2	.581	14.8	152	27	.22	5.5	33	147	.50	12.7	0.100	2.5	5.00	SPR	CG	Z
0.781	19.84	V-64	.75	19.1	.667	16.9	14	2.4	.49	13	6.9	31	.26	6.5	0.057	1.4	4.50	SST	CG	N
0.781	19.84	S-29	.75	19.1	.541	13.7	458	80	.14	3.4	62	275	.48	12.2	0.120	3.0	4.00	SST	CG	N
0.781	19.84	3743	.88	22.2	.699	17.8	3.3	.59	.63	16	2.1	9.3	.25	6.2	0.041	1.0	5.00	SPR	C	Z
0.781	19.84	11379	.88	22.2	.691	17.6	6.6	1.1	.65	17	4.3	19	.23	5.7	0.045	1.1	4.00	SST	C	N
0.781	19.84	LL-50	.88	22.2	.681	17.3	12	2.0	.51	13	5.9	26	.25	6.4	0.050	1.3	4.00	SPR	C	Z
0.781	19.84	S-971	.91	23.0	.705	17.9	2.1	.37	.72	18	1.5	6.7	.19	4.8	0.038	1.0	5.00	SST	CG	N
0.781	19.84	S-3254	.91	23.0	.541	13.7	458	80	.14	3.4	62	275	.48	12.2	0.120	3.0	4.00	SST	CG	N
0.781	19.84	I-61	.94	23.8	.657	16.7	12	2.2	.57	14	7.0	31	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.781	19.84	DD-81	1.00	25.4	.621	15.8	61	11	.34	8.8	21	93	.36	9.1	0.080	2.0	4.50	SST	CG	N
0.781	19.84	S-398	1.06	27.0	.531	13.5	315	55	.22	5.6	70	310	.69	17.5	0.125	3.2	5.50	SST	CG	N
0.781	19.84	3208	1.06	27.0	.399	10.1	3105	544	.07	1.9	227	1011	.96	24.3	0.191	4.9	5.00	SPR	CG	Z
0.781	19.84	S-357	1.09	27.8	.541	13.7	299	52	.21	5.3	62	275	.60	15.2	0.120	3.0	5.00	SST	CG	N
0.781	19.84	12558	1.13	28.6	.501	12.7	559	98	.18	4.7	103	456	.81	20.4	0.140	3.6	5.75	SPR	CG	N
0.781	19.84	10761	1.25	31.8	.661	16.8	9.9	1.7	.77	20	7.7	34	.48	12.2	0.060	1.5	7.00	SPR	C	Z
0.781	19.84	WW-38	1.25	31.8	.657	16.7	12	2.2	.84	21	10	46	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.781	19.84	XX-65	1.25	31.8	.531	13.5	249	44	.31	7.8	76	339	.88	22.2	0.125	3.2	7.00	SPR	CG	Z
0.781	19.84	B18-187	1.28	32.5	.673	17.1	7.5	1.3	.89	23	6.7	30	.39	9.9	0.054	1.4	6.25	SPR	C	Z
0.781	19.84	4282	1.31	33.3	.725	18.4	.32	.06	1.0	27	.33	1.5	.27	6.8	0.028	0.7	8.50	MW	C	T

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.781	19.84	4225	1.31	33.3	.639	16.2	29	5.1	.54	14	16	70	.46	11.7	0.071	1.8	5.50	SPR	C	Z
0.781	19.84	2835	1.31	33.3	.511	13.0	443	78	.21	5.3	92	411	.81	20.6	0.135	3.4	6.00	SPR	CG	Z
0.781	19.84	KK-91	1.44	36.5	.661	16.8	6.2	1.1	.84	21	5.2	23	.60	15.2	0.060	1.5	10.0	SPR	CG	Z
0.781	19.84	2973	1.50	38.1	.679	17.2	2.6	.45	.91	23	2.4	10	.59	15.1	0.051	1.3	11.8	SPR	CG	Z
0.781	19.84	3498	1.50	38.1	.651	16.5	8.7	1.5	.79	20	6.9	31	.72	18.2	0.065	1.7	10.0	SPR	C	Z
0.781	19.84	11909	1.50	38.1	.639	16.2	18	3.2	.81	21	15	65	.50	12.6	0.071	1.8	7.00	SST	CG	N
0.781	19.84	10991	1.50	38.1	.531	13.5	207	36	.37	9.4	76	339	1.00	25.4	0.125	3.2	8.00	HD	CG	Z
0.781	19.84	11167	1.50	38.1	.531	13.5	216	38	.35	9.0	76	339	.97	24.6	0.125	3.2	7.75	SPR	CG	Z
0.781	19.84	B11-25	1.50	38.1	.409	10.4	2042	358	.10	2.6	212	941	1.12	28.3	0.186	4.7	6.00	SPR	CG	N
0.781	19.84	3127	1.63	41.3	.641	16.3	19	3.4	.78	20	15	67	.49	12.4	0.070	1.8	7.00	SPR	CG	Z
0.781	19.84	64	1.63	41.3	.541	13.7	147	26	.46	12	68	302	1.08	27.4	0.120	3.0	9.00	HD	CG	Z
0.781	19.84	BB-55	1.63	41.3	.461	11.7	582	102	.22	5.7	130	577	1.28	32.5	0.160	4.1	8.00	SST	CG	N
0.781	19.84	S-300	1.88	47.6	.637	16.2	16	2.8	.98	25	15	68	.58	14.6	0.072	1.8	8.00	SST	CG	N
0.781	19.84	11950	2.00	50.8	.461	11.7	605	106	.24	6.1	146	650	1.36	34.5	0.160	4.1	8.50	SPR	CG	Z
0.781	19.84	387	2.25	57.2	.541	13.7	103	18	.66	17	68	302	1.44	36.6	0.120	3.0	12.0	HD	CG	Z
0.781	19.84	S-1198	2.38	60.3	.657	16.7	9.0	1.6	1.2	29	10	46	.47	11.8	0.062	1.6	7.50	SST	CG	N
0.781	19.84	S-1273	2.44	61.9	.673	17.1	4.6	.81	1.5	38	6.9	31	.43	11.0	0.054	1.4	8.00	SST	CG	N
0.781	19.84	4204	2.50	63.5	.699	17.8	2.0	.35	1.7	44	3.5	15	.29	7.3	0.041	1.0	7.00	SPR	CG	Z
0.781	19.84	4139	2.63	66.7	.515	13.1	154	27	.58	15	89	394	1.70	43.1	0.133	3.4	12.8	SPR	CG	Z
0.781	19.84	3361	2.69	68.2	.511	13.0	161	28	.57	15	92	411	1.76	44.6	0.135	3.4	13.0	SPR	CG	Z
0.781	19.84	3760	2.75	69.9	.691	17.6	2.6	.45	1.8	45	4.6	20	.39	10.0	0.045	1.1	7.75	SPR	C	Z
0.781	19.84	12322	2.78	70.6	.609	15.5	20	3.4	1.4	36	28	123	1.20	30.6	0.086	2.2	14.0	SPR	CG	GI
0.781	19.84	12275	2.84	72.2	.587	14.9	57	9.9	.66	17	38	168	.87	22.2	0.097	2.5	9.00	SPR	CG	Z
0.781	19.84	3484	2.88	73.0	.531	13.5	131	23	.58	15	76	339	1.44	36.5	0.125	3.2	11.5	HD	CG	Z
0.781	19.84	YY-38	3.38	85.7	.691	17.6	1.2	.20	2.7	70	3.2	14	.63	16.0	0.045	1.1	13.0	SST	C	N
0.781	19.84	10818	3.50	88.9	.731	18.6	.10	.02	3.1	79	.32	1.4	.39	10.0	0.025	0.6	14.8	MW	C	N
0.781	19.84	3293	3.50	88.9	.661	16.8	4.1	.73	2.4	62	10	45	.90	22.9	0.060	1.5	14.0	SPR	C	Z
0.781	19.84	3305	3.50	88.9	.597	15.2	29	5.0	1.1	29	32	144	1.20	30.4	0.092	2.3	13.0	SPR	CG	Z
0.781	19.84	3224	3.56	90.5	.585	14.9	28	4.9	1.4	36	39	173	1.67	42.3	0.098	2.5	17.0	SPR	CG	Z
0.781	19.84	3461	3.63	92.1	.657	16.7	5.7	1.0	1.9	49	11	49	.74	18.9	0.062	1.6	12.0	HD	CG	Z
0.781	19.84	4217	4.00	101.6	.689	17.5	1.5	.27	3.2	80	4.9	22	.62	15.8	0.046	1.2	12.5	SPR	C	Z
0.781	19.84	11533	4.00	101.6	.657	16.7	2.7	.47	2.5	63	6.6	29	1.52	38.6	0.062	1.6	23.5	SPR	CG	Z
0.781	19.84	B7-53	4.19	106.4	.637	16.2	6.1	1.1	2.5	64	15	68	1.28	32.5	0.072	1.8	17.8	SST	CG	N
0.781	19.84	12037	5.56	141.3	.589	15.0	17	3.0	2.1	54	37	163	2.30	58.5	0.096	2.4	24.0	SPR	CG	Z
0.785	19.94	12787	1.31	33.3	.709	18.0	1.9	.34	1.1	27	2.0	9.0	.26	6.5	0.038	1.0	5.75	MW	C	N
0.796	20.22	2740	.66	16.7	.652	16.6	34	5.9	.30	7.5	10	45	.36	9.1	0.072	1.8	5.00	MW	CG	Z
0.796	20.22	1647	.75	19.1	.688	17.5	9.0	1.6	.41	10	3.7	16	.34	8.7	0.054	1.4	5.33	SPR	C	Z
0.796	20.22	11810	.84	21.4	.674	17.1	17	2.9	.54	14	9.0	40	.31	7.7	0.061	1.5	5.00	SPR	CG	Z
0.796	20.22	PP-88	.97	24.6	.536	13.6	463	81	.18	4.5	82	363	.65	16.5	0.130	3.3	5.00	SPR	CG	N
0.796	20.22	B11-38	1.00	25.4	.708	18.0	3.6	.63	.76	19	2.7	12	.24	6.1	0.044	1.1	5.50	SPR	CG	N
0.796	20.22	MM-99	1.03	26.2	.536	13.6	352	62	.21	5.3	73	327	.72	18.2	0.130	3.3	5.50	SST	CG	N
0.796	20.22	A11-32	1.06	27.0	.612	15.5	87	15	.34	8.6	29	131	.46	11.7	0.092	2.3	5.00	SST	CG	N
0.796	20.22	S-491	1.06	27.0	.546	13.9	294	52	.23	5.9	68	304	.69	17.5	0.125	3.2	5.50	SST	CG	N
0.796	20.22	S-804	1.19	30.2	.688	17.5	6.5	1.1	.86	22	5.6	25	.32	8.2	0.054	1.4	6.00	SST	CG	N
0.796	20.22	2857	1.22	31.0	.666	16.9	16	2.9	.83	21	14	61	.39	9.9	0.065	1.7	6.00	MW	CG	Z
0.796	20.22	Y-28	1.28	32.5	.596	15.1	90	16	.45	11	41	180	.68	17.1	0.100	2.5	6.75	SPR	CG	Z
0.796	20.22	S-870	1.31	33.3	.702	17.8	5.3	.92	.91	23	4.8	21	.22	5.7	0.047	1.2	4.75	SST	CG	N
0.796	20.22	3759	1.31	33.3	.616	15.6	60	10	.50	13	30	132	.68	17.1	0.090	2.3	6.50	SPR	C	Z
0.796	20.22	S-441	1.31	33.3	.614	15.6	55	9.7	.51	13	29	127	.59	15.0	0.091	2.3	6.50	SST	CG	N
0.796	20.22	3116	1.34	34.1	.526	13.4	367	64	.25	6.3	91	404	.88	22.3	0.135	3.4	6.50	SPR	CG	Z
0.796	20.22	B8-51	1.38	34.9	.456	11.6	979	171	.17	4.4	170	758	1.19	30.2	0.170	4.3	7.00	SPR	CG	Z
0.796	20.22	S-1142	1.50	38.1	.716	18.2	1.3	.24	1.2	29	1.6	6.9	.34	8.6	0.040	1.0	7.50	SST	C	N
0.796	20.22	S-1207	1.50	38.1	.652	16.6	22	3.9	.68	17	15	67	.43	11.0	0.072	1.8	6.00	SST	CG	N
0.796	20.22	MM-51	1.50	38.1	.596	15.1	58	10	.65	16	38	167	.85	21.6	0.100	2.5	8.50	SST	CG	N
0.796	20.22	A13-66	1.50	38.1	.586	14.9	94	16	.46	12	43	193	.74	18.7	0.105	2.7	7.00	SST	CG	N
0.796	20.22	10668	1.50	38.1	.552	14.0	181	32	.39	9.8	70	311	.95	24.0	0.122	3.1	7.75	SPR	CG	Z
0.796	20.22	S-3156	1.56	39.7	.672	17.1	5.8	1.0	.94	24	5.5	24	.62	15.7	0.062	1.6	10.0	SST	CG	N
0.796	20.22	BB-28	1.63	41.3	.676	17.2	9.2	1.6	1.0	26	9.3	41	.39	9.9	0.060	1.5	6.50	SST	CG	N
0.796	20.22	S-234	1.69	42.8	.688	17.5	5.3	.93	1.3	33	6.8	30	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.796	20.22	S-1173	1.75	44.5	.586	14.9	46	8.1	.49	12	23	100	1.26	32.0	0.105	2.7	12.0	SST	CG	N
0.796	20.22	B8-52	1.91	48.4	.680	17.3	7.0	1.2	1.3	32	8.9	40	.45	11.4	0.058	1.5	7.75	SPR	CG	N
0.796	20.22	10628	2.00	50.8	.672	17.1	5.7	.99	1.3	33	7.3	32	.71	18.1	0.062	1.6	11.5	SPR	CG	Z
0.796	20.22	S-1029	2.00	50.8	.668	17.0	4.5	.78	1.1	28	4.9	22	.90	22.8	0.064	1.6	14.0	SST	CG	N
0.796	20.22	LL-48	2.00	50.8	.656	16.7	6.7	1.2	1.0	26	6.8	30	.98	24.9	0.070	1.8	14.0	SST	CG	N
0.796	20.22	2798	2.00	50.8	.612	15.5	42	7.4	.75	19	32	141	.83	21.0	0.092	2.3	9.00	SPR	CG	Z
0.796	20.22	10052	2.00	50.8	.484	12.3	481	84	.28	7.1	134	596	1.37	34.7	0.156	4.0	8.75	SPR	CG	Z
0.796	20.22	11594	2.03	51.6	.476	12.1	523	92	.27	7.0	144	640	1.60	40.6	0.160	4.1	9.00	SPR	CG	Z
0.796	20.22	CC-47	2.28	57.9	.636	16.2	21	3.7	1.0	26	22	98	.76	19.3	0.080	2.0	9.50	SPR	CG	Z
0.796	20.22	S-1132	2.31	58.7	.686	17.4	3.1	.55	1.7	42	5.2	23	.66	16.8	0.055	1.4	11.0	SST	C	N
0.796	20.22	M-95	2.50	63.5	.698	17.7	3.3	.58	1.7	44	5.8	26	.39	10.0	0.049	1.2	8.00	SPR	CG	N
0.796	20.22	1749	2.50	63.5	.586	14.9	59	10	1.1	28	65	291	1.26	32.0	0.105	2.7	11.0	MW	C	Z
0.796	20.22	12165	2.63	66.7	.636	16.2	20	3.5	1.1	28	22	98	.80	20.3	0.080	2.0	10.0	SPR	CG	Z
0.796	20.22	4234	2.75	69.9	.636	16.2	16	2.8	1.4	35	22	98	.96	24.4	0.080	2.0	12.0	SPR	CG	Z
0.796	20.22	11141	2.78	70.6	.612	15.5	34	5.9	.94	24	32	141	.99	25.1	0.092	2.3	10.8	HD	CG	Z
0.796	20.22	10737	2.78	70.6	.566	14.4	60	11	.89	23	54	239	1.58	40.2	0.115	2.9	13.8	SST	CG	N
0.796	20.22	11647	2.88	73.0	.614	15.6	26	4.5	1.2	31	31	137	1.18	30.0	0.091	2.3	13.0	SPR	CG	Z
0.796	20.22	12161	2.94	74.6	.652	16.6	5.7	.99	1.5	38	8.5	38	1.44	36.6	0.072	1.8	20.0	SPR	CG	Z
0.796	20.22	10500	3.00	76.2	.668	17.0	6.0	1.1	2.0	51	12	53	.85	21.5	0.064	1.6	12.3	SPR	C	Z
0.796	20.22	10494	3.00	76.2	.664	16.9	8.8	1.5	1.5	38	13	58	.66	16.8	0.066	1.7	10.0	SPR	CG	Z
0.796	20.22	10667	3.13	79.4	.560	14.2	87	15	.73	18	63	282	1.45	36.7	0.118	3.0	12.3	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.796	20.22	S-232	3.25	82.6	.638	16.2	14	2.4	1.4	36	20	88	.91	23.1	0.079	2.0	11.5	SST	CG	N
0.796	20.22	3466	3.25	82.6	.586	14.9	38	6.6	1.2	31	47	208	1.79	45.3	0.105	2.7	16.0	HD	C	Z
0.796	20.22	B17-202	3.34	84.9	.652	16.6	11	2.0	1.4	36	16	71	.79	20.1	0.072	1.8	11.0	SPR	CG	N
0.796	20.22	12035	3.38	85.7	.598	15.2	27	4.8	1.4	37	39	175	1.68	42.7	0.099	2.5	17.0	SPR	CG	Z
0.796	20.22	1547	3.50	88.9	.642	16.3	13	2.2	1.5	39	20	87	1.06	26.9	0.077	2.0	12.8	SPR	C	Z
0.796	20.22	3099	3.50	88.9	.604	15.3	22	3.9	1.6	41	36	160	1.73	43.9	0.096	2.4	18.0	SPR	CG	Z
0.796	20.22	11778	4.25	108.0	.602	15.3	23	4.1	1.6	40	37	165	1.75	44.3	0.097	2.5	18.0	SPR	CG	N
0.796	20.22	12204	4.31	109.5	.636	16.2	11	1.9	2.0	50	22	98	1.32	33.5	0.080	2.0	16.5	SPR	CG	Z
0.796	20.22	S-1584	7.75	196.9	.636	16.2	14	2.5	1.4	37	21	91	.96	24.4	0.080	2.0	12.0	SST	CG	N
0.796	20.22	10848	8.25	209.6	.676	17.2	2.3	.41	4.2	107	9.9	44	1.38	35.1	0.060	1.5	22.0	SPR	C	GI
0.796	20.22	3054	9.00	228.6	.672	17.1	3.0	.52	3.6	93	11	48	1.30	33.1	0.062	1.6	20.0	SPR	C	Z
0.796	20.22	S-76	11.4	288.9	.466	11.8	88	15	1.6	40	139	619	7.26	184.4	0.165	4.2	44.0	SST	CG	N
0.812	20.62	DD-6	.38	9.5	.762	19.4	.33	.06	.21	5.4	.07	.31	.16	4.1	0.025	0.6	5.50	MW	C	Z
0.812	20.62	BB-77	.44	11.1	.698	17.7	18	3.1	.21	5.3	3.7	16	.23	5.8	0.057	1.4	4.00	SPR	CG	N
0.812	20.62	2856	.47	11.9	.704	17.9	11	2.0	.23	5.7	2.5	11	.24	6.2	0.054	1.4	4.50	HD	CG	Z
0.812	20.62	FF-36	.50	12.7	.692	17.6	18	3.1	.17	4.3	3.0	13	.33	8.4	0.060	1.5	4.50	SPR	C	N
0.812	20.62	S-939	.69	17.4	.668	17.0	56	9.9	.26	6.7	15	66	.25	6.4	0.072	1.8	3.50	SST	CG	N
0.812	20.62	3356	.69	17.4	.642	16.3	98	17	.26	6.7	26	114	.34	8.6	0.085	2.2	4.00	SPR	CG	Z
0.812	20.62	DD-84	.72	18.2	.722	18.3	3.2	.57	.47	12	1.5	6.8	.25	6.3	0.045	1.1	5.50	SST	CG	N
0.812	20.62	II-7	.78	19.8	.692	17.6	9.7	1.7	.42	11	4.1	18	.36	9.1	0.060	1.5	6.00	SST	CG	N
0.812	20.62	11432	.81	20.6	.662	16.8	28	5.0	.36	9.2	10	46	.45	11.4	0.075	1.9	6.00	SPR	CG	Z
0.812	20.62	H-21	.81	20.6	.602	15.3	195	34	.22	5.5	43	189	.45	11.3	0.105	2.7	4.25	SST	CG	N
0.812	20.62	12639	.88	22.2	.520	13.2	1474	258	.07	1.7	101	448	.51	13.0	0.146	3.7	3.50	SST	C	N
0.812	20.62	S-123	1.00	25.4	.704	17.9	11	1.9	.61	16	6.7	30	.23	5.8	0.054	1.4	4.25	SST	CG	N
0.812	20.62	10340	1.00	25.4	.686	17.4	18	3.1	.62	16	11	50	.38	9.6	0.063	1.6	5.00	SPR	C	Z
0.812	20.62	FF-68	1.00	25.4	.532	13.5	497	87	.18	4.6	89	397	.74	18.7	0.140	3.6	5.25	SST	CG	N
0.812	20.62	3038	1.03	26.2	.632	16.1	61	11	.48	12	29	129	.55	14.0	0.090	2.3	6.00	SPR	CG	GI
0.812	20.62	B10-52	1.13	28.6	.648	16.5	42	7.3	.55	14	23	103	.49	12.5	0.082	2.1	6.00	SPR	CG	Z
0.812	20.62	4160	1.19	30.2	.496	12.6	801	140	.17	4.3	137	607	.95	24.1	0.158	4.0	6.00	SPR	CG	Z
0.812	20.62	S-1609	1.22	31.0	.602	15.3	110	19	.39	9.9	43	189	.63	16.0	0.105	2.7	6.00	SST	CG	N
0.812	20.62	1918	1.22	31.0	.504	12.8	710	124	.18	4.5	127	565	.92	23.5	0.154	3.9	6.00	SPR	CG	Z
0.812	20.62	KK-6	1.25	31.8	.592	15.0	122	21	.42	11	51	226	.77	19.6	0.110	2.8	7.00	SPR	CG	N
0.812	20.62	S-933	1.28	32.5	.686	17.4	12	2.1	.84	21	10	45	.44	11.2	0.063	1.6	6.00	SST	C	N
0.812	20.62	K-48	1.38	34.9	.528	13.4	389	68	.27	6.8	103	460	.99	25.2	0.142	3.6	7.00	SPR	CG	Z
0.812	20.62	2680	1.38	34.9	.500	12.7	670	117	.28	7.0	184	821	1.01	25.8	0.156	4.0	6.50	MW	CG	Z
0.812	20.62	63	1.38	34.9	.488	12.4	721	126	.20	5.2	147	652	1.13	28.8	0.162	4.1	7.00	HD	CG	Z
0.812	20.62	S-25	1.50	38.1	.758	19.3	.34	.06	1.3	33	.45	2.0	.19	4.8	0.027	0.7	6.00	SST	C	N
0.812	20.62	10601	1.50	38.1	.728	18.5	1.4	.25	1.1	27	1.5	6.7	.42	10.7	0.042	1.1	9.00	SPR	C	Z
0.812	20.62	S-366	1.50	38.1	.718	18.2	3.4	.60	1.2	31	4.1	18	.28	7.2	0.047	1.2	6.00	SST	CG	N
0.812	20.62	12554	1.50	38.1	.652	16.6	26	4.6	.77	20	20	90	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.812	20.62	S-3207	1.53	38.9	.602	15.3	88	15	.48	12	43	189	.74	18.7	0.105	2.7	7.00	SST	CG	N
0.812	20.62	10788	1.63	41.3	.688	17.5	9.9	1.7	1.0	26	10	45	.47	11.8	0.062	1.6	6.50	SST	C	N
0.812	20.62	3960	1.63	41.3	.572	14.5	138	24	.47	12	65	291	1.02	25.9	0.120	3.0	8.50	SPR	CG	Z
0.812	20.62	S-799	1.66	42.1	.716	18.2	3.8	.66	1.3	34	5.0	22	.29	7.3	0.048	1.2	6.00	SST	CG	N
0.812	20.62	3801	1.69	42.8	.602	15.3	76	13	.60	15	46	204	.89	22.7	0.105	2.7	8.50	SPR	CG	GI
0.812	20.62	2645	1.75	44.5	.688	17.5	4.2	.73	.82	21	3.4	15	.93	23.6	0.062	1.6	14.0	HD	C	Z
0.812	20.62	12605	1.75	44.5	.652	16.6	27	4.8	1.1	27	29	130	.68	17.3	0.080	2.0	7.50	MW	C	N
0.812	20.62	3079	1.75	44.5	.572	14.5	124	22	.53	13	65	291	1.11	28.2	0.120	3.0	9.25	SPR	CG	Z
0.812	20.62	3354	1.75	44.5	.572	14.5	129	23	.51	13	65	291	1.20	30.5	0.120	3.0	9.00	SPR	C	Z
0.812	20.62	3139	1.78	45.2	.518	13.2	380	67	.30	7.6	114	507	1.18	29.9	0.147	3.7	8.00	SPR	CG	Z
0.812	20.62	12490	1.81	46.0	.706	17.9	3.8	.66	1.3	34	5.0	22	.48	12.1	0.053	1.3	8.00	SST	C	N
0.812	20.62	65	1.88	47.6	.572	14.5	116	20	.56	14	65	291	1.17	29.7	0.120	3.0	9.75	HD	CG	Z
0.812	20.62	2974	2.00	50.8	.730	18.5	1.1	.19	1.5	39	1.7	7.6	.45	11.5	0.041	1.0	10.0	SPR	C	Z
0.812	20.62	3282	2.00	50.8	.688	17.5	5.0	.88	1.3	32	6.3	28	.74	18.9	0.062	1.6	12.0	HD	CG	Z
0.812	20.62	12157	2.13	54.0	.650	16.5	26	4.6	.85	21	22	99	.65	16.5	0.081	2.1	8.00	SPR	CG	GI
0.812	20.62	S-1215	2.13	54.0	.612	15.5	35	6.1	.93	23	32	142	1.20	30.5	0.100	2.5	12.0	SST	CG	N
0.812	20.62	11959	2.16	54.8	.744	18.9	.52	.09	1.8	46	.94	4.2	.34	8.6	0.034	0.9	9.00	SST	C	N
0.812	20.62	3945	2.19	55.6	.704	17.9	3.1	.55	1.5	39	4.8	21	.65	16.5	0.054	1.4	11.0	SPR	C	Z
0.812	20.62	B8-35	2.25	57.2	.708	18.0	2.7	.46	1.7	44	4.6	20	.52	13.2	0.052	1.3	10.0	SST	CG	N
0.812	20.62	69	2.25	57.2	.602	15.3	55	9.6	.84	21	46	204	1.26	32.0	0.105	2.7	11.0	HD	CG	Z
0.812	20.62	70	2.25	57.2	.572	14.5	112	20	.58	15	65	291	1.32	33.5	0.120	3.0	10.0	HD	C	Z
0.812	20.62	11217	2.25	57.2	.562	14.3	117	20	.63	16	74	328	1.41	35.7	0.125	3.2	11.3	HD	CG	Z
0.812	20.62	12145	2.50	63.5	.684	17.4	5.2	.92	1.7	42	8.7	39	.83	21.1	0.064	1.6	13.0	SPR	CG	Z
0.812	20.62	S-1612	2.50	63.5	.682	17.3	4.6	.80	1.5	39	6.9	31	.98	24.8	0.065	1.7	14.0	SST	C	N
0.812	20.62	12061	2.50	63.5	.652	16.6	14	2.4	1.5	37	20	89	1.04	26.4	0.080	2.0	13.0	SPR	CG	Z
0.812	20.62	11188	2.50	63.5	.642	16.3	19	3.4	1.3	32	24	107	1.02	25.9	0.085	2.2	11.0	SST	C	N
0.812	20.62	S-3090	2.50	63.5	.612	15.5	41	7.1	.91	23	37	164	1.05	26.7	0.100	2.5	10.5	SST	CG	N
0.812	20.62	3459	2.50	63.5	.602	15.3	55	9.6	.84	21	46	204	1.16	29.3	0.105	2.7	11.0	HD	CG	Z
0.812	20.62	12606	2.66	67.5	.542	13.8	166	29	.75	19	125	556	1.65	42.0	0.135	3.4	11.3	MW	C	N
0.812	20.62	12163	2.75	69.9	.686	17.4	5.4	.94	2.0	51	11	48	.76	19.2	0.063	1.6	12.0	SPR	CG	GI
0.812	20.62	12543	2.75	69.9	.562	14.3	114	20	.73	18	83	369	1.56	39.7	0.125	3.2	11.5	OT	C	N
0.812	20.62	4173	2.88	73.0	.628	16.0	25	4.4	1.2	32	31	139	1.20	30.4	0.092	2.3	13.0	SPR	CG	N
0.812	20.62	1727	3.00	76.2	.708	18.0	3.4	.60	1.9	47	6.3	28	.52	13.2	0.052	1.3	9.00	SPR	C	Z
0.812	20.62	10709	3.00	76.2	.686	17.4	5.4	.94	2.1	53	11	50	.82	20.8	0.063	1.6	12.0	SPR	C	Z
0.812	20.62	3236	3.00	76.2	.648	16.5	18	3.1	1.3	33	23	103	1.01	25.7	0.082	2.1	11.3	SPR	C	Z
0.812	20.62	12492	3.00	76.2	.630	16.0	22	3.8	1.4	35	30	134	1.27	32.4	0.091	2.3	14.0	SPR	CG	N
0.812	20.62	11475	3.19	81.0	.672	17.1	8.4	1.5	1.7	44	15	65	.91	23.1	0.070	1.8	12.0	SPR	C	Z
0.812	20.62	3970	3.19	81.0	.668	17.0	9.1	1.6	1.7	44	16	70	.90	22.9	0.072	1.8	12.5	SPR	CG	Z
0.812	20.62	4102	3.38	85.7	.692	17.6	3.0	.52	2.3	59	6.9	31	1.07	27.1	0.060	1.5	16.8	SPR	C	Z
0.812	20.62	37	3.75	95.3	.542	13.8	91	16	.99	25	89	398	2.57	65.2	0.135	3.4	19.0	HD	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.812	20.62	S-1400	3.88	98.4	.668	17.0	6.6	1.2	2.2	57	15	66	1.12	28.3	0.072	1.8	14.5	SST	C	N
0.812	20.62	10687	3.88	98.4	.652	16.6	11	1.9	1.9	49	22	96	1.24	31.5	0.080	2.0	15.5	SPR	CG	Z
0.812	20.62	2837	4.25	108.0	.724	18.4	1.3	.23	3.1	79	4.1	18	.53	13.4	0.044	1.1	11.0	SPR	C	GI
0.812	20.62	12431	4.25	108.0	.724	18.4	1.3	.23	3.1	79	4.1	18	.53	13.4	0.044	1.1	11.0	SPR	C	GI
0.812	20.62	11248	4.50	114.3	.592	15.0	31	5.5	1.6	41	51	226	2.37	60.1	0.110	2.8	21.5	SPR	CG	Z
0.812	20.62	S-966	4.75	120.7	.652	16.6	7.7	1.4	2.6	66	20	90	1.51	38.4	0.080	2.0	19.0	SST	CG	N
0.812	20.62	2701	5.13	130.2	.626	15.9	15	2.7	2.9	74	45	200	2.02	51.4	0.093	2.4	20.8	MW	C	Z
0.812	20.62	11601	5.13	130.2	.536	13.6	71	12	1.3	34	95	423	3.73	94.6	0.138	3.5	26.0	SPR	C	Z
0.812	20.62	2589	5.19	131.8	.488	12.4	180	32	.81	21	147	652	3.56	90.5	0.162	4.1	22.0	HD	CG	Z
0.812	20.62	2738	5.50	139.7	.592	15.0	30	5.2	1.7	44	51	226	2.48	62.9	0.110	2.8	22.5	SPR	CG	Z
0.812	20.62	10214	7.00	177.8	.602	15.3	22	3.8	2.1	53	46	204	2.57	65.4	0.105	2.7	24.5	SPR	CG	Z
0.812	20.62	2997	9.19	233.4	.516	13.1	54	9.4	2.2	55	116	517	6.81	172.9	0.148	3.8	46.0	SPR	CG	Z
0.812	20.62	12741	10.0	254.0	.558	14.2	31	5.4	2.5	64	77	343	5.21	132.3	0.127	3.2	40.0	SPR	C	N
0.812	20.62	4244	15.5	393.7	.602	15.3	11	1.9	4.1	105	46	204	4.88	124.0	0.105	2.7	46.5	SPR	CG	Z
0.822	20.88	B2-66	2.63	66.7	.550	14.0	160	28	.65	16	105	466	1.70	43.2	0.136	3.5	11.5	0T	C	N
0.828	21.03	11483	.50	12.7	.728	18.5	19	3.3	.29	7.4	5.5	25	.20	5.1	0.050	1.3	3.00	SPR	CG	Z
0.828	21.03	B14-67	.50	12.7	.672	17.1	126	22	.16	3.9	20	87	.23	5.9	0.078	2.0	3.00	SPR	CG	Z
0.828	21.03	KK-62	.50	12.7	.588	14.9	745	130	.08	2.0	59	261	.36	9.1	0.120	3.0	3.00	SST	CG	N
0.828	21.03	S-349	.72	18.2	.642	16.3	320	56	.09	2.3	29	130	.26	6.5	0.093	2.4	2.75	SST	CG	N
0.828	21.03	S-416	.78	19.8	.704	17.9	10	1.8	.41	10	4.3	19	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.828	21.03	S-1111	.81	20.6	.764	19.4	1.0	.18	.64	16	.66	2.9	.18	4.5	0.032	0.8	4.50	SST	C	N
0.828	21.03	3872	.81	20.6	.732	18.6	11	1.9	.49	12	5.2	23	.22	5.5	0.048	1.2	3.50	SPR	C	Z
0.828	21.03	11361	.81	20.6	.668	17.0	71	12	.28	7.0	20	88	.30	7.6	0.080	2.0	3.75	SST	CG	N
0.828	21.03	11227	.84	21.4	.474	12.0	2922	512	.06	1.6	185	822	.66	16.9	0.177	4.5	3.75	SPR	CG	Z
0.828	21.03	CC-68	.88	22.2	.648	16.5	42	7.3	.25	6.2	10	45	.63	16.0	0.090	2.3	7.00	SST	CG	N
0.828	21.03	2958	.91	23.0	.734	18.6	3.7	.64	.62	16	2.3	10	.28	7.2	0.047	1.2	6.00	SPR	CG	Z
0.828	21.03	12430	.94	23.8	.742	18.8	9.0	1.6	.39	10	3.5	16	.17	4.4	0.043	1.1	3.00	SST	C	N
0.828	21.03	S-3206	.94	23.8	.732	18.6	8.1	1.4	.60	15	4.9	22	.18	4.6	0.048	1.2	3.75	SST	CG	N
0.828	21.03	12315	1.00	25.4	.764	19.4	.75	.13	.81	21	.60	2.7	.19	4.9	0.032	0.8	6.00	SPR	CG	Z
0.828	21.03	KK-58	1.00	25.4	.728	18.5	9.5	1.7	.58	15	5.5	25	.20	5.1	0.050	1.3	4.00	SPR	CG	Z
0.828	21.03	4333	1.00	25.4	.704	17.9	16	2.8	.63	16	9.9	44	.37	9.4	0.062	1.6	5.00	SPR	C	N
0.828	21.03	10792	1.00	25.4	.646	16.4	55	9.6	.45	12	25	110	.55	13.9	0.091	2.3	6.00	SST	CG	N
0.828	21.03	KK-97	1.00	25.4	.608	15.4	112	20	.29	7.2	32	142	.72	18.2	0.110	2.8	6.50	SST	CG	N
0.828	21.03	11478	1.03	26.2	.728	18.5	9.5	1.7	.58	15	5.5	25	.25	6.4	0.050	1.3	4.00	SPR	CG	Z
0.828	21.03	3852	1.06	27.0	.732	18.6	4.3	.75	.74	19	3.2	14	.32	8.2	0.048	1.2	5.75	SPR	C	Z
0.828	21.03	11696	1.06	27.0	.648	16.5	59	10	.49	12	29	128	.54	13.7	0.090	2.3	6.00	SPR	CG	GI
0.828	21.03	12176	1.22	31.0	.516	13.1	701	123	.18	4.7	130	576	.94	23.8	0.156	4.0	6.00	SPR	CG	Z
0.828	21.03	10702	1.38	34.9	.700	17.8	18	3.2	.64	16	12	51	.32	8.1	0.064	1.6	5.00	SPR	CG	Z
0.828	21.03	A13-64	1.38	34.9	.686	17.4	28	4.9	.53	13	15	66	.36	9.0	0.071	1.8	5.00	SPR	CG	GI
0.828	21.03	10944	1.50	38.1	.708	18.0	10	1.8	.92	23	9.5	42	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.828	21.03	S-3163	1.50	38.1	.708	18.0	29	5.1	.30	7.7	8.9	40	.48	12.2	0.060	1.5	6.00	SST	CG	N
0.828	21.03	3424	1.50	38.1	.418	10.6	2100	368	.07	1.7	136	607	1.44	36.4	0.205	5.2	7.00	SPR	CG	Z
0.828	21.03	S-292	1.63	41.3	.644	16.4	35	6.1	.82	21	28	126	.78	19.9	0.092	2.3	8.50	SST	CG	N
0.828	21.03	S-1080	1.75	44.5	.724	18.4	4.3	.76	1.3	34	5.8	26	.39	9.9	0.052	1.3	6.50	SST	C	N
0.828	21.03	11768	1.75	44.5	.648	16.5	39	6.8	.73	19	29	128	.72	18.3	0.090	2.3	8.00	SPR	CG	Z
0.828	21.03	KK-35	1.81	46.0	.608	15.4	53	9.3	.55	14	29	129	1.27	32.1	0.110	2.8	11.5	SST	CG	N
0.828	21.03	TT-59	1.88	47.6	.668	17.0	24	4.3	.81	21	20	88	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.828	21.03	NN-8	1.88	47.6	.588	14.9	115	20	.51	13	59	261	1.02	25.9	0.120	3.0	8.50	SST	CG	N
0.828	21.03	10527	1.91	48.4	.532	13.5	366	64	.31	7.9	114	509	1.18	30.1	0.148	3.8	8.00	SPR	CG	N
0.828	21.03	12211	1.94	49.2	.708	18.0	8.2	1.4	1.2	29	9.5	42	.42	10.7	0.060	1.5	7.00	SPR	CG	Z
0.828	21.03	S-339	2.00	50.8	.578	14.7	117	21	.56	14	66	294	1.19	30.2	0.125	3.2	9.50	SST	CG	N
0.828	21.03	3226	2.09	53.2	.638	16.2	42	7.4	.79	20	34	150	.95	24.1	0.095	2.4	9.00	SPR	C	Z
0.828	21.03	S-361	2.13	54.0	.668	17.0	17	3.1	1.1	29	20	88	.72	18.3	0.080	2.0	9.00	SST	CG	N
0.828	21.03	10591	2.13	54.0	.668	17.0	23	4.1	.90	23	21	94	.72	18.3	0.080	2.0	8.00	SPR	C	Z
0.828	21.03	11987	2.19	55.6	.716	18.2	2.9	.51	1.5	38	4.4	19	.70	17.8	0.056	1.4	12.5	SPR	CG	GI
0.828	21.03	DD-80	2.50	63.5	.668	17.0	15	2.7	1.4	35	21	94	.90	22.9	0.080	2.0	11.3	SPR	CG	GI
0.828	21.03	11354	2.50	63.5	.668	17.0	14	2.4	1.4	36	20	88	.96	24.4	0.080	2.0	11.0	SST	C	N
0.828	21.03	1903	2.50	63.5	.646	16.4	25	4.4	1.2	30	30	132	1.07	27.2	0.091	2.3	11.8	SPR	CG	Z
0.828	21.03	11258	2.50	63.5	.578	14.7	101	18	.72	18	72	322	1.50	38.1	0.125	3.2	12.0	SPR	CG	Z
0.828	21.03	11933	2.63	66.7	.738	18.7	1.8	.31	2.2	56	3.9	17	.41	10.3	0.045	1.1	9.00	SPR	CG	Z
0.828	21.03	10806	2.63	66.7	.658	16.7	18	3.2	1.3	33	24	105	1.02	25.9	0.085	2.2	11.0	SST	C	N
0.828	21.03	S-287	2.75	69.9	.742	18.8	.88	.15	2.2	57	2.0	8.8	.52	13.1	0.043	1.1	12.0	SST	CG	N
0.828	21.03	S-3038	2.88	73.0	.454	11.5	553	97	.32	8.1	177	788	2.34	59.4	0.187	4.7	12.5	SST	CG	N
0.828	21.03	S-3202	3.00	76.2	.762	19.4	.25	.04	2.5	64	.64	2.8	.46	11.7	0.033	0.8	14.0	SST	CG	N
0.828	21.03	S-63	3.00	76.2	.758	19.3	.31	.05	2.5	64	.79	3.5	.49	12.4	0.035	0.9	14.0	SST	CG	N
0.828	21.03	S-72	3.00	76.2	.618	15.7	50	8.8	.83	21	42	186	1.16	29.3	0.105	2.7	10.0	SST	C	N
0.828	21.03	B8-38	3.00	76.2	.576	14.6	77	14	.87	22	68	301	1.76	44.8	0.126	3.2	14.0	SST	CG	N
0.828	21.03	S-3011	3.13	79.4	.704	17.9	4.1	.72	2.4	60	9.8	44	.74	18.9	0.062	1.6	12.0	SST	CG	N
0.828	21.03	G-43	3.31	84.1	.746	18.9	.74	.13	2.8	71	2.1	9.1	.53	13.5	0.041	1.0	12.0	SST	C	N
0.828	21.03	B9-52	3.50	88.9	.620	15.7	28	4.8	1.6	40	44	195	1.87	47.5	0.104	2.6	18.0	SPR	CG	Z
0.828	21.03	3185	3.53	89.7	.744	18.9	.93	.16	3.0	77	2.8	13	.50	12.7	0.042	1.1	12.0	SPR	CG	Z
0.828	21.03	3679	3.66	92.9	.558	14.2	110	19	.80	20	88	391	2.03	51.4	0.135	3.4	15.0	SPR	CG	Z
0.828	21.03	11268	3.75	95.3	.672	17.1	9.7	1.7	2.0	51	20	87	1.25	31.7	0.078	2.0	15.0	SPR	C	Z
0.828	21.03	11321	3.75	95.3	.588	14.9	56	9.8	1.1	29	64	286	2.04	51.8	0.120	3.0	17.0	SPR	CG	Z
0.828	21.03	12062	3.78	96.0	.698	17.7	4.4	.76	2.8	70	12	54	.99	25.2	0.065	1.7	15.3	SPR	CG	Z
0.828	21.03	11103	3.81	96.8	.588	14.9	56	9.8	1.1	29	64	286	2.04	51.8	0.120	3.0	17.0	SPR	CG	Z
0.828	21.03	11620	3.88	98.4	.682	17.3	5.9	1.0	2.5	63	15	66	1.39	35.2	0.073	1.9	18.0	SPR	CG	Z
0.828	21.03	12113	3.88	98.4	.600	15.2	37	6.5	1.5	38	55	247	2.28	57.9	0.114	2.9	20.0	SPR	CG	Z
0.828	21.03	3100	5.00	127.0	.618	15.7	24	4.3	1.9	47	45	200	2.21	56.0	0.105	2.7	21.0	SPR	CG	Z
0.828	21.03	11801	5.22	132.6	.668	17.0	8.0	1.4	2.6	67	21	94	1.64	41.7	0.080	2.0	19.5	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.828	21.03	S-3231	6.03	153.2	.474	12.0	197	35	.83	21	164	730	4.43	112.4	0.177	4.5	25.0	SST	CG	N
0.828	21.03	1940	6.75	171.5	.646	16.4	9.9	1.7	3.0	76	30	132	2.46	62.4	0.091	2.3	27.0	SPR	CG	Z
0.828	21.03	1705	9.00	228.6	.640	16.3	8.8	1.5	3.7	94	33	145	3.31	84.2	0.094	2.4	34.3	SPR	C	Z
0.828	21.03	12542	10.0	254.0	.702	17.8	.82	.14	6.4	164	5.3	24	3.56	90.4	0.063	1.6	55.5	SST	CL	N
0.828	21.03	10154	10.0	254.0	.646	16.4	8.2	1.4	3.6	92	30	132	2.91	74.0	0.091	2.3	32.0	SPR	CG	GI
0.843	21.41	U-43	.28	7.1	.805	20.4	.33	.06	.21	5.2	.07	.31	.08	1.9	0.019	0.5	3.00	MW	C	N
0.843	21.41	B4-15	.50	12.7	.743	18.9	12	2.1	.33	8.3	3.9	17	.18	4.4	0.050	1.3	3.50	SPR	CG	N
0.843	21.41	CC-40	.50	12.7	.723	18.4	39	6.8	.24	6.1	9.3	42	.24	6.1	0.060	1.5	3.00	SPR	C	Z
0.843	21.41	H-38	.69	17.4	.649	16.5	89	16	.20	5.1	18	80	.49	12.3	0.097	2.5	5.00	SST	CG	N
0.843	21.41	B2-56	.69	17.4	.649	16.5	102	18	.20	5.1	21	92	.49	12.3	0.097	2.5	5.00	MW	CG	N
0.843	21.41	11530	.69	17.4	.575	14.6	743	130	.05	1.3	38	167	.64	16.2	0.134	3.4	3.75	SPR	CG	Z
0.843	21.41	4310	.69	17.4	.573	14.6	1076	188	.08	2.0	86	385	.44	11.1	0.135	3.4	3.25	SPR	CG	Z
0.843	21.41	S-371	.75	19.1	.657	16.7	111	19	.26	6.6	29	128	.37	9.4	0.093	2.4	4.00	SST	CG	N
0.843	21.41	XX-54	.81	20.6	.683	17.3	77	13	.25	6.4	19	87	.28	7.1	0.080	2.0	3.50	SST	CG	N
0.843	21.41	S-226	.91	23.0	.665	16.9	37	6.4	.28	7.2	10	46	.62	15.8	0.089	2.3	7.00	SST	CG	N
0.843	21.41	PP-48	1.00	25.4	.783	19.9	.96	.17	.88	22	.85	3.8	.12	3.0	0.030	0.8	4.00	SST	CG	N
0.843	21.41	S-150	1.00	25.4	.749	19.0	4.0	.71	.72	18	2.9	13	.28	7.2	0.047	1.2	5.00	SST	C	N
0.843	21.41	S-1155	1.00	25.4	.719	18.3	19	3.4	.50	13	9.7	43	.25	6.3	0.062	1.6	4.00	SST	CG	N
0.843	21.41	10028	1.00	25.4	.703	17.9	37	6.5	.37	9.5	14	62	.28	7.1	0.070	1.8	4.00	SPR	CG	Z
0.843	21.41	S-255	1.00	25.4	.693	17.6	26	4.6	.60	15	16	70	.40	10.2	0.075	1.9	5.33	SST	CG	N
0.843	21.41	S-1627	1.00	25.4	.673	17.1	56	9.7	.42	11	23	103	.49	12.4	0.085	2.2	4.75	SST	C	N
0.843	21.41	12668	1.00	25.4	.659	16.7	81	14	.52	13	42	187	.46	11.7	0.092	2.3	5.00	MW	CG	N
0.843	21.41	12674	1.00	25.4	.659	16.7	108	19	.39	9.9	42	187	.39	9.9	0.092	2.3	4.25	MW	CG	N
0.843	21.41	B15-22	1.03	26.2	.723	18.4	17	3.0	.51	13	8.8	39	.24	6.1	0.060	1.5	4.00	SST	CG	N
0.843	21.41	B6-47	1.06	27.0	.723	18.4	19	3.4	.48	12	9.3	42	.30	7.6	0.060	1.5	4.00	SPR	C	N
0.843	21.41	MM-56	1.09	27.8	.723	18.4	9.1	1.6	.72	18	6.6	29	.38	9.5	0.060	1.5	6.25	SPR	CG	N
0.843	21.41	QQ-59	1.13	28.6	.699	17.8	18	3.2	.69	18	13	56	.43	11.0	0.072	1.8	6.00	SST	CG	N
0.843	21.41	11139	1.19	30.2	.661	16.8	77	14	.38	9.6	29	130	.55	13.9	0.091	2.3	5.00	SPR	C	Z
0.843	21.41	M-23	1.25	31.8	.775	19.7	1.2	.21	1.0	27	1.3	5.6	.20	5.2	0.034	0.9	5.00	SPR	C	N
0.843	21.41	S-882	1.25	31.8	.713	18.1	16	2.9	.68	17	11	50	.32	8.0	0.065	1.7	5.00	SST	CG	N
0.843	21.41	K-63	1.25	31.8	.707	18.0	17	2.9	.82	21	14	60	.41	10.4	0.068	1.7	6.00	SPR	CG	GI
0.843	21.41	3095	1.25	31.8	.693	17.6	27	4.7	.64	16	17	76	.43	11.0	0.075	1.9	5.75	SPR	CG	Z
0.843	21.41	2892	1.28	32.5	.683	17.3	27	4.8	.73	19	20	88	.55	14.0	0.080	2.0	7.00	SPR	CG	Z
0.843	21.41	MM-12	1.28	32.5	.663	16.8	44	7.6	.60	15	26	116	.59	14.9	0.090	2.3	6.50	SST	CG	N
0.843	21.41	S-77	1.38	34.9	.761	19.3	2.1	.37	1.1	28	2.4	10	.26	6.5	0.041	1.0	5.25	SST	C	N
0.843	21.41	11995	1.38	34.9	.715	18.2	7.3	1.3	.80	20	5.8	26	.58	14.6	0.064	1.6	9.00	SPR	CG	Z
0.843	21.41	S-807	1.41	35.7	.683	17.3	29	5.0	.67	17	19	87	.48	12.2	0.080	2.0	6.00	SST	CG	N
0.843	21.41	11784	1.41	35.7	.647	16.4	71	12	.51	13	36	161	.64	16.2	0.098	2.5	6.50	SPR	CG	N
0.843	21.41	10821	1.41	35.7	.583	14.8	227	40	.34	8.7	78	345	.91	23.1	0.130	3.3	7.00	SPR	CG	Z
0.843	21.41	3168	1.47	37.3	.735	18.7	5.0	.87	1.1	28	5.4	24	.38	9.6	0.054	1.4	7.00	SPR	CG	Z
0.843	21.41	1649	1.50	38.1	.731	18.6	7.3	1.3	1.0	27	7.6	34	.39	10.0	0.056	1.4	6.00	SPR	C	Z
0.843	21.41	3214	1.50	38.1	.715	18.2	17	3.0	.66	17	11	50	.38	9.8	0.064	1.6	5.00	SPR	CG	Z
0.843	21.41	B12-64	1.50	38.1	.713	18.1	12	2.1	.98	25	12	53	.49	12.4	0.065	1.7	6.50	SPR	C	N
0.843	21.41	12612	1.50	38.1	.683	17.3	33	5.8	.63	16	21	92	.48	12.2	0.080	2.0	6.00	SPR	CG	Z
0.843	21.41	S-54	1.50	38.1	.623	15.8	124	22	.36	9.2	45	199	.63	16.1	0.110	2.8	5.75	SST	CG	N
0.843	21.41	S-1483	1.56	39.7	.683	17.3	18	3.1	.88	22	16	70	.68	17.3	0.080	2.0	8.50	SST	CG	N
0.843	21.41	1775	1.59	40.5	.715	18.2	6.2	1.1	.94	24	5.8	26	.66	16.7	0.064	1.6	10.3	SPR	CG	Z
0.843	21.41	1569	1.63	41.3	.763	19.4	2.0	.36	1.4	35	2.8	12	.26	6.6	0.040	1.0	5.50	SPR	C	Z
0.843	21.41	S-1478	1.63	41.3	.727	18.5	5.8	1.0	1.2	31	7.1	32	.41	10.3	0.058	1.5	7.00	SST	CG	N
0.843	21.41	S-3001	1.63	41.3	.719	18.3	10	1.8	.94	24	9.7	43	.36	9.1	0.062	1.6	5.75	SST	CG	N
0.843	21.41	10703	1.75	44.5	.735	18.7	5.9	1.0	1.2	30	6.8	30	.39	10.0	0.054	1.4	6.25	SPR	C	Z
0.843	21.41	S-824	1.75	44.5	.683	17.3	14	2.5	.95	24	14	61	.80	20.3	0.080	2.0	10.0	SST	CG	N
0.843	21.41	B12-37	2.00	50.8	.661	16.8	39	6.8	.75	19	29	130	.82	20.8	0.091	2.3	8.00	SPR	C	N
0.843	21.41	12613	2.00	50.8	.643	16.3	58	10	.92	23	54	239	.90	22.9	0.100	2.5	8.00	MW	C	N
0.843	21.41	S-82	2.00	50.8	.603	15.3	110	19	.53	13	58	257	1.11	28.2	0.120	3.0	8.25	SST	C	N
0.843	21.41	JJ-54	2.00	50.8	.503	12.8	499	87	.29	7.4	145	643	1.53	38.9	0.170	4.3	9.00	SST	CG	N
0.843	21.41	MM-55	2.03	51.6	.603	15.3	93	16	.62	16	58	257	1.14	29.0	0.120	3.0	9.50	SST	CG	N
0.843	21.41	S-66	2.06	52.4	.603	15.3	112	20	.52	13	58	257	.99	25.1	0.120	3.0	8.25	SST	CG	N
0.843	21.41	11949	2.09	53.2	.517	13.1	409	72	.31	8.0	128	571	1.47	37.3	0.163	4.1	9.00	SST	CG	N
0.843	21.41	10239	2.19	55.6	.661	16.8	66	12	.44	11	29	130	.50	12.7	0.091	2.3	5.50	SPR	CG	Z
0.843	21.41	S-3258	2.25	57.2	.703	17.9	11	1.9	1.2	30	13	58	.56	14.2	0.070	1.8	8.00	SST	CG	N
0.843	21.41	11781	2.28	57.9	.525	13.3	364	64	.33	8.4	120	532	1.43	36.3	0.159	4.0	9.00	SST	CG	N
0.843	21.41	3501	2.44	61.9	.699	17.8	12	2.1	1.7	44	21	92	.72	18.3	0.072	1.8	9.00	MW	C	Z
0.843	21.41	11185	2.47	62.7	.633	16.1	62	11	.71	18	44	197	.95	24.0	0.105	2.7	9.00	HD	CG	Z
0.843	21.41	2842	2.50	63.5	.709	18.0	7.1	1.2	1.8	45	13	56	.72	18.3	0.067	1.7	10.8	HD	CG	Z
0.843	21.41	B10-9	2.50	63.5	.697	17.7	12	2.2	1.3	33	16	70	.68	17.2	0.073	1.9	9.25	SPR	CG	BO
0.843	21.41	3266	2.75	69.9	.633	16.1	51	9.0	.87	22	44	197	1.10	28.0	0.105	2.7	10.5	SPR	CG	Z
0.843	21.41	11902	2.81	71.4	.579	14.7	110	19	.73	19	81	361	1.72	43.6	0.132	3.4	13.0	SPR	CG	N
0.843	21.41	S-201	3.00	76.2	.717	18.2	5.2	.91	2.0	50	10	45	.69	17.6	0.063	1.6	10.0	SST	C	N
0.843	21.41	3388	3.00	76.2	.673	17.1	16	2.7	1.6	40	25	110	1.11	28.1	0.085	2.2	13.0	SPR	CG	Z
0.843	21.41	B17-191	3.00	76.2	.589	15.0	72	13	.94	24	68	303	1.84	46.8	0.127	3.2	14.5	SST	CG	N
0.843	21.41	12246	3.25	82.6	.731	18.6	3.9	.68	2.0	50	7.6	34	.53	13.5	0.056	1.4	9.50	SPR	CG	Z
0.843	21.41	1567	3.25	82.6	.699	17.8	9.4	1.6	1.6	41	15	68	.86	21.9	0.072	1.8	11.0	SPR	C	Z
0.843	21.41	S-1631	3.28	83.3	.649	16.5	26	4.5	1.3	32	33	145	1.21	30.8	0.097	2.5	12.5	SST	CG	N
0.843	21.41	11350	3.50	88.9	.709	18.0	5.5	.96	2.2	56	12	54	.80	20.4	0.067	1.7	12.0	SST	CG	N
0.843	21.41	12511	3.67	93.3	.727	18.5	4.1	.71	2.9	73	12	52	.60	15.1	0.058	1.5	10.3	MW	CG	T1
0.843	21.41	S-1136	3.75	95.3	.659	16.7	14	2.5	2.0	50	28	124	1.56	39.7	0.092	2.3	17.0	SST	CG	N
0.843	21.41	12101	4.56	115.9	.737	18.7	.85	.15	3.1	80	2.7	12	1.43	36.3	0.053	1.3	26.0	SST	C	N
0.843	21.41	10979	4.66	118.3	.593	15.1	49	8.5	1.5	37	71	317	2.69	68.3	0.125	3.2	21.5	HD	CG	Z
0.843	21.41	10541	4.69	119.0	.583	14.8	58	10	1.3	34	78	345	2.80	71.0	0.130	3.3	21.5	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.843	21.41	2752	4.88	123.8	.683	17.3	4.7	.82	2.5	62	12	51	2.42	61.5	0.080	2.0	30.3	HD	CG	Z
0.843	21.41	11967	4.91	124.6	.663	16.8	9.2	1.6	2.6	65	24	105	2.34	59.4	0.090	2.3	26.0	SPR	CG	Z
0.843	21.41	3131	5.13	130.2	.627	15.9	27	4.8	1.8	45	48	214	2.16	54.9	0.108	2.7	20.0	SPR	CG	Z
0.843	21.41	S-3212	7.13	181.0	.701	17.8	3.2	.56	4.3	108	14	61	1.70	43.3	0.071	1.8	24.0	SST	CG	N
0.843	21.41	3405	11.0	279.4	.679	17.2	4.1	.72	5.5	138	22	99	3.12	79.1	0.082	2.1	38.0	SPR	CG	Z
0.850	21.59	72136	.75	19.1	.750	19.1	13	2.3	.58	15	7.5	33	.17	4.3	0.050	1.3	3.38	MW	CG	N
0.850	21.59	72136S	.75	19.1	.750	19.1	11	1.9	.46	12	5.1	23	.17	4.3	0.050	1.3	3.38	SST	CG	N
0.850	21.59	72146	.75	19.1	.740	18.8	18	3.2	.55	14	9.9	44	.19	4.9	0.055	1.4	3.50	MW	CG	N
0.850	21.59	72146S	.75	19.1	.740	18.8	15	2.7	.44	11	6.7	30	.19	4.9	0.055	1.4	3.50	SST	CG	N
0.850	21.59	72162	.75	19.1	.716	18.2	34	6.0	.50	13	17	76	.25	6.4	0.067	1.7	3.75	MW	CG	N
0.850	21.59	72162S	.75	19.1	.716	18.2	29	5.1	.42	11	12	54	.25	6.4	0.067	1.7	3.75	SST	CG	N
0.850	21.59	72172	.75	19.1	.714	18.1	36	6.3	.50	13	18	79	.26	6.5	0.068	1.7	3.75	MW	CG	N
0.850	21.59	72172S	.75	19.1	.714	18.1	31	5.3	.41	11	13	56	.26	6.5	0.068	1.7	3.75	SST	CG	N
0.850	21.59	72210	.75	19.1	.690	17.5	67	12	.43	11	29	128	.31	7.9	0.080	2.0	3.88	MW	CG	N
0.850	21.59	72210S	.75	19.1	.690	17.5	57	9.9	.34	8.6	19	86	.31	7.9	0.080	2.0	3.88	SST	CG	N
0.850	21.59	72233	.75	19.1	.688	17.5	68	12	.43	11	29	128	.32	8.2	0.081	2.1	4.00	MW	CG	N
0.850	21.59	72233S	.75	19.1	.688	17.5	58	10	.35	8.8	20	89	.32	8.2	0.081	2.1	4.00	SST	CG	N
0.850	21.59	72246	.75	19.1	.680	17.3	84	15	.41	10	34	153	.34	8.6	0.085	2.2	4.00	MW	CG	N
0.850	21.59	72246S	.75	19.1	.680	17.3	71	12	.32	8.2	23	103	.34	8.6	0.085	2.2	4.00	SST	CG	N
0.850	21.59	72137	.88	22.4	.750	19.1	11	1.9	.69	17	7.5	33	.18	4.6	0.050	1.3	3.63	MW	CG	N
0.850	21.59	72137S	.88	22.4	.750	19.1	9.2	1.6	.55	14	5.1	23	.18	4.6	0.050	1.3	3.63	SST	CG	N
0.850	21.59	72147	.88	22.4	.740	18.8	15	2.6	.66	17	9.9	44	.21	5.2	0.055	1.4	3.75	MW	CG	N
0.850	21.59	72147S	.88	22.4	.740	18.8	13	2.2	.52	13	6.7	30	.21	5.2	0.055	1.4	3.75	SST	CG	N
0.850	21.59	72163	.88	22.4	.716	18.2	28	5.0	.60	15	17	76	.28	7.0	0.067	1.7	4.13	MW	CG	N
0.850	21.59	72163S	.88	22.4	.716	18.2	24	4.2	.50	13	12	54	.28	7.0	0.067	1.7	4.13	SST	CG	N
0.850	21.59	72173	.88	22.4	.714	18.1	30	5.2	.60	15	18	79	.28	7.1	0.068	1.7	4.13	MW	CG	N
0.850	21.59	72173S	.88	22.4	.714	18.1	25	4.4	.50	13	13	56	.28	7.1	0.068	1.7	4.13	SST	CG	N
0.850	21.59	72186	.88	22.4	.706	17.9	41	7.1	.52	13	21	94	.29	7.3	0.072	1.8	4.00	MW	CG	N
0.850	21.59	72186S	.88	22.4	.706	17.9	35	6.0	.41	10	14	63	.29	7.3	0.072	1.8	4.00	SST	CG	N
0.850	21.59	72195	.88	22.4	.702	17.8	40	7.0	.57	14	23	101	.31	8.0	0.074	1.9	4.25	MW	CG	N
0.850	21.59	72195S	.88	22.4	.702	17.8	34	6.0	.45	11	15	68	.31	8.0	0.074	1.9	4.25	SST	CG	N
0.850	21.59	72212	.88	22.4	.690	17.5	55	9.6	.52	13	29	128	.35	8.9	0.080	2.0	4.38	MW	CG	N
0.850	21.59	72212S	.88	22.4	.690	17.5	47	8.2	.41	10	19	86	.35	8.9	0.080	2.0	4.38	SST	CG	N
0.850	21.59	72234	.88	22.4	.688	17.5	57	9.9	.53	13	30	132	.35	9.0	0.081	2.1	4.38	MW	CG	N
0.850	21.59	72234S	.88	22.4	.688	17.5	48	8.4	.42	11	20	89	.35	9.0	0.081	2.1	4.38	SST	CG	N
0.850	21.59	72247	.88	22.4	.680	17.3	67	12	.50	13	33	148	.38	9.7	0.085	2.2	4.50	MW	CG	N
0.850	21.59	72247S	.88	22.4	.680	17.3	57	10	.41	10	23	103	.38	9.7	0.085	2.2	4.50	SST	CG	N
0.850	21.59	72262	.88	22.4	.668	17.0	90	16	.45	11	40	180	.41	10.4	0.091	2.3	4.50	MW	CG	N
0.850	21.59	72262S	.88	22.4	.668	17.0	76	13	.35	8.9	27	119	.41	10.4	0.091	2.3	4.50	SST	CG	N
0.850	21.59	72276	.88	22.4	.666	16.9	90	16	.45	12	41	182	.43	10.8	0.092	2.3	4.63	MW	CG	N
0.850	21.59	72276S	.88	22.4	.666	16.9	77	13	.36	9.2	28	123	.43	10.8	0.092	2.3	4.63	SST	CG	N
0.850	21.59	72138	1.00	25.4	.750	19.1	9.4	1.6	.80	20	7.5	33	.19	4.9	0.050	1.3	3.88	MW	CG	N
0.850	21.59	72138S	1.00	25.4	.750	19.1	8.0	1.4	.64	16	5.1	23	.19	4.9	0.050	1.3	3.88	SST	CG	N
0.850	21.59	72148	1.00	25.4	.740	18.8	13	2.3	.77	19	9.9	44	.22	5.6	0.055	1.4	4.00	MW	CG	N
0.850	21.59	72148S	1.00	25.4	.740	18.8	11	1.9	.61	15	6.7	30	.22	5.6	0.055	1.4	4.00	SST	CG	N
0.850	21.59	72164	1.00	25.4	.716	18.2	24	4.3	.70	18	17	76	.30	7.7	0.067	1.7	4.50	MW	CG	N
0.850	21.59	72164S	1.00	25.4	.716	18.2	21	3.6	.58	15	12	54	.30	7.7	0.067	1.7	4.50	SST	CG	N
0.850	21.59	72174	1.00	25.4	.714	18.1	26	4.5	.69	18	18	79	.31	7.8	0.068	1.7	4.50	MW	CG	N
0.850	21.59	72174S	1.00	25.4	.714	18.1	22	3.8	.58	15	13	56	.31	7.8	0.068	1.7	4.50	SST	CG	N
0.850	21.59	72187	1.00	25.4	.706	17.9	35	6.1	.60	15	21	94	.32	8.0	0.072	1.8	4.38	MW	CG	N
0.850	21.59	72187S	1.00	25.4	.706	17.9	30	5.2	.48	12	14	63	.32	8.0	0.072	1.8	4.38	SST	CG	N
0.850	21.59	72196	1.00	25.4	.702	17.8	34	6.0	.65	16	22	99	.35	8.9	0.074	1.9	4.75	MW	CG	N
0.850	21.59	72196S	1.00	25.4	.702	17.8	29	5.1	.53	13	15	68	.35	8.9	0.074	1.9	4.75	SST	CG	N
0.850	21.59	72214	1.00	25.4	.690	17.5	47	8.2	.62	16	29	128	.38	9.7	0.080	2.0	4.75	MW	CG	N
0.850	21.59	72214S	1.00	25.4	.690	17.5	40	7.0	.49	12	19	86	.38	9.7	0.080	2.0	4.75	SST	CG	N
0.850	21.59	72235	1.00	25.4	.688	17.5	48	8.4	.61	15	29	129	.39	10.0	0.081	2.1	4.88	MW	CG	N
0.850	21.59	72235S	1.00	25.4	.688	17.5	41	7.1	.49	12	20	89	.39	10.0	0.081	2.1	4.88	SST	CG	N
0.850	21.59	72248	1.00	25.4	.680	17.3	59	10	.58	15	34	153	.41	10.5	0.085	2.2	4.88	MW	CG	N
0.850	21.59	72248S	1.00	25.4	.680	17.3	50	8.8	.46	12	23	103	.41	10.5	0.085	2.2	4.88	SST	CG	N
0.850	21.59	72264	1.00	25.4	.668	17.0	76	13	.53	14	40	180	.46	11.6	0.091	2.3	5.00	MW	CG	N
0.850	21.59	72264S	1.00	25.4	.668	17.0	65	11	.41	11	27	119	.46	11.6	0.091	2.3	5.00	SST	CG	N
0.850	21.59	72277	1.00	25.4	.666	16.9	77	13	.53	13	41	181	.47	12.0	0.092	2.3	5.13	MW	CG	N
0.850	21.59	72277S	1.00	25.4	.666	16.9	65	11	.42	11	28	123	.47	12.0	0.092	2.3	5.13	SST	CG	N
0.850	21.59	72287	1.00	25.4	.654	16.6	100	18	.50	13	50	222	.50	12.8	0.098	2.5	5.13	MW	CG	N
0.850	21.59	72287S	1.00	25.4	.654	16.6	85	15	.39	9.9	33	148	.50	12.8	0.098	2.5	5.13	SST	CG	N
0.850	21.59	72297	1.00	25.4	.650	16.5	125	22	.43	11	53	237	.48	12.1	0.100	2.5	4.75	MW	CG	N
0.850	21.59	72297S	1.00	25.4	.650	16.5	106	19	.33	8.5	35	157	.48	12.1	0.100	2.5	4.75	SST	CG	N
0.850	21.59	72308	1.00	25.4	.640	16.3	135	24	.46	12	62	274	.54	13.7	0.105	2.7	5.13	MW	CG	N
0.850	21.59	72308S	1.00	25.4	.640	16.3	115	20	.36	9.0	41	181	.54	13.7	0.105	2.7	5.13	SST	CG	N
0.850	21.59	72139	1.25	31.8	.750	19.1	7.3	1.3	1.0	26	7.5	33	.22	5.6	0.050	1.3	4.38	MW	CG	N
0.850	21.59	72139S	1.25	31.8	.750	19.1	6.2	1.1	.81	21	5.1	23	.22	5.6	0.050	1.3	4.38	SST	CG	N
0.850	21.59	72149	1.25	31.8	.740	18.8	10	1.8	.98	25	9.9	44	.25	6.5	0.055	1.4	4.63	MW	CG	N
0.850	21.59	72149S	1.25	31.8	.740	18.8	8.6	1.5	.78	20	6.7	30	.25	6.5	0.055	1.4	4.63	SST	CG	N
0.850	21.59	72165	1.25	31.8	.716	18.2	19	3.3	.90	23	17	75	.35	8.9	0.067	1.7	5.25	MW	CG	N
0.850	21.59	72165S	1.25	31.8	.716	18.2	16	2.8	.75	19	12	54	.35	8.9	0.067	1.7	5.25	SST	CG	N
0.850	21.59	72175	1.25	31.8	.714	18.1	20	3.5	.89	23	18	79	.36	9.1	0.068	1.7	5.25	MW	CG	N
0.850	21.59	72175S	1.25	31.8	.714	18.1	17	2.9	.75	19	13	56	.36	9.1	0.068	1.7	5.25	SST	CG	N
0.850	21.59	72188	1.25	31.8	.706	17.9	27	4.7	.79	20	21	94	.36	9.1	0.072	1.8	5.00	MW	CG	N
0.850	21.59	72188S	1.25	31.8	.706	17.9	23	4.0	.62	16	14	63	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.850	21.59	72197	1.25	31.8	.702	17.8	27	4.6	.84	21	22	99	.41	10.3	0.074	1.9	5.50	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None





COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.850	21.59	72197S	1.25	31.8	.702	17.8	23	3.9	.68	17	15	68	.41	10.3	0.074	1.9	5.50	SST	CG	N
0.850	21.59	72216	1.25	31.8	.690	17.5	36	6.3	.80	20	29	128	.45	11.4	0.080	2.0	5.63	MW	CG	N
0.850	21.59	72216S	1.25	31.8	.690	17.5	31	5.4	.63	16	19	86	.45	11.4	0.080	2.0	5.63	SST	CG	N
0.850	21.59	72236	1.25	31.8	.688	17.5	37	6.5	.79	20	30	132	.46	11.6	0.081	2.1	5.63	MW	CG	N
0.850	21.59	72236S	1.25	31.8	.688	17.5	32	5.6	.63	16	20	89	.46	11.6	0.081	2.1	5.63	SST	CG	N
0.850	21.59	72249	1.25	31.8	.680	17.3	45	7.8	.76	19	34	152	.49	12.4	0.085	2.2	5.75	MW	CG	N
0.850	21.59	72249S	1.25	31.8	.680	17.3	38	6.7	.61	15	23	103	.49	12.4	0.085	2.2	5.75	SST	CG	N
0.850	21.59	72266	1.25	31.8	.668	17.0	58	10	.69	18	40	180	.53	13.6	0.091	2.3	5.88	MW	CG	N
0.850	21.59	72266S	1.25	31.8	.668	17.0	49	8.7	.54	14	27	119	.53	13.6	0.091	2.3	5.88	SST	CG	N
0.850	21.59	72278	1.25	31.8	.666	16.9	59	10	.70	18	41	183	.55	14.0	0.092	2.3	6.00	MW	CG	N
0.850	21.59	72278S	1.25	31.8	.666	16.9	50	8.8	.55	14	28	123	.55	14.0	0.092	2.3	6.00	SST	CG	N
0.850	21.59	72288	1.25	31.8	.654	16.6	77	13	.65	17	50	222	.60	15.2	0.098	2.5	6.13	MW	CG	N
0.850	21.59	72288S	1.25	31.8	.654	16.6	65	11	.51	13	33	148	.60	15.2	0.098	2.5	6.13	SST	CG	N
0.850	21.59	72298	1.25	31.8	.650	16.5	95	17	.56	14	53	237	.56	14.3	0.100	2.5	5.63	MW	CG	N
0.850	21.59	72298S	1.25	31.8	.650	16.5	81	14	.44	11	35	157	.56	14.3	0.100	2.5	5.63	SST	CG	N
0.850	21.59	72310	1.25	31.8	.640	16.3	103	18	.60	15	62	274	.64	16.3	0.105	2.7	6.13	MW	CG	N
0.850	21.59	72310S	1.25	31.8	.640	16.3	87	15	.47	12	41	181	.64	16.3	0.105	2.7	6.13	SST	CG	N
0.850	21.59	72237	1.38	35.1	.688	17.5	34	6.0	.88	22	30	133	.49	12.3	0.081	2.1	6.00	MW	CG	N
0.850	21.59	72237S	1.38	35.1	.688	17.5	29	5.1	.69	18	20	89	.49	12.3	0.081	2.1	6.00	SST	CG	N
0.850	21.59	72250	1.38	35.1	.680	17.3	42	7.4	.82	21	34	153	.51	13.0	0.085	2.2	6.00	MW	CG	N
0.850	21.59	72250S	1.38	35.1	.680	17.3	36	6.3	.65	16	23	103	.51	13.0	0.085	2.2	6.00	SST	CG	N
0.850	21.59	72140	1.50	38.1	.750	19.1	6.0	1.1	1.2	32	7.5	33	.24	6.2	0.050	1.3	4.88	MW	CG	N
0.850	21.59	72140S	1.50	38.1	.750	19.1	5.1	.90	.99	25	5.1	23	.24	6.2	0.050	1.3	4.88	SST	CG	N
0.850	21.59	72150	1.50	38.1	.740	18.8	8.3	1.5	1.2	30	9.9	44	.28	7.2	0.055	1.4	5.13	MW	CG	N
0.850	21.59	72150S	1.50	38.1	.740	18.8	7.1	1.2	.95	24	6.7	30	.28	7.2	0.055	1.4	5.13	SST	CG	N
0.850	21.59	72166	1.50	38.1	.716	18.2	15	2.7	1.1	28	17	76	.39	10.0	0.067	1.7	5.88	MW	CG	N
0.850	21.59	72166S	1.50	38.1	.716	18.2	13	2.3	.92	23	12	54	.39	10.0	0.067	1.7	5.88	SST	CG	N
0.850	21.59	72176	1.50	38.1	.714	18.1	16	2.8	1.1	28	18	78	.41	10.4	0.068	1.7	6.00	MW	CG	N
0.850	21.59	72176S	1.50	38.1	.714	18.1	14	2.4	.92	23	13	56	.41	10.4	0.068	1.7	6.00	SST	CG	N
0.850	21.59	72189	1.50	38.1	.706	17.9	22	3.8	.97	25	21	94	.41	10.5	0.072	1.8	5.75	MW	CG	N
0.850	21.59	72189S	1.50	38.1	.706	17.9	19	3.2	.76	19	14	63	.41	10.5	0.072	1.8	5.75	SST	CG	N
0.850	21.59	72198	1.50	38.1	.702	17.8	22	3.8	1.0	26	22	100	.46	11.7	0.074	1.9	6.25	MW	CG	N
0.850	21.59	72198S	1.50	38.1	.702	17.8	18	3.2	.83	21	15	68	.46	11.7	0.074	1.9	6.25	SST	CG	N
0.850	21.59	72218	1.50	38.1	.690	17.5	29	5.1	.98	25	29	128	.51	13.0	0.080	2.0	6.38	MW	CG	N
0.850	21.59	72218S	1.50	38.1	.690	17.5	25	4.4	.77	20	19	86	.51	13.0	0.080	2.0	6.38	SST	CG	N
0.850	21.59	72238	1.50	38.1	.688	17.5	30	5.3	.97	25	30	131	.53	13.4	0.081	2.1	6.50	MW	CG	N
0.850	21.59	72238S	1.50	38.1	.688	17.5	26	4.5	.78	20	20	89	.53	13.4	0.081	2.1	6.50	SST	CG	N
0.850	21.59	72251	1.50	38.1	.680	17.3	37	6.4	.94	24	34	153	.56	14.3	0.085	2.2	6.63	MW	CG	N
0.850	21.59	72251S	1.50	38.1	.680	17.3	31	5.5	.74	19	23	103	.56	14.3	0.085	2.2	6.63	SST	CG	N
0.850	21.59	72267	1.50	38.1	.668	17.0	49	8.6	.83	21	40	180	.60	15.3	0.091	2.3	6.63	MW	CG	N
0.850	21.59	72267S	1.50	38.1	.668	17.0	42	7.3	.64	16	27	119	.60	15.3	0.091	2.3	6.63	SST	CG	N
0.850	21.59	72279	1.50	38.1	.666	16.9	48	8.4	.86	22	41	182	.64	16.4	0.092	2.3	7.00	MW	CG	N
0.850	21.59	72279S	1.50	38.1	.666	16.9	41	7.1	.68	17	28	123	.64	16.4	0.092	2.3	7.00	SST	CG	N
0.850	21.59	72289	1.50	38.1	.654	16.6	63	11	.80	20	50	224	.69	17.4	0.098	2.5	7.00	MW	CG	N
0.850	21.59	72289S	1.50	38.1	.654	16.6	53	9.4	.62	16	33	148	.69	17.4	0.098	2.5	7.00	SST	CG	N
0.850	21.59	72299	1.50	38.1	.650	16.5	77	13	.69	18	53	237	.65	16.5	0.100	2.5	6.50	MW	CG	N
0.850	21.59	72299S	1.50	38.1	.650	16.5	65	11	.54	14	35	157	.65	16.5	0.100	2.5	6.50	SST	CG	N
0.850	21.59	72312	1.50	38.1	.640	16.3	83	14	.74	19	62	274	.75	19.0	0.105	2.7	7.13	MW	CG	N
0.850	21.59	72312S	1.50	38.1	.640	16.3	70	12	.58	15	41	181	.75	19.0	0.105	2.7	7.13	SST	CG	N
0.850	21.59	72152	1.75	44.5	.740	18.8	7.1	1.2	1.4	36	9.9	44	.32	8.0	0.055	1.4	5.75	MW	CG	N
0.850	21.59	72152S	1.75	44.5	.740	18.8	6.0	1.1	1.1	28	6.7	30	.32	8.0	0.055	1.4	5.75	SST	CG	N
0.850	21.59	72177	1.75	44.5	.714	18.1	14	2.4	1.3	33	18	78	.46	11.7	0.068	1.7	6.75	MW	CG	N
0.850	21.59	72177S	1.75	44.5	.714	18.1	12	2.0	1.1	28	13	56	.46	11.7	0.068	1.7	6.75	SST	CG	N
0.850	21.59	72190	1.75	44.5	.706	17.9	18	3.2	1.1	29	21	94	.47	11.9	0.072	1.8	6.50	MW	CG	N
0.850	21.59	72190S	1.75	44.5	.706	17.9	16	2.7	.91	23	14	63	.47	11.9	0.072	1.8	6.50	SST	CG	N
0.850	21.59	72200	1.75	44.5	.702	17.8	19	3.3	1.2	31	23	102	.51	12.9	0.074	1.9	6.88	MW	CG	N
0.850	21.59	72200S	1.75	44.5	.702	17.8	16	2.8	.95	24	15	68	.51	12.9	0.074	1.9	6.88	SST	CG	N
0.850	21.59	72220	1.75	44.5	.690	17.5	25	4.3	1.2	30	29	128	.58	14.7	0.080	2.0	7.25	MW	CG	N
0.850	21.59	72220S	1.75	44.5	.690	17.5	21	3.7	.92	23	19	86	.58	14.7	0.080	2.0	7.25	SST	CG	N
0.850	21.59	72239	1.75	44.5	.688	17.5	26	4.5	1.2	29	29	131	.60	15.2	0.081	2.1	7.38	MW	CG	N
0.850	21.59	72239S	1.75	44.5	.688	17.5	22	3.8	.92	23	20	89	.60	15.2	0.081	2.1	7.38	SST	CG	N
0.850	21.59	72252	1.75	44.5	.680	17.3	31	5.4	1.1	28	34	153	.63	15.9	0.085	2.2	7.38	MW	CG	N
0.850	21.59	72252S	1.75	44.5	.680	17.3	26	4.6	.88	22	23	103	.63	15.9	0.085	2.2	7.38	SST	CG	N
0.850	21.59	72268	1.75	44.5	.668	17.0	41	7.2	.99	25	40	180	.68	17.3	0.091	2.3	7.50	MW	CG	N
0.850	21.59	72268S	1.75	44.5	.668	17.0	35	6.1	.77	20	27	119	.68	17.3	0.091	2.3	7.50	SST	CG	N
0.850	21.59	72280	1.75	44.5	.666	16.9	40	7.0	1.0	26	41	182	.72	18.4	0.092	2.3	7.88	MW	CG	N
0.850	21.59	72280S	1.75	44.5	.666	16.9	34	6.0	.81	21	28	123	.72	18.4	0.092	2.3	7.88	SST	CG	N
0.850	21.59	72290	1.75	44.5	.654	16.6	53	9.2	.96	24	50	224	.77	19.6	0.098	2.5	7.88	MW	CG	N
0.850	21.59	72290S	1.75	44.5	.654	16.6	45	7.8	.75	19	33	148	.77	19.6	0.098	2.5	7.88	SST	CG	N
0.850	21.59	72300	1.75	44.5	.650	16.5	64	11	.83	21	53	237	.73	18.4	0.100	2.5	7.25	MW	CG	N
0.850	21.59	72300S	1.75	44.5	.650	16.5	55	9.6	.65	16	35	157	.73	18.4	0.100	2.5	7.25	SST	CG	N
0.850	21.59	72314	1.75	44.5	.640	16.3	69	12	.89	23	62	274	.85	21.7	0.105	2.7	8.13	MW	CG	N
0.850	21.59	72314S	1.75	44.5	.640	16.3	59	10	.69	18	41	181	.85	21.7	0.105	2.7	8.13	SST	CG	N
0.850	21.59	72141	2.00	50.8	.750	19.1	4.4	.78	1.7	43	7.5	33	.30	7.6	0.050	1.3	6.00	MW	CG	N
0.850	21.59	72141S	2.00	50.8	.750	19.1	3.8	.66	1.3	34	5.1	23	.30	7.6	0.050	1.3	6.00	SST	CG	N
0.850	21.59	72153	2.00	50.8	.740	18.8	6.1	1.1	1.6	41	9.9	44	.34	8.7	0.055	1.4	6.25	MW	CG	N
0.850	21.59	72153S	2.00	50.8	.740	18.8	5.2	.91	1.3	33	6.7	30	.34	8.7	0.055	1.4	6.25	SST	CG	N
0.850	21.59	72167	2.00	50.8	.716	18.2	11	2.0	1.5	38	17	75	.49	12.6	0.067	1.7	7.38	MW	CG	N
0.850	21.59	72167S	2.00	50.8	.716	18.2	9.6	1.7	1.3	32	12	54	.49	12.6	0.067	1.7	7.38	SST	CG	N
0.850	21.59	72178	2.00	50.8	.714	18.1	12	2.1	1.5	38	18	78	.51	13.0	0.068	1.7	7.50	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.850	21.59	72178S	2.00	50.8	.714	18.1	10	1.8	1.3	32	13	56	.51	13.0	0.068	1.7	7.50	SST	CG	N
0.850	21.59	72191	2.00	50.8	.706	17.9	16	2.8	1.3	33	21	94	.51	13.0	0.072	1.8	7.13	MW	CG	N
0.850	21.59	72191S	2.00	50.8	.706	17.9	14	2.4	1.0	26	14	63	.51	13.0	0.072	1.8	7.13	SST	CG	N
0.850	21.59	72201	2.00	50.8	.702	17.8	16	2.8	1.4	36	22	100	.58	14.8	0.074	1.9	7.88	MW	CG	N
0.850	21.59	72201S	2.00	50.8	.702	17.8	13	2.4	1.1	29	15	68	.58	14.8	0.074	1.9	7.88	SST	CG	N
0.850	21.59	72222	2.00	50.8	.690	17.5	21	3.7	1.3	34	29	128	.64	16.3	0.080	2.0	8.00	MW	CG	N
0.850	21.59	72222S	2.00	50.8	.690	17.5	18	3.2	1.1	27	19	86	.64	16.3	0.080	2.0	8.00	SST	CG	N
0.850	21.59	72240	2.00	50.8	.688	17.5	22	3.8	1.3	34	29	129	.67	17.0	0.081	2.1	8.25	MW	CG	N
0.850	21.59	72240S	2.00	50.8	.688	17.5	19	3.2	1.1	27	20	89	.67	17.0	0.081	2.1	8.25	SST	CG	N
0.850	21.59	72253	2.00	50.8	.680	17.3	26	4.6	1.3	33	34	151	.71	18.1	0.085	2.2	8.38	MW	CG	N
0.850	21.59	72253S	2.00	50.8	.680	17.3	22	3.9	1.0	26	23	103	.71	18.1	0.085	2.2	8.38	SST	CG	N
0.850	21.59	72269	2.00	50.8	.668	17.0	35	6.1	1.2	29	40	180	.77	19.6	0.091	2.3	8.50	MW	CG	N
0.850	21.59	72269S	2.00	50.8	.668	17.0	30	5.2	.90	23	27	119	.77	19.6	0.091	2.3	8.50	SST	CG	N
0.850	21.59	72281	2.00	50.8	.666	16.9	35	6.0	1.2	30	41	182	.82	20.7	0.092	2.3	8.88	MW	CG	N
0.850	21.59	72281S	2.00	50.8	.666	16.9	29	5.1	.94	24	28	123	.82	20.7	0.092	2.3	8.88	SST	CG	N
0.850	21.59	72291	2.00	50.8	.654	16.6	45	7.9	1.1	28	50	224	.87	22.1	0.098	2.5	8.88	MW	CG	N
0.850	21.59	72291S	2.00	50.8	.654	16.6	38	6.7	.87	22	33	148	.87	22.1	0.098	2.5	8.88	SST	CG	N
0.850	21.59	72301	2.00	50.8	.650	16.5	55	9.7	.96	24	53	237	.81	20.6	0.100	2.5	8.13	MW	CG	N
0.850	21.59	72301S	2.00	50.8	.650	16.5	47	8.2	.75	19	35	157	.81	20.6	0.100	2.5	8.13	SST	CG	N
0.850	21.59	72316	2.00	50.8	.640	16.3	60	10	1.0	26	62	274	.96	24.3	0.105	2.7	9.13	MW	CG	N
0.850	21.59	72316S	2.00	50.8	.640	16.3	51	8.9	.80	20	41	181	.96	24.3	0.105	2.7	9.13	SST	CG	N
0.850	21.59	72155	2.25	57.2	.740	18.8	5.4	.95	1.8	47	9.9	44	.38	9.6	0.055	1.4	6.88	MW	CG	N
0.850	21.59	72155S	2.25	57.2	.740	18.8	4.6	.80	1.5	37	6.7	30	.38	9.6	0.055	1.4	6.88	SST	CG	N
0.850	21.59	72179	2.25	57.2	.714	18.1	10	1.8	1.7	43	18	79	.55	14.0	0.068	1.7	8.13	MW	CG	N
0.850	21.59	72179S	2.25	57.2	.714	18.1	8.8	1.5	1.4	36	13	56	.55	14.0	0.068	1.7	8.13	SST	CG	N
0.850	21.59	72203	2.25	57.2	.702	17.8	14	2.5	1.6	40	23	102	.62	15.7	0.074	1.9	8.38	MW	CG	N
0.850	21.59	72203S	2.25	57.2	.702	17.8	12	2.1	1.3	32	15	68	.62	15.7	0.074	1.9	8.38	SST	CG	N
0.850	21.59	72224	2.25	57.2	.690	17.5	19	3.3	1.5	39	29	128	.71	18.0	0.080	2.0	8.88	MW	CG	N
0.850	21.59	72224S	2.25	57.2	.690	17.5	16	2.8	1.2	31	19	86	.71	18.0	0.080	2.0	8.88	SST	CG	N
0.850	21.59	72241	2.25	57.2	.688	17.5	19	3.4	1.5	39	29	131	.73	18.5	0.081	2.1	9.00	MW	CG	N
0.850	21.59	72241S	2.25	57.2	.688	17.5	16	2.9	1.2	31	20	89	.73	18.5	0.081	2.1	9.00	SST	CG	N
0.850	21.59	72254	2.25	57.2	.680	17.3	23	4.1	1.5	37	34	153	.78	19.7	0.085	2.2	9.13	MW	CG	N
0.850	21.59	72254S	2.25	57.2	.680	17.3	20	3.5	1.2	30	23	103	.78	19.7	0.085	2.2	9.13	SST	CG	N
0.850	21.59	72270	2.25	57.2	.668	17.0	31	5.4	1.3	33	40	180	.84	21.4	0.091	2.3	9.25	MW	CG	N
0.850	21.59	72270S	2.25	57.2	.668	17.0	26	4.6	1.0	26	27	119	.84	21.4	0.091	2.3	9.25	SST	CG	N
0.850	21.59	72282	2.25	57.2	.666	16.9	30	5.3	1.4	34	41	183	.90	22.8	0.092	2.3	9.75	MW	CG	N
0.850	21.59	72282S	2.25	57.2	.666	16.9	26	4.5	1.1	27	28	123	.90	22.8	0.092	2.3	9.75	SST	CG	N
0.850	21.59	72292	2.25	57.2	.654	16.6	39	6.9	1.3	32	50	224	.97	24.6	0.098	2.5	9.88	MW	CG	N
0.850	21.59	72292S	2.25	57.2	.654	16.6	33	5.8	1.0	25	33	148	.97	24.6	0.098	2.5	9.88	SST	CG	N
0.850	21.59	72302	2.25	57.2	.650	16.5	49	8.5	1.1	28	53	237	.90	22.9	0.100	2.5	9.00	MW	CG	N
0.850	21.59	72302S	2.25	57.2	.650	16.5	41	7.2	.85	22	35	157	.90	22.9	0.100	2.5	9.00	SST	CG	N
0.850	21.59	72318	2.25	57.2	.640	16.3	52	9.2	1.2	30	62	274	1.06	27.0	0.105	2.7	10.1	MW	CG	N
0.850	21.59	72318S	2.25	57.2	.640	16.3	44	7.8	.92	23	41	181	1.06	27.0	0.105	2.7	10.1	SST	CG	N
0.850	21.59	72142	2.50	63.5	.750	19.1	3.5	.61	2.1	54	7.5	33	.35	8.9	0.050	1.3	7.00	MW	CG	N
0.850	21.59	72142S	2.50	63.5	.750	19.1	3.0	.52	1.7	43	5.1	23	.35	8.9	0.050	1.3	7.00	SST	CG	N
0.850	21.59	72156	2.50	63.5	.740	18.8	4.8	.85	2.1	52	9.9	44	.41	10.3	0.055	1.4	7.38	MW	CG	N
0.850	21.59	72156S	2.50	63.5	.740	18.8	4.1	.72	1.6	42	6.7	30	.41	10.3	0.055	1.4	7.38	SST	CG	N
0.850	21.59	72168	2.50	63.5	.716	18.2	8.9	1.6	1.9	49	17	76	.59	14.9	0.067	1.7	8.75	MW	CG	N
0.850	21.59	72168S	2.50	63.5	.716	18.2	7.6	1.3	1.6	41	12	54	.59	14.9	0.067	1.7	8.75	SST	CG	N
0.850	21.59	72180	2.50	63.5	.714	18.1	9.3	1.6	1.9	48	18	78	.60	15.3	0.068	1.7	8.88	MW	CG	N
0.850	21.59	72180S	2.50	63.5	.714	18.1	7.9	1.4	1.6	41	13	56	.60	15.3	0.068	1.7	8.88	SST	CG	N
0.850	21.59	72192	2.50	63.5	.706	17.9	12	2.2	1.7	43	21	94	.62	15.8	0.072	1.8	8.63	MW	CG	N
0.850	21.59	72192S	2.50	63.5	.706	17.9	11	1.9	1.3	34	14	63	.62	15.8	0.072	1.8	8.63	SST	CG	N
0.850	21.59	72204	2.50	63.5	.702	17.8	12	2.2	1.8	46	22	99	.70	17.9	0.074	1.9	9.50	MW	CG	N
0.850	21.59	72204S	2.50	63.5	.702	17.8	11	1.8	1.5	37	15	68	.70	17.9	0.074	1.9	9.50	SST	CG	N
0.850	21.59	72226	2.50	63.5	.690	17.5	17	2.9	1.7	44	29	128	.77	19.6	0.080	2.0	9.63	MW	CG	N
0.850	21.59	72226S	2.50	63.5	.690	17.5	14	2.5	1.4	34	19	86	.77	19.6	0.080	2.0	9.63	SST	CG	N
0.850	21.59	72242	2.50	63.5	.688	17.5	17	3.0	1.7	43	29	130	.80	20.3	0.081	2.1	9.88	MW	CG	N
0.850	21.59	72242S	2.50	63.5	.688	17.5	15	2.6	1.4	35	20	89	.80	20.3	0.081	2.1	9.88	SST	CG	N
0.850	21.59	72255	2.50	63.5	.680	17.3	21	3.7	1.7	42	34	153	.85	21.6	0.085	2.2	10.0	MW	CG	N
0.850	21.59	72255S	2.50	63.5	.680	17.3	18	3.1	1.3	33	23	103	.85	21.6	0.085	2.2	10.0	SST	CG	N
0.850	21.59	72271	2.50	63.5	.668	17.0	28	4.9	1.4	37	40	180	.91	23.1	0.091	2.3	10.0	MW	CG	N
0.850	21.59	72271S	2.50	63.5	.668	17.0	24	4.2	1.1	29	27	119	.91	23.1	0.091	2.3	10.0	SST	CG	N
0.850	21.59	72283	2.50	63.5	.666	16.9	27	4.7	1.5	38	41	182	.99	25.1	0.092	2.3	10.8	MW	CG	N
0.850	21.59	72283S	2.50	63.5	.666	16.9	23	4.0	1.2	31	28	123	.99	25.1	0.092	2.3	10.8	SST	CG	N
0.850	21.59	72293	2.50	63.5	.654	16.6	35	6.2	1.4	36	50	224	1.07	27.1	0.098	2.5	10.9	MW	CG	N
0.850	21.59	72293S	2.50	63.5	.654	16.6	30	5.2	1.1	28	33	148	1.07	27.1	0.098	2.5	10.9	SST	CG	N
0.850	21.59	72303	2.50	63.5	.650	16.5	43	7.6	1.2	31	53	237	.99	25.1	0.100	2.5	9.88	MW	CG	N
0.850	21.59	72303S	2.50	63.5	.650	16.5	37	6.5	.96	24	35	157	.99	25.1	0.100	2.5	9.88	SST	CG	N
0.850	21.59	72320	2.50	63.5	.640	16.3	47	8.2	1.3	34	62	274	1.17	29.7	0.105	2.7	11.1	MW	CG	N
0.850	21.59	72320S	2.50	63.5	.640	16.3	40	6.9	1.0	26	41	181	1.17	29.7	0.105	2.7	11.1	SST	CG	N
0.850	21.59	72158	2.75	69.9	.740	18.8	4.4	.77	2.3	57	9.9	44	.44	11.2	0.055	1.4	8.00	MW	CG	N
0.850	21.59	72158S	2.75	69.9	.740	18.8	3.7	.65	1.8	46	6.7	30	.44	11.2	0.055	1.4	8.00	SST	CG	N
0.850	21.59	72182	2.75	69.9	.714	18.1	8.7	1.5	2.1	54	18	82	.64	16.2	0.068	1.7	9.38	MW	CG	N
0.850	21.59	72182S	2.75	69.9	.714	18.1	7.4	1.3	1.7	43	13	56	.64	16.2	0.068	1.7	9.38	SST	CG	N
0.850	21.59	72206	2.75	69.9	.702	17.8	12	2.0	2.0	50	23	102	.74	18.8	0.074	1.9	10.0	MW	CG	N
0.850	21.59	72206S	2.75	69.9	.702	17.8	9.9	1.7	1.6	39	15	68	.74	18.8	0.074	1.9	10.0	SST	CG	N
0.850	21.59	72228	2.75	69.9	.690	17.5	15	2.7	1.9	48	29	128	.84	21.3	0.080	2.0	10.5	MW	CG	N
0.850	21.59	72228S	2.75	69.9	.690	17.5	13	2.3	1.5	38	19	86	.84	21.3	0.080	2.0	10.5	SST	CG	N
0.850	21.59	72243	2.75	69.9	.688	17.5	15	2.7	1.9	48	29	129	.87	22.1	0.081	2.1	10.8	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; **HD** - Hard Drawn; **OT** - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.850	21.59	72243S	2.75	69.9	.688	17.5	13	2.3	1.5	39	20	89	.87	22.1	0.081	2.1	10.8	SST	CG	N
0.850	21.59	72256	2.75	69.9	.680	17.3	19	3.3	1.8	46	34	153	.92	23.5	0.085	2.2	10.9	MW	CG	N
0.850	21.59	72256S	2.75	69.9	.680	17.3	16	2.8	1.4	36	23	103	.92	23.5	0.085	2.2	10.9	SST	CG	N
0.850	21.59	72272	2.75	69.9	.668	17.0	25	4.4	1.6	41	40	180	1.00	25.4	0.091	2.3	11.0	MW	CG	N
0.850	21.59	72272S	2.75	69.9	.668	17.0	21	3.7	1.3	32	27	119	1.00	25.4	0.091	2.3	11.0	SST	CG	N
0.850	21.59	72284	2.75	69.9	.666	16.9	24	4.3	1.7	42	41	181	1.08	27.5	0.092	2.3	11.8	MW	CG	N
0.850	21.59	72284S	2.75	69.9	.666	16.9	21	3.6	1.3	34	28	123	1.08	27.5	0.092	2.3	11.8	SST	CG	N
0.850	21.59	72294	2.75	69.9	.654	16.6	32	5.6	1.6	40	50	224	1.15	29.2	0.098	2.5	11.8	MW	CG	N
0.850	21.59	72294S	2.75	69.9	.654	16.6	27	4.7	1.2	31	33	148	1.15	29.2	0.098	2.5	11.8	SST	CG	N
0.850	21.59	72304	2.75	69.9	.650	16.5	39	6.9	1.4	35	53	237	1.08	27.3	0.100	2.5	10.8	MW	CG	N
0.850	21.59	72304S	2.75	69.9	.650	16.5	33	5.8	1.1	27	35	157	1.08	27.3	0.100	2.5	10.8	SST	CG	N
0.850	21.59	72322	2.75	69.9	.640	16.3	42	7.4	1.5	37	62	274	1.26	32.0	0.105	2.7	12.0	MW	CG	N
0.850	21.59	72322S	2.75	69.9	.640	16.3	36	6.3	1.1	29	41	181	1.26	32.0	0.105	2.7	12.0	SST	CG	N
0.850	21.59	72143	3.00	76.2	.750	19.1	2.9	.51	2.6	65	7.5	33	.40	10.2	0.050	1.3	8.00	MW	CG	N
0.850	21.59	72143S	3.00	76.2	.750	19.1	2.5	.43	2.0	52	5.1	23	.40	10.2	0.050	1.3	8.00	SST	CG	N
0.850	21.59	72159	3.00	76.2	.740	18.8	4.0	.70	2.5	63	9.9	44	.47	11.9	0.055	1.4	8.50	MW	CG	N
0.850	21.59	72159S	3.00	76.2	.740	18.8	3.4	.60	2.0	50	6.7	30	.47	11.9	0.055	1.4	8.50	SST	CG	N
0.850	21.59	72169	3.00	76.2	.716	18.2	7.3	1.3	2.3	59	17	76	.69	17.4	0.067	1.7	10.3	MW	CG	N
0.850	21.59	72169S	3.00	76.2	.716	18.2	6.2	1.1	1.9	49	12	54	.69	17.4	0.067	1.7	10.3	SST	CG	N
0.850	21.59	72183	3.00	76.2	.714	18.1	7.7	1.3	2.3	58	18	79	.71	17.9	0.068	1.7	10.4	MW	CG	N
0.850	21.59	72183S	3.00	76.2	.714	18.1	6.5	1.1	1.9	49	13	56	.71	17.9	0.068	1.7	10.4	SST	CG	N
0.850	21.59	72193	3.00	76.2	.706	17.9	10	1.8	2.0	52	21	94	.71	18.1	0.072	1.8	9.88	MW	CG	N
0.850	21.59	72193S	3.00	76.2	.706	17.9	8.8	1.5	1.6	41	14	63	.71	18.1	0.072	1.8	9.88	SST	CG	N
0.850	21.59	72207	3.00	76.2	.702	17.8	10	1.8	2.2	56	22	99	.81	20.7	0.074	1.9	11.0	MW	CG	N
0.850	21.59	72207S	3.00	76.2	.702	17.8	8.7	1.5	1.8	45	15	68	.81	20.7	0.074	1.9	11.0	SST	CG	N
0.850	21.59	72230	3.00	76.2	.690	17.5	14	2.4	2.1	53	29	128	.90	22.9	0.080	2.0	11.3	MW	CG	N
0.850	21.59	72230S	3.00	76.2	.690	17.5	12	2.1	1.6	41	19	86	.90	22.9	0.080	2.0	11.3	SST	CG	N
0.850	21.59	72244	3.00	76.2	.688	17.5	14	2.5	2.1	53	29	131	.93	23.7	0.081	2.1	11.5	MW	CG	N
0.850	21.59	72244S	3.00	76.2	.688	17.5	12	2.1	1.7	42	20	89	.93	23.7	0.081	2.1	11.5	SST	CG	N
0.850	21.59	72257	3.00	76.2	.680	17.3	17	3.0	2.0	50	34	153	.99	25.1	0.085	2.2	11.6	MW	CG	N
0.850	21.59	72257S	3.00	76.2	.680	17.3	15	2.6	1.6	40	23	103	.99	25.1	0.085	2.2	11.6	SST	CG	N
0.850	21.59	72273	3.00	76.2	.668	17.0	23	4.0	1.8	45	40	180	1.07	27.2	0.091	2.3	11.8	MW	CG	N
0.850	21.59	72273S	3.00	76.2	.668	17.0	20	3.4	1.4	35	27	119	1.07	27.2	0.091	2.3	11.8	SST	CG	N
0.850	21.59	72285	3.00	76.2	.666	16.9	22	3.9	1.8	47	41	182	1.16	29.5	0.092	2.3	12.6	MW	CG	N
0.850	21.59	72285S	3.00	76.2	.666	16.9	19	3.3	1.5	37	28	123	1.16	29.5	0.092	2.3	12.6	SST	CG	N
0.850	21.59	72295	3.00	76.2	.654	16.6	29	5.1	1.7	44	50	224	1.25	31.7	0.098	2.5	12.8	MW	CG	N
0.850	21.59	72295S	3.00	76.2	.654	16.6	25	4.3	1.4	34	33	148	1.25	31.7	0.098	2.5	12.8	SST	CG	N
0.850	21.59	72305	3.00	76.2	.650	16.5	36	6.2	1.5	38	53	237	1.16	29.5	0.100	2.5	11.6	MW	CG	N
0.850	21.59	72305S	3.00	76.2	.650	16.5	30	5.3	1.2	30	35	157	1.16	29.5	0.100	2.5	11.6	SST	CG	N
0.850	21.59	72324	3.00	76.2	.640	16.3	38	6.7	1.6	41	62	274	1.38	35.0	0.105	2.7	13.1	MW	CG	N
0.850	21.59	72324S	3.00	76.2	.640	16.3	32	5.7	1.3	32	41	181	1.38	35.0	0.105	2.7	13.1	SST	CG	N
0.850	21.59	72258	3.25	82.6	.680	17.3	15	2.7	2.1	54	33	146	1.11	28.1	0.085	2.2	13.0	MW	CG	N
0.850	21.59	72258S	3.25	82.6	.680	17.3	13	2.3	1.8	45	23	103	1.11	28.1	0.085	2.2	13.0	SST	CG	N
0.850	21.59	72144	3.50	88.9	.750	19.1	2.5	.43	3.0	77	7.5	33	.46	11.6	0.050	1.3	9.13	MW	CG	N
0.850	21.59	72144S	3.50	88.9	.750	19.1	2.1	.37	2.4	61	5.1	23	.46	11.6	0.050	1.3	9.13	SST	CG	N
0.850	21.59	72160	3.50	88.9	.740	18.8	3.4	.60	2.9	74	9.9	44	.53	13.4	0.055	1.4	9.63	MW	CG	N
0.850	21.59	72160S	3.50	88.9	.740	18.8	2.9	.51	2.3	59	6.7	30	.53	13.4	0.055	1.4	9.63	SST	CG	N
0.850	21.59	72170	3.50	88.9	.716	18.2	6.3	1.1	2.7	69	17	76	.78	19.8	0.067	1.7	11.6	MW	CG	N
0.850	21.59	72170S	3.50	88.9	.716	18.2	5.3	.93	2.3	58	12	54	.78	19.8	0.067	1.7	11.6	SST	CG	N
0.850	21.59	72184	3.50	88.9	.714	18.1	6.5	1.1	2.7	68	18	78	.81	20.5	0.068	1.7	11.9	MW	CG	N
0.850	21.59	72184S	3.50	88.9	.714	18.1	5.5	.97	2.3	58	13	56	.81	20.5	0.068	1.7	11.9	SST	CG	N
0.850	21.59	72194	3.50	88.9	.706	17.9	8.8	1.5	2.4	61	21	94	.81	20.6	0.072	1.8	11.3	MW	CG	N
0.850	21.59	72194S	3.50	88.9	.706	17.9	7.5	1.3	1.9	48	14	63	.81	20.6	0.072	1.8	11.3	SST	CG	N
0.850	21.59	72208	3.50	88.9	.702	17.8	8.7	1.5	2.6	65	22	99	.93	23.7	0.074	1.9	12.6	MW	CG	N
0.850	21.59	72208S	3.50	88.9	.702	17.8	7.4	1.3	2.1	53	15	68	.93	23.7	0.074	1.9	12.6	SST	CG	N
0.850	21.59	72232	3.50	88.9	.690	17.5	12	2.1	2.4	62	29	128	1.03	26.2	0.080	2.0	12.9	MW	CG	N
0.850	21.59	72232S	3.50	88.9	.690	17.5	10	1.8	1.9	49	19	86	1.03	26.2	0.080	2.0	12.9	SST	CG	N
0.850	21.59	72245	3.50	88.9	.688	17.5	12	2.1	2.4	61	29	129	1.08	27.5	0.081	2.1	13.4	MW	CG	N
0.850	21.59	72245S	3.50	88.9	.688	17.5	10	1.8	2.0	50	20	89	1.08	27.5	0.081	2.1	13.4	SST	CG	N
0.850	21.59	72259	3.50	88.9	.680	17.3	15	2.6	2.4	60	34	153	1.15	29.1	0.085	2.2	13.5	MW	CG	N
0.850	21.59	72259S	3.50	88.9	.680	17.3	12	2.2	1.9	47	23	103	1.15	29.1	0.085	2.2	13.5	SST	CG	N
0.850	21.59	72275	3.50	88.9	.668	17.0	19	3.3	2.2	55	40	180	1.27	32.4	0.091	2.3	14.0	MW	CG	N
0.850	21.59	72275S	3.50	88.9	.668	17.0	16	2.8	1.7	43	27	119	1.27	32.4	0.091	2.3	14.0	SST	CG	N
0.850	21.59	72286	3.50	88.9	.666	16.9	19	3.3	2.2	55	41	182	1.33	33.9	0.092	2.3	14.5	MW	CG	N
0.850	21.59	72286S	3.50	88.9	.666	16.9	16	2.8	1.7	44	28	123	1.33	33.9	0.092	2.3	14.5	SST	CG	N
0.850	21.59	72296	3.50	88.9	.654	16.6	25	4.3	2.0	52	50	224	1.43	36.4	0.098	2.5	14.6	MW	CG	N
0.850	21.59	72296S	3.50	88.9	.654	16.6	21	3.7	1.6	40	33	148	1.43	36.4	0.098	2.5	14.6	SST	CG	N
0.850	21.59	72306	3.50	88.9	.650	16.5	30	5.3	1.8	45	53	237	1.33	33.7	0.100	2.5	13.3	MW	CG	N
0.850	21.59	72306S	3.50	88.9	.650	16.5	26	4.5	1.4	35	35	157	1.33	33.7	0.100	2.5	13.3	SST	CG	N
0.850	21.59	72326	3.50	88.9	.640	16.3	32	5.7	1.9	48	62	274	1.58	40.0	0.105	2.7	15.0	MW	CG	N
0.850	21.59	72326S	3.50	88.9	.640	16.3	28	4.8	1.5	38	41	181	1.58	40.0	0.105	2.7	15.0	SST	CG	N
0.850	21.59	72145	4.00	101.6	.750	19.1	2.2	.38	3.5	88	7.5	33	.51	12.9	0.050	1.3	10.1	MW	CG	N
0.850	21.59	72145S	4.00	101.6	.750	19.1	1.8	.32	2.8	70	5.1	23	.51	12.9	0.050	1.3	10.1	SST	CG	N
0.850	21.59	72161	4.00	101.6	.740	18.8	3.0	.52	3.3	85	9.9	44	.60	15.2	0.055	1.4	10.9	MW	CG	N
0.850	21.59	72161S	4.00	101.6	.740	18.8	2.5	.44	2.7	68	6.7	30	.60	15.2	0.055	1.4	10.9	SST	CG	N
0.850	21.59	72171	4.00	101.6	.716	18.2	5.5	.95	3.1	79	17	76	.88	22.3	0.067	1.7	13.1	MW	CG	N
0.850	21.59	72171S	4.00	101.6	.716	18.2	4.6	.81	2.6	66	12	54	.88	22.3	0.067	1.7	13.1	SST	CG	N
0.850	21.59	72185	4.00	101.6	.714	18.1	5.7	1.0	3.1	79	18	79	.90	22.9	0.068	1.7	13.3	MW	CG	N
0.850	21.59	72185S	4.00	101.6	.714	18.1	4.8	.85	2.6	66	13	56	.90	22.9	0.068	1.7	13.3	SST	CG	N
0.850	21.59	72260	4.00	101.6	.680	17.3	13	2.2	2.7	69	34	152	1.30	32.9	0.085	2.2	15.3	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.850	21.59	72260S	4.00	101.6	.680	17.3	11	1.9	2.1	54	23	103	1.30	32.9	0.085	2.2	15.3	SST	CG	N
0.859	21.82	12624	.31	7.9	.673	17.1	319	56	.06	1.4	18	81	.26	6.5	0.093	2.4	2.75	SST	CG	N
0.859	21.82	G-1	.41	10.3	.673	17.1	277	49	.10	2.6	28	126	.26	6.5	0.093	2.4	2.75	SST	CG	N
0.859	21.82	GG-83	.44	11.1	.675	17.1	318	56	.09	2.2	27	122	.24	6.1	0.092	2.3	2.75	SST	CG	N
0.859	21.82	3786	.50	12.7	.675	17.1	228	40	.13	3.3	30	131	.28	7.0	0.092	2.3	3.00	SPR	CG	Z
0.859	21.82	B4-22	.53	13.5	.759	19.3	11	2.0	.36	9.0	4.0	18	.18	4.4	0.050	1.3	3.50	SPR	CG	N
0.859	21.82	S-915	.56	14.3	.751	19.1	18	3.2	.34	8.6	6.2	28	.22	5.7	0.054	1.4	3.13	SST	C	N
0.859	21.82	II-85	.63	15.9	.715	18.2	34	6.0	.34	8.6	12	52	.29	7.3	0.072	1.8	4.00	SST	CG	N
0.859	21.82	1581	.63	15.9	.649	16.5	272	48	.15	3.9	41	184	.47	12.0	0.105	2.7	3.50	SPR	C	Z
0.859	21.82	AA-59	.63	15.9	.619	15.7	369	65	.15	3.7	54	238	.48	12.2	0.120	3.0	4.00	SPR	CG	GI
0.859	21.82	11710	.66	16.7	.743	18.9	21	3.7	.39	10	8.3	37	.20	5.2	0.058	1.5	3.50	SPR	CG	Z
0.859	21.82	11678	.72	18.2	.677	17.2	174	30	.16	4.2	29	127	.30	7.5	0.091	2.3	3.25	SPR	CG	Z
0.859	21.82	A13-35	.75	19.1	.793	20.1	1.3	.23	.59	15	.78	3.5	.17	4.2	0.033	0.8	4.00	SST	C	N
0.859	21.82	S-345	.75	19.1	.699	17.8	28	4.8	.27	6.9	7.5	33	.48	12.2	0.080	2.0	6.00	SST	CG	N
0.859	21.82	10793	.81	20.6	.639	16.2	162	28	.27	6.9	44	196	.52	13.3	0.110	2.8	4.75	SST	CG	N
0.859	21.82	S-3091	.88	22.2	.757	19.2	5.3	.94	.57	14	3.0	14	.31	7.8	0.051	1.3	5.00	SST	C	N
0.859	21.82	12284	.88	22.2	.695	17.7	69	12	.32	8.0	22	98	.33	8.3	0.082	2.1	4.00	SPR	CG	Z
0.859	21.82	KK-85	.88	22.2	.639	16.2	250	44	.19	4.9	48	215	.44	11.2	0.110	2.8	4.00	SPR	CG	N
0.859	21.82	12486	.91	23.0	.699	17.8	62	11	.33	8.3	20	91	.40	10.2	0.080	2.0	4.00	SPR	C	N
0.859	21.82	2951	.91	23.0	.669	17.0	131	23	.25	6.3	32	144	.38	9.7	0.095	2.4	4.00	SPR	CG	Z
0.859	21.82	B12-46	1.00	25.4	.765	19.4	4.0	.71	.71	18	2.8	13	.29	7.5	0.047	1.2	5.25	SPR	C	N
0.859	21.82	PP-92	1.00	25.4	.725	18.4	25	4.4	.47	12	12	53	.27	6.8	0.067	1.7	4.00	SST	CG	N
0.859	21.82	N-55	1.03	26.2	.739	18.8	9.1	1.6	.67	17	6.1	27	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.859	21.82	K-50	1.13	28.6	.735	18.7	21	3.7	.48	12	10	45	.25	6.3	0.062	1.6	4.00	SPR	CG	N
0.859	21.82	S-185	1.25	31.8	.769	19.5	1.2	.21	.76	19	.90	4.0	.50	12.6	0.045	1.1	10.0	SST	C	N
0.859	21.82	B11-69	1.25	31.8	.753	19.1	8.7	1.5	.73	19	6.3	28	.24	6.1	0.053	1.3	4.50	SPR	CG	Z
0.859	21.82	A15-52	1.25	31.8	.737	18.7	14	2.5	.63	16	9.1	40	.30	7.6	0.061	1.5	4.75	SST	CG	N
0.859	21.82	11512	1.25	31.8	.731	18.6	19	3.4	.58	15	11	49	.35	8.9	0.064	1.6	4.50	SPR	CG	Z
0.859	21.82	10148	1.25	31.8	.723	18.4	23	4.0	.59	15	13	59	.32	8.2	0.068	1.7	4.75	SPR	CG	Z
0.859	21.82	12138	1.25	31.8	.699	17.8	25	4.4	.69	18	17	76	.56	14.2	0.080	2.0	7.00	SPR	CG	Z
0.859	21.82	12225	1.28	32.5	.751	19.1	12	2.1	.57	15	6.7	30	.27	6.9	0.054	1.4	4.00	SPR	C	Z
0.859	21.82	12488	1.28	32.5	.699	17.8	42	7.3	.49	12	20	91	.48	12.2	0.080	2.0	5.00	SPR	C	N
0.859	21.82	2773	1.41	35.7	.645	16.4	111	19	.58	15	64	286	.64	16.3	0.107	2.7	6.00	MW	CG	Z
0.859	21.82	S-1307	1.44	36.5	.725	18.4	14	2.5	.83	21	12	53	.37	9.4	0.067	1.7	5.50	SST	CG	N
0.859	21.82	3864	1.44	36.5	.723	18.4	21	3.6	.64	16	13	59	.41	10.4	0.068	1.7	5.00	SPR	C	Z
0.859	21.82	B7-65	1.50	38.1	.735	18.7	14	2.4	.72	18	10	45	.31	7.9	0.062	1.6	5.00	SPR	CG	N
0.859	21.82	11776	1.50	38.1	.723	18.4	18	3.1	.75	19	13	59	.44	11.2	0.068	1.7	5.50	SPR	C	Z
0.859	21.82	10023	1.50	38.1	.719	18.3	22	3.8	.64	16	14	61	.37	9.3	0.070	1.8	5.25	SPR	CG	Z
0.859	21.82	OO-53	1.50	38.1	.639	16.2	137	24	.32	8.2	44	196	.58	14.7	0.110	2.8	5.25	SST	CG	N
0.859	21.82	B15-1	1.53	38.9	.779	19.8	1.1	.19	1.2	30	1.3	5.7	.34	8.6	0.040	1.0	7.50	SST	C	N
0.859	21.82	MM-88	1.59	40.5	.519	13.2	667	117	.24	6.1	160	713	1.28	32.4	0.170	4.3	7.50	SPR	CG	Z
0.859	21.82	S-73	1.63	41.3	.751	19.1	3.3	.57	1.2	30	3.8	17	.45	11.3	0.054	1.4	8.25	SST	CG	N
0.859	21.82	TT-69	1.63	41.3	.649	16.5	79	14	.51	13	40	180	.68	17.3	0.105	2.7	6.50	SST	CG	N
0.859	21.82	11435	1.63	41.3	.609	15.5	127	22	.50	13	63	282	1.13	28.6	0.125	3.2	9.00	SPR	CG	Z
0.859	21.82	10646	1.63	41.3	.567	14.4	360	63	.30	7.5	107	474	1.02	26.0	0.146	3.7	7.00	SPR	CG	Z
0.859	21.82	S-1175	1.75	44.5	.505	12.8	774	135	.21	5.2	159	709	1.24	31.5	0.177	4.5	7.00	SST	CG	N
0.859	21.82	3321	1.88	47.6	.575	14.6	248	43	.40	10	98	438	1.12	28.4	0.142	3.6	8.00	SPR	CG	Z
0.859	21.82	B8-33	1.94	49.2	.651	16.5	78	14	.54	14	42	188	.73	18.5	0.104	2.6	7.00	SPR	CG	N
0.859	21.82	B17-195	1.97	50.0	.499	12.7	599	105	.26	6.6	155	689	1.62	41.1	0.180	4.6	9.00	SST	CG	N
0.859	21.82	2776	2.00	50.8	.673	17.1	55	9.6	.56	14	31	136	.69	17.4	0.093	2.4	6.33	SPR	C	Z
0.859	21.82	10502	2.00	50.8	.663	16.8	43	7.5	.83	21	36	158	.88	22.4	0.098	2.5	9.00	SPR	CG	Z
0.859	21.82	12465	2.00	50.8	.619	15.7	123	22	.51	13	62	277	.96	24.4	0.120	3.0	8.00	SPR	CG	Z
0.859	21.82	S-459	2.06	52.4	.675	17.1	25	4.3	1.1	28	27	122	.92	23.4	0.092	2.3	10.0	SST	CG	N
0.859	21.82	KK-81	2.25	57.2	.539	13.7	460	81	.29	7.5	135	601	1.28	32.5	0.160	4.1	8.00	SPR	CG	Z
0.859	21.82	A13-39	2.34	59.5	.697	17.7	15	2.6	1.4	35	20	88	.81	20.6	0.081	2.1	10.0	SST	CG	N
0.859	21.82	10370	2.38	60.3	.709	18.0	11	1.9	1.5	38	16	72	.88	22.4	0.075	1.9	10.8	SPR	C	Z
0.859	21.82	S-465	2.44	61.9	.649	16.5	48	8.5	.84	21	40	180	.98	24.9	0.105	2.7	9.33	SST	CG	N
0.859	21.82	10829	2.50	63.5	.699	17.8	17	3.0	1.2	31	20	91	.75	19.0	0.080	2.0	9.33	SPR	CG	Z
0.859	21.82	11430	2.50	63.5	.659	16.7	36	6.4	.96	24	35	156	1.00	25.4	0.100	2.5	10.0	SST	CG	N
0.859	21.82	11174	2.53	64.3	.641	16.3	53	9.3	.84	21	45	200	1.09	27.7	0.109	2.8	10.0	SST	CG	N
0.859	21.82	S-381	2.63	66.7	.765	19.4	1.8	.31	2.2	57	3.9	17	.40	10.1	0.047	1.2	8.50	SST	CG	N
0.859	21.82	11510	2.63	66.7	.563	14.3	202	35	.55	14	111	493	1.85	47.0	0.148	3.8	11.5	SPR	CG	Z
0.859	21.82	11953	2.69	68.2	.687	17.4	24	4.3	1.0	26	25	112	.77	19.7	0.086	2.2	9.00	SPR	CG	Z
0.859	21.82	2908	2.75	69.9	.669	17.0	26	4.6	1.2	31	32	144	1.14	29.0	0.095	2.4	12.0	SPR	CG	Z
0.859	21.82	4305	2.75	69.9	.609	15.5	83	14	.85	22	70	312	1.59	40.5	0.125	3.2	12.8	SPR	CG	Z
0.859	21.82	11591	2.78	70.6	.643	16.3	58	10	.82	21	47	210	1.19	30.2	0.108	2.7	10.0	SPR	CG	GI
0.859	21.82	10935	2.84	72.2	.777	19.7	.93	.16	2.4	61	2.2	9.9	.45	11.5	0.041	1.0	10.0	SPR	C	N
0.859	21.82	A13-43	3.00	76.2	.767	19.5	1.6	.29	2.6	65	4.2	19	.39	9.9	0.046	1.2	8.50	SST	CG	N
0.859	21.82	3770	3.00	76.2	.505	12.8	424	74	.42	11	180	799	2.21	56.2	0.177	4.5	12.5	SPR	CG	Z
0.859	21.82	2741	3.25	82.6	.707	18.0	10	1.7	1.8	45	18	78	.91	23.2	0.076	1.9	12.0	SPR	CG	Z
0.859	21.82	2593	3.41	86.5	.743	18.9	3.0	.53	2.7	68	8.1	36	.73	18.4	0.058	1.5	12.5	SPR	CG	GI
0.859	21.82	11947	3.56	90.5	.735	18.7	8.4	1.5	1.2	31	10	45	.43	11.0	0.062	1.6	7.00	SPR	CG	N
0.859	21.82	11829	3.63	92.1	.737	18.7	3.5	.61	2.6	66	9.1	40	.73	18.6	0.061	1.5	12.0	SST	CG	N
0.859	21.82	1561	3.75	95.3	.629	16.0	51	8.9	1.1	27	55	245	1.61	40.9	0.115	2.9	14.0	SPR	CG	Z
0.859	21.82	B18-189	4.00	101.6	.719	18.3	4.8	.85	2.8	72	14	61	1.16	29.3	0.070	1.8	16.5	SPR	CG	N
0.859	21.82	B17-186	4.19	106.4	.771	19.6	1.0	.18	3.5	89	3.7	16	.46	11.7	0.044	1.1	10.5	SST	CG	N
0.859	21.82	S-3067	4.63	117.5	.735	18.7	3.6	.64	2.6	66	9.5	42	.81	20.5	0.062	1.6	12.0	SST	C	N
0.859	21.82	3227	4.69	119.0	.609	15.5	45	7.9	1.6	40	70	312	2.72	69.1	0.125	3.2	21.8	SPR	CG	Z
0.859	21.82	10464	5.25	133.4	.649	16.5	23	4.0	1.9	49	44	194	2.10	53.3	0.105	2.7	20.0	SPR	CG	Z
0.859	21.82	12021	5.50	139.7	.785	19.9	.24	.04	4.7	119	1.1	5.1	.81	20.7	0.037	0.9	22.0	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.859	21.82	3101	6.75	171.5	.579	14.7	55	9.7	1.7	43	94	420	4.04	102.7	0.140	3.6	29.0	SPR	CG	Z
0.859	21.82	12153	8.56	217.5	.609	15.5	32	5.6	2.2	56	70	312	3.75	95.3	0.125	3.2	30.0	SPR	CG	Z
0.859	21.82	3075	9.00	228.6	.667	16.9	8.4	1.5	4.0	101	33	149	3.32	84.4	0.096	2.4	34.8	SPR	CG	Z
0.875	22.23	2726	.41	10.3	.765	19.4	24	4.2	.24	6.1	5.7	26	.17	4.2	0.055	1.4	3.00	HD	CG	Z
0.875	22.23	S-189	.41	10.3	.755	19.2	30	5.2	.23	5.7	6.8	30	.18	4.6	0.060	1.5	3.00	SST	CG	N
0.875	22.23	BB-86	.47	11.9	.725	18.4	89	16	.19	4.7	17	74	.23	5.7	0.075	1.9	3.00	SPR	CG	Z
0.875	22.23	3011	.56	14.3	.793	20.1	4.0	.70	.37	9.3	1.5	6.5	.19	4.9	0.041	1.0	3.75	SPR	C	Z
0.875	22.23	S-1022	.59	15.1	.779	19.8	6.0	1.0	.35	9.0	2.1	9.4	.24	6.1	0.048	1.2	4.00	SST	C	N
0.875	22.23	S-1414	.63	15.9	.773	19.6	5.0	.88	.32	8.1	1.6	7.1	.31	7.8	0.051	1.3	5.00	SST	C	N
0.875	22.23	3271	.66	16.7	.775	19.7	16	2.8	.33	8.3	5.2	23	.20	5.1	0.050	1.3	3.00	SPR	C	Z
0.875	22.23	10469	.66	16.7	.751	19.1	40	6.9	.25	6.4	9.9	44	.25	6.3	0.062	1.6	3.00	SPR	C	Z
0.875	22.23	3702	.66	16.7	.635	16.1	346	61	.18	4.5	61	271	.48	12.2	0.120	3.0	4.00	SPR	CG	Z
0.875	22.23	10942	.69	17.4	.605	15.4	1178	206	.07	1.8	84	372	.41	10.3	0.135	3.4	3.00	SPR	CG	Z
0.875	22.23	11386	.75	19.1	.785	19.9	4.6	.80	.57	14	2.6	12	.18	4.6	0.045	1.1	4.00	SST	CG	N
0.875	22.23	S-3177	.75	19.1	.767	19.5	15	2.7	.40	10	6.2	28	.18	4.5	0.054	1.4	3.25	SST	CG	N
0.875	22.23	1733	.75	19.1	.751	19.1	14	2.5	.39	10	5.6	25	.36	9.1	0.062	1.6	4.75	HD	C	Z
0.875	22.23	S-1438	.81	20.6	.825	21.0	.27	.05	.66	17	.18	.78	.15	3.8	0.025	0.6	5.00	SST	C	N
0.875	22.23	LL-3	.88	22.2	.775	19.7	2.8	.50	.53	13	1.5	6.6	.35	8.9	0.050	1.3	7.00	SST	CG	N
0.875	22.23	S-1698	.88	22.2	.705	17.9	88	15	.25	6.5	22	100	.30	7.6	0.085	2.2	3.50	SST	CG	N
0.875	22.23	26	.88	22.2	.693	17.6	88	15	.32	8.2	28	125	.49	12.3	0.091	2.3	4.33	HD	C	Z
0.875	22.23	S-886	.94	23.8	.793	20.1	4.1	.71	.72	18	2.9	13	.18	4.7	0.041	1.0	3.50	SST	C	N
0.875	22.23	10315	.94	23.8	.751	19.1	26	4.6	.38	9.6	9.9	44	.28	7.1	0.062	1.6	3.50	SPR	C	Z
0.875	22.23	4184	1.00	25.4	.675	17.1	77	14	.40	10	31	137	.60	15.2	0.100	2.5	6.00	SPR	CG	Z
0.875	22.23	12133	1.03	26.2	.757	19.2	16	2.8	.53	14	8.6	38	.24	6.0	0.059	1.5	4.00	SPR	CG	Z
0.875	22.23	3686	1.06	27.0	.715	18.2	59	10	.34	8.7	20	89	.32	8.1	0.080	2.0	4.00	SPR	CG	Z
0.875	22.23	S-1437	1.09	27.8	.665	16.9	111	19	.36	9.1	40	177	.53	13.3	0.105	2.7	5.00	SST	CG	N
0.875	22.23	GG-53	1.13	28.6	.655	16.6	157	27	.30	7.7	47	211	.55	14.0	0.110	2.8	5.00	SPR	CG	Z
0.875	22.23	11118	1.16	29.4	.799	20.3	1.4	.24	.90	23	1.2	5.5	.26	6.5	0.038	1.0	5.75	MW	C	N
0.875	22.23	H-37	1.25	31.8	.785	19.9	1.2	.22	.74	19	.92	4.1	.51	13.0	0.045	1.1	10.3	MW	C	N
0.875	22.23	S-127	1.28	32.5	.775	19.7	3.0	.53	.91	23	2.8	12	.38	9.5	0.050	1.3	7.50	SST	CG	N
0.875	22.23	10307	1.31	33.3	.715	18.2	23	4.1	.75	19	18	78	.56	14.2	0.080	2.0	7.00	SPR	CG	Z
0.875	22.23	S-1446	1.38	34.9	.751	19.1	8.6	1.5	1.0	25	8.6	38	.37	9.4	0.062	1.6	6.00	SST	CG	N
0.875	22.23	11263	1.38	34.9	.693	17.6	32	5.5	.67	17	21	94	.71	17.9	0.091	2.3	7.75	SST	CG	N
0.875	22.23	914	1.38	34.9	.665	16.9	96	17	.45	11	43	190	.74	18.7	0.105	2.7	6.00	HD	C	Z
0.875	22.23	3167	1.44	36.5	.615	15.6	221	39	.34	8.6	75	334	.85	21.5	0.130	3.3	6.50	SPR	CG	Z
0.875	22.23	S-1359	1.50	38.1	.813	20.7	.96	.17	1.3	34	1.3	5.7	.16	3.9	0.031	0.8	4.00	SST	C	N
0.875	22.23	11550	1.50	38.1	.789	20.0	2.8	.50	1.2	32	3.5	16	.26	6.6	0.043	1.1	5.00	SPR	C	Z
0.875	22.23	10497	1.50	38.1	.731	18.6	12	2.1	.91	23	11	48	.59	15.1	0.072	1.8	8.25	SPR	CG	Z
0.875	22.23	10398	1.50	38.1	.715	18.2	18	3.2	.82	21	15	66	.68	17.3	0.080	2.0	8.50	SPR	CG	Z
0.875	22.23	4389	1.56	39.7	.731	18.6	10	1.8	.90	23	9.2	41	.67	16.9	0.072	1.8	9.25	SPR	CG	Z
0.875	22.23	S-1574	1.59	40.5	.775	19.7	3.5	.62	1.2	32	4.4	20	.35	8.9	0.050	1.3	6.00	SST	C	N
0.875	22.23	S-208	1.63	41.3	.751	19.1	6.9	1.2	1.2	30	8.2	36	.43	11.0	0.062	1.6	7.00	SST	CG	N
0.875	22.23	S-42	1.63	41.3	.727	18.5	15	2.6	1.0	25	15	66	.52	13.2	0.074	1.9	7.00	SST	CG	N
0.875	22.23	11584	1.75	44.5	.733	18.6	9.4	1.6	1.0	26	9.4	42	.75	18.9	0.071	1.8	9.50	SPR	CG	Z
0.875	22.23	11999	1.78	45.2	.665	16.9	70	12	.62	16	43	190	.79	20.0	0.105	2.7	7.50	SPR	CG	Z
0.875	22.23	S-1390	1.88	47.6	.715	18.2	17	3.0	1.1	28	19	83	.72	18.3	0.080	2.0	8.00	SST	C	N
0.875	22.23	3525	1.88	47.6	.491	12.5	943	165	.22	5.7	212	943	1.63	41.5	0.192	4.9	8.50	HD	CG	Z
0.875	22.23	B7-52	1.91	48.4	.643	16.3	64	11	.72	18	46	204	1.19	30.2	0.116	2.9	10.3	SST	CG	N
0.875	22.23	2588	1.94	49.2	.693	17.6	41	7.2	.69	17	28	125	.64	16.2	0.091	2.3	7.00	HD	CG	Z
0.875	22.23	A13-70	1.97	50.0	.731	18.6	15	2.6	.94	24	14	61	.54	13.7	0.072	1.8	6.50	SST	C	N
0.875	22.23	12264	2.00	50.8	.749	19.0	11	1.9	.98	25	10	46	.44	11.2	0.063	1.6	6.00	SPR	C	Z
0.875	22.23	1916	2.00	50.8	.731	18.6	16	2.8	.92	23	15	65	.55	14.0	0.072	1.8	6.67	SPR	C	Z
0.875	22.23	II-65	2.00	50.8	.695	17.7	32	5.7	.84	21	27	121	.81	20.6	0.090	2.3	8.00	SPR	C	Z
0.875	22.23	3308	2.00	50.8	.691	17.6	61	11	.47	12	29	129	.60	15.2	0.092	2.3	5.50	SPR	C	Z
0.875	22.23	3926	2.00	50.8	.665	16.9	77	13	.56	14	43	190	.84	21.3	0.105	2.7	7.00	SPR	C	Z
0.875	22.23	68	2.00	50.8	.635	16.1	99	17	.62	16	61	272	1.08	27.4	0.120	3.0	9.00	HD	CG	Z
0.875	22.23	808	2.00	50.8	.521	13.2	572	100	.31	7.9	177	787	1.64	41.6	0.177	4.5	9.25	HD	CG	Z
0.875	22.23	2825	2.03	51.6	.631	16.0	76	13	.58	15	44	196	1.45	36.8	0.122	3.1	12.0	SPR	CG	GI
0.875	22.23	10552	2.06	52.4	.765	19.4	4.3	.76	1.6	40	6.9	31	.47	11.9	0.055	1.4	7.50	SPR	C	Z
0.875	22.23	11841	2.06	52.4	.667	16.9	46	8.0	.91	23	42	185	1.04	26.4	0.104	2.6	10.0	SPR	CG	Z
0.875	22.23	12449	2.06	52.4	.633	16.1	120	21	.52	13	63	279	.97	24.6	0.121	3.1	8.00	SPR	CG	N
0.875	22.23	11205	2.13	54.0	.745	18.9	5.4	.94	1.4	36	7.5	34	.72	18.2	0.065	1.7	10.0	SST	C	N
0.875	22.23	3025	2.13	54.0	.625	15.9	139	24	.50	13	69	307	1.13	28.6	0.125	3.2	8.00	SPR	C	Z
0.875	22.23	A14-66	2.16	54.8	.741	18.8	12	2.1	.97	25	12	52	.40	10.2	0.067	1.7	6.00	SST	CG	N
0.875	22.23	2971	2.19	55.6	.691	17.6	48	8.3	.61	15	29	129	.69	17.5	0.092	2.3	6.50	SPR	C	Z
0.875	22.23	12005	2.19	55.6	.689	17.5	45	7.9	.67	17	30	133	.65	16.5	0.093	2.4	7.00	SPR	CG	Z
0.875	22.23	S-299	2.22	56.4	.795	20.2	.92	.16	1.9	47	1.7	7.6	.36	9.1	0.040	1.0	8.00	SST	C	N
0.875	22.23	11104	2.25	57.2	.761	19.3	5.0	.88	1.5	39	7.7	34	.48	12.3	0.057	1.4	7.50	SPR	C	N
0.875	22.23	3895	2.25	57.2	.725	18.4	11	1.9	1.5	38	17	74	.75	19.1	0.075	1.9	10.0	SPR	CG	Z
0.875	22.23	10119	2.25	57.2	.649	16.5	59	10	.87	22	51	228	1.24	31.6	0.113	2.9	11.0	SPR	CG	Z
0.875	22.23	2927	2.38	60.3	.767	19.5	2.2	.39	1.7	44	3.9	17	.64	16.3	0.054	1.4	12.0	SPR	CG	GI
0.875	22.23	3952	2.38	60.3	.731	18.6	11	1.9	1.4	35	15	65	.72	18.3	0.072	1.8	9.00	SPR	C	Z
0.875	22.23	S-1314	2.44	61.9	.665	16.9	35	6.1	1.1	29	40	177	1.21	30.7	0.105	2.7	11.5	SST	CG	N
0.875	22.23	11272	2.50	63.5	.665	16.9	59	10	.73	18	43	190	.89	22.7	0.105	2.7	8.50	SPR	CG	Z
0.875	22.23	864	2.50	63.5	.635	16.1	69	12	.88	22	61	272	1.44	36.6	0.120	3.0	12.0	HD	CG	Z
0.875	22.23	49	2.50	63.5	.605	15.4	118	21	.71	18	84	372	1.62	41.1	0.135	3.4	12.0	HD	CG	Z
0.875	22.23	4142	2.75	69.9	.663	16.8	47	8.2	.94	24	44	196	1.11	28.3	0.106	2.7	10.5	SPR	CG	Z
0.875	22.23	52	2.75	69.9	.579	14.7	163	29	.67	17	109	485	1.92	48.9	0.148	3.8	13.0	HD	CG	Z
0.875	22.23	2762	2.81	71.4	.761	19.3	3.7	.65	2.1	53	7.7	34	.60	15.2	0.057	1.4	9.50	SPR	C	GI
0.875	22.23	3096	2.88	73.0	.693	17.6	20	3.6	1.4	35	28	125	1.09	27.7	0.091	2.3	12.0	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.875	22.23	2906	2.94	74.6	.715	18.2	12	2.1	1.7	43	20	89	.95	24.1	0.080	2.0	12.0	SPR	CG	Z
0.875	22.23	55	3.00	76.2	.693	17.6	19	3.4	1.4	37	28	125	1.14	28.9	0.091	2.3	12.5	HD	CG	Z
0.875	22.23	56	3.00	76.2	.665	16.9	34	6.0	1.3	32	43	190	1.39	35.3	0.105	2.7	13.3	HD	CG	Z
0.875	22.23	12464	3.06	77.8	.691	17.6	21	3.7	1.4	35	29	129	1.13	28.6	0.092	2.3	12.3	SPR	CG	N
0.875	22.23	DD-78	3.25	82.6	.695	17.7	14	2.5	1.9	47	27	119	1.40	35.4	0.090	2.3	15.5	SPR	CG	Z
0.875	22.23	12166	3.38	85.7	.749	19.0	4.7	.82	2.2	56	10	46	.76	19.2	0.063	1.6	11.0	SPR	C	Z
0.875	22.23	3412	3.50	88.9	.723	18.4	13	2.4	1.3	33	17	77	.68	17.4	0.076	1.9	9.00	SPR	CG	Z
0.875	22.23	4293	3.50	88.9	.715	18.2	9.8	1.7	2.1	52	20	89	1.20	30.5	0.080	2.0	14.0	SPR	C	Z
0.875	22.23	3277	3.63	92.1	.551	14.0	282	49	.49	12	138	613	2.01	51.0	0.162	4.1	12.3	SPR	CG	Z
0.875	22.23	3860	3.75	95.3	.651	16.5	36	6.4	1.4	35	50	223	1.79	45.5	0.112	2.8	16.0	SPR	CG	GI
0.875	22.23	10808	4.00	101.6	.731	18.6	6.8	1.2	2.2	55	15	65	1.01	25.6	0.072	1.8	13.0	SPR	C	Z
0.875	22.23	2711	4.00	101.6	.715	18.2	8.4	1.5	2.4	61	20	89	1.52	38.5	0.080	2.0	17.5	SPR	C	Z
0.875	22.23	2808	4.00	101.6	.715	18.2	7.5	1.3	2.5	64	19	84	1.49	37.8	0.080	2.0	17.8	HD	C	Z
0.875	22.23	891	4.00	101.6	.715	18.2	9.0	1.6	2.2	56	20	89	1.28	32.5	0.080	2.0	15.0	HD	C	Z
0.875	22.23	S-460	4.00	101.6	.691	17.6	16	2.8	1.7	43	27	120	1.36	34.5	0.092	2.3	13.8	SST	C	N
0.875	22.23	3279	4.00	101.6	.685	17.4	18	3.1	1.8	46	32	142	1.62	41.0	0.095	2.4	16.0	SPR	C	Z
0.875	22.23	4253	4.00	101.6	.665	16.9	27	4.7	1.6	40	43	190	1.81	46.0	0.105	2.7	16.3	SPR	C	Z
0.875	22.23	12797	4.31	109.5	.625	15.9	50	8.8	1.9	49	96	428	2.33	59.1	0.125	3.2	18.6	MW	CG	N
0.875	22.23	11151	4.41	111.9	.625	15.9	58	10	1.2	30	69	307	2.16	54.8	0.125	3.2	16.0	HD	C	Z
0.875	22.23	2826	4.50	114.3	.675	17.1	17	3.0	2.5	64	43	193	1.99	50.5	0.100	2.5	20.0	MW	CG	GI
0.875	22.23	653	4.50	114.3	.521	13.2	227	40	.78	20	177	787	3.58	91.0	0.177	4.5	20.3	HD	CG	Z
0.875	22.23	2732	4.94	125.4	.691	17.6	15	2.6	2.0	50	29	129	1.52	38.6	0.092	2.3	16.5	SPR	CG	Z
0.875	22.23	3933	5.50	139.7	.693	17.6	12	2.1	2.3	59	28	125	1.73	43.9	0.091	2.3	19.0	SPR	CG	Z
0.875	22.23	11973	5.63	142.9	.675	17.1	16	2.8	3.2	81	52	231	2.10	53.3	0.100	2.5	21.0	MW	CG	Z
0.875	22.23	883	6.00	152.4	.693	17.6	9.3	1.6	3.0	77	28	125	2.18	55.5	0.091	2.3	24.0	HD	CG	Z
0.875	22.23	872	6.00	152.4	.665	16.9	16	2.8	2.7	67	43	190	2.81	71.3	0.105	2.7	25.8	HD	C	Z
0.875	22.23	865	6.00	152.4	.635	16.1	29	5.1	2.1	54	61	272	3.12	79.2	0.120	3.0	26.0	HD	CG	Z
0.875	22.23	855	6.00	152.4	.605	15.4	46	8.0	1.8	46	84	372	3.75	95.2	0.135	3.4	27.8	HD	CG	Z
0.875	22.23	818	6.00	152.4	.579	14.7	70	12	1.6	40	109	485	4.11	104.3	0.148	3.8	27.8	HD	CG	Z
0.875	22.23	1939	6.50	165.1	.689	17.5	7.6	1.3	3.5	88	27	118	3.02	76.8	0.093	2.4	31.5	SPR	C	Z
0.875	22.23	395	7.13	181.0	.647	16.4	20	3.5	2.7	68	53	234	3.41	86.7	0.114	2.9	30.0	SPR	CG	Z
0.875	22.23	892	7.75	196.9	.715	18.2	4.5	.79	4.4	113	20	89	2.32	58.9	0.080	2.0	28.0	HD	C	Z
0.875	22.23	11686	7.75	196.9	.661	16.8	13	2.2	3.6	92	45	201	3.88	98.5	0.107	2.7	35.3	SPR	C	Z
0.875	22.23	11982	8.22	208.8	.671	17.0	10	1.8	3.9	98	39	175	3.57	90.7	0.102	2.6	35.0	SPR	CG	Z
0.875	22.23	11525	8.28	210.3	.685	17.4	12	2.1	2.7	69	32	142	2.28	57.9	0.095	2.4	23.0	SPR	CG	Z
0.875	22.23	377	8.50	215.9	.731	18.6	3.7	.65	3.9	100	15	65	1.66	42.1	0.072	1.8	22.0	HD	C	Z
0.875	22.23	10004	8.88	225.4	.635	16.1	18	3.2	3.4	85	61	272	4.80	121.9	0.120	3.0	40.0	SPR	CG	Z
0.875	22.23	289	12.0	304.8	.751	19.1	1.2	.22	8.0	204	9.9	44	2.17	55.1	0.062	1.6	34.0	HD	C	Z
0.875	22.23	899	12.0	304.8	.731	18.6	2.1	.36	7.1	181	15	65	2.83	71.8	0.072	1.8	38.3	HD	C	Z
0.875	22.23	893	12.0	304.8	.715	18.2	2.9	.50	7.0	177	20	89	3.49	88.7	0.080	2.0	42.7	HD	C	Z
0.875	22.23	10677	12.3	311.2	.645	16.4	11	1.9	5.0	127	54	240	6.33	160.7	0.115	2.9	55.0	SPR	CG	Z
0.875	22.23	4015	18.5	469.9	.715	18.2	1.9	.33	11	272	20	89	5.24	133.1	0.080	2.0	64.5	HD	C	Z
0.875	22.23	4037	26.5	673.1	.605	15.4	10	1.8	8.2	207	84	372	15.8	401.2	0.135	3.4	117.0	SPR	CG	Z
0.890	22.61	2827	.63	15.9	.730	18.5	37	6.5	.23	5.7	8.3	37	.40	10.2	0.080	2.0	5.00	HD	CG	Z
0.890	22.61	AA-64	.63	15.9	.630	16.0	468	82	.11	2.7	49	218	.52	13.2	0.130	3.3	4.00	SPR	CG	Z
0.890	22.61	10584	.91	23.0	.650	16.5	261	46	.23	5.9	60	268	.54	13.7	0.120	3.0	4.50	SPR	CG	Z
0.890	22.61	10031	1.00	25.4	.796	20.2	2.9	.51	.67	17	2.0	8.7	.33	8.4	0.047	1.2	6.00	SPR	C	Z
0.890	22.61	1910	1.00	25.4	.780	19.8	11	2.0	.61	15	6.8	30	.22	5.6	0.055	1.4	4.00	SPR	CG	Z
0.890	22.61	11919	1.09	27.8	.682	17.3	102	18	.37	9.4	38	169	.52	13.2	0.104	2.6	5.00	SST	CG	N
0.890	22.61	PP-64	1.38	34.9	.770	19.6	8.1	1.4	1.0	26	8.3	37	.36	9.1	0.060	1.5	6.00	SPR	CG	N
0.890	22.61	11232	1.38	34.9	.748	19.0	11	1.9	.81	20	8.9	40	.57	14.4	0.071	1.8	8.00	SPR	CG	N
0.890	22.61	3383	1.38	34.9	.736	18.7	34	6.0	.52	13	18	78	.44	11.2	0.077	2.0	4.75	SPR	C	Z
0.890	22.61	11412	1.38	34.9	.680	17.3	90	16	.47	12	42	187	.63	16.0	0.105	2.7	6.00	SPR	CG	Z
0.890	22.61	S-324	1.38	34.9	.566	14.4	595	104	.20	5.1	121	536	.93	23.7	0.162	4.1	5.75	SST	CG	N
0.890	22.61	11863	1.41	35.7	.768	19.5	5.0	.87	.80	20	4.0	18	.61	15.5	0.061	1.5	9.00	SPR	C	N
0.890	22.61	10293	1.44	36.5	.746	18.9	14	2.5	.93	24	13	59	.50	12.8	0.072	1.8	7.00	SPR	CG	Z
0.890	22.61	10165	1.44	36.5	.578	14.7	431	75	.28	7.2	122	542	1.09	27.7	0.156	4.0	7.00	SPR	CG	Z
0.890	22.61	A14-54	1.50	38.1	.806	20.5	1.8	.32	1.2	32	2.3	10	.25	6.4	0.042	1.1	6.00	SPR	CG	N
0.890	22.61	11318	1.50	38.1	.748	19.0	13	2.2	.99	25	12	56	.51	13.1	0.071	1.8	7.25	SPR	CG	Z
0.890	22.61	10338	1.50	38.1	.730	18.5	18	3.1	.84	21	15	66	.66	16.8	0.080	2.0	8.25	SPR	CG	Z
0.890	22.61	11171	1.50	38.1	.730	18.5	20	3.5	.90	23	18	81	.60	15.2	0.080	2.0	7.50	SPR	CG	Z
0.890	22.61	WW-66	1.63	41.3	.786	20.0	2.2	.39	1.1	28	2.5	11	.52	13.2	0.052	1.3	9.00	SST	C	N
0.890	22.61	10656	1.63	41.3	.750	19.1	10	1.8	1.0	27	10	47	.58	14.7	0.070	1.8	8.25	SPR	CG	Z
0.890	22.61	10488	1.69	42.8	.626	15.9	154	27	.50	13	77	343	1.12	28.5	0.132	3.4	8.50	SPR	CG	Z
0.890	22.61	12175	1.78	45.2	.620	15.7	185	32	.45	11	82	367	1.08	27.4	0.135	3.4	8.00	SPR	CG	N
0.890	22.61	OO-88	1.88	47.6	.658	16.7	57	10	.66	17	38	168	1.22	30.9	0.116	2.9	10.5	SST	CG	N
0.890	22.61	3254	1.88	47.6	.576	14.6	341	60	.36	9.2	124	552	1.33	33.9	0.157	4.0	8.50	SPR	CG	Z
0.890	22.61	S-1218	2.00	50.8	.720	18.3	17	2.9	1.2	30	20	88	.81	20.5	0.085	2.2	9.50	SST	CG	N
0.890	22.61	S-3103	2.00	50.8	.710	18.0	20	3.5	1.0	26	20	90	.99	25.1	0.090	2.3	10.0	SST	C	N
0.890	22.61	PP-76	2.00	50.8	.590	15.0	245	43	.39	10	97	430	1.28	32.4	0.150	3.8	8.50	SST	CG	N
0.890	22.61	11851	2.03	51.6	.722	18.3	17	3.0	1.2	31	21	95	.76	19.2	0.084	2.1	9.00	SST	CG	N
0.890	22.61	12027	2.03	51.6	.598	15.2	244	43	.42	11	103	460	1.24	31.5	0.146	3.7	8.50	SPR	CG	N
0.890	22.61	11523	2.22	56.4	.732	18.6	12	2.0	1.3	32	15	66	.95	24.1	0.079	2.0	11.0	SPR	C	Z
0.890	22.61	S-284	2.25	57.2	.810	20.6	.87	.15	1.9	48	1.6	7.3	.36	9.1	0.040	1.0	8.00	SST	C	N
0.890	22.61	3362	2.25	57.2	.766	19.5	6.2	1.1	1.6	40	9.8	43	.56	14.2	0.062	1.6	8.00	HD	C	Z
0.890	22.61	MM-32	2.25	57.2	.766	19.5	4.8	.84	1.8	45	8.5	38	.48	12.2	0.062	1.6	8.00	SST	CG	N
0.890	22.61	12173	2.25	57.2	.678	17.2	63	11	.69	18	43	193	.85	21.5	0.106	2.7	8.00	SPR	CG	Z
0.890	22.61	S-3015	2.31	58.7	.720	18.3	17	2.9	1.3	34	22	98	.81	20.5	0.085	2.2	9.50	SST	CG	N
0.890	22.61	10822	2.38	60.3	.640	16.3	90	16	.76	19	68	302	1.34	34.1	0.125	3.2	10.8	SPR	CG	Z
0.890	22.61	12698	2.50	63.5	.680	17.3	56	9.7	.76	19	42	187	.89	22.7	0.105	2.7	8.50	HD	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.890	22.61	10967	2.75	69.9	.640	16.3	87	15	.78	20	68	302	.00	0.0	0.125	3.2	11.0	HD	CG	Z
0.890	22.61	12055	2.88	73.0	.726	18.4	8.8	1.5	1.6	40	14	61	1.31	33.3	0.082	2.1	16.0	SPR	CG	Z
0.890	22.61	11411	2.88	73.0	.708	18.0	18	3.2	1.5	38	28	123	1.23	31.2	0.091	2.3	12.5	SPR	C	Z
0.890	22.61	3363	3.00	76.2	.620	15.7	106	19	.78	20	82	367	1.69	42.9	0.135	3.4	12.5	SPR	CG	Z
0.890	22.61	2995	3.13	79.4	.650	16.5	59	10	1.0	26	60	268	1.56	39.6	0.120	3.0	13.0	SPR	CG	GI
0.890	22.61	10715	3.25	82.6	.764	19.4	4.4	.78	2.3	58	10	46	.69	17.6	0.063	1.6	11.0	SPR	CG	GI
0.890	22.61	11891	3.38	85.7	.782	19.9	2.6	.46	2.5	63	6.5	29	.54	13.7	0.054	1.4	10.0	SPR	CG	N
0.890	22.61	3470	3.50	88.9	.730	18.5	6.7	1.2	1.9	49	13	58	1.56	39.6	0.080	2.0	18.5	HD	C	Z
0.890	22.61	3473	3.50	88.9	.726	18.4	10	1.8	2.1	52	21	94	1.23	31.2	0.082	2.1	14.0	SPR	C	Z
0.890	22.61	S-173	3.63	92.1	.650	16.5	41	7.1	1.4	34	55	245	1.92	48.8	0.120	3.0	16.0	SST	CG	N
0.890	22.61	11962	5.56	141.3	.688	17.5	16	2.8	2.3	60	38	167	2.12	53.9	0.101	2.6	21.0	SPR	CG	Z
0.890	22.61	11764	6.00	152.4	.620	15.7	43	7.5	1.9	49	82	367	3.75	95.2	0.135	3.4	27.8	SPR	CG	Z
0.890	22.61	12395	6.13	155.6	.650	16.5	27	4.8	2.2	56	60	268	3.24	82.3	0.120	3.0	26.0	SPR	C	Z
0.890	22.61	12604	6.88	174.6	.578	14.7	82	14	2.1	53	171	759	4.56	115.9	0.156	4.0	28.3	MW	C	N
0.906	23.01	2766	.50	12.7	.686	17.4	417	73	.11	2.8	46	205	.33	8.4	0.110	2.8	3.00	SPR	CG	Z
0.906	23.01	1777	.59	15.1	.782	19.9	11	1.9	.21	5.2	2.2	9.9	.39	9.9	0.062	1.6	5.25	HD	C	Z
0.906	23.01	3542	.59	15.1	.780	19.8	19	3.3	.34	8.7	6.4	29	.25	6.4	0.063	1.6	4.00	HD	CG	Z
0.906	23.01	12410	.63	15.9	.798	20.3	20	3.5	.32	8.2	6.4	28	.22	5.5	0.054	1.4	3.00	SPR	C	N
0.906	23.01	10008	.63	15.9	.782	19.9	35	6.2	.27	6.9	9.6	43	.19	4.7	0.062	1.6	3.00	SPR	CG	Z
0.906	23.01	10118	.63	15.9	.782	19.9	18	3.1	.32	8.0	5.6	25	.31	7.9	0.062	1.6	4.00	HD	C	Z
0.906	23.01	2954	.75	19.1	.786	20.0	15	2.7	.51	13	7.8	35	.24	6.1	0.060	1.5	4.00	SPR	CG	Z
0.906	23.01	A11-51	.75	19.1	.664	16.9	340	59	.18	4.5	61	270	.47	11.9	0.121	3.1	4.00	SPR	CG	Z
0.906	23.01	10551	.81	20.6	.834	21.2	2.4	.43	.65	17	1.6	7.1	.16	4.1	0.036	0.9	3.50	SPR	C	Z
0.906	23.01	2538	.91	23.0	.656	16.7	368	65	.18	4.6	67	297	.50	12.7	0.125	3.2	4.00	SPR	CG	Z
0.906	23.01	11847	1.16	29.4	.812	20.6	4.9	.86	.86	22	4.2	19	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.906	23.01	11536	1.16	29.4	.760	19.3	24	4.1	.63	16	15	66	.44	11.1	0.073	1.9	5.00	SPR	CG	Z
0.906	23.01	10390	1.22	31.0	.736	18.7	27	4.7	.62	16	17	75	.60	15.1	0.085	2.2	7.00	SPR	CG	Z
0.906	23.01	1579	1.25	31.8	.746	18.9	42	7.3	.46	12	19	86	.44	11.2	0.080	2.0	4.50	SPR	C	Z
0.906	23.01	PP-72	1.25	31.8	.746	18.9	23	4.1	.73	19	17	75	.52	13.2	0.080	2.0	6.50	SPR	CG	BO
0.906	23.01	10463	1.25	31.8	.734	18.6	25	4.3	.58	15	14	64	.67	16.9	0.086	2.2	7.75	SPR	CG	Z
0.906	23.01	11121	1.25	31.8	.724	18.4	33	5.8	.57	14	19	84	.68	17.3	0.091	2.3	7.50	HD	CG	Z
0.906	23.01	PP-45	1.28	32.5	.846	21.5	.17	.03	.89	23	.15	.69	.39	9.9	0.030	0.8	12.0	MW	C	GI
0.906	23.01	2881	1.31	33.3	.782	19.9	12	2.1	.81	21	9.6	43	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.906	23.01	10567	1.38	34.9	.746	18.9	17	2.9	.72	18	12	53	.66	16.8	0.080	2.0	8.25	SPR	CG	Z
0.906	23.01	10397	1.47	37.3	.750	19.1	16	2.7	.84	21	13	59	.62	15.8	0.078	2.0	8.00	SPR	CG	Z
0.906	23.01	S-1546	1.50	38.1	.864	21.9	.03	.01	1.2	31	.04	.19	.28	7.1	0.021	0.5	12.3	SST	C	N
0.906	23.01	11319	1.50	38.1	.750	19.1	19	3.3	.88	22	16	73	.62	15.8	0.078	2.0	7.00	SPR	C	Z
0.906	23.01	10377	1.50	38.1	.746	18.9	16	2.8	.82	21	13	59	.68	17.3	0.080	2.0	8.50	SPR	CG	Z
0.906	23.01	10345	1.50	38.1	.736	18.7	23	4.0	.74	19	17	74	.77	19.4	0.085	2.2	8.00	SPR	C	Z
0.906	23.01	S-1196	1.50	38.1	.696	17.7	49	8.6	.66	17	33	145	.84	21.3	0.105	2.7	8.00	SST	CG	N
0.906	23.01	B17-187	1.53	38.9	.734	18.6	29	5.0	.84	21	24	107	.60	15.3	0.086	2.2	7.00	SPR	CG	Z
0.906	23.01	10674	1.56	39.7	.766	19.5	9.8	1.7	.93	24	9.2	41	.63	16.0	0.070	1.8	8.00	SPR	C	Z
0.906	23.01	10842	1.56	39.7	.746	18.9	20	3.5	.90	23	18	80	.66	16.8	0.080	2.0	7.25	SPR	C	N
0.906	23.01	3149	1.56	39.7	.666	16.9	112	20	.53	13	59	264	.90	22.9	0.120	3.0	7.50	SPR	CG	Z
0.906	23.01	3754	1.75	44.5	.696	17.7	68	12	.61	15	41	184	.74	18.7	0.105	2.7	7.00	HD	CG	Z
0.906	23.01	11941	1.75	44.5	.636	16.2	174	30	.47	12	81	361	1.08	27.4	0.135	3.4	8.00	SPR	CG	Z
0.906	23.01	1603	2.13	54.0	.810	20.6	1.1	.19	1.5	38	1.6	7.3	.62	15.8	0.048	1.2	13.0	MW	CG	Z
0.906	23.01	10739	2.25	57.2	.790	20.1	4.9	.85	1.6	41	7.9	35	.49	12.5	0.058	1.5	7.50	SPR	C	N
0.906	23.01	10614	2.31	58.7	.746	18.9	12	2.0	1.4	36	17	74	.88	22.4	0.080	2.0	11.0	SPR	CG	Z
0.906	23.01	11924	2.34	59.5	.746	18.9	16	2.8	1.2	31	19	86	.68	17.3	0.080	2.0	8.50	SPR	CG	Z
0.906	23.01	11853	2.38	60.3	.840	21.3	.65	.11	2.2	55	1.4	6.2	.21	5.4	0.033	0.8	5.50	SST	C	N
0.906	23.01	10378	2.38	60.3	.782	19.9	2.9	.52	1.5	38	4.4	20	.87	22.0	0.062	1.6	14.0	SPR	CG	Z
0.906	23.01	12104	2.47	62.7	.550	14.0	416	73	.42	11	175	777	1.96	49.7	0.178	4.5	11.0	SPR	CG	Z
0.906	23.01	53	2.75	69.9	.696	17.7	35	6.2	1.2	30	41	184	1.33	33.8	0.105	2.7	11.7	HD	C	Z
0.906	23.01	1665	3.13	79.4	.756	19.2	8.8	1.5	2.2	57	20	87	.90	22.9	0.075	1.9	11.0	MW	C	Z
0.906	23.01	1537	3.16	80.2	.762	19.4	7.2	1.3	2.0	50	14	63	.88	22.4	0.072	1.8	11.3	SPR	C	Z
0.906	23.01	2679	3.19	81.0	.724	18.4	14	2.4	1.7	43	23	104	1.48	37.6	0.091	2.3	15.3	MW	C	Z
0.906	23.01	3463	3.38	85.7	.722	18.3	20	3.5	1.4	36	28	125	1.15	29.2	0.092	2.3	11.5	HD	C	Z
0.906	23.01	B9-55	3.50	88.9	.826	21.0	.52	.09	3.0	76	1.5	6.8	.52	13.2	0.040	1.0	13.0	SPR	CG	N
0.906	23.01	3233	3.56	90.5	.714	18.1	19	3.3	1.7	43	32	142	1.46	37.2	0.096	2.4	14.3	SPR	C	Z
0.906	23.01	12109	3.59	91.3	.760	19.3	8.8	1.5	1.7	43	15	66	.73	18.5	0.073	1.9	10.0	SPR	CG	Z
0.906	23.01	S-3042	3.63	92.1	.610	15.5	115	20	.83	21	95	424	2.07	52.6	0.148	3.8	14.0	SST	CG	N
0.906	23.01	3342	4.00	101.6	.756	19.2	3.7	.65	2.2	57	8.2	37	1.76	44.8	0.075	1.9	23.5	SPR	CG	Z
0.906	23.01	3435	4.25	108.0	.806	20.5	1.4	.25	3.5	90	5.1	23	.65	16.5	0.050	1.3	12.0	SPR	C	Z
0.906	23.01	1689	5.00	127.0	.746	18.9	7.1	1.2	2.7	70	19	86	1.34	34.0	0.080	2.0	16.8	SPR	CG	Z
0.906	23.01	12677	5.38	136.5	.656	16.7	35	6.1	1.9	48	67	297	3.00	76.2	0.125	3.2	23.0	SPR	C	N
0.906	23.01	12158	8.75	222.3	.756	19.2	2.5	.43	6.2	157	15	68	2.55	64.8	0.075	1.9	34.0	SPR	CG	Z
0.906	23.01	3912	9.00	228.6	.696	17.7	13	2.3	3.2	81	41	184	2.94	74.7	0.105	2.7	28.0	SPR	CG	Z
0.906	23.01	3147	14.0	355.6	.724	18.4	4.0	.70	6.8	172	27	121	4.39	111.5	0.091	2.3	47.3	SPR	C	Z
0.906	23.01	3150	14.8	374.7	.696	17.7	5.7	1.0	7.3	185	41	184	6.48	164.7	0.105	2.7	61.8	SPR	CG	Z
0.921	23.39	2817	.50	12.7	.701	17.8	395	69	.16	4.1	63	281	.33	8.4	0.110	2.8	3.00	MW	CG	Z
0.921	23.39	10714	.63	15.9	.811	20.6	20	3.5	.33	8.3	6.6	29	.22	5.6	0.055	1.4	3.00	SPR	C	N
0.921	23.39	11195	.66	16.7	.813	20.7	17	2.9	.35	9.0	5.9	26	.22	5.5	0.054	1.4	3.00	SST	C	N
0.921	23.39	12711	.88	22.2	.775	19.7	33	5.9	.58	15	20	87	.29	7.4	0.073	1.9	4.00	MW	CG	N
0.921	23.39	2690	.88	22.2	.681	17.3	258	45	.32	8.0	82	363	.51	13.0	0.120	3.0	4.25	MW	CG	Z
0.921	23.39	3333	.94	23.8	.801	20.3	7.3	1.3	.58	15	4.2	19	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.921	23.39	10785	1.00	25.4	.775	19.7	30	5.2	.46	12	14	61	.37	9.3	0.073	1.9	4.00	SST	C	N
0.921	23.39	10766	1.13	28.6	.811	20.6	6.8	1.2	.80	20	5.4	24	.33	8.4	0.055	1.4	5.00	SPR	C	N
0.921	23.39	3828	1.13	28.6	.761	19.3	33	5.8	.58	15	19	85	.40	10.2	0.080	2.0	5.00	HD	CG	Z
0.921	23.39	S-3029	1.13	28.6	.721	18.3	90	16	.36	9.2	33	146	.45	11.4	0.100	2.5	4.50	SST	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.921	23.39	B18-158	1.25	31.8	.817	20.8	2.8	.50	.89	23	2.5	11	.36	9.2	0.052	1.3	7.00	SST	CG	N
0.921	23.39	BB-43	1.25	31.8	.801	20.3	7.3	1.3	.89	23	6.5	29	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.921	23.39	10197	1.25	31.8	.749	19.0	27	4.7	.65	16	18	78	.60	15.3	0.086	2.2	7.00	SPR	CG	Z
0.921	23.39	11250	1.25	31.8	.731	18.6	59	10	.51	13	30	135	.52	13.3	0.095	2.4	5.50	SPR	CG	Z
0.921	23.39	11382	1.31	33.3	.813	20.7	3.3	.58	.93	24	3.1	14	.38	9.6	0.054	1.4	7.00	SST	CG	N
0.921	23.39	10716	1.31	33.3	.739	18.8	46	8.1	.58	15	27	119	.61	15.6	0.091	2.3	5.75	SPR	C	Z
0.921	23.39	10456	1.38	34.9	.749	19.0	23	4.1	.71	18	17	74	.67	16.9	0.086	2.2	7.75	SPR	CG	Z
0.921	23.39	10706	1.38	34.9	.739	18.8	31	5.5	.69	18	22	96	.68	17.3	0.091	2.3	7.50	SPR	CG	Z
0.921	23.39	11233	1.38	34.9	.739	18.8	38	6.7	.70	18	27	119	.59	15.0	0.091	2.3	6.50	SPR	CG	Z
0.921	23.39	S-474	1.50	38.1	.761	19.3	29	5.0	.62	16	18	80	.40	10.2	0.080	2.0	5.00	SST	CG	N
0.921	23.39	S-140	1.50	38.1	.547	13.9	1104	193	.15	3.7	163	725	1.03	26.1	0.187	4.7	5.50	SST	CG	N
0.921	23.39	10254	1.56	39.7	.771	19.6	33	5.8	.47	12	16	70	.32	8.1	0.075	1.9	4.25	SPR	CG	Z
0.921	23.39	10610	1.56	39.7	.703	17.9	79	14	.53	14	42	188	.68	17.3	0.109	2.8	6.25	SST	CG	N
0.921	23.39	3189	1.59	40.5	.761	19.3	15	2.7	.91	23	14	62	.68	17.3	0.080	2.0	8.50	SPR	CG	GI
0.921	23.39	11207	1.69	42.8	.721	18.3	58	10	.57	14	33	146	.60	15.2	0.100	2.5	6.00	SST	CG	N
0.921	23.39	3815	1.75	44.5	.661	16.8	166	29	.43	11	72	319	.91	23.1	0.130	3.3	7.00	SPR	CG	Z
0.921	23.39	PP-1	2.03	51.6	.621	15.8	244	43	.43	11	106	470	1.28	32.4	0.150	3.8	8.50	SPR	CG	Z
0.921	23.39	11637	2.06	52.4	.799	20.3	4.5	.78	1.5	38	6.8	30	.55	13.9	0.061	1.5	9.00	SPR	CG	Z
0.921	23.39	11236	2.38	60.3	.797	20.2	2.8	.49	1.5	38	4.2	19	.87	22.0	0.062	1.6	14.0	SPR	CG	Z
0.921	23.39	1737	2.75	69.9	.665	16.9	72	13	.98	25	70	313	1.63	41.5	0.128	3.3	12.8	HD	CG	Z
0.921	23.39	S-1611	2.78	70.6	.731	18.6	17	2.9	1.5	39	26	115	1.24	31.4	0.095	2.4	13.0	SST	CG	N
0.921	23.39	10597	3.00	76.2	.777	19.7	7.0	1.2	2.0	51	14	62	.86	21.9	0.072	1.8	11.0	SPR	C	Z
0.921	23.39	3351	3.00	76.2	.761	19.3	9.9	1.7	1.9	49	19	85	.96	24.4	0.080	2.0	12.0	HD	CG	Z
0.921	23.39	3070	3.00	76.2	.671	17.0	75	13	.87	22	66	293	1.41	35.7	0.125	3.2	11.3	SPR	CG	GI
0.921	23.39	MM-92	3.00	76.2	.541	13.7	505	88	.39	10	198	880	2.19	55.5	0.190	4.8	11.5	SPR	CG	N
0.921	23.39	12103	3.22	81.8	.821	20.9	1.5	.26	2.7	68	4.0	18	.55	14.0	0.050	1.3	11.0	SPR	CG	Z
0.921	23.39	1888	3.31	84.1	.777	19.7	7.0	1.2	2.0	51	14	62	.86	21.9	0.072	1.8	11.0	HD	C	Z
0.921	23.39	1685	4.50	114.3	.711	18.1	25	4.3	1.7	42	41	182	1.68	42.7	0.105	2.7	15.0	SPR	C	Z
0.921	23.39	12174	4.75	120.7	.711	18.1	21	3.8	1.9	48	41	182	1.79	45.3	0.105	2.7	17.0	SPR	CG	Z
0.921	23.39	12040	5.50	139.7	.791	20.1	2.0	.36	4.1	103	8.3	37	1.43	36.3	0.065	1.7	22.0	SPR	CG	Z
0.921	23.39	S-462	6.25	158.8	.777	19.7	3.7	.65	3.5	89	13	58	1.28	32.5	0.072	1.8	16.8	SST	C	N
0.921	23.39	3285	6.50	165.1	.701	17.8	19	3.3	2.4	61	45	201	2.53	64.3	0.110	2.8	23.0	SPR	CG	Z
0.921	23.39	4017	19.8	501.7	.631	16.0	20	3.5	5.0	126	98	437	10.2	259.7	0.145	3.7	70.5	SPR	CG	Z
0.938	23.83	3663	.44	11.1	.828	21.0	19	3.3	.27	6.9	5.2	23	.17	4.2	0.055	1.4	3.00	SPR	CG	Z
0.938	23.83	3687	.63	15.9	.828	21.0	19	3.3	.34	8.6	6.5	29	.22	5.6	0.055	1.4	3.00	SPR	C	Z
0.938	23.83	S-3040	.75	19.1	.678	17.2	451	79	.14	3.6	63	282	.46	11.6	0.130	3.3	3.50	SST	CG	N
0.938	23.83	4235	.75	19.1	.668	17.0	615	108	.13	3.2	79	350	.47	12.0	0.135	3.4	3.50	SPR	CG	Z
0.938	23.83	MM-75	.78	19.8	.758	19.3	46	8.0	.33	8.4	15	67	.45	11.4	0.090	2.3	5.00	SST	CG	N
0.938	23.83	1855	.94	23.8	.698	17.7	218	38	.37	9.4	80	357	.54	13.7	0.120	3.0	4.50	MW	CG	Z
0.938	23.83	S-902	.94	23.8	.694	17.6	260	46	.21	5.4	55	245	.49	12.4	0.122	3.1	4.00	SST	CG	N
0.938	23.83	924	1.13	28.6	.728	18.5	86	15	.44	11	38	170	.68	17.3	0.105	2.7	5.50	HD	C	Z
0.938	23.83	11762	1.16	29.4	.622	15.8	755	132	.16	4.1	121	537	.71	18.1	0.158	4.0	4.50	SPR	CG	Z
0.938	23.83	2609	1.19	30.2	.614	15.6	605	106	.21	5.4	130	577	.89	22.6	0.162	4.1	5.50	HD	CG	Z
0.938	23.83	GG-41	1.22	31.0	.758	19.3	46	8.0	.52	13	24	105	.45	11.4	0.090	2.3	5.00	SST	CG	N
0.938	23.83	1617	1.25	31.8	.826	21.0	5.2	.90	.86	22	4.4	20	.39	10.0	0.056	1.4	6.00	SPR	C	Z
0.938	23.83	10524	1.25	31.8	.734	18.6	71	12	.52	13	37	164	.59	14.9	0.102	2.6	5.75	SPR	CG	Z
0.938	23.83	B2-59	1.25	31.8	.668	17.0	284	50	.39	9.8	110	489	.71	18.0	0.135	3.4	5.25	MW	CG	N
0.938	23.83	10211	1.38	34.9	.814	20.7	9.0	1.6	1.0	26	9.3	41	.34	8.7	0.062	1.6	5.50	SPR	CG	Z
0.938	23.83	10268	1.38	34.9	.814	20.7	11	1.8	.88	22	9.3	41	.37	9.4	0.062	1.6	5.00	SPR	C	N
0.938	23.83	S-1123	1.38	34.9	.768	19.5	26	4.6	.78	20	21	91	.60	15.1	0.085	2.2	6.00	SST	C	N
0.938	23.83	11794	1.38	34.9	.700	17.8	105	18	.53	14	56	249	.83	21.2	0.119	3.0	7.00	SPR	CG	Z
0.938	23.83	11738	1.38	34.9	.666	16.9	318	56	.25	6.4	80	357	.68	17.3	0.136	3.5	5.00	SPR	CG	Z
0.938	23.83	11724	1.41	35.7	.754	19.2	43	7.4	.64	16	27	121	.55	14.0	0.092	2.3	6.00	SPR	CG	Z
0.938	23.83	10726	1.50	38.1	.848	21.5	.97	.17	.98	25	.96	4.3	.52	13.1	0.045	1.1	10.5	SPR	C	Z
0.938	23.83	3885	1.50	38.1	.738	18.7	54	9.5	.64	16	35	155	.65	16.5	0.100	2.5	6.50	SPR	CG	GI
0.938	23.83	10977	1.50	38.1	.728	18.5	76	13	.53	13	40	179	.63	16.0	0.105	2.7	6.00	HD	CG	Z
0.938	23.83	PP-62	1.50	38.1	.718	18.2	93	16	.48	12	45	198	.66	16.8	0.110	2.8	6.00	SPR	CG	Z
0.938	23.83	3625	1.50	38.1	.688	17.5	137	24	.66	17	90	401	.84	21.4	0.125	3.2	6.75	MW	CG	Z
0.938	23.83	CC-34	1.50	38.1	.618	15.7	355	62	.31	8.0	111	495	1.12	28.4	0.160	4.1	7.00	SST	CG	N
0.938	23.83	11149	1.59	40.5	.698	17.7	121	21	.47	12	57	255	.78	19.8	0.120	3.0	6.50	SPR	CG	Z
0.938	23.83	S-443	1.66	42.1	.838	21.3	3.8	.66	1.2	31	4.6	20	.25	6.4	0.050	1.3	5.00	SST	CG	N
0.938	23.83	828	1.75	44.5	.698	17.7	99	17	.58	15	57	255	1.02	25.9	0.120	3.0	7.50	HD	C	Z
0.938	23.83	S-940	1.78	45.2	.794	20.2	13	2.3	.98	25	13	57	.50	12.8	0.072	1.8	6.00	SST	C	N
0.938	23.83	10622	1.78	45.2	.728	18.5	54	9.4	.69	18	37	166	.74	18.7	0.105	2.7	7.00	SST	CG	N
0.938	23.83	11719	1.84	46.8	.666	16.9	191	33	.42	11	80	357	1.09	27.6	0.136	3.5	7.00	SPR	C	Z
0.938	23.83	3683	1.94	49.2	.810	20.6	5.8	1.0	1.4	36	8.1	36	.53	13.4	0.064	1.6	8.25	SPR	CG	Z
0.938	23.83	67	2.00	50.8	.778	19.8	17	3.1	1.1	27	19	83	.67	16.9	0.080	2.0	7.33	HD	C	Z
0.938	23.83	S-1361	2.00	50.8	.770	19.6	15	2.7	1.3	33	20	88	.71	18.1	0.084	2.1	8.50	SST	CG	N
0.938	23.83	S-463	2.03	51.6	.698	17.7	76	13	.69	18	52	233	.99	25.1	0.120	3.0	8.25	SST	CG	N
0.938	23.83	12448	2.06	52.4	.778	19.8	16	2.8	1.2	29	19	83	.62	15.7	0.080	2.0	7.75	SPR	CG	N
0.938	23.83	10514	2.13	54.0	.766	19.5	23	4.0	1.0	26	23	103	.65	16.4	0.086	2.2	7.50	SPR	CG	Z
0.938	23.83	11598	2.13	54.0	.549	13.9	834	146	.25	6.3	208	926	1.75	44.5	0.195	4.9	8.00	SPR	CG	Z
0.938	23.83	3922	2.25	57.2	.738	18.7	31	5.3	1.1	29	35	155	1.00	25.4	0.100	2.5	10.0	SPR	CG	Z
0.938	23.83	3458	2.25	57.2	.688	17.5	109	19	.59	15	65	288	1.00	25.4	0.125	3.2	8.00	HD	CG	Z
0.938	23.83	12227	2.41	61.1	.784	19.9	16	2.8	1.1	27	17	75	.62	15.6	0.077	2.0	7.00	SPR	C	Z
0.938	23.83	10046	2.50	63.5	.836	21.2	2.8	.49	1.9	47	5.2	23	.41	10.4	0.051	1.3	7.00	SPR	C	Z
0.938	23.83	3295	2.63	66.7	.624	15.8	193	34	.61	16	119	528	1.81	45.9	0.157	4.0	11.5	SPR	CG	Z
0.938	23.83	10660	2.66	67.5	.782	19.9	10	1.8	1.7	43	17	77	.53	13.5	0.078	2.0	7.50	PB	CG	N
0.938	23.83	11936	2.78	70.6	.780	19.8	11	1.9	1.6	42	18	80	.79	20.1	0.079	2.0	10.0	SPR	CG	Z
0.938	23.83	12084	2.84	72.2	.578	14.7	408	71	.41	10	167	744	1.89	48.0	0.180	4.6	10.5	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.938	23.83	1701	3.00	76.2	.794	20.2	6.6	1.2	2.1	53	14	61	.86	21.9	0.072	1.8	11.0	SPR	C	Z
0.938	23.83	832	3.00	76.2	.728	18.5	30	5.3	1.3	34	40	179	1.26	32.0	0.105	2.7	12.0	HD	CG	Z
0.938	23.83	3939	3.00	76.2	.688	17.5	54	9.5	1.2	30	65	288	1.75	44.5	0.125	3.2	14.0	SPR	CG	Z
0.938	23.83	S-3162	3.25	82.6	.752	19.1	19	3.4	1.3	34	26	116	1.02	26.0	0.093	2.4	10.0	SST	C	N
0.938	23.83	42	3.25	82.6	.524	13.3	588	103	.42	11	248	1101	2.79	71.0	0.207	5.3	13.5	HD	CG	Z
0.938	23.83	11494	3.38	85.7	.740	18.8	19	3.4	1.7	44	34	150	1.49	37.7	0.099	2.5	14.0	SPR	C	Z
0.938	23.83	4287	3.63	92.1	.794	20.2	7.9	1.4	1.7	44	14	61	.68	17.4	0.072	1.8	9.50	SPR	CG	Z
0.938	23.83	1541	3.75	95.3	.698	17.7	52	9.1	1.1	28	57	255	1.62	41.1	0.120	3.0	12.5	SPR	C	Z
0.938	23.83	36	4.00	101.6	.642	16.3	89	16	1.2	29	103	456	2.63	66.7	0.148	3.8	17.8	HD	CG	Z
0.938	23.83	10650	4.19	106.4	.804	20.4	4.9	.85	2.4	61	12	52	.74	18.7	0.067	1.7	11.0	SPR	CG	Z
0.938	23.83	3125	4.31	109.5	.798	20.3	5.3	.92	2.4	61	13	56	.84	21.3	0.070	1.8	12.0	SPR	CG	Z
0.938	23.83	S-1407	4.38	111.1	.814	20.7	1.8	.32	3.3	84	6.1	27	1.05	26.8	0.062	1.6	17.0	SST	CG	N
0.938	23.83	3931	4.50	114.3	.626	15.9	122	21	.95	24	116	518	2.43	61.6	0.156	4.0	15.8	SPR	CG	Z
0.938	23.83	4342	5.00	127.0	.742	18.8	15	2.7	2.2	55	33	146	1.64	41.7	0.098	2.5	16.8	SPR	CG	Z
0.938	23.83	332	5.00	127.0	.584	14.8	175	31	.96	24	167	743	3.60	91.4	0.177	4.5	20.3	HD	CG	Z
0.938	23.83	2843	5.13	130.2	.764	19.4	10	1.8	2.3	59	24	107	1.31	33.1	0.087	2.2	15.0	SPR	CG	GI
0.938	23.83	S-154	5.25	133.4	.642	16.3	55	9.7	1.7	42	92	411	3.55	90.2	0.148	3.8	24.0	SST	CG	N
0.938	23.83	11627	5.25	133.4	.642	16.3	67	12	1.5	39	103	456	3.37	85.5	0.148	3.8	22.8	SPR	CG	Z
0.938	23.83	4149	6.00	152.4	.754	19.2	9.0	1.6	3.0	77	27	121	2.02	51.4	0.092	2.3	21.0	SPR	C	Z
0.938	23.83	3113	6.38	161.9	.794	20.2	4.1	.72	3.3	85	14	61	1.19	30.2	0.072	1.8	16.5	SPR	CG	Z
0.938	23.83	2569	7.25	184.2	.728	18.5	15	2.6	2.7	67	40	179	2.42	61.3	0.105	2.7	22.0	SPR	C	Z
0.938	23.83	11945	8.75	222.3	.810	20.6	1.1	.19	6.5	165	7.1	32	2.24	56.9	0.064	1.6	35.0	SPR	CG	Z
0.938	23.83	4233	9.75	247.7	.698	17.7	23	4.0	2.5	64	57	255	3.24	82.3	0.120	3.0	26.0	SPR	C	Z
0.938	23.83	3076	10.5	266.7	.756	19.2	6.8	1.2	3.9	98	26	117	2.34	59.5	0.091	2.3	25.8	SPR	CG	Z
0.938	23.83	1938	11.1	282.6	.664	16.9	29	5.0	2.9	73	82	365	5.00	127.0	0.137	3.5	36.5	SPR	CG	Z
0.953	24.21	NN-24	.69	17.4	.633	16.1	1511	265	.08	2.1	124	549	.52	13.2	0.160	4.1	3.25	SPR	CG	GI
0.953	24.21	11915	.88	22.2	.771	19.6	68	12	.35	9.0	24	107	.36	9.2	0.091	2.3	4.00	SST	CG	N
0.953	24.21	KK-68	.94	23.8	.833	21.2	6.5	1.1	.58	15	3.8	17	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.953	24.21	3343	.94	23.8	.823	20.9	9.2	1.6	.55	14	5.0	22	.39	9.9	0.065	1.7	6.00	SPR	CG	Z
0.953	24.21	3010	.97	24.6	.771	19.6	77	13	.34	8.6	26	115	.36	9.2	0.091	2.3	4.00	SPR	CG	GI
0.953	24.21	S-1559	.98	25.0	.849	21.6	5.0	.88	.70	18	3.5	16	.29	7.3	0.052	1.3	4.50	SST	C	N
0.953	24.21	12699	1.00	25.4	.873	22.2	2.8	.49	.82	21	2.3	10	.18	4.6	0.040	1.0	3.50	SST	C	N
0.953	24.21	10683	1.00	25.4	.849	21.6	5.7	.99	.73	18	4.1	18	.27	6.9	0.052	1.3	4.25	SST	C	N
0.953	24.21	CC-72	1.00	25.4	.833	21.2	13	2.3	.63	16	8.3	37	.30	7.6	0.060	1.5	4.00	SPR	C	Z
0.953	24.21	3396	1.13	28.6	.825	21.0	12	2.2	.76	19	9.4	42	.37	9.3	0.064	1.6	4.75	SPR	C	Z
0.953	24.21	1907	1.25	31.8	.845	21.5	4.2	.74	.93	24	3.9	17	.32	8.2	0.054	1.4	6.00	SPR	CG	Z
0.953	24.21	4271	1.25	31.8	.829	21.1	7.5	1.3	.82	21	6.1	27	.43	11.0	0.062	1.6	6.00	SPR	C	Z
0.953	24.21	N-126	1.25	31.8	.797	20.2	14	2.5	.70	18	9.9	44	.55	13.9	0.078	2.0	7.00	SST	CG	N
0.953	24.21	2761	1.25	31.8	.639	16.2	433	76	.31	7.8	133	593	.94	23.9	0.157	4.0	6.00	MW	CG	Z
0.953	24.21	S-1254	1.28	32.5	.793	20.1	15	2.7	.72	18	11	49	.56	14.2	0.080	2.0	7.00	SST	CG	N
0.953	24.21	12213	1.31	33.3	.599	15.2	863	151	.19	4.9	165	733	.97	24.7	0.177	4.5	5.50	SPR	CG	GI
0.953	24.21	11385	1.41	35.7	.743	18.9	64	11	.62	16	39	175	.79	20.0	0.105	2.7	6.50	SPR	C	Z
0.953	24.21	11541	1.47	37.3	.721	18.3	137	24	.38	9.5	51	228	.73	18.4	0.116	2.9	5.25	SPR	CG	GI
0.953	24.21	S-94	1.50	38.1	.703	17.9	90	16	.50	13	45	199	1.00	25.4	0.125	3.2	8.00	SST	CG	N
0.953	24.21	B18-140	1.50	38.1	.619	15.7	430	75	.29	7.3	124	552	1.13	28.6	0.167	4.2	6.75	SST	CG	N
0.953	24.21	11856	1.63	41.3	.805	20.4	11	2.0	1.1	28	12	55	.52	13.2	0.074	1.9	7.00	SST	CG	N
0.953	24.21	3954	1.75	44.5	.809	20.5	6.6	1.2	.92	23	6.1	27	.83	21.0	0.072	1.8	10.5	SPR	C	Z
0.953	24.21	3385	1.75	44.5	.797	20.2	26	4.6	.65	16	17	76	.39	9.9	0.078	2.0	5.00	SPR	CG	Z
0.953	24.21	11492	1.75	44.5	.689	17.5	158	28	.46	12	73	323	1.06	26.8	0.132	3.4	7.00	SPR	CG	GI
0.953	24.21	2932	1.81	46.0	.739	18.8	44	7.8	.85	22	38	168	.96	24.5	0.107	2.7	9.00	SPR	CG	Z
0.953	24.21	S-984	1.91	48.4	.791	20.1	11	1.9	1.1	29	12	55	.77	19.5	0.081	2.1	9.50	SST	CG	N
0.953	24.21	AA-72	1.94	49.2	.693	17.6	98	17	.70	18	69	307	1.24	31.4	0.130	3.3	9.50	SPR	CG	Z
0.953	24.21	11157	2.00	50.8	.699	17.8	140	24	.48	12	67	297	.86	21.8	0.127	3.2	6.75	SPR	CG	Z
0.953	24.21	2875	2.13	54.0	.717	18.2	77	13	.70	18	54	240	1.09	27.7	0.118	3.0	8.25	SPR	C	Z
0.953	24.21	10566	2.28	57.9	.823	20.9	7.0	1.2	1.5	38	11	47	.54	13.6	0.065	1.7	7.25	SPR	C	Z
0.953	24.21	MM-54	2.44	61.9	.593	15.1	483	85	.29	7.5	142	633	1.44	36.6	0.180	4.6	8.00	SST	CG	N
0.953	24.21	S-1149	2.75	69.9	.793	20.1	11	1.9	1.6	40	17	77	.80	20.3	0.080	2.0	9.00	SST	C	N
0.953	24.21	11868	3.00	76.2	.783	19.9	12	2.2	1.7	43	21	92	.87	22.1	0.085	2.2	10.3	SST	CG	N
0.953	24.21	2917	3.69	93.6	.711	18.1	51	8.9	1.1	29	58	258	1.63	41.5	0.121	3.1	12.5	SPR	C	Z
0.953	24.21	2914	3.75	95.3	.793	20.1	11	1.9	1.7	42	18	82	.88	22.4	0.080	2.0	10.0	SPR	C	Z
0.953	24.21	11524	3.94	100.0	.743	18.9	23	4.0	1.7	44	40	176	1.63	41.3	0.105	2.7	14.5	SPR	CG	Z
0.953	24.21	11955	4.00	101.6	.763	19.4	19	3.2	1.6	40	29	131	1.24	31.4	0.095	2.4	12.0	SPR	C	Z
0.953	24.21	3423	4.38	111.1	.819	20.8	4.6	.81	2.5	63	12	51	.80	20.4	0.067	1.7	11.0	SPR	C	Z
0.953	24.21	3335	4.44	112.7	.693	17.6	59	10	1.2	30	69	309	2.02	51.2	0.130	3.3	14.5	SPR	C	Z
0.953	24.21	2642	4.81	122.2	.641	16.3	99	17	1.2	29	115	511	2.96	75.3	0.156	4.0	19.0	SPR	CG	Z
0.953	24.21	11558	7.75	196.9	.793	20.1	3.3	.57	5.4	136	18	78	2.40	61.0	0.080	2.0	29.0	SPR	CG	Z
0.953	24.21	3341	8.00	203.2	.539	13.7	254	45	.96	24	245	1088	5.59	142.0	0.207	5.3	27.0	SPR	CG	Z
0.968	24.59	S-182	.69	17.4	.786	20.0	86	15	.27	7.0	24	105	.41	10.4	0.091	2.3	3.50	SST	C	N
0.968	24.59	11911	.75	19.1	.880	22.4	1.8	.32	.47	12	.86	3.8	.28	7.1	0.044	1.1	5.33	SST	C	N
0.968	24.59	KK-54	.78	19.8	.688	17.5	486	85	.17	4.4	85	378	.56	14.2	0.140	3.6	4.00	SPR	CG	GI
0.968	24.59	11692	1.00	25.4	.844	21.4	9.5	1.7	.69	18	6.6	29	.31	7.9	0.062	1.6	5.00	SPR	CG	Z
0.968	24.59	3657	1.03	26.2	.842	21.4	15	2.7	.62	16	9.4	42	.32	8.0	0.063	1.6	4.00	SPR	C	Z
0.968	24.59	S-1476	1.09	27.8	.878	22.3	2.2	.38	.82	21	1.8	8.0	.27	6.9	0.045	1.1	5.00	SST	C	N
0.968	24.59	S-1140	1.13	28.6	.882	22.4	2.0	.34	.88	22	1.7	7.7	.25	6.3	0.043	1.1	4.75	SST	C	N
0.968	24.59	S-1256	1.31	33.3	.874	22.2	3.9	.68	1.0	26	4.0	18	.19	4.8	0.047	1.2	4.00	SST	CG	N
0.968	24.59	PP-78	1.44	36.5	.848	21.5	6.2	1.1	1.1	27	6.7	30	.36	9.1	0.060	1.5	6.00	SPR	CG	Z
0.968	24.59	S-343	1.50	38.1	.794	20.2	30	5.2	.73	19	22	97	.48	12.2	0.087	2.2	5.50	SST	CG	N
0.968	24.59	11128	1.50	38.1	.614	15.6	671	117	.24	6.2	163	724	1.11	28.1	0.177	4.5	6.25	SPR	CG	Z
0.968	24.59	12770	1.56	39.7	.592	15.0	946	166	.19	4.9	184	820	1.13	28.7	0.188	4.8	6.00	HD	CG	Z
0.968	24.59	11183	1.63	41.3	.728	18.5	122	21	.46	12	56	248	.72	18.3	0.120	3.0	6.00	SPR	CG	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.968	24.59	S-1230	1.75	44.5	.888	22.6	.89	.16	1.5	37	1.3	5.7	.30	7.6	0.040	1.0	6.50	SST	C	N
0.968	24.59	S-80	1.88	47.6	.808	20.5	9.7	1.7	1.1	28	11	48	.76	19.3	0.080	2.0	9.50	SST	CG	N
0.968	24.59	11819	2.00	50.8	.794	20.2	21	3.7	1.0	26	22	97	.61	15.5	0.087	2.2	7.00	SST	CG	N
0.968	24.59	10484	2.00	50.8	.718	18.2	107	19	.59	15	63	280	.94	23.8	0.125	3.2	7.50	SPR	CG	Z
0.968	24.59	10510	2.19	55.6	.816	20.7	17	3.0	.93	24	16	70	.46	11.6	0.076	1.9	6.00	SPR	CG	Z
0.968	24.59	11106	2.25	57.2	.874	22.2	2.2	.39	1.9	49	4.3	19	.33	8.4	0.047	1.2	6.00	MW	C	N
0.968	24.59	10496	2.25	57.2	.852	21.6	3.9	.69	1.8	45	6.9	31	.49	12.5	0.058	1.5	7.50	SPR	C	Z
0.968	24.59	2504	2.25	57.2	.838	21.3	3.5	.61	1.5	37	5.1	23	.78	19.8	0.065	1.7	12.0	HD	CG	Z
0.968	24.59	3403	2.25	57.2	.768	19.5	38	6.7	.88	22	34	150	.78	19.7	0.100	2.5	7.75	SPR	CG	Z
0.968	24.59	3119	2.31	58.7	.844	21.4	4.1	.71	1.7	43	6.9	31	.62	15.7	0.062	1.6	9.00	SPR	C	Z
0.968	24.59	2952	2.34	59.5	.824	20.9	11	1.9	1.2	32	13	59	.50	12.8	0.072	1.8	7.00	SPR	CG	Z
0.968	24.59	3018	2.44	61.9	.808	20.5	11	1.8	1.6	42	17	77	.80	20.3	0.080	2.0	10.0	SPR	CG	Z
0.968	24.59	3223	2.53	64.3	.812	20.6	15	2.6	1.1	28	17	75	.62	15.8	0.078	2.0	7.00	SPR	C	Z
0.968	24.59	4272	2.63	66.7	.688	17.5	111	19	.76	19	85	378	1.51	38.2	0.140	3.6	10.8	SPR	CG	Z
0.968	24.59	A13-68	2.78	70.6	.832	21.1	7.5	1.3	1.5	38	11	50	.48	12.1	0.068	1.7	7.00	SST	CG	N
0.968	24.59	11913	2.81	71.4	.788	20.0	15	2.7	1.5	38	23	102	.90	22.9	0.090	2.3	10.0	SST	CG	N
0.968	24.59	S-429	3.06	77.8	.780	19.8	15	2.7	1.7	43	26	116	1.08	27.5	0.094	2.4	11.5	SST	CG	N
0.968	24.59	B17-176	3.28	83.3	.718	18.2	42	7.4	1.4	35	57	255	1.79	45.5	0.125	3.2	14.3	SST	CG	N
0.968	24.59	3175	3.38	85.7	.878	22.3	.94	.16	2.9	74	2.7	12	.45	11.4	0.045	1.1	10.0	SPR	CG	Z
0.968	24.59	11436	3.38	85.7	.728	18.5	47	8.2	1.2	30	56	248	1.50	38.1	0.120	3.0	12.5	SPR	CG	Z
0.968	24.59	3106	3.38	85.7	.698	17.7	83	14	.92	23	76	340	1.62	41.1	0.135	3.4	12.0	SPR	CG	Z
0.968	24.59	1661	3.50	88.9	.758	19.3	30	5.3	1.3	33	39	173	1.26	32.0	0.105	2.7	11.0	SPR	C	Z
0.968	24.59	11486	4.09	104.0	.808	20.5	8.4	1.5	2.2	55	18	81	1.04	26.4	0.080	2.0	12.0	SPR	CG	Z
0.968	24.59	11640	4.38	111.1	.808	20.5	5.6	.98	3.0	77	17	75	1.36	34.5	0.080	2.0	17.0	SPR	CG	Z
0.968	24.59	10655	4.56	115.9	.720	18.3	49	8.6	1.2	32	61	273	1.67	42.5	0.124	3.1	13.5	SPR	CG	Z
0.968	24.59	11563	7.25	184.2	.778	19.8	7.7	1.3	3.8	96	29	129	2.47	62.7	0.095	2.4	25.0	SPR	CG	Z
0.968	24.59	12457	12.0	304.8	.728	18.5	14	2.4	4.1	103	56	248	4.38	111.3	0.120	3.0	35.5	SPR	O	Z
0.968	24.59	3065	15.3	387.4	.758	19.3	5.8	1.0	6.7	171	39	173	5.15	130.7	0.105	2.7	49.0	SPR	CG	GI
0.968	24.59	3077	16.1	409.6	.808	20.5	2.0	.34	9.3	236	18	81	3.60	91.4	0.080	2.0	45.0	SPR	CG	Z
0.975	24.77	72327	.75	19.1	.849	21.6	26	4.5	.51	13	13	58	.20	5.0	0.063	1.6	3.13	MW	CG	N
0.975	24.77	72327S	.75	19.1	.849	21.6	22	3.8	.40	10	8.8	39	.20	5.0	0.063	1.6	3.13	SST	CG	N
0.975	24.77	72339	.75	19.1	.831	21.1	40	6.9	.47	12	18	82	.24	6.2	0.072	1.8	3.38	MW	CG	N
0.975	24.77	72339S	.75	19.1	.831	21.1	34	5.9	.37	9.4	12	55	.24	6.2	0.072	1.8	3.38	SST	CG	N
0.975	24.77	72351	.75	19.1	.827	21.0	40	7.0	.49	12	20	87	.26	6.6	0.074	1.9	3.50	MW	CG	N
0.975	24.77	72351S	.75	19.1	.827	21.0	34	5.9	.40	10	13	60	.26	6.6	0.074	1.9	3.50	SST	CG	N
0.975	24.77	72367	.75	19.1	.813	20.7	61	11	.43	11	26	117	.27	6.9	0.081	2.1	3.38	MW	CG	N
0.975	24.77	72367S	.75	19.1	.813	20.7	51	9.0	.34	8.7	18	78	.27	6.9	0.081	2.1	3.38	SST	CG	N
0.975	24.77	72352	.88	22.4	.827	21.0	33	5.8	.60	15	20	88	.28	7.0	0.074	1.9	3.75	MW	CG	N
0.975	24.77	72352S	.88	22.4	.827	21.0	28	4.9	.48	12	13	60	.28	7.0	0.074	1.9	3.75	SST	CG	N
0.975	24.77	72379	.88	22.4	.805	20.4	54	9.4	.54	14	29	129	.34	8.6	0.085	2.2	4.00	MW	CG	N
0.975	24.77	72379S	.88	22.4	.805	20.4	46	8.0	.44	11	20	90	.34	8.6	0.085	2.2	4.00	SST	CG	N
0.975	24.77	72394	.88	22.4	.791	20.1	72	13	.50	13	36	160	.38	9.6	0.092	2.3	4.13	MW	CG	N
0.975	24.77	72394S	.88	22.4	.791	20.1	61	11	.40	10	24	108	.38	9.6	0.092	2.3	4.13	SST	CG	N
0.975	24.77	72403	.88	22.4	.783	19.9	85	15	.48	12	41	182	.40	10.1	0.096	2.4	4.13	MW	CG	N
0.975	24.77	72403S	.88	22.4	.783	19.9	72	13	.38	9.7	28	123	.40	10.1	0.096	2.4	4.13	SST	CG	N
0.975	24.77	72415	.88	22.4	.765	19.4	119	21	.43	11	52	230	.45	11.3	0.105	2.7	4.25	MW	CG	N
0.975	24.77	72415S	.88	22.4	.765	19.4	101	18	.35	9.0	36	160	.45	11.3	0.105	2.7	4.25	SST	CG	N
0.975	24.77	72427	.88	22.4	.751	19.1	155	27	.40	10	62	278	.48	12.1	0.112	2.8	4.25	MW	CG	N
0.975	24.77	72427S	.88	22.4	.751	19.1	131	23	.31	8.0	41	184	.48	12.1	0.112	2.8	4.25	SST	CG	N
0.975	24.77	72455	.88	22.4	.725	18.4	247	43	.33	8.5	82	365	.55	13.9	0.125	3.2	4.38	MW	CG	N
0.975	24.77	72455S	.88	22.4	.725	18.4	210	37	.27	6.9	57	253	.55	13.9	0.125	3.2	4.38	SST	CG	N
0.975	24.77	72467	.88	22.4	.705	17.9	357	62	.30	7.6	106	473	.57	14.6	0.135	3.4	4.25	MW	CG	N
0.975	24.77	72467S	.88	22.4	.705	17.9	303	53	.23	5.7	68	304	.57	14.6	0.135	3.4	4.25	SST	CG	N
0.975	24.77	72328	1.00	25.4	.849	21.6	18	3.2	.71	18	13	58	.23	5.8	0.063	1.6	3.63	MW	CG	N
0.975	24.77	72328S	1.00	25.4	.849	21.6	16	2.7	.57	14	8.8	39	.23	5.8	0.063	1.6	3.63	SST	CG	N
0.975	24.77	72340	1.00	25.4	.831	21.1	28	4.9	.66	17	18	82	.28	7.1	0.072	1.8	3.88	MW	CG	N
0.975	24.77	72340S	1.00	25.4	.831	21.1	24	4.2	.52	13	12	55	.28	7.1	0.072	1.8	3.88	SST	CG	N
0.975	24.77	72353	1.00	25.4	.827	21.0	28	4.9	.69	18	20	87	.31	7.8	0.074	1.9	4.13	MW	CG	N
0.975	24.77	72353S	1.00	25.4	.827	21.0	24	4.2	.56	14	13	60	.31	7.8	0.074	1.9	4.13	SST	CG	N
0.975	24.77	72368	1.00	25.4	.813	20.7	44	7.6	.60	15	26	117	.32	8.2	0.081	2.1	4.00	MW	CG	N
0.975	24.77	72368S	1.00	25.4	.813	20.7	37	6.5	.47	12	18	78	.32	8.2	0.081	2.1	4.00	SST	CG	N
0.975	24.77	72380	1.00	25.4	.805	20.4	52	9.0	.59	15	30	134	.35	8.9	0.085	2.2	4.13	MW	CG	N
0.975	24.77	72380S	1.00	25.4	.805	20.4	44	7.7	.46	12	20	90	.35	8.9	0.085	2.2	4.13	SST	CG	N
0.975	24.77	72395	1.00	25.4	.791	20.1	61	11	.59	15	36	159	.41	10.5	0.092	2.3	4.50	MW	CG	N
0.975	24.77	72395S	1.00	25.4	.791	20.1	52	9.1	.47	12	24	108	.41	10.5	0.092	2.3	4.50	SST	CG	N
0.975	24.77	72404	1.00	25.4	.783	19.9	74	13	.56	14	42	185	.42	10.7	0.096	2.4	4.38	MW	CG	N
0.975	24.77	72404S	1.00	25.4	.783	19.9	63	11	.44	11	28	123	.42	10.7	0.096	2.4	4.38	SST	CG	N
0.975	24.77	72416	1.00	25.4	.765	19.4	101	18	.51	13	52	231	.49	12.3	0.105	2.7	4.63	MW	CG	N
0.975	24.77	72416S	1.00	25.4	.765	19.4	86	15	.42	11	36	160	.49	12.3	0.105	2.7	4.63	SST	CG	N
0.975	24.77	72428	1.00	25.4	.751	19.1	131	23	.47	12	61	272	.53	13.5	0.112	2.8	4.75	MW	CG	N
0.975	24.77	72428S	1.00	25.4	.751	19.1	111	19	.37	9.4	41	184	.53	13.5	0.112	2.8	4.75	SST	CG	N
0.975	24.77	72429	1.00	25.4	.751	19.1	151	26	.42	11	63	281	.49	12.4	0.112	2.8	4.38	MW	CG	N
0.975	24.77	72429S	1.00	25.4	.751	19.1	128	22	.32	8.2	41	184	.49	12.4	0.112	2.8	4.38	SST	CG	N
0.975	24.77	72456	1.00	25.4	.725	18.4	207	36	.41	10	84	374	.59	15.1	0.125	3.2	4.75	MW	CG	N
0.975	24.77	72456S	1.00	25.4	.725	18.4	176	31	.32	8.2	57	253	.59	15.1	0.125	3.2	4.75	SST	CG	N
0.975	24.77	72468	1.00	25.4	.705	17.9	298	52	.36	9.1	106	473	.64	16.3	0.135	3.4	4.75	MW	CG	N
0.975	24.77	72468S	1.00	25.4	.705	17.9	253	44	.27	6.9	68	304	.64	16.3	0.135	3.4	4.75	SST	CG	N
0.975	24.77	72475	1.00	25.4	.679	17.2	459	80	.30	7.7	139	617	.68	17.4	0.148	3.8	4.63	MW	CG	N
0.975	24.77	72475S	1.00	25.4	.679	17.2	390	68	.23	5.8	89	397	.68	17.4	0.148	3.8	4.63	SST	CG	N
0.975	24.77	72329	1.25	31.8	.849	21.6	14	2.5	.91	23	13	58	.26	6.6	0.063	1.6	4.13	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.975	24.77	72329S	1.25	31.8	.849	21.6	12	2.1	.73	19	8.8	39	.26	6.6	0.063	1.6	4.13	SST	CG	N
0.975	24.77	72341	1.25	31.8	.831	21.1	22	3.8	.85	22	18	82	.32	8.0	0.072	1.8	4.38	MW	CG	N
0.975	24.77	72341S	1.25	31.8	.831	21.1	18	3.2	.67	17	12	55	.32	8.0	0.072	1.8	4.38	SST	CG	N
0.975	24.77	72354	1.25	31.8	.827	21.0	22	3.8	.90	23	19	87	.35	8.9	0.074	1.9	4.75	MW	CG	N
0.975	24.77	72354S	1.25	31.8	.827	21.0	18	3.2	.73	19	13	60	.35	8.9	0.074	1.9	4.75	SST	CG	N
0.975	24.77	72369	1.25	31.8	.813	20.7	34	5.9	.77	20	26	117	.36	9.3	0.081	2.1	4.50	MW	CG	N
0.975	24.77	72369S	1.25	31.8	.813	20.7	29	5.0	.61	15	18	78	.36	9.3	0.081	2.1	4.50	SST	CG	N
0.975	24.77	72381	1.25	31.8	.805	20.4	40	6.9	.76	19	30	134	.40	10.3	0.085	2.2	4.75	MW	CG	N
0.975	24.77	72381S	1.25	31.8	.805	20.4	34	5.9	.60	15	20	90	.40	10.3	0.085	2.2	4.75	SST	CG	N
0.975	24.77	72396	1.25	31.8	.791	20.1	47	8.2	.77	19	36	159	.48	12.3	0.092	2.3	5.25	MW	CG	N
0.975	24.77	72396S	1.25	31.8	.791	20.1	40	7.0	.61	16	24	108	.48	12.3	0.092	2.3	5.25	SST	CG	N
0.975	24.77	72405	1.25	31.8	.783	19.9	56	9.9	.74	19	42	185	.49	12.5	0.096	2.4	5.13	MW	CG	N
0.975	24.77	72405S	1.25	31.8	.783	19.9	48	8.4	.57	15	28	123	.49	12.5	0.096	2.4	5.13	SST	CG	N
0.975	24.77	72417	1.25	31.8	.765	19.4	81	14	.67	17	54	241	.55	14.0	0.105	2.7	5.25	MW	CG	N
0.975	24.77	72417S	1.25	31.8	.765	19.4	69	12	.52	13	36	160	.55	14.0	0.105	2.7	5.25	SST	CG	N
0.975	24.77	72430	1.25	31.8	.751	19.1	102	18	.62	16	63	281	.62	15.6	0.112	2.8	5.50	MW	CG	N
0.975	24.77	72430S	1.25	31.8	.751	19.1	87	15	.48	12	41	184	.62	15.6	0.112	2.8	5.50	SST	CG	N
0.975	24.77	72457	1.25	31.8	.725	18.4	155	27	.55	14	85	378	.70	17.9	0.125	3.2	5.63	MW	CG	N
0.975	24.77	72457S	1.25	31.8	.725	18.4	132	23	.43	11	57	253	.70	17.9	0.125	3.2	5.63	SST	CG	N
0.975	24.77	72330	1.50	38.1	.849	21.6	12	2.0	1.1	28	13	58	.29	7.4	0.063	1.6	4.63	MW	CG	N
0.975	24.77	72330S	1.50	38.1	.849	21.6	9.9	1.7	.89	23	8.8	39	.29	7.4	0.063	1.6	4.63	SST	CG	N
0.975	24.77	72342	1.50	38.1	.831	21.1	18	3.1	1.0	27	18	82	.36	9.1	0.072	1.8	5.00	MW	CG	N
0.975	24.77	72342S	1.50	38.1	.831	21.1	15	2.6	.83	21	12	55	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.975	24.77	72355	1.50	38.1	.827	21.0	18	3.1	1.1	28	20	87	.40	10.1	0.074	1.9	5.38	MW	CG	N
0.975	24.77	72355S	1.50	38.1	.827	21.0	15	2.6	.89	23	13	60	.40	10.1	0.074	1.9	5.38	SST	CG	N
0.975	24.77	72370	1.50	38.1	.813	20.7	28	4.8	.95	24	26	117	.42	10.5	0.081	2.1	5.13	MW	CG	N
0.975	24.77	72370S	1.50	38.1	.813	20.7	23	4.1	.75	19	18	78	.42	10.5	0.081	2.1	5.13	SST	CG	N
0.975	24.77	72382	1.50	38.1	.805	20.4	32	5.6	.94	24	30	134	.45	11.3	0.085	2.2	5.25	MW	CG	N
0.975	24.77	72382S	1.50	38.1	.805	20.4	27	4.8	.74	19	20	90	.45	11.3	0.085	2.2	5.25	SST	CG	N
0.975	24.77	72397	1.50	38.1	.791	20.1	38	6.6	.95	24	36	159	.55	14.0	0.092	2.3	6.00	MW	CG	N
0.975	24.77	72397S	1.50	38.1	.791	20.1	32	5.6	.76	19	24	108	.55	14.0	0.092	2.3	6.00	SST	CG	N
0.975	24.77	72406	1.50	38.1	.783	19.9	46	8.0	.91	23	42	185	.56	14.3	0.096	2.4	5.88	MW	CG	N
0.975	24.77	72406S	1.50	38.1	.783	19.9	39	6.8	.71	18	28	123	.56	14.3	0.096	2.4	5.88	SST	CG	N
0.975	24.77	72418	1.50	38.1	.765	19.4	65	11	.83	21	54	241	.63	16.0	0.105	2.7	6.00	MW	CG	N
0.975	24.77	72418S	1.50	38.1	.765	19.4	56	9.7	.65	16	36	160	.63	16.0	0.105	2.7	6.00	SST	CG	N
0.975	24.77	72431	1.50	38.1	.751	19.1	82	14	.77	20	63	281	.70	17.8	0.112	2.8	6.25	MW	CG	N
0.975	24.77	72431S	1.50	38.1	.751	19.1	70	12	.59	15	41	184	.70	17.8	0.112	2.8	6.25	SST	CG	N
0.975	24.77	72447	1.50	38.1	.735	18.7	114	20	.68	17	77	344	.75	19.1	0.120	3.0	6.25	MW	CG	N
0.975	24.77	72447S	1.50	38.1	.735	18.7	97	17	.52	13	51	225	.75	19.1	0.120	3.0	6.25	SST	CG	N
0.975	24.77	72458	1.50	38.1	.725	18.4	131	23	.66	17	87	388	.80	20.2	0.125	3.2	6.38	MW	CG	N
0.975	24.77	72458S	1.50	38.1	.725	18.4	112	20	.51	13	57	253	.80	20.2	0.125	3.2	6.38	SST	CG	N
0.975	24.77	72469	1.50	38.1	.705	17.9	177	31	.60	15	106	473	.88	22.3	0.135	3.4	6.50	MW	CG	N
0.975	24.77	72469S	1.50	38.1	.705	17.9	150	26	.45	12	68	304	.88	22.3	0.135	3.4	6.50	SST	CG	N
0.975	24.77	72476	1.50	38.1	.679	17.2	268	47	.52	13	139	617	.96	24.4	0.148	3.8	6.50	MW	CG	N
0.975	24.77	72476S	1.50	38.1	.679	17.2	228	40	.39	9.9	89	397	.96	24.4	0.148	3.8	6.50	SST	CG	N
0.975	24.77	72482	1.50	38.1	.651	16.5	415	73	.42	11	176	782	1.05	26.7	0.162	4.1	6.50	MW	CG	N
0.975	24.77	72482S	1.50	38.1	.651	16.5	353	62	.32	8.0	111	496	1.05	26.7	0.162	4.1	6.50	SST	CG	N
0.975	24.77	72331	1.75	44.5	.849	21.6	9.9	1.7	1.3	34	13	58	.32	8.0	0.063	1.6	5.00	MW	CG	N
0.975	24.77	72331S	1.75	44.5	.849	21.6	8.4	1.5	1.1	27	8.8	39	.32	8.0	0.063	1.6	5.00	SST	CG	N
0.975	24.77	72343	1.75	44.5	.831	21.1	15	2.6	1.2	32	18	82	.40	10.1	0.072	1.8	5.50	MW	CG	N
0.975	24.77	72343S	1.75	44.5	.831	21.1	13	2.2	.98	25	12	55	.40	10.1	0.072	1.8	5.50	SST	CG	N
0.975	24.77	72357	1.75	44.5	.827	21.0	16	2.7	1.3	33	20	89	.43	10.8	0.074	1.9	5.75	MW	CG	N
0.975	24.77	72357S	1.75	44.5	.827	21.0	13	2.3	1.0	26	13	60	.43	10.8	0.074	1.9	5.75	SST	CG	N
0.975	24.77	72371	1.75	44.5	.813	20.7	23	4.1	1.1	29	26	117	.47	11.8	0.081	2.1	5.75	MW	CG	N
0.975	24.77	72371S	1.75	44.5	.813	20.7	20	3.5	.89	23	18	78	.47	11.8	0.081	2.1	5.75	SST	CG	N
0.975	24.77	72383	1.75	44.5	.805	20.4	30	5.3	1.0	25	30	134	.47	11.9	0.085	2.2	5.50	MW	CG	N
0.975	24.77	72383S	1.75	44.5	.805	20.4	26	4.5	.79	20	20	90	.47	11.9	0.085	2.2	5.50	SST	CG	N
0.975	24.77	72384	1.75	44.5	.805	20.4	25	4.3	1.2	31	30	134	.53	13.5	0.085	2.2	6.25	MW	CG	N
0.975	24.77	72384S	1.75	44.5	.805	20.4	21	3.7	.96	24	20	90	.53	13.5	0.085	2.2	6.25	SST	CG	N
0.975	24.77	72407	1.75	44.5	.783	19.9	40	7.0	1.0	27	42	185	.62	15.8	0.096	2.4	6.50	MW	CG	N
0.975	24.77	72407S	1.75	44.5	.783	19.9	34	5.9	.82	21	28	123	.62	15.8	0.096	2.4	6.50	SST	CG	N
0.975	24.77	72419	1.75	44.5	.765	19.4	54	9.5	1.0	25	54	241	.72	18.3	0.105	2.7	6.88	MW	CG	N
0.975	24.77	72419S	1.75	44.5	.765	19.4	46	8.1	.78	20	36	160	.72	18.3	0.105	2.7	6.88	SST	CG	N
0.975	24.77	72432	1.75	44.5	.751	19.1	71	12	.89	23	63	281	.78	19.9	0.112	2.8	7.00	MW	CG	N
0.975	24.77	72432S	1.75	44.5	.751	19.1	60	11	.68	17	41	184	.78	19.9	0.112	2.8	7.00	SST	CG	N
0.975	24.77	72440	1.75	44.5	.745	18.9	78	14	.88	22	68	304	.82	20.8	0.115	2.9	7.13	MW	CG	N
0.975	24.77	72440S	1.75	44.5	.745	18.9	66	12	.67	17	45	199	.82	20.8	0.115	2.9	7.13	SST	CG	N
0.975	24.77	72448	1.75	44.5	.735	18.7	95	17	.81	21	77	344	.84	21.3	0.120	3.0	7.00	MW	CG	N
0.975	24.77	72448S	1.75	44.5	.735	18.7	81	14	.63	16	51	225	.84	21.3	0.120	3.0	7.00	SST	CG	N
0.975	24.77	72459	1.75	44.5	.725	18.4	109	19	.80	20	87	388	.91	23.0	0.125	3.2	7.25	MW	CG	N
0.975	24.77	72459S	1.75	44.5	.725	18.4	93	16	.61	16	57	253	.91	23.0	0.125	3.2	7.25	SST	CG	N
0.975	24.77	72332	2.00	50.8	.849	21.6	8.5	1.5	1.5	39	13	58	.35	8.8	0.063	1.6	5.50	MW	CG	N
0.975	24.77	72332S	2.00	50.8	.849	21.6	7.3	1.3	1.2	31	8.8	39	.35	8.8	0.063	1.6	5.50	SST	CG	N
0.975	24.77	72344	2.00	50.8	.831	21.1	13	2.3	1.4	36	18	82	.44	11.2	0.072	1.8	6.13	MW	CG	N
0.975	24.77	72344S	2.00	50.8	.831	21.1	11	1.9	1.1	29	12	55	.44	11.2	0.072	1.8	6.13	SST	CG	N
0.975	24.77	72358	2.00	50.8	.827	21.0	13	2.3	1.5	38	19	87	.49	12.5	0.074	1.9	6.63	MW	CG	N
0.975	24.77	72358S	2.00	50.8	.827	21.0	11	1.9	1.2	31	13	60	.49	12.5	0.074	1.9	6.63	SST	CG	N
0.975	24.77	72372	2.00	50.8	.813	20.7	20	3.5	1.3	33	26	117	.51	12.9	0.081	2.1	6.25	MW	CG	N
0.975	24.77	72372S	2.00	50.8	.813	20.7	17	3.0	1.0	26	18	78	.51	12.9	0.081	2.1	6.25	SST	CG	N
0.975	24.77	72385	2.00	50.8	.805	20.4	23	4.1	1.3	33	30	134	.55	14.0	0.085	2.2	6.50	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.975	24.77	72385S	2.00	50.8	.805	20.4	20	3.5	1.0	26	20	90	.55	14.0	0.085	2.2	6.50	SST	CG	N
0.975	24.77	72398	2.00	50.8	.791	20.1	27	4.8	1.3	33	36	160	.69	17.5	0.092	2.3	7.50	MW	CG	N
0.975	24.77	72398S	2.00	50.8	.791	20.1	23	4.1	1.0	27	24	108	.69	17.5	0.092	2.3	7.50	SST	CG	N
0.975	24.77	72408	2.00	50.8	.783	19.9	33	5.8	1.3	32	42	185	.71	18.0	0.096	2.4	7.38	MW	CG	N
0.975	24.77	72408S	2.00	50.8	.783	19.9	28	4.9	.98	25	28	123	.71	18.0	0.096	2.4	7.38	SST	CG	N
0.975	24.77	72420	2.00	50.8	.765	19.4	47	8.2	1.2	29	54	241	.80	20.3	0.105	2.7	7.63	MW	CG	N
0.975	24.77	72420S	2.00	50.8	.765	19.4	40	7.0	.90	23	36	160	.80	20.3	0.105	2.7	7.63	SST	CG	N
0.975	24.77	72433	2.00	50.8	.751	19.1	59	10	1.1	27	63	281	.90	22.8	0.112	2.8	8.00	MW	CG	N
0.975	24.77	72433S	2.00	50.8	.751	19.1	50	8.8	.82	21	41	184	.90	22.8	0.112	2.8	8.00	SST	CG	N
0.975	24.77	72441	2.00	50.8	.745	18.9	68	12	1.0	26	68	304	.91	23.0	0.115	2.9	7.88	MW	CG	N
0.975	24.77	72441S	2.00	50.8	.745	18.9	58	10	.77	20	45	199	.91	23.0	0.115	2.9	7.88	SST	CG	N
0.975	24.77	72449	2.00	50.8	.735	18.7	82	14	.94	24	77	344	.95	24.0	0.120	3.0	7.88	MW	CG	N
0.975	24.77	72449S	2.00	50.8	.735	18.7	70	12	.73	18	51	225	.95	24.0	0.120	3.0	7.88	SST	CG	N
0.975	24.77	72460	2.00	50.8	.725	18.4	94	16	.93	24	87	388	1.02	25.8	0.125	3.2	8.13	MW	CG	N
0.975	24.77	72460S	2.00	50.8	.725	18.4	80	14	.71	18	57	253	1.02	25.8	0.125	3.2	8.13	SST	CG	N
0.975	24.77	72470	2.00	50.8	.705	17.9	126	22	.85	21	106	473	1.13	28.7	0.135	3.4	8.38	MW	CG	N
0.975	24.77	72470S	2.00	50.8	.705	17.9	107	19	.64	16	68	304	1.13	28.7	0.135	3.4	8.38	SST	CG	N
0.975	24.77	72477	2.00	50.8	.679	17.2	190	33	.73	19	139	617	1.24	31.5	0.148	3.8	8.38	MW	CG	N
0.975	24.77	72477S	2.00	50.8	.679	17.2	161	28	.55	14	89	397	1.24	31.5	0.148	3.8	8.38	SST	CG	N
0.975	24.77	72483	2.00	50.8	.651	16.5	291	51	.60	15	176	782	1.36	34.5	0.162	4.1	8.38	MW	CG	N
0.975	24.77	72483S	2.00	50.8	.651	16.5	248	43	.45	11	111	496	1.36	34.5	0.162	4.1	8.38	SST	CG	N
0.975	24.77	72333	2.25	57.2	.849	21.6	7.5	1.3	1.7	44	13	58	.38	9.6	0.063	1.6	6.00	MW	CG	N
0.975	24.77	72333S	2.25	57.2	.849	21.6	6.4	1.1	1.4	35	8.8	39	.38	9.6	0.063	1.6	6.00	SST	CG	N
0.975	24.77	72345	2.25	57.2	.831	21.1	11	2.0	1.6	41	18	82	.48	12.1	0.072	1.8	6.63	MW	CG	N
0.975	24.77	72345S	2.25	57.2	.831	21.1	9.7	1.7	1.3	33	12	55	.48	12.1	0.072	1.8	6.63	SST	CG	N
0.975	24.77	72360	2.25	57.2	.827	21.0	12	2.1	1.7	43	20	89	.52	13.2	0.074	1.9	7.00	MW	CG	N
0.975	24.77	72360S	2.25	57.2	.827	21.0	10	1.8	1.3	34	13	60	.52	13.2	0.074	1.9	7.00	SST	CG	N
0.975	24.77	72373	2.25	57.2	.813	20.7	18	3.1	1.5	38	26	117	.56	14.1	0.081	2.1	6.88	MW	CG	N
0.975	24.77	72373S	2.25	57.2	.813	20.7	15	2.6	1.2	30	18	78	.56	14.1	0.081	2.1	6.88	SST	CG	N
0.975	24.77	72386	2.25	57.2	.805	20.4	23	4.0	1.3	33	30	134	.56	14.3	0.085	2.2	6.63	MW	CG	N
0.975	24.77	72386S	2.25	57.2	.805	20.4	19	3.4	1.0	26	20	90	.56	14.3	0.085	2.2	6.63	SST	CG	N
0.975	24.77	72387	2.25	57.2	.805	20.4	19	3.3	1.6	41	30	134	.65	16.5	0.085	2.2	7.63	MW	CG	N
0.975	24.77	72387S	2.25	57.2	.805	20.4	16	2.8	1.3	32	20	90	.65	16.5	0.085	2.2	7.63	SST	CG	N
0.975	24.77	72409	2.25	57.2	.783	19.9	30	5.3	1.4	35	42	185	.77	19.5	0.096	2.4	8.00	MW	CG	N
0.975	24.77	72409S	2.25	57.2	.783	19.9	26	4.5	1.1	27	28	123	.77	19.5	0.096	2.4	8.00	SST	CG	N
0.975	24.77	72421	2.25	57.2	.765	19.4	41	7.2	1.3	33	54	241	.89	22.7	0.105	2.7	8.50	MW	CG	N
0.975	24.77	72421S	2.25	57.2	.765	19.4	35	6.1	1.0	26	36	160	.89	22.7	0.105	2.7	8.50	SST	CG	N
0.975	24.77	72434	2.25	57.2	.751	19.1	54	9.5	1.2	30	63	281	.95	24.2	0.112	2.8	8.50	MW	CG	N
0.975	24.77	72434S	2.25	57.2	.751	19.1	46	8.0	.90	23	41	184	.95	24.2	0.112	2.8	8.50	SST	CG	N
0.975	24.77	72442	2.25	57.2	.745	18.9	59	10	1.2	29	68	304	1.01	25.6	0.115	2.9	8.75	MW	CG	N
0.975	24.77	72442S	2.25	57.2	.745	18.9	50	8.8	.89	23	45	199	1.01	25.6	0.115	2.9	8.75	SST	CG	N
0.975	24.77	72450	2.25	57.2	.735	18.7	71	12	1.1	28	77	344	1.05	26.7	0.120	3.0	8.75	MW	CG	N
0.975	24.77	72450S	2.25	57.2	.735	18.7	60	11	.84	21	51	225	1.05	26.7	0.120	3.0	8.75	SST	CG	N
0.975	24.77	72461	2.25	57.2	.725	18.4	82	14	1.1	27	87	388	1.13	28.6	0.125	3.2	9.00	MW	CG	N
0.975	24.77	72461S	2.25	57.2	.725	18.4	70	12	.82	21	57	253	1.13	28.6	0.125	3.2	9.00	SST	CG	N
0.975	24.77	72334	2.50	63.5	.849	21.6	6.7	1.2	1.9	49	13	58	.40	10.2	0.063	1.6	6.38	MW	CG	N
0.975	24.77	72334S	2.50	63.5	.849	21.6	5.7	1.0	1.5	39	8.8	39	.40	10.2	0.063	1.6	6.38	SST	CG	N
0.975	24.77	72346	2.50	63.5	.831	21.1	10	1.8	1.8	46	18	82	.51	13.0	0.072	1.8	7.13	MW	CG	N
0.975	24.77	72346S	2.50	63.5	.831	21.1	8.6	1.5	1.4	36	12	55	.51	13.0	0.072	1.8	7.13	SST	CG	N
0.975	24.77	72361	2.50	63.5	.827	21.0	10	1.8	1.9	49	20	87	.57	14.6	0.074	1.9	7.75	MW	CG	N
0.975	24.77	72361S	2.50	63.5	.827	21.0	8.7	1.5	1.6	39	13	60	.57	14.6	0.074	1.9	7.75	SST	CG	N
0.975	24.77	72374	2.50	63.5	.813	20.7	16	2.8	1.7	42	26	117	.61	15.4	0.081	2.1	7.50	MW	CG	N
0.975	24.77	72374S	2.50	63.5	.813	20.7	13	2.4	1.3	33	18	78	.61	15.4	0.081	2.1	7.50	SST	CG	N
0.975	24.77	72388	2.50	63.5	.805	20.4	18	3.2	1.6	42	30	134	.66	16.7	0.085	2.2	7.75	MW	CG	N
0.975	24.77	72388S	2.50	63.5	.805	20.4	16	2.7	1.3	33	20	90	.66	16.7	0.085	2.2	7.75	SST	CG	N
0.975	24.77	72399	2.50	63.5	.791	20.1	22	3.8	1.7	42	36	160	.83	21.0	0.092	2.3	9.00	MW	CG	N
0.975	24.77	72399S	2.50	63.5	.791	20.1	18	3.2	1.3	34	24	108	.83	21.0	0.092	2.3	9.00	SST	CG	N
0.975	24.77	72410	2.50	63.5	.783	19.9	26	4.5	1.6	41	42	185	.85	21.6	0.096	2.4	8.88	MW	CG	N
0.975	24.77	72410S	2.50	63.5	.783	19.9	22	3.9	1.2	32	28	123	.85	21.6	0.096	2.4	8.88	SST	CG	N
0.975	24.77	72422	2.50	63.5	.765	19.4	36	6.4	1.5	38	54	241	.97	24.7	0.105	2.7	9.25	MW	CG	N
0.975	24.77	72422S	2.50	63.5	.765	19.4	31	5.4	1.2	29	36	160	.97	24.7	0.105	2.7	9.25	SST	CG	N
0.975	24.77	72435	2.50	63.5	.751	19.1	46	8.0	1.4	35	63	281	1.08	27.4	0.112	2.8	9.63	MW	CG	N
0.975	24.77	72435S	2.50	63.5	.751	19.1	39	6.8	1.1	27	41	184	1.08	27.4	0.112	2.8	9.63	SST	CG	N
0.975	24.77	72443	2.50	63.5	.745	18.9	52	9.1	1.3	33	68	304	1.11	28.1	0.115	2.9	9.63	MW	CG	N
0.975	24.77	72443S	2.50	63.5	.745	18.9	44	7.7	1.0	26	45	199	1.11	28.1	0.115	2.9	9.63	SST	CG	N
0.975	24.77	72451	2.50	63.5	.735	18.7	64	11	1.2	31	77	344	1.14	29.0	0.120	3.0	9.50	MW	CG	N
0.975	24.77	72451S	2.50	63.5	.735	18.7	54	9.5	.93	24	51	225	1.14	29.0	0.120	3.0	9.50	SST	CG	N
0.975	24.77	72462	2.50	63.5	.725	18.4	73	13	1.2	30	87	388	1.23	31.4	0.125	3.2	9.88	MW	CG	N
0.975	24.77	72462S	2.50	63.5	.725	18.4	62	11	.92	23	57	253	1.23	31.4	0.125	3.2	9.88	SST	CG	N
0.975	24.77	72471	2.50	63.5	.705	17.9	98	17	1.1	28	106	473	1.38	35.1	0.135	3.4	10.3	MW	CG	N
0.975	24.77	72471S	2.50	63.5	.705	17.9	83	15	.82	21	68	304	1.38	35.1	0.135	3.4	10.3	SST	CG	N
0.975	24.77	72478	2.50	63.5	.679	17.2	147	26	.95	24	139	617	1.54	39.0	0.148	3.8	10.4	MW	CG	N
0.975	24.77	72478S	2.50	63.5	.679	17.2	125	22	.72	18	89	397	1.54	39.0	0.148	3.8	10.4	SST	CG	N
0.975	24.77	72484	2.50	63.5	.651	16.5	224	39	.78	20	176	782	1.66	42.2	0.162	4.1	10.3	MW	CG	N
0.975	24.77	72484S	2.50	63.5	.651	16.5	191	33	.58	15	111	496	1.66	42.2	0.162	4.1	10.3	SST	CG	N
0.975	24.77	72335	2.75	69.9	.849	21.6	6.1	1.1	2.1	54	13	58	.43	11.0	0.063	1.6	6.88	MW	CG	N
0.975	24.77	72335S	2.75	69.9	.849	21.6	5.2	.91	1.7	43	8.8	39	.43	11.0	0.063	1.6	6.88	SST	CG	N
0.975	24.77	72347	2.75	69.9	.831	21.1	9.2	1.6	2.0	51	18	82	.56	14.2	0.072	1.8	7.75	MW	CG	N
0.975	24.77	72347S	2.75	69.9	.831	21.1	7.8	1.4	1.6	40	12	55	.56	14.2	0.072	1.8	7.75	SST	CG	N
0.975	24.77	72363	2.75	69.9	.827	21.0	9.6	1.7	2.1	53	20	89	.60	15.3	0.074	1.9	8.13	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; **HD** - Hard Drawn; **OT** - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None



COMPRESSION SPRINGS

O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.975	24.77	72363S	2.75	69.9	.827	21.0	8.2	1.4	1.6	42	13	60	.60	15.3	0.074	1.9	8.13	SST	CG	N
0.975	24.77	72375	2.75	69.9	.813	20.7	14	2.5	1.8	47	26	117	.65	16.5	0.081	2.1	8.00	MW	CG	N
0.975	24.77	72375S	2.75	69.9	.813	20.7	12	2.1	1.4	37	18	78	.65	16.5	0.081	2.1	8.00	SST	CG	N
0.975	24.77	72389	2.75	69.9	.805	20.4	18	3.2	1.6	42	30	134	.66	16.7	0.085	2.2	7.75	MW	CG	N
0.975	24.77	72389S	2.75	69.9	.805	20.4	16	2.8	1.3	33	20	90	.66	16.7	0.085	2.2	7.75	SST	CG	N
0.975	24.77	72390	2.75	69.9	.805	20.4	15	2.7	2.0	50	30	134	.77	19.4	0.085	2.2	9.00	MW	CG	N
0.975	24.77	72390S	2.75	69.9	.805	20.4	13	2.3	1.6	40	20	90	.77	19.4	0.085	2.2	9.00	SST	CG	N
0.975	24.77	72411	2.75	69.9	.783	19.9	24	4.3	1.7	44	42	185	.90	22.9	0.096	2.4	9.38	MW	CG	N
0.975	24.77	72411S	2.75	69.9	.783	19.9	21	3.6	1.3	34	28	123	.90	22.9	0.096	2.4	9.38	SST	CG	N
0.975	24.77	72423	2.75	69.9	.765	19.4	33	5.7	1.7	42	54	241	1.06	27.0	0.105	2.7	10.1	MW	CG	N
0.975	24.77	72423S	2.75	69.9	.765	19.4	28	4.9	1.3	33	36	160	1.06	27.0	0.105	2.7	10.1	SST	CG	N
0.975	24.77	72436	2.75	69.9	.751	19.1	43	7.5	1.5	37	63	281	1.13	28.8	0.112	2.8	10.1	MW	CG	N
0.975	24.77	72436S	2.75	69.9	.751	19.1	37	6.4	1.1	29	41	184	1.13	28.8	0.112	2.8	10.1	SST	CG	N
0.975	24.77	72463	2.75	69.9	.725	18.4	62	11	1.3	34	84	372	1.41	35.7	0.125	3.2	11.3	MW	CG	N
0.975	24.77	72463S	2.75	69.9	.725	18.4	53	9.3	1.1	27	57	253	1.41	35.7	0.125	3.2	11.3	SST	CG	N
0.975	24.77	72336	3.00	76.2	.849	21.6	5.6	.97	2.3	59	13	58	.46	11.8	0.063	1.6	7.38	MW	CG	N
0.975	24.77	72336S	3.00	76.2	.849	21.6	4.7	.83	1.9	47	8.8	39	.46	11.8	0.063	1.6	7.38	SST	CG	N
0.975	24.77	72348	3.00	76.2	.831	21.1	8.4	1.5	2.2	56	18	82	.59	15.1	0.072	1.8	8.25	MW	CG	N
0.975	24.77	72348S	3.00	76.2	.831	21.1	7.1	1.2	1.7	44	12	55	.59	15.1	0.072	1.8	8.25	SST	CG	N
0.975	24.77	72364	3.00	76.2	.827	21.0	8.4	1.5	2.3	59	20	87	.67	16.9	0.074	1.9	9.00	MW	CG	N
0.975	24.77	72364S	3.00	76.2	.827	21.0	7.1	1.3	1.9	48	13	60	.67	16.9	0.074	1.9	9.00	SST	CG	N
0.975	24.77	72376	3.00	76.2	.813	20.7	13	2.3	2.0	51	26	117	.70	17.7	0.081	2.1	8.63	MW	CG	N
0.975	24.77	72376S	3.00	76.2	.813	20.7	11	1.9	1.6	40	18	78	.70	17.7	0.081	2.1	8.63	SST	CG	N
0.975	24.77	72391	3.00	76.2	.805	20.4	15	2.6	2.0	51	30	134	.77	19.4	0.085	2.2	9.00	MW	CG	N
0.975	24.77	72391S	3.00	76.2	.805	20.4	13	2.3	1.6	40	20	90	.77	19.4	0.085	2.2	9.00	SST	CG	N
0.975	24.77	72400	3.00	76.2	.791	20.1	18	3.1	2.0	52	36	160	.97	24.5	0.092	2.3	10.5	MW	CG	N
0.975	24.77	72400S	3.00	76.2	.791	20.1	15	2.6	1.6	41	24	108	.97	24.5	0.092	2.3	10.5	SST	CG	N
0.975	24.77	72412	3.00	76.2	.783	19.9	21	3.7	1.9	49	42	185	1.00	25.3	0.096	2.4	10.4	MW	CG	N
0.975	24.77	72412S	3.00	76.2	.783	19.9	18	3.2	1.5	39	28	123	1.00	25.3	0.096	2.4	10.4	SST	CG	N
0.975	24.77	72424	3.00	76.2	.765	19.4	30	5.2	1.8	46	54	241	1.14	29.0	0.105	2.7	10.9	MW	CG	N
0.975	24.77	72424S	3.00	76.2	.765	19.4	25	4.4	1.4	36	36	160	1.14	29.0	0.105	2.7	10.9	SST	CG	N
0.975	24.77	72437	3.00	76.2	.751	19.1	38	6.6	1.7	43	63	281	1.26	32.0	0.112	2.8	11.3	MW	CG	N
0.975	24.77	72437S	3.00	76.2	.751	19.1	32	5.6	1.3	33	41	184	1.26	32.0	0.112	2.8	11.3	SST	CG	N
0.975	24.77	72444	3.00	76.2	.745	18.9	43	7.5	1.6	40	68	304	1.29	32.9	0.115	2.9	11.3	MW	CG	N
0.975	24.77	72444S	3.00	76.2	.745	18.9	37	6.4	1.2	31	45	199	1.29	32.9	0.115	2.9	11.3	SST	CG	N
0.975	24.77	72452	3.00	76.2	.735	18.7	52	9.1	1.5	38	77	344	1.34	33.9	0.120	3.0	11.1	MW	CG	N
0.975	24.77	72452S	3.00	76.2	.735	18.7	44	7.7	1.1	29	51	225	1.34	33.9	0.120	3.0	11.1	SST	CG	N
0.975	24.77	72464	3.00	76.2	.725	18.4	60	10	1.5	37	87	388	1.45	36.9	0.125	3.2	11.6	MW	CG	N
0.975	24.77	72464S	3.00	76.2	.725	18.4	51	8.9	1.1	29	57	253	1.45	36.9	0.125	3.2	11.6	SST	CG	N
0.975	24.77	72472	3.00	76.2	.705	17.9	80	14	1.3	34	106	473	1.64	41.6	0.135	3.4	12.1	MW	CG	N
0.975	24.77	72472S	3.00	76.2	.705	17.9	68	12	1.0	26	68	304	1.64	41.6	0.135	3.4	12.1	SST	CG	N
0.975	24.77	72479	3.00	76.2	.679	17.2	120	21	1.2	29	139	617	1.81	46.1	0.148	3.8	12.3	MW	CG	N
0.975	24.77	72479S	3.00	76.2	.679	17.2	102	18	.88	22	89	397	1.81	46.1	0.148	3.8	12.3	SST	CG	N
0.975	24.77	72485	3.00	76.2	.651	16.5	183	32	.96	24	176	782	1.96	49.9	0.162	4.1	12.1	MW	CG	N
0.975	24.77	72485S	3.00	76.2	.651	16.5	155	27	.72	18	111	496	1.96	49.9	0.162	4.1	12.1	SST	CG	N
0.975	24.77	72337	3.50	88.9	.849	21.6	4.7	.83	2.7	70	13	58	.52	13.2	0.063	1.6	8.25	MW	CG	N
0.975	24.77	72337S	3.50	88.9	.849	21.6	4.0	.71	2.2	56	8.8	39	.52	13.2	0.063	1.6	8.25	SST	CG	N
0.975	24.77	72349	3.50	88.9	.831	21.1	7.1	1.2	2.6	66	18	82	.68	17.1	0.072	1.8	9.38	MW	CG	N
0.975	24.77	72349S	3.50	88.9	.831	21.1	6.1	1.1	2.0	52	12	55	.68	17.1	0.072	1.8	9.38	SST	CG	N
0.975	24.77	72365	3.50	88.9	.827	21.0	7.1	1.2	2.7	70	19	87	.76	19.3	0.074	1.9	10.3	MW	CG	N
0.975	24.77	72365S	3.50	88.9	.827	21.0	6.0	1.1	2.2	57	13	60	.76	19.3	0.074	1.9	10.3	SST	CG	N
0.975	24.77	72377	3.50	88.9	.813	20.7	11	1.9	2.4	60	26	117	.79	20.1	0.081	2.1	9.75	MW	CG	N
0.975	24.77	72377S	3.50	88.9	.813	20.7	9.4	1.7	1.9	47	18	78	.79	20.1	0.081	2.1	9.75	SST	CG	N
0.975	24.77	72392	3.50	88.9	.805	20.4	13	2.3	2.3	60	30	134	.87	22.1	0.085	2.2	10.3	MW	CG	N
0.975	24.77	72392S	3.50	88.9	.805	20.4	11	1.9	1.9	47	20	90	.87	22.1	0.085	2.2	10.3	SST	CG	N
0.975	24.77	72401	3.50	88.9	.791	20.1	15	2.6	2.4	61	36	160	1.10	28.0	0.092	2.3	12.0	MW	CG	N
0.975	24.77	72401S	3.50	88.9	.791	20.1	13	2.2	1.9	48	24	108	1.10	28.0	0.092	2.3	12.0	SST	CG	N
0.975	24.77	72413	3.50	88.9	.783	19.9	18	3.2	2.3	58	42	185	1.14	29.0	0.096	2.4	11.9	MW	CG	N
0.975	24.77	72413S	3.50	88.9	.783	19.9	15	2.7	1.8	45	28	123	1.14	29.0	0.096	2.4	11.9	SST	CG	N
0.975	24.77	72425	3.50	88.9	.765	19.4	26	4.5	2.1	54	54	241	1.30	33.0	0.105	2.7	12.4	MW	CG	N
0.975	24.77	72425S	3.50	88.9	.765	19.4	22	3.8	1.6	42	36	160	1.30	33.0	0.105	2.7	12.4	SST	CG	N
0.975	24.77	72438	3.50	88.9	.751	19.1	32	5.6	2.0	50	63	281	1.46	37.0	0.112	2.8	13.0	MW	CG	N
0.975	24.77	72438S	3.50	88.9	.751	19.1	27	4.8	1.5	39	41	184	1.46	37.0	0.112	2.8	13.0	SST	CG	N
0.975	24.77	72445	3.50	88.9	.745	18.9	36	6.3	1.9	48	68	304	1.50	38.0	0.115	2.9	13.0	MW	CG	N
0.975	24.77	72445S	3.50	88.9	.745	18.9	31	5.4	1.5	37	45	199	1.50	38.0	0.115	2.9	13.0	SST	CG	N
0.975	24.77	72453	3.50	88.9	.735	18.7	44	7.7	1.8	45	77	344	1.55	39.2	0.120	3.0	12.9	MW	CG	N
0.975	24.77	72453S	3.50	88.9	.735	18.7	37	6.5	1.4	34	51	225	1.55	39.2	0.120	3.0	12.9	SST	CG	N
0.975	24.77	72465	3.50	88.9	.725	18.4	50	8.8	1.7	44	87	388	1.67	42.5	0.125	3.2	13.4	MW	CG	N
0.975	24.77	72465S	3.50	88.9	.725	18.4	43	7.5	1.3	34	57	253	1.67	42.5	0.125	3.2	13.4	SST	CG	N
0.975	24.77	72473	3.50	88.9	.705	17.9	67	12	1.6	40	106	473	1.89	48.0	0.135	3.4	14.0	MW	CG	N
0.975	24.77	72473S	3.50	88.9	.705	17.9	57	10	1.2	30	68	304	1.89	48.0	0.135	3.4	14.0	SST	CG	N
0.975	24.77	72480	3.50	88.9	.679	17.2	101	18	1.4	35	139	617	2.09	53.1	0.148	3.8	14.1	MW	CG	N
0.975	24.77	72480S	3.50	88.9	.679	17.2	86	15	1.0	26	89	397	2.09	53.1	0.148	3.8	14.1	SST	CG	N
0.975	24.77	72486	3.50	88.9	.651	16.5	154	27	1.1	29	176	782	2.27	57.6	0.162	4.1	14.0	MW	CG	N
0.975	24.77	72486S	3.50	88.9	.651	16.5	131	23	.85	22	111	496	2.27	57.6	0.162	4.1	14.0	SST	CG	N
0.975	24.77	72338	4.00	101.6	.849	21.6	4.1	.72	3.2	80	13	58	.58	14.8	0.063	1.6	9.25	MW	CG	N
0.975	24.77	72338S	4.00	101.6	.849	21.6	3.5	.61	2.5	64	8.8	39	.58	14.8	0.063	1.6	9.25	SST	CG	N
0.975	24.77	72350	4.00	101.6	.831	21.1	6.2	1.1	3.0	76	18	82	.76	19.2	0.072	1.8	10.5	MW	CG	N
0.975	24.77	72350S	4.00	101.6	.831	21.1	5.3	.92	2.3	60	12	55	.76	19.2	0.072	1.8	10.5	SST	CG	N
0.975	24.77	72366	4.00	101.6	.827	21.0	6.2	1.1	3.1	80	20	87	.85	21.6	0.074	1.9	11.5	MW	CG	N

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; **SST** - Stainless Steel; **BC** - Beryllium Copper; **PB** - Phosphor Bronze

ENDS: **C** - Closed; **G** - Ground; **O** - Open

FINISH: **Z** - Zinc; **BO** - Black Oxide; **GI** - Gold Irridite; **T** - Tinned Wire; **N** - None

COMPRESSION SPRINGS



O.D. Inches	O.D. mm	CENTURY STOCK NUMBER	FREE LENGTH Inches	FREE LENGTH mm	I.D. Inches	I.D. mm	RATE Lbs./In.	RATE N/mm	SUGG.MAX.DEFL. Inches	SUGG.MAX.DEFL. mm	SUGG.MAX.LOAD Lbs.	SUGG.MAX.LOAD N	SOLID LENGTH Inches	SOLID LENGTH mm	WIRE DIA. Inches	WIRE DIA. mm	TOTAL COILS	MAT'L	ENDS	FINISH
0.975	24.77	72366S	4.00	101.6	.827	21.0	5.3	.92	2.6	65	13	60	.85	21.6	0.074	1.9	11.5	SST	CG	N
0.975	24.77	72378	4.00	101.6	.813	20.7	9.7	1.7	2.7	69	26	117	.89	22.6	0.081	2.1	11.0	MW	CG	N
0.975	24.77	72378S	4.00	101.6	.813	20.7	8.2	1.4	2.1	54	18	78	.89	22.6	0.081	2.1	11.0	SST	CG	N
0.975	24.77	72393	4.00	101.6	.805	20.4	12	2.2	2.4	62	30	134	.89	22.7	0.085	2.2	10.5	MW	CG	N
0.975	24.77	72393S	4.00	101.6	.805	20.4	11	1.9	1.9	49	20	90	.89	22.7	0.085	2.2	10.5	SST	CG	N
0.975	24.77	72402	4.00	101.6	.791	20.1	13	2.3	2.8	70	36	159	1.24	31.5	0.092	2.3	13.5	MW	CG	N
0.975	24.77	72402S	4.00	101.6	.791	20.1	11	1.9	2.2	56	24	108	1.24	31.5	0.092	2.3	13.5	SST	CG	N
0.975	24.77	72414	4.00	101.6	.783	19.9	16	2.8	2.6	65	42	185	1.26	32.0	0.096	2.4	13.1	MW	CG	N
0.975	24.77	72414S	4.00	101.6	.783	19.9	14	2.4	2.0	51	28	123	1.26	32.0	0.096	2.4	13.1	SST	CG	N
0.975	24.77	72426	4.00	101.6	.765	19.4	22	3.9	2.4	62	54	241	1.46	37.0	0.105	2.7	13.9	MW	CG	N
0.975	24.77	72426S	4.00	101.6	.765	19.4	19	3.3	1.9	48	36	160	1.46	37.0	0.105	2.7	13.9	SST	CG	N
0.975	24.77	72439	4.00	101.6	.751	19.1	29	5.0	2.2	56	63	281	1.60	40.5	0.112	2.8	14.3	MW	CG	N
0.975	24.77	72439S	4.00	101.6	.751	19.1	24	4.3	1.7	43	41	184	1.60	40.5	0.112	2.8	14.3	SST	CG	N
0.975	24.77	72446	4.00	101.6	.745	18.9	32	5.6	2.1	54	68	304	1.65	42.0	0.115	2.9	14.4	MW	CG	N
0.975	24.77	72446S	4.00	101.6	.745	18.9	27	4.8	1.6	42	45	199	1.65	42.0	0.115	2.9	14.4	SST	CG	N
0.975	24.77	72454	4.00	101.6	.735	18.7	38	6.7	2.0	52	77	344	1.74	44.2	0.120	3.0	14.5	MW	CG	N
0.975	24.77	72454S	4.00	101.6	.735	18.7	32	5.7	1.6	40	51	225	1.74	44.2	0.120	3.0	14.5	SST	CG	N
0.975	24.77	72466	4.00	101.6	.725	18.4	44	7.7	2.0	51	87	388	1.89	48.0	0.125	3.2	15.1	MW	CG	N
0.975	24.77	72466S	4.00	101.6	.725	18.4	37	6.5	1.5	39	57	253	1.89	48.0	0.125	3.2	15.1	SST	CG	N
0.975	24.77	72474	4.00	101.6	.705	17.9	58	10	1.8	46	106	473	2.14	54.4	0.135	3.4	15.9	MW	CG	N
0.975	24.77	72474S	4.00	101.6	.705	17.9	50	8.7	1.4	35	68	304	2.14	54.4	0.135	3.4	15.9	SST	CG	N
0.975	24.77	72481	4.00	101.6	.679	17.2	87	15	1.6	40	139	617	2.37	60.1	0.148	3.8	16.0	MW	CG	N
0.975	24.77	72481S	4.00	101.6	.679	17.2	74	13	1.2	31	89	397	2.37	60.1	0.148	3.8	16.0	SST	CG	N
0.975	24.77	72487	4.00	101.6	.651	16.5	133	23	1.3	34	176	782	2.57	65.3	0.162	4.1	15.9	MW	CG	N
0.975	24.77	72487S	4.00	101.6	.651	16.5	113	20	.99	25	111	496	2.57	65.3	0.162	4.1	15.9	SST	CG	N
0.984	24.99	3336	.72	18.2	.794	20.2	111	19	.26	6.5	29	127	.33	8.4	0.095	2.4	3.50	SPR	CG	Z
0.984	24.99	2832	.81	20.6	.800	20.3	97	17	.38	9.5	36	162	.41	10.5	0.092	2.3	3.50	MW	C	Z
0.984	24.99	12579	.81	20.6	.794	20.2	111	19	.26	6.5	29	127	.33	8.5	0.095	2.4	3.50	SPR	CG	Z
0.984	24.99	S-3104	.88	22.2	.904	23.0	1.3	.22	.64	16	.81	3.6	.24	6.1	0.040	1.0	5.00	SST	C	N
0.984	24.99	10652	.94	23.8	.824	20.9	29	5.1	.48	12	14	62	.46	11.7	0.080	2.0	4.75	SPR	C	GI
0.984	24.99	1659	1.00	25.4	.860	21.8	11	1.9	.66	17	7.1	32	.34	8.7	0.062	1.6	4.50	SPR	C	Z
0.984	24.99	11942	1.00	25.4	.792	20.1	44	7.6	.42	11	18	82	.58	14.6	0.096	2.4	6.00	SPR	CG	Z
0.984	24.99	2635	1.00	25.4	.690	17.5	763	134	.18	4.5	135	600	.51	13.1	0.147	3.7	3.50	MW	CG	Z
0.984	24.99	3146	1.03	26.2	.894	22.7	2.5	.43	.81	21	2.0	8.9	.22	5.6	0.045	1.1	5.00	SPR	CG	Z
0.984	24.99	1513	1.06	27.0	.914	23.2	1.0	.18	.87	22	.88	3.9	.19	4.9	0.035	0.9	4.50	HD	C	Z
0.984	24.99	B12-24	1.06	27.0	.890	22.6	2.8	.50	.83	21	2.4	10	.24	6.0	0.047	1.2	5.00	SPR	CG	N
0.984	24.99	S-1048	1.19	30.2	.840	21.3	15	2.6	.83	21	12	54	.36	9.1	0.072	1.8	5.00	SST	CG	N
0.984	24.99	322	1.19	30.2	.824	20.9	30	5.2	.60	15	18	80	.45	11.5	0.080	2.0	4.67	SPR	C	GI
0.984	24.99	S-3087	1.25	31.8	.894	22.7	3.1	.54	1.0	26	3.2	14	.23	5.7	0.045	1.1	4.00	SST	C	N
0.984	24.99	3402	1.25	31.8	.656	16.7	539	94	.24	6.1	129	574	.90	22.9	0.164	4.2	5.50	SPR	CG	Z
0.984	24.99	11866	1.31	33.3	.862	21.9	13	2.2	.67	17	8.4	38	.31	7.7	0.061	1.5	4.00	SPR	C	N
0.984	24.99	12041	1.34	34.1	.674	17.1	485	85	.23	5.7	110	488	.78	19.7	0.155	3.9	5.00	SPR	CG	Z
0.984	24.99	S-183	1.41	35.7	.784	19.9	53	9.2	.58	15	31	137	.55	14.0	0.100	2.5	5.50	SST	CG	N
0.984	24.99	S-3084	1.47	37.3	.814	20.7	26	4.5	.78	20	20	89	.47	11.9	0.085	2.2	5.50	SST	CG	N
0.984	24.99	12205	1.50	38.1	.800	20.3	32	5.6	.81	20	26	116	.60	15.2	0.092	2.3	6.50	SPR	CG	Z
0.984	24.99	2599	1.50	38.1	.774	19.7	57	10	.67	17	38	171	.68	17.3	0.105	2.7	6.50	SPR	CG	Z
0.984	24.99	12704	1.63	41.3	.796	20.2	40	7.0	.97	25	38	171	.66	16.7	0.094	2.4	6.00	MW	C	N
0.984	24.99	S-1570	1.72	43.6	.916	23.3	.53	.09	1.5	38	.79	3.5	.23	5.8	0.034	0.9	5.75	SST	C	N
0.984	24.99	10861	1.75	44.5	.914	23.2	.60	.10	1.5	38	.90	4.0	.24	6.0	0.035	0.9	5.75	SST	C	N
0.984	24.99	II-78	1.75	44.5	.704	17.9	153	27	.55	14	84	372	1.12	28.4	0.140	3.6	8.00	SPR	CG	Z
0.984	24.99	S-470	1.78	45.2	.688	17.5	209	37	.42	11	89	394	1.04	26.3	0.148	3.8	7.00	SST	CG	N
0.984	24.99	S-1201	1.81	46.0	.814	20.7	9.0	1.6	.79	20	7.1	32	1.02	25.9	0.085	2.2	12.0	SST	CG	N
0.984	24.99	3862	1.88	47.6	.774	19.7	37	6.4	.93	24	34	152	.95	24.0	0.105	2.7	9.00	HD	CG	Z
0.984	24.99	B18-199	2.09	53.2	.784	19.9	31	5.4	1.0	25	31	137	.90	22.9	0.100	2.5	8.00	SST	C	N
0.984	24.99	12427	2.16	54.8	.884	22.5	3.3	.57	1.3	34	4.4	20	.30	7.6	0.050	1.3	5.00	SST	C	N
0.984	24.99	S-1590	2.25	57.2	.906	23.0	.58	.10	1.9	48	1.1	4.9	.35	8.9	0.039	1.0	8.00	SST	C	N
0.984	24.99	10395	2.25	57.2	.834	21.2	15	2.7	.98	25	15	66	.53	13.3	0.075	1.9	6.00	SPR	C	Z
0.984	24.99	11673	2.38	60.3	.686	17.4	187	33	.54	14	100	446	1.27	32.2	0.149	3.8	8.50	SPR	CG	Z
0.984	24.99	M-141	2.47	62.7	.484	12.3	2367	414	.16	4.1	385	1714	2.00	50.8	0.250	6.4	8.00	SPR	CG	Z
0.984	24.99	11752	2.50	63.5	.824	20.9	10	1.7	1.7	43	17	75	.80	20.3	0.080	2.0	10.0	SPR	CG	Z
0.984	24.99	2622	2.72	69.0	.600	15.2	562	98	.34	8.7	193	859	1.73	43.9	0.192	4.9	9.00	SPR	CG	Z
0.984	24.99	4371	3.00	76.2	.814	20.7	12	2.1	1.8	46	21	95	.91	23.2	0.085	2.2	10.8	SPR	CG	Z
0.984	24.99	1807	3.00	76.2	.774	19.7	22	3.9	1.6	40	35	157	1.42	36.0	0.105	2.7	13.5	HD	CG	Z
0.984	24.99	10429	3.50	88.9	.758	19.3	31	5.4	1.5	38	46	205	1.53	38.7	0.113	2.9	13.5	SPR	CG	Z
0.984	24.99	3188	3.63	92.1	.890	22.6	1.1	.19	3.1	79	3.3	15	.52	13.1	0.047	1.2	10.0	SPR	C	Z
0.984	24.99	10586	3.75	95.3	.820	20.8	6.0	1.1	2.5	64	15	68	1.23	31.2	0.082	2.1	15.0	SST	CG	N
0.984	24.99	11623	4.00	101.6	.626	15.9	189	33	.88	22	166	737	3.04	77.3	0.179	4.5	17.0	SPR	CG	Z
0.984	24.99	11630	4.00	101.6	.624	15.8	194	34	.83	21	161	715	3.06	77.7	0.180	4.6	17.0	SPR	CG	Z
0.984	24.99	3410	5.00	127.0	.660	16.8	94	17	1.3	34	124	554	3.61	91.6	0.162	4.1	22.0	SPR	CG	Z
0.984	24.99	10924	6.94	176.2	.760	19.3	12	2.0	3.5	89	41	182	3.14	79.7	0.112	2.8	28.0	SST	CG	N
0.984	24.99	11998	8.06	204.8	.564	14.3	246	43	1.0	26	248	1104	5.57	141.4	0.210	5.3	26.5	SPR	CG	Z
1.000	25.40	LL-49	.66	16.7	.760	19.3	437	77	.12	3.1	54	241	.36	9.1	0.120	3.0	3.00	SPR	CG	Z
1.000	25.40	11894	.78	19.8	.894	22.7	6.7	1.2	.52	13	3.4	15	.27	6.7	0.053	1.3	4.00	SPR	C	N
1.000	25.40	10287	.84	21.4	.876	22.3	10	1.8	.56	14	5.8	26	.28	7.1	0.062	1.6	4.50	SPR	CG	Z
1.000	25.40	2692	.88	22.2	.906	23.0	4.1	.71	.64	16	2.6	12	.24	6.0	0.047	1.2	4.00	HD	C	Z
1.000	25.40	B8-41	.88	22.2	.858	21.8	10	1.8	.45	11	4.5	20	.43	10.8	0.071	1.8	6.00	SST	CG	N
1.000	25.40	S-1233	.88	22.2	.856	21.7	11	1.8	.44	11	4.7	21	.43	11.0	0.072	1.8	6.00	SST	CG	N
1.000	25.40	S-178	.88	22.2	.790	20.1	106	19	.33	8.4	35	156	.42	10.7	0.105	2.7	4.00	SST	CG	N
1.000	25.40	AA-48	.94	23.8	.820	20.8	32	5.6	.44	11	14	62	.50	12.6	0.090	2.3	5.50	SST	CG	N
1.000	25.40	4211	1.00	25.4	.910	23.1	2.7	.47	.75	19	2.0	9.1	.25	6.3	0.045	1.1	4.50	SPR	C	Z

CENTURY SPRINGS PTY. LTD.

Sales & Enquiries: 1300 360 318 Tel: (02) 9313 5295 Fax: (02) 9700 9422

MATERIAL: MW - Music Wire; SPR - Spring Steel; HD - Hard Drawn; OT - Oil Tempered; SST - Stainless Steel; BC - Beryllium Copper; PB - Phosphor Bronze

ENDS: C - Closed; G - Ground; O - Open

FINISH: Z - Zinc; BO - Black Oxide; GI - Gold Irridite; T - Tinned Wire; N - None